PHOTOGRAPH THIS SHEET AD-E850 050 ATTENTION: Camera Operator AD A 0 98 61 When Filming attached document use Bell & Howell camera ONLY::: LEVEL Consult with Supervisor for INVENTORY further instructions. Rept. No. USAFETAC/DS-81/025

DOCUMENT IDENTIFICATION

16 Jun. 65 DISTRIBUTION STATEMENT A Approved for public release; Distribution Unlimited DISTRIBUTION STATEMENT **ACCESSION FOR** NTIS GRA&I DTIC TAB UNANNOUNCED **JUSTIFICATION** BY DISTRIBUTION / AVAILABILITY CODES DIST AVAIL AND/OR SPECIAL DATE ACCESSIONED (RUSSWO) Rpts, 10 years, old or older request by Originator. Co In Goald Chief. DELC/DO. DISTRIBUTION STAMP 30: MAR_#81_ DATE RECEIVED IN DTIC PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-DDA-2 **DOCUMENT PROCESSING SHEET**

DTIC FORM 70A

DS-81/025

ADF 750 050

*52*2

AD A 0 9 8 6 1 0

DATA PROCESSING DIVISION ETAC, USAF

Air Weather Service (MATS)

REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS

FUKUOKA KYUSHU JAPAN/ITAZUKE AB WBAN #43310 N 33 35 E 130 27 ELEV 22 FT RJFF WMO #47808

PARTS A-F
POR FROM HOURLY OBS SEP 46-JAN 47, NAY 47-DEC 64
POR FROM DAILY OBS SEP 46-JAN 47, MAY 47-MAY 64

FEDERAL BUILDING ASHEVILLE, N. C.

DISTRIBUTION STATEMENT A

Approved for public release; Distribution Unlimited

89-4820/1

Review and Approval Statement

This report is approved for public release. There is no objection to unlimited distribution of this report to the public at large, or by DTIC to the National Technical Information Service (NTIS).

This technical report has been reviewed and is approved for publication.

Wayne E. M. Collom.
WAYNE F. MCCOLLOM, Chief
Technical Information Section

USAFETAC/TST

FOR THE COMMANDER

AWS Scientific and Technical Information Officer (STINFO)

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

REPORT DOCUMENTATION P	AGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
USAFETAC/DS-81/025	GOVT ACCESSION NO	
TITLE (and Subtitie)		5. TYPE OF REPORT & PEPIOD COVERED
Revised Uniform Summary of Surface W Observations (RUSSWO)-	eather	Final rept.
ITAZUKE AB, FUKOKA KYUSHU, JAPAN		6. PERFORMING ORG. REPORT NUMBER
AUTHOR(s)		8. CONTRACT OR GRANT NUMBER(*)
PERFORMING ORGANIZATION NAME AND ADDRESS USAFETAC/OL-A		PROGRAM ELEMENT, PROJECT, TASK
Air Force Environmental Technical Ap Scott AFB IL 62225	pl. Center	
JSAFETAC/CBD	· · · · · · · · · · · · · · · · · · ·	12 REPORT DATE
JSAFETAC/CBD Air Weather Service (MAC)		16 JUNE, 1965
Scott AFB IL 62225		13 NUMBER OF PAGES
4 MONITORING AGENCY NAME & ADDRESS(1) different for	rom Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED
		1
		15. DECLASSIFICATION DOWNGRADING SCHEDULE
S DISTRIBUTION STATEMENT (of this Report)		15# DECLASSIFICATION/ DOWNGRADING SCHEDULE
Approved for public release; dist	ribution unlim	
		ited.
Approved for public release; dist		ited.
Approved for public release; dist		ited.
Approved for public release; dist		ited.
Approved for public release; dist DISTRIBUTION STATEMENT (of the obstract entered in B. SUPPLEMENTARY NOTES	Block 20, If different lic	ited。
Approved for public release; dist DISTRIBUTION STATEMENT (of the abstract entered in S. SUPPLEMENTARY NOTES ARCES (Continue on reverse alde if necessary and in Daily temperatu	Block 20, If different fro	ited. Ospheric pressure
Approved for public release; dist DISTRIBUTION STATEMENT (of the abstract entered in Supplementary notes *KUSSWO Daily temperatu Snowfall Extreme snow de	dentily by block number res Atmo	ited. Sepheric pressure reme surface winds
Approved for public release; dist DISTRIBUTION STATEMENT (of the abstract entered in S. SUPPLEMENTARY NOTES RUSSWO Daily temperatu Snowfall Extreme snow de Climatology Sea-level press	dentily by block number res Atmo	ited. Spheric pressure reme surface winds chrometéric summary
Approved for public release; dist DISTRIBUTION STATEMENT (of the abstract entered in Supplementary notes *KUSSWO Daily temperatu Snowfall Extreme snow de	dentify by block number res Atmo pth Exti ure Psyt ture Cei	ited. Sepheric pressure reme surface winds

ITAZUKE AB. FUKUNKA KYUSHU, JAPAN
It contains the following parts: (A) Weather Conditions; Atmospheric Phenomena;
(B) Precipitation, Snowfall and Snow Depth (daily amounts and extreme values);
(C) Surface winds; (D) Ceiling versus Visibility; Sky Cover; (E) Psybrometric Summaries (daily maximum and minimum temperatures, extreme maximum and minimum temperatures, psychrometric summary of wet-bulb temperature depression versus dry-bulb temperature, means and standard deviations of dry-bulb, wet-bulb (over)

DD 1 JAN 73 1473

UNCLASSIFIED

¥,

- 19. Percentage frenquency of distribution tables
 Dry-bulb temperature versus wet-bulb temperature
 Cumulative percentage frequency of distribution tables
- 20. and dew point temperatures and relative humidity); and (F) Pressure Summary (means, standard, deviations, and observation counts of station pressure and sea-level pressure). Data in this report are presented in tabular form, in most cases in percentage frequency of occurance or cumulative percentage frequency of occuring tables.

UNCLASSIFIED

SECURITY CHASSIFICATION OF THIS PAGEOWhen Date Enlared

REVISED

å-

-	ADDITIONAL DATA LOCATOR	
CL NUMBER	TYPE OF ADDITIONAL INFORMATION	LOCATION OF DATA
4362	Pressure Temperature Distribution	In CL File
4428	11. 1 1 pre 111 - High Lovel would Tabulation	i cifile
4:16 7	Winds Mirt	1 1/2
4933	Absolute Frax 1 min AV Gind (MPH)	Ail Tile
`	CHAPIC CETA	Incline
5882	mean S.L.P. and mean hamly departure 9 St.P. from Monthly Mean	In Chfile
	Correlation of mind components	1
_	Ceiling Class Mean Lemper Tours	dr. (12 L. La
	"E Part rec'd	E File
<u> </u>	XTRMS & X OF MR: DP TEMP & PRECIPBLE WITE	IN CL FILE
7408	I MIN. WNOS AND DEAK GUSTS	
7302	% FREQ OF SIM. CIG + VSBY	
18036	max wind speids	afile

والمراج المراجع المراج

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA

Revised UNIFORM SUMMARY of

X.

Sec. 34

SURFACE WEATHER OBSERVATIONS

DESCRIPTION OF SUMMARIES:

Preceding each section is a brief description of the data comprising each part of the revised Uniform Summary of Surface Weather Observations and the manner of presentation. Tabulations are prepared from hourly and daily observations recorded by stations operated by the U. S. Services and some foreign stations using similar reporting practices.

HOURLY OBSERVATIONS are defined as those record or record-special observations recorded at scheduled hourly intervals.

<u>DAILY OBSERVATIONS</u> are selected from all data recorded on reporting forms and combined into Summary of the Day observations. (Selected from record-special, local, summary of the day, remarks, etc.)

STANDARD 3-HOUR GROUPS All summaries requiring diurnal variations are summarized in eight 3-hour periods corresponding to the following sets of hourly observations: 0000-0200, 0300-0500, 0600-0800, 0900-1100, 1200-1400, 1500-1700, 1800-2000, 2100-2300 hours local standard time.

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA A

880 - J. 122272 | 300

¥.,

ď: . •

PART A

THE PROPERTY OF THE PROPERTY O

1

WEATHER CONDITIONS

This summary is a percentage frequency occurrence of various atmospheric phenomena and obstructions to vision, derived from hourly observations, and is presented in two tables as follows:

- 1. By month and annual, all hours and years combined.
- 2. By month, all years combined, by standard 3-hour groups.

Occurrences of the various phenomena included in each category on the forms are listed below:

Thunderstorms - All reported occurrences of thunderstorm, tornado, and waterspout.

Rain and/or drizzle - All liquid precipitation, falling to the ground, not freezing.

Freezing rain and/or freezing drizzle(glaze) - Precipitation falling in liquid form, but freezing on contact with an unheated surface.

Snow and/or sleet - Included are snow, sleet, snow pellets (soft bail), snow grains, and ice crystals.

Hail - Occurrences of hail and small hail are included.

Percentage of observations with precipitation - Included in this category are the observations when one or more of the above phenomena occurred. Since more than one type of precipitation may be reported in the same observation, the sums of the individual categories may exceed the total columns.

Fog - Included are fog, ice fog, and ground fog.

Smoke and/or haze - Occurrences of smoke, haze, or combination of smoke and haze are included.

Blowing snow - Occurrences of blowing snow (also drifting snow when reported from non-WBAN sources.)

Dust and/or sand - Included are blowing dust, blowing sand, and dust.

Blowing spray - This item if reported, is not shown in a separate category on this form but is included in the computation Percentage of Observations with Obstructions to Vision, below.

Percentage of observations with obstructions to vision - Included in this category are the observations when one or more of the above obstructions to vision occurred. Since more than one type of obstruction may be

reported in the same observation, the sums of the individual categories may exceed the percentage total columns. Also, although precipitation may reduce visibility, it is not considered an obstruction to vision for purposes of this summary; therefore, the percentage total of obstructions to vision need not reflect the total observations with reduced visibility.

· Continues Cont

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

43310

FUKUUKA KYUSHU JAPAN/ITAZUKE AB

46-64

ALL

£.

STATION

STATION NAME

VEAR

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OSS.
MAL	ALL	.1	12.4		7.5	•0	19.6	7.8	27.6	•0	_	31.7	13390
FEB		•0	13.1		3.9	.1	16.7	8.7	30.6	•0	•0	35.3	11544
MAR		•2	14.4	•0	• 9	•0	15.2	8.7	29.8		•0	33.9	12646
APR		.3	16.4		•0		16.5	11.0	31.5		.7	35.0	12240
HAY		.1	16.7				16.7	12.7	33.0		•0	40.6	13386
JUN		.4	19.6				19.6	12.1	39.2			45.9	12956
Jul		1.0	14.1				14.1	6.4	21.0			25.3	13377
A UG		1.4	9.9				9.9	5.3	21.0			24.2	15372
SEP		. 5	14.0				14.0	9.9	23.0			29.6	13516
DCT		.1	8.8		.0		8.9	10.1	25.7			31.6	14128
NCV		.0	10.2		.0	•0	10.2	10.7	34.6	.0		39.9	13679
DEC		•0	11.2		1.5	•0	12.6	7.5	31.6			35.6	14132
TOTALS		.4	13.3	•0	1.1	.0	14.4	9.2	29.0	.0	.1	34.2	158368

1210 WS FORM 0-10-5 (Cet 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE. N. C. 288C1

WEATHER CONDITIONS

÷ 😘

4331C

FUKUCKA KYUSHU JAPAN/11A/UKE AB

MAL

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FRCM HCURLY CBSERVATIONS

MONTH	HOURS (L S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
JAN	60-62	•1	12.6		6.6		18.9	8•9	25.5			30.6	1674
	C3-C5	•1	11.0		8.2	-1	20.1	9•3	24.6			30.0	1674
	(6-68	• 2	13.9		9.3		22.9	13.0	31.2	.1		37.3	1674
	69-11		13.0		9.4		22.0	9.4	31.8	.1	<u></u>	36.0	1674
	12-14	•2	11.5		8.8	.1	20.0	4.4	16.6	.1		19.2	1674
	15-17	.2	12.6		6.6	.1	18.7	3.8	16.7			19.0	1673
	18-2C	.1	12.0		5.6		17.4	5.4	40.0	.1		42.9	1674
	21-23		11.9		5.1		16.7	8 • 0	34.5			38-4	1673
ļ								·		 			
		 					<u> </u>						
<u> </u>													
TOTALS		.1	12.4	<u></u>	7.5	0	19.6	7.8	27.6	.0		31.7	13390

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING CIRISION ETAC, USAF ASHEVILLE, N. C. 288C1

WEATHER CONDITIONS

FUKURKA KYUSHU JAPAN/ITAZUKE AD

The state of the s

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERTATIONS

HINCH.	L.S.T	THUNDER. STORMS	RAIN AND, OR DRIZZE_	FREEZING RAIN A/OR DRIZZLE	SNOW AND/OR SLEET	MAIL	% OF USS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	SLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
FCP	CC-12	,1	1?.8		3.6	. 1	17.4	8.5	29.5			34.7	1443
	<u> </u>	. 1	15	! 	3.4		18.9	9.4	24.7			31.0	1443
	C6-08	. 1	13.5		5.2	.1	18.4	16.8	37.5			44.8	1443
	C9-11		12.4		5.1		17.2	9.5	34.2			38.5	1443
	12-14		11		4.2	. 1	15.1	5.3	17.1	•1		20.2	1443
	15-17		13.0		3.5		16.2	5.7	18.6			21.7	1443
	18-20		13.0		2.8	.1	15.5	7.5	42.0	.1		46.3	1443
	21-23		12.7		۷.8	.1	15.3	7.5	4C.8		-1	45.0	1443
				' 	·								
T(+/ALS		. c	13.1		3.9	.1	16.7	8.7	30.6	.0	<u>.</u>	35.3	11544

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

CATA PRUCESSING CIVISION ETAC. USAF ASHEVILLE. N. C. 28901

WEATHER CONDITIONS

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64 MAR
STATION STATION NAME YEARS MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE CF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN&/OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
MAR	CG-62	• 2	15.7		.7	-	16.3	9.6	30.2			35.1	1580
	03-05	.4	15.8		1.1		16.8	11.8	26.9			33.7	1581
	C6-08	•1	16.C		• 9	•1	17.0	20.3	42.6			50.1	1581
	C9-11		15.7		1.8	.1	17.3	9.0	31.6			35.3	1581
	12-14	•1	12.5		1.3		13.6	4.7	16.7			19.5	1581
	15-17		12.1	.1	.4		12.6	4.7	16.4		.1	19.2	1581
	18-2C	• 2	13.5		•6		14.0	4.4	36.4			38.3	1581
	21-23	.4	13.5		.4		13.9	4.7	37.5			39.7	1580
								- .					
TOTALS		• 2	14.4	.0	• 9	•0	15.2	8.7	29.8		.0	33.9	12646

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Town Alexander Alexander

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

43310 STATION FUKUGKA KYUSHU JAPAN/ITAZUKE AB

-64

APR

PERCENTAGE FREQUENCY OF OCCURRENCE CF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	fOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO.OF OBS.
APR	C0-02	. 3	14.8		• 1		15.0	11.6	32.6		• 6	38.8	1530
	C3-05	.1	17.8				17.8	16.5	29.3		. 5	39.0	1530
	C6-08	.1	19.1		.1		19.2	24.0	44.1		.7	55.4	1530
	C9-11	• 3	17.4				17.4	9.0	28.2		•8	34.0	1530
	12-14	. 3	15.2		.1		15.3	5.4	17.3		• 9	21.6	1530
	15-17	.2	16.1		•1		16.2	5.8	18.8		• 8	23.2	1530
	18-20	.6	16.4				16.4	7.7	39.1		• 8	44.7	153C
	21-23	• 5	14.5		•1		14.6	8.2	42.4		• 8	47.8	1530
						I			- 				·
						-							
TOTALS		3	16.4		•0		16.5	11.0	31.5		• 7	38.0	12240

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETS

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

WEATHER CONDITIONS

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OSS WITH OSST TO VISION	TOTAL NO. OF OBS.
MAY	CC-02	.4	16.C				16.0	15.7	34.5			44.3	1672
	C3-C5	.1	18.2				18.2	20.3	35.8			47.3	1674
	C6-08	.3	18.6			 _	18.6	25.3	45.2			56.7	1673
	09-11	.1	16.7				16.7	9.0	29.4			35.2	1673
	12-14	.2	15.4				15.4	5.3	20.1		•2	24.1	1674
	15-17		16.2			·	16.2	5.5	21.0		.1	25•2	167
	18-20		16.5				16.5	8.9	35.2			41.4	1673
	21-23		15.9				15.9	11.5	43.0			50.7	1674
TOTALS		.1	16.7				16.7	12.7	33.0		.0	40.6	1338

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CATA PRUCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

43310 STATION FUKUCKA KYUSHI TOWAN/I TAZUKE AB

7-64

NU L

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OSS.
JUN	CO-02	• 2	18.3				18.3	11.8	44.4			51.0	1620
	C3-05	. 3	20.4				20.4	20.6	43.3			53.6	1620
	C6-08	.7	21.8				21.8	23.1	51.3			61.0	1620
	C9-11	• 5	20.8				20.8	10.7	36.5			43.1	1620
	12-14	. 6	19.4				19.4	6.6	26.0			30.9	1620
	15-17	• 2	19.4				19.4	6.6	24.3			28.7	1616
	18-2C	.2	19.4				19.4	8.7	40.2			45.9	1620
	21-23	.4	17.2			<u> </u>	17.2	8.5	47.7			52.8	1620
TOTALS		.4	19.6		,		19.6	12.1	39.2			45.9	1295

1210 WS FORM 0-10-5 (Dat 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

WEATHER CONDITIONS

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64 JUL
STATION STATION NAME YEARS MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN&/OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OSS.
JUL	CC-C2	. 8	12.5				12.5	6.2	24.9			29.0	1674
	C3-C5	1.1	14.8				14.8	16.7	25.0			33.2	167
	80-93	.6	14.6				14.6	13.0	30.0			37.7	167
	C9-11	.7	14.0				14.0	4.8	18.3			21.7	167
	12-14	1.9	16.1				16.1	3.1	13.3			15.9	167
	15-17	1.7	16.3				16.3	3.6	12.6			15.4	167
···	18-20	8.	14.3				14.3	5.3	19.9			22.9	167
	21-23	. 8	10.2				10.2	4.1	23.8			26.3	167
TOTALS		1.0	14.1				14.1	6.4	21.0			25.3	1337

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

CARL

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

47-64

AUG

STATION

STATION NAM

YEARS

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER. STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OSS.
AUG	00-02	1.1	7.9				7.9	5.6	21.0			25.3	1674
	03-05	1.2	10.2				10.2	10.0	23.7			30.2	1673
	06-68	. 4	9.9				9.9	14.3	37.5			43.4	1674
	09-11	.2	9.1				9.1	2.3	20.8			22.2	1674
	12-14	1.7	10.7				10.7	2.0	11.0			13.4	1672
	15-17	3.0	13.0				13.0	1.6	11.5			13.0	1666
	18-20	2.5	10.1				10.1	3.4	19.4			21.4	1666
-	21-23	1.3	8.4				8.4	3.6	21.8			24.4	1671
TOTALS		1.4	9.9				9.9	5.3	21.0			24.2	13372

1210 WS FORM 0.10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

43310 STATION

FUKUCKA KYUSHU JAPAN/ITALUKE AB
STATION NAME

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
SEP	CC-02	. 3	12.9				12.9	12.0	21.1			30.0	1687
·	C3-05	. 5	15.0				15.0	15.4	22.3		_	33.6	1688
	C6-08	.4	15.2				15.2	25.2	34.2			46.8	1688
	C9-11	.4	13.7				13.7	5.5	22.0			25.6	1692
	12-14	.3	14.1				14.1	2.8	12.5			14.7	1692
	15-17	• 5	15.3				15.3	4-1	15.7			19.0	1691
	18-20	8.	14.3		· · · · · · · · · · · · · · · · · · ·		14.3	6.1	30.1	<u> </u>		34.3	1690
-	21-23	.5	12.1				12.1	8.2	25.9			32.5	1690
			<u></u>						-				
													· <u> </u>
					_								
3													
TOTALS		. 5	14.0				14.C	9.9	23.0			29.6	13518

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE. N. C. 28801

WEATHER CONDITIONS

. \$

43310 FUKUGKA KYUSHU JAPAN/I TAZUKE AB 46-64 OCT

PERCENTAGE FREQUENCY OF GCCURRENCE CF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
ОСТ	CO-02	. 1	9.1		.1		9.1	12.1	24.2	-		33.3	1767
	C3-05	.1	9.4		• 2		9.6	15.7	22.9	_		34.2	1767
	C6-08	-1	9.2		• 2		9.4	28.5	37.9			49.2	1767
	C9-11	.1	8.6				8.6	7.2	28.1			32.0	1766
	12-14	.1	7.8				7.8	2.3	10.9			12.6	1764
	15-17	• 3	9.2				9.2	2.1	12.9			14.3	1765
	18-20	.1	9.0				9.0	4.5	35.5			38.6	1767
	21-23	.1	8.3				8.3	8.0	33.0			38.6	1765
TOTALS		.1	8.8		•0		8.9	10.1	25.7			31.6	14128

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE ORSOLETE

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

4331C FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64 NOV
STATION STATION NAME YEARS MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE CF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

монтн	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
710V	00-62		9.3		.1		9.4	13.5	34.9			42.4	1710
	C3-05		10.C				10.0	15.6	28.9			37.3	1710
	C6-08		10.9				10.9	24.0	40.9			49.4	1710
	C9-11		10.4		.1		10.5	9.0	36.2			39.4	1709
	12-14		9.5				9.5	2.7	14.6			16.6	171C
	15-17	.1	10.6				10.6	3.8	_18.7			21.2	171c
	18-2C	.1	11.0			•1	11.0	6.2	54.3	.1		58.3	171C
	21-23		9.6				9.6	10.9	48.5			55.0	1710
							_						
								·					
TOTALS		.0	10.2		•0	•0	10.2	10.7	34.6	.0		39.9	13679

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

WEATHER CONDITIONS

4	3	3	1	C	
_		51	ī	TION	

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

DEC

PERCENTAGE FREQUENCY OF OCCURRENCE CF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

HOURS (L.S.T.)	THUNDER. STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
CO-62		10.9		1.4		12.3	8.6	29.0			34.2	176
C3-05		11.3		1.3	.1	12.5	16.0	25.0			31.1	176
80-60		11.3		2.2		13.2	15.5	34.7			40.5	176
C9-11		10.4		2.2		12.5	8 • 3	37.4			40.6	176
12-14		11.1		1.4		12.4	1.9	16.2			17.3	176
15-17	• 1	11.3		1.0		12.2	2.2	19.1			20.2	176
18-20	• 2	10.9		1.0		11.7	5.2	50.3			54.2	176
21-23		12.7		1.2		13.8	8.1	41.2			46.5	176
_					-							
												14132
	(.s.r.) CO-C2 C3-05 C6-08 C9-11 12-14 15-17 18-20	CO-C2 C3-05 C6-08 C9-11 12-14 15-17 18-20 21-23	CO-C2 10.9 C3-05 11.3 C6-08 11.3 C9-11 10.4 12-14 11.1 15-17 .1 11.3 18-2C .2 10.9 21-23 12.7	CO-C2 10.9 C3-05 11.3 C6-08 11.3 C9-11 10.4 12-14 11.1 15-17 .1 11.3 18-2C .2 10.9 21-23 12.7	CO-C2	CO-C2	CO-C2	CO-C2	CO-C2	CO-C2	CO-C2	CO-C2

210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PART A

ATMOSPHERIC PHENOMENA

This summary is a presentation of the percentage of days with occurrences of various atmospheric phenomena. These data are obtained from all recorded information on the reporting forms and combined into a daily observation.

The descriptions of the phenomena in the Weather Conditions Summary above also apply for the categories summarized in these tabulations. However, it should be noted that in this summary the columns headed, "% OF OBS WITH PRECIP" and "% OF OBS WITH OBST TO VISION" show the percentage of days rather than percentage of observations. Since more than one type of precipitation or more than one type of obstruction may occur in the same daily observation, the sum of the values in the individual columns may not equal the total columns.

This presentation is by month with annual totals, and is prepared with all years combined.

NOTE: A day with rain and/or drizzle was not separately reported in WRAN data prior to January 1949.

Therefore percentages in this column are restricted to the period January 1949 and later.

A day with dust and/or sand was punched and included in this summary only when visibility was less than 5/8 mile.

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

WEATHER CONDITIONS

\$3.23 · . .

43310

-at-

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

46-64

ALL

STATION

STATION NAM

YEARS

MONTH

PERCENTAGE OF DAYS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM DAILY OBSERVATIONS

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND/OR DRIZZLE	FREEZING RAIN & / OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND/OR HAZE	BLOWING SNOW	DUST AND/OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS.
JAN	DAILY	1.8	56.0		31.9	• 9	73.7	32.8	70.3	.9		74.7	558
FEB		1.5	54.9		20.4	1.7	64.9	37.4	77.5	.4		82.3	481
MAR		2.5	55.0		6.6	.4	57.1	40.8	80.6			83.5	527
APR		2.9	55.8		.8		55.5	47.4	85.5	•2	• 2	89.4	510
MAY		1.6	54.8				53.8	52.0	86.0			91.8	598
JUN		4.3	60.2				58.8	46.7	86.3			91.8	510
JUL		14.8	59.8			.2	61.3	32.6	63.4			70.0	527
AUG		16.1	51.4				50.3	34.5	67.4			72.9	521
SEP		8.3	59.6				56.5	52.3	75.4			85.0	533
00.1		1.3	41.9				41.4	54.5	79.4			86.6	558
NOV		.6	45.6		1.1	.2	45.2	49.4	87.4			90.0	540
DEC		.7	57.4	•2	10.2	1.1	63.3	38.4	83.2	.2		85.3	550
TOTALS		4.6	54.4	•0	5.9	.4	56,7	~~ 43 . 3	78.5	.1	• (83.6	6381

1210 WS FORM 0-10-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA

PART B

PRECIPITATION, SNOWFALL & SNOW DEPTH

of the following:

PRECIPITATION

DERIVED FROM DAILY OBSERVATIONS

SNOWFALL

DERIVED FROM DAILY OBSERVATIONS

SNOW DEPTH

DERIVED FROM DAILY OBSERVATIONS

- The first table for each of the above presents the percentage frequency of various daily amounts, by month and annual, all years combined. The percentage of days with measurable amounts is also computed monthly and annually. Also shown for the precipitation and snowfall tables, are the monthly mean amounts, annual mean amounts (sum of monthly mean amounts), and the extreme monthly amounts (greatest and least). The latter statistics above are not presented for the snow depth summary since they would have limited use and may be misleading.
- The second set of tables for each of the above presents the extreme daily amounts by individual year and month for the entire period of record available. Also provided are the means and standard deviations for each month and annual (all months). The extremes for a month are not printed nor used in computations if one or more observations are missing.

NOTE: Snow depth was recorded and punched at various hours during the period available from U. S. operated stations. The periods and hours used in the snow depth summary vary by service and period as follows:

Air Force Stations

From beginning of record thru 1945 Jan 46-May 57

Snow depth at 0800 LST Snow depth at 1230 GCT

Jun 57-present

Snow depth at 1200 GCT

US Navy and Weather Bureau Stations

From beginning of record thru Jun 52

Snow depth at 0030 GCT Snow depth at 1230 GCT

Jul 52-May 57 Jun 57-present

Snow depth at 1200 GCT

*HAIL WAS INCLUDED IN SNOWFALL OCCURRENCE IN THE SUMMARY OF THE DAY OBSERVATION PRIOR TO JAN 1986.

Page B 1

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLED N. L. 28801

DAILY AMOUNTS

PERCENTAGE FREQUENCY OF PRECIPITATION (FROM DAILY OBSERVATIONS)

43310

FUKUUKA KYUSHU JAPAN/I TAZUKE AB 46-64

						AMO	OUNTS (II	CHES)						PERCENT			HLY AMO	UNTS
PRECIP	NONE	TRACE	01	02. 05	06-10	11- 25	26- 50	51-1 00	1 01 2 50	2 51-5 00	5 01-10 00	10 01 20 00	OVER 20 00	OF DAYS	NO		(INCHES)	
SHOW 'ALL	NONE	TRACE	01.04	0514	1524	2534	3 5 4 4	4364	6 5.10 4	10 5 15 4	15 5-25 4	25 5 50 4	OVER 50 4	MEASUR-	OF OBS	MEAN	GREATEST	LEAST
SHOW- DEPTH	NONE	TRACE	1	2	3	46	7 12	13 24	25-36	37-48	49-60	61-127	OVER 120	AMTS				
MAL	26.7	24.0	5.6	12.0	8.1	10.2	8.1	43.9	1.3	. 2				49.3	558	3.23	6.68	1.2
PEB	35.1	22.q	2.7	10.8	7.1	9.1	5.8	11.75 · S	1.9	• 2				42.8	481	3.36	8.91	.6
MAR	42.7	16.4	2.7	9.1	4.7	9.9	7.0	1,0 4.7	1.9	.4				40.4	527	3.67	6.04	• 8:
APR	46.2	15.4	ż.5	6.5	3.7	7.3	7.3	11.6.9	3.3	.6	• 2	2		38.3	460	5.14	13.71	1.8
MAY	46.1	11.1	2.2	5.7	5.2	10.9	ŧ	11.5.9	1	1.3				42.8	550	6.11	16.58	2.0
אטנ	41.0	15.1	4.7	4.1	3.3	7.3	3.7	180.0	7.3	2.5	•/	.4		43.9	510	10.92	42.16	2.51
ານເ	38.7	17.8	2.7	6.5	3.8	7.4	4.6	18.6.6	8.0	3.6	.4			43.5	527	10.95	21.17	. 3
AUG	49.5	13.3	2.7	5.5	4.9	6.9	4.4	1.6.8	4.4	1.1		>		37.2	527	6.74	14.20	1.3
SEP	40.6	15.9	3.7	6.5	3.7	7.3	7.1	56.5	6.5	2.0	.4			43.5	510	8.47	16.40	2.7
ОСТ	58.1	13.1	2.8	6.6	4.9	4.9	3.6	4,5	2.3	.4	•	2		28.8	527	3.25	10.40	۶.
NOV	54.8	13.0	3.0	5.2	3.9	7.6	6.1	6.4.8	1.7					32.2	540	2.90	7.C2	. 8
DEC	36.6	22.2	4.1	8.6	5.6	10.9	6.3	\$\hat{9}4.3	1.4					41.2	558	2.98	5.92	.4
ANNUAL	43.0	16.7	3.3	7.3	4.9	8.3	5.3	5.5	3.7	1.0	,	2 •0)	40.3	6303	67.81	X	\times

1210 WS $_{
m JUL-64}^{
m FORM}$ 0.15.5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLÉTE

DATA PROCESSING DIVISION ETAC. USAF ASHLVILLE, N.C. 28801

EXTREME VALUES

-6e aveid

1.5%

ري

PRECIPITATION
(FROM DAILY OBSERVATIONS)

43310 STATION FUKUDKA KYUSHU JAPAN/ITAZUKE AB

46-64

YEARS

24 HOUR AMOUNTS IN INCHES

MONTH	JAN.	FEB.	MAR.	APR.	MAY	JUN.	JUL.	AUG.	SEP.	oct.	NOV.	DEC.	ALL MONTHS
46											1.58	.86	
47	1.0				4.83	3.30	3.74	1.03	1.32	-34	.48	1.24	
48	•49	.66	1.13	1.66	2.53	3.04	5.30	5.61	4-10	.46	1.18	1.27	5, 61
49	.66	2.80	1.10	.94	1.32	2.44	3.97	5.49	1.52	1.52	- 86	1.27	5.49
50	2.80	2.24	2.65	1.53	1.63	1.70	1.23	1.39	6.10	1.14	2.23	.68	6.10
51	1.09	1.14	-65	1.07	.80 1.36	2.86	4.52	3.35	2.76	5.82	1.56	-64 -78	5.82 3.23
52 53	-58	1.28	.67 1.37	3.23	1.68	2.84	3.96	2.20	3.54	.22	.95	1.32	10.17
54	.70	.96	1.00	1.08	2.41	2.82	3.56	2.42	5.06	.36	1.13	.49	6.06
55	44	1.43	-58	5.38		5.57	3.66	1.13	2.75	.63	.69	.36	5.57
56	1.08	1.98	.76	-85	1.27	2.51	2.50	5.80	2.03	2.02	.61	.20	5.80
57	.22	.56	.41	.93	.53	1.49	3.23	2.60	1.92	.85	-50	.50	3.23
58	.55	.93	3.17	2.61	1.12	1.56	-29	3.26	1.27	1.20	.79	.79	3.26
59	99	.74	2.15	1.79	1.48	1.60	5.62	.77	1.75	.22	.66	1.18	5.62
60	1.02	-30	. 84	1.79	3.08	3.35	.67	.92	4.95	1.30	.78	.54	4.95
61	.73	.48	.84	1.60	1.73	2.12	1.64	. 88	4.36	4.15	.91	.56	4.36
62	1.13	.72	.39	-61	1.34	2.53	3.60	3.56	2.10	1.35	1.09	1.02	3.60
6.3	1.09	.81	1.18	1.17	3.54	10.63	2.41	3.66	1.03	1.15	.90	.43	10.63
64	1.43	.51	•60		2.40								
	,			1					,	,	.,	÷	
										•			
	63	1 02		• •	1 . 4	3.64	3 05	2.71				.80	5.39
MEAN S D	•93 •558	1.09	1.15 .790	1.71	1.107	3.56	3.05		2.89	1.41	.442	.354	2.151
TOTAL OBS.	558	481	527	480	558	510	527	527	51a	527	540	558	6303
TOTAL USS.	226	401	261	700	226	214	261	261	714	78 1	274	220	8303

1210 WS FORM 0-88-5 (Det 50)

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

DAILY AMOUNTS

21 34

35 /A

PERCENTAGE FREQUENCY OF SNOWFALL [FROM DAILY OBSERVATIONS]

43/10 FUKUDKA KYUSHU JAPAN/ITAZUKE AB 46-64
STATION NAME YEARS

						AM	OUNTS (II	NCHES)						PERCENT		MONI	HLY AMO	UNTS
PRECIP	NONE	TRACE	01	C2 05	06 10	11 25	26 50	5) 1 00	101250	2 51-5 00	5 01 10 00	10 01 20 00	OVER 20 00	OF DAYS			(INCHES)	
SNOWFALL	NONE	TACE	0304	0514	1524	2534	3 5 4 4	4564	6 5 10 4	10 5 15 4	15 5 25 4	25 5-50 4	OVER 50 4		OF OBS	MEAN	GREATEST	LEAST
SHOW DEPTH	NONE	TRACE	,	2	3	4 6	7.12	13 24	25 36	37.48	49 60	61 120	OVER 120	AMT5				
MAL	68.5	23,5	2.9	3.6	. 4	.4	1	•5		• 2			15,	7.9	۹58	3.1	19.3	•0
FEB	3•0B	14.6	2.5	. e	1.2		.4		.4				٠, `J	5.4	481	2.4	11.9	• d
MAR	94.1	5.5	• 2	. 2										.4	527	.1	.6	•0
APR	99.4	. 4													510	TRACE	TRACE	•0
MAY	106.0														358	•0	• 0	•0
אטנ	100.0														510	•0	•0	•0
JUL	100.0													- '\	527	•0	•0	•0
AUG	100.0													,	527	•0	•0	•0
SEP	100.0													0	510	•0	•0	•0
ост	100.0													1	55 8	•0	• 0	•0
NOV	98.9	1.1													540	TRACE	TRACE	•0
DEC	90.5	8.8	۰۶	.2	.4								0.4	.7	558	•3	3.3	•0
ANNUAL	94.3	4.5	. 5	.4	• 2	•0	.0	•0	•6	•0				1.2	6364	5.8	\times	\times

1210 WS JUL 64 0-15-5 (Det 50) PRÉVIOUS EDITIONS OF THIS FORM ARE OBSOLÉTE

V

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N.C. 20801

EXTREME VALUES

12754

χ,

<u>ئىتى.</u>

SNOWFALL
[FROM DAILY OBSERVATIONS]

۶۰۰ ۴

43310 STATION

()

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

46-64

YEARS

24 HOUR AMOUNTS IN INCHES

				/	1	70		5110)			
MONTH	MAL	FEB.	MAR.	APR.	MAY	אטנ.	JUL.	AUG.	SEP.	oct.	NOV.	DEC.	ALL MONTHS
46	1.4				. 0	.0	•a	•0	• a	•0	•0	1.5	
48	3.1	• (TRACE	• 0	•0	• 3	•0	٠ŭ	•0	• 0	• q	•0	3.1
49	1.1	6.5	TRACE	• d	9	p.	•0		. d	d	d	TRACE	6.5
50	TRACE	TRACE	TRACE	• 0	-0	• 0	• 0	•0	• 0	• 0	TRACE	TRACE	TRACE
51	TRACE	٤ .	TRACE	. d	• ü	• d	•d	. q		. d	TRACE	TRACE	3
52	• 2	TRACE	TRACE	• d	• ध	• 0	• 0	•0	• 0	•0		TRACE	• 2
53	TRACE	. 4	TRACE	• 0	q		<u>. a</u>	• q	<u>•</u> q	<u>.a</u>	. d	0	.4
54	TRACE	8.5	FRACE	• 0	• 0	• q	.q	.0	• q	.0	• 0	TRACE	8.5
55	1.0	TRACE	• a	• 0	0	o	<u>•d</u>	•0	<u>•u</u>	a	•0	•0	1.0
56	. 7	4.4	TRACE	• 0	• 0	• q	• q	•0	•d	• 0	• 0	•0	4.4
57	<u>• d</u>		6	a	0	q	• d	<u>.a</u>	.0	0	• ជ		•6
58	1.4	TRACE	• 4	• 0	• q	• 9	•d	•0	•d	• q	- 4	TRACE	1.4
59	3.0	. d	• 0	• 0	0	<u>•q</u>	• 0	•0	<u>.</u> d	<u>. q</u>		TRACE	3.0
60	1.4	TRACE	• 0	• 0	• 0	• 0	• q	.0	• q	• 0	TRACE	1.5	1.5
61	. 7	. 7	TRACE		• 0	.0	•0	.0	-,0	q	•0	TRACE	
62	5.Q	TRACE			•0	• 9	• q	•0	• q	• q	• q		5.0
63	10.9	1.7	TRACE	TRACE	•0	-0	<u>• 0</u>	.0	•0	.0	TRACE	TRACE	10.9
64	2.2	2.0	•0	• 0	• 0								
													
					- (-						
MEAN	1.76	1.49	.06	TRACE	.00	•00	•00	•00	•00	30.	TRACE	.17	2.97
S D.	2.652			.000	.000	.000	.000	.000	.000	.000			3.282
TOTAL OBS.	558	481	527		558	510	527	527	510	558	540		6364

1210 WS FORM 0-88-5 (Det 50)

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

A STATE OF THE STA

DAILY AMOUNTS

\$ B

PERCENTAGE FREQUENCY OF SNOWDEPTH (FROM DAILY OBSERVATIONS)

43310 FUKURKA KYUSHU JAPAN/ITAZUKE AB 46-64
STATION NAME YEARS

						AM	OUNTS (II	NCHES)						PERCENT		MON	THLY AMO	
PRECIP	NONE	TRACE	01	02- 05	06-10	11- 25	2650	51-1 90	1 01-2 50	2 51-5 00	5 07-10 00	10 01-20 00	OVER 20 00	OF DAYS	NO.		(INCHES)	,
SHOWFALL	NONE	TRACE	0104	0514	1.5 2 4	2534	3 5 4 4	4564	6 5 10 4	10 5-15 4	15 5 25 4	25 5 50 4	OVER 50 4	MEASUR-	OF OBS.	MEAN	GREATEST	LEAST
SNOW- DEPTH	HONE	TRACE	1	2	3	46	7-12	13-24	25-36	37-48	49-60	61-120	OVER 120	AMTS				
JAN	92.5	5.7	• 9	. 7		• 2								1.8	558			
FEB	96.9	2.3	.6		• 2									.8	481			
MAR	100.0														527			
APR	100.0														510			
MAY	100.0														558			
NUL	100.0														510			
JUL	100.0														527			
AUG	100.0			!						<u> </u>					52 7		<u></u>	
SEP	100.0	; ;	1	<u> </u>	! 	!									510		ļ	
ОСТ	100.0		l			i L									558			
ноч	100.0														540			
DEC	99.3	• 5	.2											.2	550			
ANNUAL	99.0	.7	-1	.1	•0	•0								-2	6364		\times	\geq

1210 WS JUL 64 0-15-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Sanda Sanda Sanda

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

EXTREME VALUES

SNOWDEPTH
(FROM DAILY OBSERVATIONS)

A . .

43310 STATION

- Bulling Control

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

VEARE

DATLY SNOWDEPTH IN INCHES

MONTH	JAN,	FEB.	MAR.	APR.	MAY	JUN.	JUL.	AUG.	SEP.	ост.	NOV.	DEC.	ALL MONTHS
46										0	Ü	ç.	
47						<u> </u>	0	0	<u> </u>	<u> </u>		TRACE	
48	2	Q	0	2	0	Ç	0	0	c	0	q	0	2
49	TRACE	TRACE	0	0	<u> </u>	0	0	0	C C	0	<u>u</u>	TRACE	TRACE
50 51	INALE	CARE	O		0	o	c	0	6	ő	o o	TRACE	TRACE
52	0	TRACE	U		<u>:</u>	0	- 8	0	G		 3	U	TRACE
ś 3	ď	1740	õ	o	o	0	ò	o	o	ŏ	d	ő	e
54	- 1		0	ō	Ú	Ö	č	0	Č	ŏ	<u>č</u>	Ö	1
55	čĺ	d	è	ŏ	ç	č	ä	è	ŏ	cl	ö	ŏ	3
56	TRACE	TRACE	o	Ö	Ö	0	d	0	C	c	0	Ċ	TRACE
57	ũ	O	o.	0	G	o	d	0	O	c	d	0	0
58	TRACE	0	0	0	0	0	0	C	Q	C	0	0	TRACE
59	2	0	O.	<u> 원</u>	. 0	0	G	0	0		0	0	2
60	TRACE	0	C	ं हो	0	C	0	0	0	0	- C	1	1
61	TRACE	0	0	최		O	0	0	0	0	0	0	TRACE
62	2	C	O	U	0	O	C	C	G	0	0	0	2
63	5	TRACE	0	U	1)	<u>c</u>		C	0	0	<u> </u>	Q	5
64	C	o	D	0	С								
<u>-</u>													
MEAN	.7	• 2	.0	.0	•0	•0	•0	•0	•0	•0	9.	.1	1.0
S. D	1.320		.000	•000	.000	•000	.000	.000	.000	.000	.000	•236	1.461
TOTAL OBS.	558	481	527	510	558	510	527	527	510	558	540	558	6364

1210 WS FORM 0-88-5 (Det 50)

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA

PART C

A

The second of th

1

SURFACE WINDS

8. 3

Presented in this part are various tabulations of surface winds as follows:

1. Extreme Values - Peak Gusts: Derived from daily observations and presented by individual year and month for the entire period of record available. Speeds are presented in knots, while directions are given in 16 compass points from the beginning of record through 1963, and in tens of degrees starting in January 1964. When 90% or more of the daily observations of peak gust wind data are available for a month, the extreme is selected and printed. These values are then used to compute means and standard deviations for the entire period. Every month of a year must have valid observations present before the ALL MONTHS value is selected for that year. Means and standard deviations are computed when four or more values are present for any column.

NOTE: According to Circular N specifications, "peak gust data are recorded only at stations with continuous instantaneous wind-speed recorders."

2. Bivariate percentage frequency tabulations: Derived from hourly observations, these tabulations are a percentage frequency of wind directions to 16 compass points and calm by wind speeds (knots) in increments of Beaufort classifications. Percentages are shown by both direction and speed, and in addition the mean wind speed for each direction.

A separate category is provided on the form for variable winds, which are reported in some data sources. In these data where light and variable winds are reported with no directions but with speeds given, the speeds will be summarized in the appropriate groups opposite the column headed VAREL.

- a. Three tables are prepared for all surface winds included, and for all years combined as follows:
 - (1) Annual all hours combined
 - (2) By month all hours combined
 - (3) By month by standard 3-hour groups
- b. A separate annual table is also presented for surface winds meeting the following ceiling and visibility conditions: INSTRUMENT CLASS: Ceiling 200 through 1400 feet inclusive with visibility equal to or greater than 1/2 mile, and/or visibility 1/2 through 2-1/2 miles inclusive with ceiling equal to or greater than 200 feet.

STATION NO: 43310	FUKUOKA KYUSHU JAPAN/ITAZ	UKE AB LATITUDE: LONGITUDE: N 33 35 E 130 27			.808 9 me:
	STATION HIS	STORY AND WIND EQUIPMENT I	NEORMATION	<u> </u>	
DATE OF CHANGE	TYPE OF STATION CHANGE	WIND EQUIPMENT LOCATION	TYPE OF TRANSMITTER	TYPE OF RECORDER	HEIGHT ABOVE GROUND
Sep 1946	Itazuke AAB AAF Wea Sta Det 162	Not available	N/A	N/A	n/a
12-31-47	Itazuke AFB Det 20-6	Not available	N/A	N/A	N/A
12-31-49	Itazuke AB Det 20-6	Not available	N/A	N/A	n/a
4-2-53	Det 6 20 Wea Sq	Between E taxiway and runway	AN/GMQ-1	ML204B	Surface
4-14-54	No change	No change	No change	No change	15 Ft
4-4-57	Det 9 15 Wea Sq	On top of observing site	No change	No change	20 Ft
4-1-58	No change	At observation site	No change	No change	25 Ft
12-4-58	Det 37 30 Wea Sq	No change manage	· No change	No change	No chang
3-2-59	No change	Located in Base Weather Station	AN/GMQ-11	RO-2	No chang
4-6-60	Det 10 10 Wea Gp	No change	No change	No change	No chang
4-4-61	Det 11 1 Wea Wg	No change	No change	No change	No chang
12-3-62	No change	#1 - 250 Ft W of active runway 15 at th 2500 Ft marker	No change	No change	14 Ft
-	1 k m = 2	#2 - 250 Ft W of active runway 33 at the 1500 Ft marker	No change	No change	24.Ft
6-30-64	Det 11 20 Wea Sq	No change	No change	No change	No chang
				-	
	•	· ~.			

5 2×

Andrew Sept. Mar.

Page 2 C

DATA PROCESSING GIVISION ETAC. USAF ASHEVILLE, N.C. 28861

EXTREME VALUES

SURFACE HTNDS

(FROM DAILY OBSERVATIONS)

6 44

43310 STATION

FUKURKA KYUSHU JAPAN/ITALUKE AB

DAILY PEAK GUSTS IN KNOTS

MONTH	JAN		JAN		JAN		FEI	В.	MA	R.	AP	R.	MA	LY	טנ	N.	וטנ	L.	AUG	G.	SEP		oc	т.	N	 ov.	DE	c.	ALL	нѕ
58																	N	34	HNH		SSE		7	4 C						
55			SSE						ENL	27		29		28	NNH			69			NN		NK	27	S	69				
60		30		26			SE	2.8	SE	33			SSE	21		29			KSH		SSE		HNH	37	MSH					
61		35		29			HSH	34		32		25		27	SE	29		50			ΝŁ		NH	23	N	50				
62		36		30			kN#	42			SSF	35			S		MMM	33			SSE		NH	40	-					
63			HNK				S	29	S_	33		44	SSE	29	NNE	39	M	25	NNE	30	MNK	25	N	33	H	44				
64	29/	33	33/	35	28/	51	24/	41	27/	25																				
			_																											
													,										<u></u>							
			-																				ļ							
						-															_		<u> </u>							
											ļ																			
MEAN	36	. 3	3	1.0	3	8.7	3	4.3	2	9.2	3	1.2	2	6.3	3:	3.0	41	• 2	3	2.2	3	0.1	3	3.3	5	0.3				
S. D.	5.0	07	3.			890				920	8.						15.4			223		441	7.	062	13.					
TOTAL OBS		86		169		103		180		186		150		123	:	54	1	80		106		179	3	166	5	062				

1210 WS FORM 0-88-5 (Det 50)

EATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

							ALL							
	_													
SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED	
N	1.0	2.2	2.3	1.2	•1		.0	_ •c				6.8	7.4	
NNE	.7	1.1	1.0	.4	C	0			•0			3.3	6.6	
NE	1.1	1.4	_•9	• 2	.0	•0	.0					3.6	5.5	
ENE	5	• 5	• 4	•1	.0	0	.c	•0		•0		1.6	5.8 5.C	
E	• 9	.1	•4	.1	•0		•0	•0				2.1	5.C	
ESE	8	.6	.4		•0	•0						1.9	5.2	
SE	2.8	3.5	3.0	1.1	.1	•0	•0	•0				10.4	6.2	
SSE	2.6	4.1	3.4	1.3	1	•0	•0	•0				11.6	6.5	
5	2.1	2.9	1.8	. 8	.1	•0	.0	.0				7.8	6.2	
SSW	5	6	. 4	.2	• 0	_ • C	.0					1.8	6.1	
SW	. 5	.6	3_		.0	•0	.0	.0				1.6	5.5	
wsw	2_	4	. 4	2_	.0	2.				Ĺ		1.2	6.9	
W	.4	8	1.2		1		.0_	.0		.0		3.5	8.7	
WNW	. 4	. 8	1,5	1.5	. 3		.0					4.6	16.0	
NW	8	2.2	3.3	1.9	. 2	0_	.0	.0	<u> </u>	<u> </u>		8.4	8.4	
NNW	7	1.8	2.7	1.3		0_	0_	.0			[6.5	8.0	
VARBL		<u> </u>			<u> </u>	<u> </u>	<u> </u>	<u> </u>	ļ					
CALM		$\geq \leq$		$\geq \leq$	$\geq \leq$	23.3								
	16.2	24.2	23.4	11.4	1.3	•2	.0	.0	•0	•0		100.C	5.4	

TOTAL NUMBER OF OBSERVATIONS

158379

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETI

FUKUCKA KYUSHU JAPAN/I IAZUKE AB 46-64

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

Ľ

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64
STATION STATION NAME

ALL WEATHER
CLASS
CONDITION

CONDITION

JAN
MONTH
ALL
HOURS (LST.)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	• 5	1.4	1.5	1.2	• 1	• 0			i			4.7	8.4
NNE	• 5	8	• 8	• 2	•0							2.3	6.5
NE	.7	1.0	. 5	.1								2.3	5.2
ENE	.5	.3	•2	• 1								1.1	5.C
E	•6	• 5	•2	•0		_						1.4	4.4
ESE	.7	•6	• 2	• 1	•							1.5	4.9
SE	2.5	3.9	3.1	1.0	• 1	•0						10.5	6.2
SSE	2.4	5.4	4.1	- 8	•0	•0					30.%	12.7	6.1
\$	1.9	3.4	1.9	• 4	•	.0	l					7.6	5.6
\$SW_	•6	.7	- 3	• 1		•0						1.8	5.1
sw	•6	. 9	• 5	. 1								2.1	5.4
wsw	•3	.7	. 9	.4	•0	•0	I — — — — — — — — — — — — — — — — — — —					2.3	7.7
w	• 3	1.2	2.5	2.9	.6							7.6	10.5
WNW	• 3	1.1	3.2	5.4	1.5	.4	0				50.4	11.9	12.1
NW	.4	1.5	3.4	4.9	• 9	•2	•0					11.3	11.0
WWW	.3	.8	1.8	1.6	• 3	.0						4.8	9.9
VARBL													
CALM		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	\geq	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		14.1	
	13.1	24.2	24.9	19.3	3.5	.8	•0					100.C	7.1

TOTAL NUMBER OF OBSERVATIONS

1339C

45

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

•

SURFACE WINDS

600 FR

¥.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	48-64	FEB
STATION	STATION NAME	YEARS	MONTH
	ALL	WEATHER	ALL
		CLASS	HOURS (L S.T.)
		CONDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	.9	2.0	2.0	1.C	•0	•0						6.0	7.3
NNE	.7	1.2	1.2	• 5	•0							3.6	6.8
NE	1.1	2.0	1.2	• 3								4.6	5.6
ENE	• 5	•5	• 3	• 1								1.4	5•2
E	.7	•6	• 2	• 1	•0							1.6	4.8
ESE	•6	•6	•2	• 1	• C							1.5	4.6
SE	2.6	3.7	1.8	• 9	•1							9.C	5.7
SSE	2.4	5.1	3.0	. 7	• 1							11.3	5.9
S	1.6	3.3	1.8	• 7	• 1	•C	.c					7.6	6.2
SSW	.4	- 8	• 3	•c	•0							1.5	5.1
SW	•5	1.0	•5	.1								2.2	5.6
wsw	•2	•5	.6	.4	•0					[1.8	7.8
w	.4	1.1	1.9	1.7		•1						5.4	9.6
WNW	.4	1.0	2.3	3.1	.6	•2	.0					7.5	10.9
NW	• 5	2.0	3.8	3.9	• 5	.0						10.7	9.9
NNW	.6	1.5	2.6	2.2	•1							7.0	9.0
VARBL													
CALM	\boxtimes	$\geq \leq$	17.3										
	14.1	26.9	23.8	15.8	1.8	•3	.0					100.C	6.2

TOTAL NUMBER OF OBSERVATIONS 11544

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

43310

SURFACE WINDS

MAR

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

IOM		STATIO	I NAME					1	TEARS			-	OMIN
	_	. — — —	···		ALL WE								LL (LST)
					CI	A55						HOURS	(131)
	_				CONI	NOTION				_			
	_						··						
										, 			
SPEED (KNTS)	1.3	4.6	7 - 10	11 - 16	17 . 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN
DIR.	'''	4.0	7.10	11 - 10	1, 1, 21	22 - 27	20 - 00	34 : 40	41 - 47	70.33		70	SPEED
N	1.1	2.4	3.2	2.1	•2	•¢	•0					O	8.1
NNE	1.0	1.5	1.7	. 8	.0							5.1	7.1
NE	1.2	1.5	1.1	• 2								4.0	5.5
ENE	.6	• 5	.3	•0								1.4	4.8
E	. 8	.5	3	• 1	•0							1.6	4.6
ESE	6	.4	. 3	•1	•0							1.5	5.3
SE	2.3	2.4	2.1	1.3	1							8.2	6.5
SSE	2.1	3.4	2.5	1.2	1	.0			 _	ļ		9.4	6.6
S	1.8	2.7	1.5	. 8	0_							6.8	6.1
ssw	. 4	.4	2			0						1.2	5.8
SW	. 5	5_	3_	2_	0				<u> </u>			1.5	5.8
wsw	2_	5_		3_						L		1.5	1.8
W	4	. 8	1.7	1.6	2_		-0					4.6	9.6
WNW	3_		1.8	2.1	.5		.0					5.6	10.6
NW	7_	1.7	3.6	2.8	2_							9,1	9.0
NNW		2.0	3.2	1.9		0_	0_	ļ			26	8.C	8.2
VARBL	<u> </u>	<u> </u>	<u> </u>	<u> </u>	L			<u></u>	<u> </u>	<u></u>	<u> </u>	 	
CALM		$\geq \leq$	$\geq \leq$	><	$\geq \leq$	$\geq \leq$	21.6						
	14.7	22.0	24.3	15.5	1.5	.3	.0					100.C	5.9

TOTAL NUMBER OF OBSERVATIONS

12648

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLET

EUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

C

1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64	<u> </u>	APR
STATION	STATION NAME	YEARS	нонтн
	ALL WEATHER		ALL
	CLASS		HOURS (L S T.)
	CONDITION		

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.2	2.6	3.2	1.8	•0				i			8.8	7.6
NNE	.8	. 9	1.0	. 3	•0			i ———	Î			3.1	6.3
NE	1.0	• 9	• 5	.1								2.5	4.8
ENE	•5	.4	. 3	• 1								1.2	5.3
E	•8	• 5	•1	•0								1.4	4.3
ESE	.7	6_	.5	• 3	.0	•0			1			2.0	6.4
SE	2.1	2.7	3.0	1.8	•2	•0	i				i	9.8	7.3
SSE	1.9	3.3	3.4	2,2	• 3	•1					27.5	11.2	7.7
s	1.8	2.1	1.4	1.1	•2	• C	.0		1			6.5	6.9
SSW	.5	.5	• 3	• 2	•0	•0	1	1				1.5	6.4
sw	.6	.4	.3	•1	•0							1.4	5.2
wsw	•3	.4	.3	.1	•0	•0					 -	1.0	6.2
w	•6	1.1	1.2	. 8	.1	C						3.8	7.9
WNW	•5	.9	1.6	1.3	.2	•0	-0					4.7	9.2
NW	1.0	2.8	4.0	1.5	.1		1		 			9.4	7.6
NNW	.7	2.4	3.1	1.4	•1	i				<u> </u>	05.4	7.6	7.8
VARBL	,							 	1		<u>`</u> -		7.00
CALM	\geq	$\geq \leq$	$\geq \leq$	$\geq \leq$	><	$\geq \leq$	><	\geq		$\geq <$		24.1	
	14.9	22.2	24.0	13.1	1.3	•2	.0					100.0	5.5

TOTAL NUMBER OF OBSERVATIONS

12238

DATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	TAT
STATION	STATION NAME	YEARS	MONTH
	ALL I	WEATHER	ALL
		CLASS	HOURS (LST)
		CONDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.0	1.9	2.1	• 8	•1							5.9	7.1
NNE	.7	•7	• 5	• 2	•0							2.1	6.1
NE	1.1	1.0	.6	• 1	•0							2.9	5.1
ENE	6	• 5	.4	• 1								1.7	5.4
E	1.0	• 9	• 5	• 1								2.4	5 · C
ESE	. 9	•6	•6	• 1								2.3	5.1
SE	2.6	2.8	2.8	1.2	• 1	•0						9.5	6.4
SSE	2.7	3.4	3.4	1.7	• 1	•C						11.4	6.8
S	2.0	2.2	1.7	1.1	• 2	.0		l		L		7.1	6.6
SSW	• 5	• 5	. 3	• 3	.0							1.6	6.6
SW	•6	. 5	• 2	• 1								1.4	4.7
wsw	.4	.3	. 3	.1				<u> </u>	<u> </u>			1.1	5.9
W	.6	1.1	1.2	.6	.0	• C	<u> </u>		<u></u>			3.5	7.3
WNW	6	1.0	1.6	1.0	.1	<u></u>			<u></u>	<u></u>		4.3	8.3
NW	1.3	2.8	4.1	1.4	.1			<u> </u>				9.7	7.4
NNW	1.0	2.7	3.4	1.0	.1	.0	L		<u> </u>			8.2	7.2
VARBL		<u></u>	L	<u> </u>	L								
CALM	$\geq <$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	\geq	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		25.1	
	17.4	22.9	23.6	10.1	.7	.1						100.0	5.0

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Company of the second

inchial fall

13389

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKU	CKA KYU	SHU JA		AZUKE	AB	47-6	4						UN
STATION			STATION			ALL WE	ATHER			YEARS			4	LL (LS.T)
		_				соя	DITION							
	SPEED (KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND
	DIR.	1.3	2.6	2.4	• 8	•0		•0					7.2	SPEED 6.6
	NNE	.7	-8	• 5	• 2								2.3	5.8
	NE	1.2	1.1	. 7	.1	<u> </u>							3.1	5.C
	ENE	•5	• 3	• 4	.1	<u> </u>							1.3	5.5
	E	1.0	.7	.5	.1		ļ	<u> </u>					2.3	4.8
	ESE	.7	.5	• 5	.1	.0							1.9	5.6
	SE	2.1	3.2	3.7	1.4	.1	<u> </u>						10.5	6.8
	SSE	2.2	2.9	3.9	1.7	1 .1	•0						10.9	7.2
	S	1.8	2.3	2.0	1.4	•1	• i	.0	ļ				7.7	7.2
	SSW	-4	.4	•5	•/-	.0	.0						1.8	7.6
	SW	- 6	•6	.3	• 1	.0	 	<u> </u>					1.7	5.6
	WSW	•2	.3	• 2	.1	•0	<u>.c</u>	 					. 9	6.9
	w	•4	1.0	.6	.4	-0	.0		-0		•C		2.5	7.3
	WNW	.5	1.0	1.3	5	<u> </u>	•0		<u> </u>	 _			3.4	7.4
	NW	1.1	2.9	3.9	1.3	• 1	-0				ļ		9.4	7.4
	NNW	•9	2.4	3.3	1.2	.0		 	ļ	 		ļ	7.9	7.4
	VARBL	ļ			ļ	<u></u>	ļ.—	Ļ	<u></u>	Ļ	Ļ			
	CALM	$\geq \leq$	$>\leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	25.3	
		15.7	23.2	24.9	10.1	.7	.1	.0	.0	l	.c]	100.C	5.1

TOTAL NUMBER OF OBSERVATIONS

12954

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE. N. C. 28801

(

SURFACE WINDS

1

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	<u> FUKU</u>	JKA KYU			AZUKE	AB	47-6	4						UL
STATION			STATIO	N NAME		_			'	TEARS				ONTH
		_				ALL HE								LL_
						GI	ASS						KOURS	(L \$.T.)
		_				CON	POITIO							
											-			
	SPEED													MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.													SPEED
	N	1.0	1.9	1.4	• 3								4.5	5.9
	NNE	.4	• 7	• 3	• 1								1.4	5.1
	NE _	. 8	. 8	.4	.1								2.1	4.8
	ENC	.4	.4	• 3	. 1	•0	. c	•0	•0				1.3	6.2
	E	1.0	1.1	. 8	. 1			•0					2.9	5.4
	ESE	.6	• 9	• 8	• 2	0							2.6	ა∙2
	SE	2.1	4.6	7.0	2.1	•1			L				15.8	7.3
	SSE	1.5	4.5	6.5	3.0	• 2	.1						15.8	7.9
	5	1.6	3.2	4.6	2.8	• 2	<u>. c</u>	¦					12.3	8.0
	SSW	.4	• 7	1.2	. 8	.1			, †		L	<u> </u>	3.2	8.3
	SW	.6	.7	-8	.4				<u> </u>	<u> </u>			2.4	6.7
	WSW	.2	. 3	• 2	.0	. C	ļ	<u> </u>	<u> </u>				• 8	5.8
	w	-4	7	•6_	.2	.0			<u> </u>				1.8	6.3
	WNW	.3	.7	• 5	.2	-0	· 		 		<u> </u>	<u> </u> i	1.7	0.7
	NW	• 9	2.2	3.3	.5	• 0	-0-			<u> </u>	<u> </u>	i	7.0	6.9
	NNW	•6	1.9	2.6	-4	0	•0-	ļ		·			5.5	6.8
	VARBL					_	ا		<u></u>		 	<u></u>	<u> </u>	
	CALM	><	><	><	><		><	!><	$\triangleright \!$	><	><		18.7	
									1	 -		<u> </u>		

TOTAL NUMBER OF OBSERVATIONS

13382

EATA PRUCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

AUG

χ,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUC	KA KYU	SHU JA		AZUKE	AB	47-6	4		YEARS				UG ONTH
		_				ALL WE	ATHER ASS							LL (L \$ T.)
		-		·		CON	DITION							
	SPEED (KNTS) DIR.	1 - 3	4 · 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
Ì	N	.9.	2.1	2.2	.6	• 1	.0						5.9	6.9
į	NNE	.7	.7	• 5	• 3	• 0	•0						2.3	6.5
	NE	. 8	1.0	. 8	• 2	• C	.0						2.9	<u>6.0</u>
į	ENE		.6	. 8	5	•1_	.0	.0			c		2.5	<u> </u>
	E	. 9	1.0	1.2	4_	1	<u> </u>	.0	0		ļ		3.7	6.8
	ESE		6_	8	2_		0	ļ		<u> </u>	<u> </u>		2.4	<u>\$ • 6</u>
	SE	2.7	3.6	4.2	1.2			-0	0_	<u> </u>		ļ	11.9	
	SSE	2.2.	3.8	4.0	1.6	2_		-0	0_		ļ		11.9	7.2
	s		3	2.0	9_		0			 	 	 _	8.3	6.5
ì	SSW	5_	<u></u>	6_	3_	0_		<u> </u>		 	 	 	2.1	<u>6.5</u>
	SW		4	3_			 			 	 	 	1.3	<u> 5.4</u>
	wsw		2	2_	بمعــــا	0_			ļ	 	 		- 5	6.5
	WNW		4	4_	-1	0_	0			 	 	 	1.8	6.7
	NV/	3	7	6_			 	 	 		 -	 	7.2	6.9
	NNW	9	2.4	3.3	1.3	0	•0	 	 -	 	 	 	7.8	7.0 7.7
	VARBL	8_				e	aU	 	 			 	1-0	
	CAJM	$\geq \leq$		$\geq \leq$	$\geq \leq$	\geq	\geq	$\geq \leq$	$\geq \leq$	\geq			26.1	
			22.	25 5	0 /	, ,	2	,	,		_		100 0	5 1

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

A STATE OF THE STATE OF

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

TOTAL NUMBER OF OBSERVATIONS

13524

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

EUKUC	KA_KYU	SHU JAI	PANII	AZUKE	AB	46-6	<u> </u>		TEARS `				EP
					ALL WE	ATHER						Α	LL
	_				CI	ASS						HOUR	(L S.
	_				CON	DITION							
													
SPEED (KNTS)		1										%	ME WI
DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	76	SPE
N	1.3	2.8	2.9_	1.2	• 2	•1	.0		 -			8.7	7
NNE	1.0	1.6	1.4	.5	•1	c_						4.5	ė
NE	1.5	2.0	1.3	.3	.0	•0	•0					5.2	5
ENE	5		.4_	• 1	•0	<u> </u>	•0					1.6	6
E	1.1	.7	•4	• 1								2.2	4
ESE	.9	•6	• 3	•1	•0	•0						2.0	5
SE	3.4	3.7	2.6	. 8_	• 1	•0	0_					10.6	5
SSE	2.8	3.2	2.6	1.1	•1	•1	•0	•0.				9.8	
5	2.4	2.3	1.2	.4	•0	C_	•C_	0_				6.4	5
SSW	.7	.7	• 3	. 2	.0	• C	•0					1.9	5
SW	.6	5_	•2	• 1	.0	. 0_						1.4	
wsw	•2	• 2	• 2	- 1								.7	2
w	.5	.7	• 5	•1	.0	•0_						1.7	9
WNW	• 3	• 7	• 7	.2								1.9	6
NW	1.0	2.3	2.1	. 3	.0	•0		.0				5.7	- 6
NNW	8_	2.0	2.6	.6	.0	•0						6.1	7
\ ARBL													
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$			$\geq \leq$		29.6	
	18.7	24.6	19.7	6.3	.6	.4	.1	•0				100.0	4

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

* 50

E.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKU	LKA KYU			AZUKE	AB	46-6	4						10 1
STATION			STATION	. NAME		-				YEARS				ONTH
		_				ALL WE								LL
						CI	ASS						HOURS	(LST)
		_					DITION							
						· ·								
		_												
	SPEED	[1	MEAN
	(KNTS)	1.3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.]			SPEED
	N	1.3	2.7	3.4	1.7	•1	•0	•0	•0			20.6	9.3	7.7
	NNE	1.2	1.9	2.0	• 9	• 1				•0			6.1	7.C
	NE	1.5	2.2	2.1	• 3	•0							6.2	5.9
	ENE	.6	• 7	. 8	• 1	•0							2.2	5.6
	Ε	1.0	•8	.3	•0								2.1	4.3
	ESE	1.1	•6	• 1	• 1	•0						}	1.9	9 و ز
	SE	3.0	2.5	1.1	• 3	• 0							6.9	4.7
	SSE	3.6	3.1	1.2	• 2	•0						21.8	8.1	4.5
	S	3.C	2.7	• 9	• 2								6.8	4.5
	SSW	.7	.5	.1	.0	.0							1.4	4.2
	SW	.5	- 3	• 2	• 0		<u></u>						• 9	4.5
	WSW	• 3	• 2	.1_	.0								. 7	5.2
	W	.3	.4	• 5	• 3	• 0							1.6	7.4
	WNW	. 3	.6	. 9	.5	.1							2.4	8.4
	NW	.7	1.7	2.0	.8	.1							5.3	7.5
	NNW	.6	1.5	2.1	. 9	.0	.0	.0	.0				5.2	7.9
	VARBL	Ì					<u> </u>		<u> </u>					
	CALM			><	><	><	><	><	><	><	><	$\triangleright < 1$	32.8	1
			 	[[[1			1			

TOTAL NUMBER OF OBSERVATIONS

14129

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE. N. C. 28801

> NW NNW VARBL

CALM

€.

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	JNUL	JAA NTU	SHU JA	PANTI	ALUNE	AD	40-0	7						
STATION			STATION							YEARS				IONTH
						ALL WE	ATHER						А	LL
				****			LASS						HOUR	\$ (L S T.)
						CON	DITION							
	SPEED													MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.										l i			SPEED
	N	1.3	2.2	2.2	1.3	•1					i		7.1	7.4
	NNE	.8	1.4	1.5	• 5	•0							4.2	6.8
	NE	1.5	2.1	1.3	. 4	•0							5.2	5.7
	ENE	• 8	.8	•5	•1								2.1	5 · C
	E	1.1	•7	.4	• 1								2.2	4.5
	ESE	1.1	•6	.3	•1								2.1	4.4
	SE	4.3	4.0	1.6	. 5	•0							10.3	4.7
	SSE	4.1	4.6	2.0	• 5	•1	•0						11.3	5.C
	S	3.0	3.4	.9	• 2	•0							7.5	4.6
	SSW	.7	•7	•2	•0	•0							1.6	4.5
	SW	•6	•5	•2	.0	•0					1		1.3	4.5
	WSW	• 3	.4	.4	• 1	•0							1.1	5.9
	W	•5	•7	1.2	•6	•1	•0						3.1	8.0
	WNW	•3	•5	1.4	• 9	•2	•0	•0					3.4	9.4
	NW	•7	1.7	2.5	1.5	•1	•0						6.5	8.1
	NNW	٠.6	1.3	2.3	1.1	•1							5.4	8.0

TOTAL NUMBER OF OBSERVATIONS

13678

4.5

25.3

100.0

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

18.9

7.9

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE. N. C. 28801

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

SURFACE WINDS

DEC

郡 我了

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

46-64

51A110A			318110	IL NAME						ICARD			-	IONIN
						ALL WE	ATHER						Δ	LL
		_				c	LASS			*****			HOUR	\$ (L S.T)
		_												
						CON	MOITION							
		_												
	SPEED	- 	l	T										MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR		[[_ [#!	SPEED
	N	.7	1.6	1.6	1.0	• 1	.0						5.C	7.7
	NNE	.4	. 9	.6	.2	• U							2.1	6.4
	NE	• 9	1.0	. 4	-1	•0							2.5	4.9
	ENE	.4	•2	.1	.0								. 7	4.5
	E	.6	.4	• 1					1				1.2	3.9
	ESE	.7	• 5	. 2	-0								1.5	4.1
	SE	3.6	5.1	2.5	• 5	•0							11.7	5.2
	SSE	3.5	6.3	4.6	. 8	• 1	.0						15.3	5.9
	S	2.3	4.4	1.6	.3	• 0							8.8	5.2
	SSW	.7	•6	. 2	•0								1.6	4.4
	SW	• 5	. 8	.4	- 1								1.8	5.5
	WSW	• 2	.7	• 7	. 3	.0	.0						1.9	7.6
	W	5	8	1.8	1.8	. 3	.1		1				5.2	9.7
	WNW	_ 4		2.1	2.9	. 8	. 2	٥.					7.2	11.2
	Wri	.5	1.9	3.3	3.8	• 5	.1						10.C	10.0
	NNW	.4	1.1	2.1	1.6	• 2	.1	.0					5.5	9.4
	VARBL													
								\sim	\sim	\sim			10 1	

TOTAL NUMBER OF OBSERVATIONS

14132

5.9

100.0

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

mideral

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

EUKUCKA KYUSHU JAPAN/ITAZUKE AB

SURFACE WINDS

TOTAL NUMBER OF OBSERVATIONS

1674

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

	_			···········	ALL WE	ATHER							-0200
	_				CON	NOITION							
SPEED												_	MEAN
(KNTS) DIR	1 - 3	4.6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
										<u> </u>			SPEED
N	-4	. 9	. 8	• 7	.1					ļ		2.9	7.8
NNE	-4	•2	<u> • 1</u>	•1								- 8	5.2
NE	.7	.7	• 2	.1								1.6	4.5
ENE	-6	.2	.1							 		1.C	3.8
E	1.2	. 5	1_									1.8	3.3
ESE	1.3	- 8	.1	1								2.3	4.1
SE	3.8	5.9	2.5	.7	•2	•1				ii		13.2	5.6
SSE	2.9	8.1	4.7	-4	.1							16.1	5.7
s	2.7	3.6	2.0	• 2					L			8.5	5.2
ssw	.8	1.0	3_									2.1	4.5
SW	5	.7	.4	-1								1.6	5.1
wsw	.2	.7	- 8	• 5	.1							2.2	8 • G
w	.1	• 5	1.8	2.4	. 4	• 1						5.2	11.2
WNW	.2	-6_	1.9	5.0	1.7	.4	-1					9.8	13.4
NW	•2		2.3	5.2	• 5	• 2	•1					9.1	12.C
NNW	.2	.4	. 8	1.1	• 2	.1						2.7	10.2
VARBL]												•
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	\times	\geq	\times	><	$\geq \leq$	><	><	$\geq <$	19.1	
	16.2	25.3	18.9	16.5	3.1	.7	•2					100.C	6.3

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

i. *

i L

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

77710	1 000	CIVA VIC	JOHO JA	L WIAN T I	MEUNE	MU	71-0	, 7					U	,,,,,
STATION			STATIO	N HAME						YEARS				OKTH
						ALL WE	ATHER						0300	-0500
		_		*		c	LASS						HOURS	(L S T.)
		_												
						CON	DITION							
		_												
		ii———									 -			
	SPEED (KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27			l .		\\	ا ره	MEAN
	DIR.	1.3	4.0	7.10	11 - 10	17 - 21	22 · 2/	28 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
	N N	.5	.8	1.0	1.C		•1				 -	{	3.3	8.6
	NNE	•4	•2	.1	1.0		•-		 	-	 		.7	4.6
	NE NE	• 7	•5	.2			 	 	 -	 	╁╼╼╌┼		1.3	4.1
	ENE	• 3	•4	•2							 		8.	4.6
	Ε	1.0	•5	.2		_	<u> </u>		 		 		1.7	3.9
	ESE	.8	• 5	•2	.1	•1		 			 		1.7	5.1
	SE	3.6	4.2	4.0	1.0	•1					 		12.8	0.0
	SSE	3.1	7.9	4.9	1.C	•2				<u> </u>			17.1	5-9
	5	2.5	4.2	1.5	• 2					 			8.4	4.9
		/ 			 -									

HINC	• 4	• 4	. • .			<u> </u>)	J	1	J]	• •	7.0
NE	.7	• 5	• 2							<u> </u>		1.3	4.1
ENE	-3	-4	• 2									.8	4.6
Ε	1.0	.5	• 2									1.7	3.9
ESE	•8	• 5	•2	.1	• 1							1.7	5.1
SE	3.6	4.2	4.0	1.C	• 1							12.8	5.0
SSE	3.1	7.9	4.9	1.C	<u>2</u>							17.1	5.9
S	2.5	4.2	1.5	• 2								8.4	4.9
SSW	• 5	. 9	4	• 1								1.9	5.3
SW	•2	•2	• 2	• 1								.7	6.1
WSW	•2	•4	7	• 5	• 1							1.9	9.1
W	• 1	1.1	1.5	2.6	.4							5.7	10.8
WNW	•1	.8	2.7	5.3	1.6	<u>•</u> 5						10.9	12.8
NW	•2	. 3	3.3	5.1	.7	• 5						10.C	12.1
NNW	•2	•2	1.3	1.1	.1							2.9	10.2
VARBL									<u> </u>				
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	X	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq <$	$\geq \leq$	18.1	
	14.2	23.0	22.6	17.9	3.1	1.1						100.C	٤.6

TOTAL NUMBER OF OBSERVATIONS

1674

1210 WS FORM 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

₩**#**#\.]

,

!

. .

4.

: 24

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

÷ , *

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	JAN
STATION	STATION NAME	YEARS	MONTH
	ALL WE	EATHER	0607-0800
		CLASS	HOURS (L S T.)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	.4	.8	1.1	1.3	•1			i	ì——			3.6	٥.3
NNE	.4	•5	• 5	.1								1.6	5.8
NE	.5	1.0	• 3									1.8	4.7
ENE	.4	•2	•2									8.	4.3
E	•8	.3	• 2							I		1.3	3.9
ESE	.7	•9	• 2	•2	•1							2.0	5.7
SE	3.5	5.3	3.3	1.1				1				13.3	5.8
SSE	2.9	6.0	5.3	1.1	.1	.1						15.5	6.3
S	2.4	4.7	2.8	•2								10.2	5.4
SSW	.7	1.0	.4	• 1								2.1	4.9
sw	•4	.7		•2								1.3	5.3
wsw	•1	.4	•5	.4		•1	i .					1.5	8.8
w	•2	.7	1.7	2.2	• 5							5.3	10.9
WNW	. 4	.8	2.6	5.0	1.1	.6						10.5	12.3
NW	•2	.7	3.2	5.0	1.1	.3						10.5	12.0
NNW	•1	.4	1.0	1.4	.1							2.9	10.7
VARBL													
CALM	> <		><	><		><	$\geq <$		><	\geq	$\geq \leq$	16.0	
	14.2	24.3	23.3	18.3	2.9	1.0						100.C	6.7

TOTAL NUMBER OF OBSERVATIONS

1674

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

pe 21

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKU	CKA KYU	SHU JA	PAN/IT			AN							
21,11101		_				ALL WE	ATHER			YEARS			0900	-1100 (L S.T.)
						COM	DITION							
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
	N	•3	1.2	1.4	1.7								4.6	9.2
	NNE	.4	.7	.9	• 2	i							2.2	6.9
	NE	.4	• 7	.6	• 1								1.9	6.0
	ENE	.4	.4	.4	• 1								1.3	5.9
	Ε	.1	• 8	•2	.1								1.2	5.5
	ESE	.4	. 5	.4	• 3								1.6	6.6
	SE	1.5	3.8	4.8	2.3			<u> </u>					12.4	7.5
	SSE	2.0	6.6	7.7	1.7								18.0	6.9
	S	1.7	4.7	3.3	.7					ļ			10.4	6.1
	SSW	.4	• 5	.4	.1				<u> </u>	 			1.3	5.4
	SW	8_	.7	.3		ļ			<u> </u>				1.8	4.2
	wsw	.2	.5	1.3	•2		<u></u>	L			L	ļ	2.3	8.C
	W	.4	.8	2.0	2.7	•4	<u></u>						6.5	10.6
	WNW	-1	.8	3.0	4.6	1.7	.2	-1		ļ	ļ		10.5	12.5
	NW	.4	•7	1.7	4.7	1.1.	- 3	-1			<u> </u>	ļ	9.0	12.4
	NNW		-4	1.6	2.6		ļ	<u> </u>		ļ			5.3	11.6
	VARBL		ļ			<u> </u>			<u> </u>	<u></u>	Ļ		<u> </u>	
	CALM	$\geq \leq$	<u> </u>	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	<u>><</u>		\geq	<u> </u>		10.1	
			220	1 20 0	1 22 4	1 20		1 .		Į.	1	l i	اء ممدا	1 7 9

TOTAL NUMBER OF OBSERVATIONS

1674

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

JAN

1200-1400 HOURS (L S T.)

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

ALL WEATHER

•					CON	MOITID							
,	_						, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	·				<u>. </u>	
SPEED (KNTS) DIR.	1.0	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	- 4	1.6	2.4	2.2	• 2	.1	1					6.9	9.
NNE	- 3	. 8	1.5	•6	.1		1	T		1		3.3	8.
NE	. 5	1.2	1.1	• 5								3.2	6.
ENE		.2	.7	• 2								1.1	8.
E	•2	.4	• 3	• 2								1.2	7.
ESE	.1		•1	•1								.2	6.
SE	1.0	1.5	3.5	1.4								7.3	7.
SSE	.8	1.5	3.6	1.3	• :					<u> </u>		7.2	7.
S	.7	2.2	1.8	1.0								5.6	7.
SSW	.7	.5	.1	•1			<u> </u>			<u> </u>		1.4	4.
SW	.5	. 8	.9					<u> </u>				2.2	5.
wsw	.2	.9	1.1	- 4				<u> </u>	<u> </u>		l	2.7	7.
W	.4	1.5	4.0	4.4	1.0	1					<u> </u>	11.3	10.
WNW	.4	2.0	4.4	7.3	2.2	.4	<u> </u>		<u> </u>		L	16.6	11.
NW	.3	2.8	5.1	6.3	1.1		<u> </u>	<u> </u>	<u> </u>	<u> </u>		15.7	10.
WNN	.4	1.4	2.9	2.4	5	.2	1	1		! !	L	7.8	10.

TOTAL NUMBER OF OBSERVATIONS

1674

8.9

6.4 100.C

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

Ti Ei

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	<u>FUKUC</u>	KA KYU			AZUKE	AB	47-6	4						AN
STATION			STATION	NAME						YEARS	_			ONTH
						ALL WE	ATHER						15CO	-170C
							A55						HOURS	(L S.T)
		_				CON	DITION							
		_												
ſ	SPEED													MEA:1
	(KNTS)	1.3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	W. YD
	DIR.								ŀ	}		ļ		SPEED
ì	N	•8	2.3	2.7	1.6	• 2		 		 		1	7.6	8.1
İ	NNE	•5	1.8	2.1	.4								4.2	1.2
İ	NE	.4	1.5	.8	.4								3.C	6.2
i	ENE	• 1	3	• 3	.1			 		-			. 8	6.7
i	E	•1	:1	•2	•1								• 5	7.4
ŀ	ESE	•1	•5	•2		 		<u> </u>					. 8	5.3
İ	SE	.4	1.6	1.9	.3								4.1	7.1
Į.	SSE	•8	1.3	1.8	•5						i		4.5	6.9
	<u> </u>	.8	1.5	1.3	.5	•2	•1		 	†	t		4.2	7.1
	SSW	•3	•2	•5_	•1	••-				 			1.1	6.9
	SW	.8	1.6	• 7	•1								3.3	5.2
ı	wsw	•5	1.0	1.0	.7		i ——			<u> </u>	<u> </u>		3.2	7.4
		.7	2.2	4.0	3.6	.7	.3			 			11.4	10.2
	WNW	•5	2.6	5.0	6.3	1.7	•2						16.3	10.9
	NW	1.1	4.5	7.7	5.7	1.1	.2		1	 -			20.2	9.5
	NNW	•6	1.9	4.2	2.0	.5			 	 			9.2	9.C
	VARBL	- •	1.07	7.6	1 - 5 - 5		1	1						
													4.8	
	CALM			1					\smile				1	i

TOTAL NUMBER OF OBSERVATIONS

1673

8.4

100.0

EATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

SURFACE WINDS

TOTAL NUMBER OF OBSERVATIONS

1674

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

4331C	FUKL	KA KYU	SHU JAI	PAN/II	AZUKE .	AB	47-6	4	 ,	EAR\$				AN
						ALL WE	ATHER							-2(C(
						CONI	NOIT,ON							
	SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 5	34 - 40	41 - 47	48 - 55	≥:56	%	MEAN WIND SPEED
	N NNE NE	1.0	2.C 1.6	1.4	.6 .1	1							5.1 3.6 3.4	5.1 4.3
<u>.</u>	ENE E	1.2 1.4 1.0	1,9 .7	.3 .1 .2									2.2	3.6
ļ	SE SSE	2.2 2.3	3.8 5.0	1.3 1.6	.4	<u>.1</u> <u>.1</u>							1.7 7.7 9.3	4.5 5.4 5.3
	S SSW SW	1.9 .7 1.3	2.7	.9 .2	.1								5.7 1.7 3.8	5.C 4.3 5.2
ļ	wsw w	.7	1.7 1.1 2.0	1.1 2.7	1 2.5	.7	1						2. ^ç 8. 6	5.9 9.7
	NW NW	.5 .7 .5	1.4	3.6 2.6 1.4	5.1 3.2 1.1	1.1 .6 .2	.1						11.6 8.6 4.5	11.6 17.3 8.7
	VARBL CALM	<u> </u>		<u></u>	\leq	$\geq \leq$	\geq	\leq	\leq	\geq	\geq	\leq	17.7	
		17.8	28.1	19.2	13.8	2.9	,5		<u> </u>	<u> </u>	<u> </u>		100.C	6.0

CATA PROCESSING CIVISION EIAC, USAF ASHCVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

331C	FUKUI	CKA KYU	SHU JA		AZUKE	AB	47-6	4						AN
FIREION		_				ALL WE	ATHER			YEARS	_		2100	-2300 (L#T.)
		_				CON	DITION							
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
	N	.4	1.3	.9	1.0								3.6	7.9
	NNE	- 5	•5	•1	• 1								1.3	5.0
	NE	; 3	.4	• 2	• 2								2.1	4.3
	ENE	.8	• 3	• 1									1.2	3.7
	E	.8	• 5	1									1.4	3.6
	ESE	1.1	•5	•2									1.8	3.6
	SE	4.3	5.3	3.1	6	.1							13.3	5.2
	SSE	4.1	6.4	3.0	. 4		• 1						13.9	5.2
	<u> </u>	2.3	4.0	1.3									7.6	4.7
	SSW	-8	1.1	.5	.1		.1_			 			2.5	5.5
	SW	.5	.7	•5	.4					<u> </u>		<u> </u>	2.1	6.1
	WSW	•2	.5	.7	• 5								2.0	8.6
	W	.2	1.0	2.6	2.7	.4				ļ	ļ		6.9	10.4
	WNW	-2	<u>• 5</u>	2.2	4.5	1.3	.4	.1	ļ			 -	9.0	12.9
	NW	.2	.8	1.6	3.8	.7	•2		ļ			 	7.4	12.1
	NNW	.2	.7	- 9	1.1	.2			 			 -	3.1	16.2
	CALM		$\overline{}$		> <	> <	> <	> <	\supset	> <	> <		20.8	
		17.9	24.6	18.0	15.3	2.6	.7	.1	,				100.C	5.9

TOTAL NUMBER OF OBSERVATIONS

1673

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

*# * *

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

FEB

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUC	KA KYU	SHU JA	PAN/II	ALUKE	АВ	48-6	4					F	£B
STATION			ROITATE	MAME		ALL WE	ATHER			rears			0000	ONTH -C2CC
		_					DITION						NOVA:	. (
	SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
i	N	.6	1.5	• 3	• 4		.1						2.8	6.5
	NNE	.6	1.1	• 3	• 1								2.1	5.2
	NE	1.5	1.5	•6	• 1								3.7	4.8
	ENE	1.0	• 3	• 2									1.5	3.8
j	£	6	•6	•1		• 1							1.5	4.6
	ESE	1.0	• 9	• 2									2.1	3.7
	SE	4.1	6.3	1.5	• 9	• 1							12.9	5.1
	SSE	4.0	7.8	3.0	• 6								15.3	5.2
	S	2.1	4.4	2.1	.6								9.1	5.6
	SSW	- 3	.7	• 3									1.2	5.1
	SW	•6	1.2	. 3	. 1								2.1	5.2
	wsw	3	• 3	• 3	. 1	i			L			<u> </u>	1.0	5.8
	w	.4	.7	1.9	1.8	• 2	.1						5.1	9 • 8
	WNW	• 3	• 5	1.3	2.4	.6	1		L				5.1	11.5
	NW	.4	• 9	1.1	2.4	.2							5.C	16.2
	NNW	• 3	.8	.8	1.0								3.0	9.0
	VARBL													
	CALM			><	><	> <		><	><		> <		6.4	

TOTAL NUMBER OF OBSERVATIONS

4.7 1443

100.C

1210 WS JUL 84 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

17.9 29.5 14.4 10.4

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

G

U

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE	AB	<u> 48–64 </u>	FEB
STATION	STATION NAME		YEARS	HORTH
		ALL	WEATHER	0301-0500
			CLASS	HOURS (LST.)
			CONDITION	

SPEED (KNTS) DIR.	1 · 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPFED
N	.7	1.2	1.0	.7					i			3.5	6.9
NNE	.6	.6	.8	•1				ļ				2.C	6.1
NE	•6	1.7	•6	•1								2.9	5.1
ENE	•1	.5	•1			•						- 8	4.9
E	1.5	.6	.1				,	,				2.1	3.5
ESE	1.0	1.1	• 2									2.4	3.9
SE	3.7	5.1	1.9	. 8	•1				Ī ——			11.4	5.2
SSE	4.0	7.4	3.2	•6	•1							15.2	5.4
S	2.4	5.0	1.8	3	•1			i				9.6	5.3
SSW	•4	1.0	.4		• 1					I		1.9	5.2
SW	.4	.6	• 3	• 1								1.5	5.2
wsw		•1	. 8	.3								1.2	9.2
w	.1	•5	1.3	1.7	.4	•1						4 • C	11.2
WNW	• 3	• 3	1.5	2.5	.4	• 3						5.3	11.7
NW	•2	1.1	1.5	3.5	• 5	•2	1					7.1	11.5
NNW	•2	•9	1.2	1.6	• 1		I					4.0	9.3
VARBL													
CALM	$\geq \leq$	><	$\geq \leq$	$\geq \leq$	$\geq \leq$	\geq	$\geq \leq$			$\geq \leq$		25.0	
	16.2	27.7	16.6	12.3	1.7	•6	J					100.0	5.2

TOTAL NUMBER OF OBSERVATIONS 1443

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE. N. C. 20801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

4331C	FUKU	JKA KYU	SHU JA		AZUKE	AB	48-6	4		TEARS				EU ONTH
•							ATLIN			LEARD				-0800
		-				ALL WE	AIHER							(LST)
						•								. (,
		-				CON	DITION							
		_									_			
	SPEED													MEAN
	(KNTS)	1 - 3	4-6	7 - 10	11 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.	{{										i i	[SPEED
	N	. 8	1.9	1.0	• 8								4.5	7.C
	NNE	. 5	1.2	. 6	. 4								2.7	6.4
	NE	.5	1.7	. 7	.1								2.9	5.3
	ENE	.2	• 3	1	. 1								• 6	5.2
	E	.7	8	.1				<u> </u>			<u> </u>		1.6	3.8
	ESE	1.0	.7	. 3									1.9	4.1
	SE	3.6	5.5	2.6	. 8			[<u> </u>				12.6	5.4
	SSE	3.5	8.2	4.4	.4	.1							16.6	5.5
	5	2.3	4.4	1.7	•6								9,1	5.7
	SSW	.5	. 8	.3									1.5	4.7
	SW	-6	. 7	.6	• 3			ļ	ļ		ļ		2.1	6.1
	WSW	-1	.3	<u> </u>		1_		 	<u> </u>				. 9	8.0
	W		- 8	9	1.0	3		 	ļ		 		3.1	10.C
	WNW	1	6	1.8	2.4		•2	ļ	ļ				5.6	11.5
	NW		- 3	2.4	4.0	•6			ļ				7.4	11.6
	NNW	-4	- 8	1.2	1.5	- 2		 	 		<u> </u>	<u> </u>	4.1	9.3
	VARBL								-				22 7	
	CALM		><	<u> </u>	<u> ><</u>		[/><		\searrow	!><			22.7	

TOTAL NUMBER OF OBSERVATIONS

1443

100.C 5.4

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	<u>EUKU(</u>	<u>IKA KYU</u>	SHU JA	PAN/IT	AZUKE	AB	48-6	4		YEARS				LH
SIMILOR			SIAILO	I DAME			4.54.50			IEARD				-1100
		_				ALL WE	AIHEK							-115 C
		_				CONI	PITION							
		-								·				
	SPEED													MEAN
	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.													SPEED
	N		1.4	2.2	1.0				L				5.3	7.9
	NNE	,7	1.0	1.5	•6								3.9	7.2
	NE	• 8	1.5	1.9	• 2								4.4	5.4
	ENE	.4	.4	. 3									1.1	5.1
	E	4	.3	.4	• 2								1.3	6.4
	ESE	.4	•6	.4	• 3	• 1							1.7	7.2
	SE	1.2	3.0	3.5	1.9	•1							9.8	7.4
	SSE	1.7	5.5	6.7	1.3	.1			Ĭ				15.2	7.C
	5	1.8	3.3	2.9	1.0	.1	•1	•1					9.2	7.1
	SSW	• 5	1.3	.5									2.3	5.C
	\$W	.6	1.5	. 8	• 1								2.9	5.8
	wsw	• 3	1	.7	• 3	• 2							1.7	9.2
	w	.6	1.1	1.7	1.9	.3							5.5	9.3
	WNW	.3	•4	2.5	2.6	.6	•3	•1					6.8	11.6
	NW	.8	1.0	3.0	4.7	1.0							10.5	11.0
	NNW	.5	1.5	2.1	2.0	.1							6.3	9.0
	VARBL													
	CALM					>							12.1	
			\vdash					\models						
		и	I .	I	1				1		1		1 2 2 2 2 1	ا م د ا

TOTAL NUMBER OF OBSERVATIONS

1443

DATA PROCESSING CIVISION ETAC. USAF ASHEVILLE. N. C. 288C1

SURFACE WINDS

X.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKU	CKA KYU	SHU JA	PAN/II	AZUKE	AB	48-6	4		YEARS				ONTH
						ALL NE	ATHER						1200	-1400
													noun	(6 \$.1.)
		_				CON	DITION							
ſ	SPEED									_	I	•		
	(KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
	N	.6	2.1	2.6	1.7								7.0	8.3
[NNE	.2	. 8	1.9	1.2	.1							4.2	9.0
į	NE	.6	2.6	1.6	. 8								5.6	6.8
ļ	ENE	2	. 4	.8	.4								1.9	8.0
[E	3_	3_	•.2_									1.1	6.2
1	ESE		• 4				<u> </u>						. 4	4.7
ļ	SE	6	1.3	1.7	1.2	.1							4.9	8.1
ļ	SSE	6	1.7	1.9	1.0	2							5.5	7.7
1	<u>\$</u>	8_	2.5	1.7	1.0			<u> </u>	ļ		ļ		6.0	7.2
	SSW	2_	.3_	.3			ļ						- 9	6.2
ļ	SW	3_	.5	3_	.3		ļ			<u> </u>		<u> </u>	1.5	7.0
ļ	wsw	3_	5_	4	9_		 			ļ			2.1	8.9
	W		1.5	3.0	2.6	4	<u>_</u>		 		ļ 		8.1	9.8
ļ	WNW	6_	1.7	3.4	5.2	1.2	2_		 				12.3	11.1
}	- NW	6_	3.0	8.0	7.6	6				ļ	 	ļ	19.8	10.0
ļ	NNW	4_	1.5	5.6	4.7				 -	ļ	<u> </u>		12.6	16.1
ļ	VARBL	<u> </u>			_				<u></u>		 			
ļ	CALM		$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	<u> </u>	$\geq \leq$	<u> </u>	$\geq \leq$	6.¢	
		7.0	21.1	33.3	29.2	3.0	4						100.c	8.6

TOTAL NUMBER OF OBSERVATIONS 1443

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

SURFACE WINDS

FER

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

48-64

					ALL WE	ATHER			1				-176C
	_					ASS						HOURS	(L S T.)
	_		<u></u>		CONE	NOITION			·				
SPEED									-\				MEAN
(KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 · 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
N	1.2	2.5	6.2	2.1	• 1				,			12.1	8.3
NNE	.4	1.0	2.5	1.C								4.9	8.0
NE	•3	2.2	2.1	• 5								5.1	7.C
ENE	• 2	.3	.6	• 2								1.3	6.8
E	•1	.7	• 5	• 1								1.4	7.C
ESE	• 3	. 3	.1	• 2								1.0	6.7
SE	.8	. 8	.6	.8						ļ		3.0	6.9
SSE	.1	.7	1.3	1.0	.1		<u> </u>					3.3	9.0
s		• 7	1.3	1.1	.1		<u> </u>	<u> </u>				3.3	9.8
SSW		.1	.2	-1					<u>-</u> :	ļ <u>.</u>		. 3	8.8
sw		.3	.8	.1	ļ. ——		<u> </u>	 	<u>'</u> -	ļ		1.5	6.6
wsw	.3	. 3	.7	-8		 	 	 	├	 	 	2.1	9.5
W	•2	1.1	2.6	3.0	.3			L		 	 	7.3	10.4
WNW	.3	1.5	4.2	4.9	.8	.1		<u> </u>	 .				9.3
NW	8_	4.3	9.8	6.6	-6	<u> </u>	ļ		<u>-</u> '	L		15.4	
NNW	•6	2.9	5.6	6.(-2_	 	 	 	 			19.4	9.6
CALM			><	><	><	> <	>	\geq	\geq	\geq	$\geq \leq$	4.1	
	6.0	19.8	39.1	28.6	2.3	•2						100.0	8.7

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PRIVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Acres & Barban

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

And a surgery and and a said

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	<u> FUKU(</u>	CKA KYU			AZUKE	AB	48-6	.4						Eb
STATION			STATIO	HAME						YEARS			*	H THO
						ALL WE	ATHER						1800	-2000
		_					AS\$						HOURS	(L 5.T.)
		_				CON	DITION							
		_												
	SPEED	1							I					MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR								••		" "		,	SPEED
	N	2.4	4.1	2.4	• 5						l		9.4	5.6
	NNE	1.3	2.8	1.3	5						 		5.9	5.7
	NE NE	2.4	3.8	1.7	• 2						 -		8.1	4.9
	ENE	• 9	1.1	•2					 				2.2	4.1
	E	• 7	•6	• 2	•1			l	† 	<u> </u>	i		1.7	4.8
	ESE	• 5	• 3	•1	.1								1.0	4.9
	SE	1.9	1.6	1.0	• 3	•1			†				5.0	5.7
	SSE	1.2	2.2	1.3	• 3								5.1	5.8
	S	1.0	2.1	1.8	• 3	.2				·			5.5	6.6
	SSW	•6	1.0	.3	.1								2.0	4.6
	sw	.9	2.1	.4	•1								3.5	5.C
	WSW	• 5	1.6	.8	.1								3.0	5.9
	W	6	2.0	2.6	• 9	. 2							6.3	7.9
	WNW	•6	1.9	2.5	2.7	. 4	• 1						8.2	5.3
	NW	.7	3.7	3.0	1.5	• 2	.1						9.1	7.8
	NNW	1.5	2.7	2.8	• 6	• 1							7.7	6.6
	VARBL													
	CALM					\geq					\geq	\nearrow	16.1	
								*	 			\longrightarrow		
	1	178	22.7	22.5	8.3	1.2	. 1	1	1	l	1		100-6	5.4

TOTAL NUMBER OF OBSERVATIONS

1443

CATA PRCCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

FUKUCKA KYUSHU JAPAN/1 TAZUKE AB

SURFACE WINDS

FEB.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

48-64

					ALL WE	ATHER						2100	-230r
	_					LASS			·			HOUR	5 (L S T.)
	_				CON	DITION							
					•								
	_												
SPEED	1		ı		I								MEAN
(KNTS)	1 - 3	4.6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
DIR.			{					• • • •	" "			"	SPEED
N	•6	1.6	.6	• 5	i	•1		 	i	i ———		3.4	6.5
NNE	1.0	1.0	.8	•1				i		i		3.C	5.4
NE	2.1	1.4	• 3	•1					i——	l		3.9	4.2
ENE	1.0	• 3	-1					i		Ì		1.5	3.3
£	1.2	•7	.1	i	·				1			2.0	3.6
ESE	1.0	.6	•1							<u> </u>		1.7	3.€
SE	4.5	5.6	1.5	.8	i — —		<u> </u>					12.3	4.8
SSE	4.2	7.6	2.4	.2				f				14.4	4.9
S	2.5	4.4	1.1	.6	•1	.1			T			8.7	5.6
SSW	5	1.2	•2	i				†		1	1	1.9	4.7
SW	•8	1.3	.6		i ——							2.6	5.2
wsw	•3	.8	1.0	• 2	i				 	ſ		2.3	6.8
w	.6	1.0	1.2	1.0	.3	1						4.1	8.7
WNW	.4	.8	1.1	1.9	.4	•1						4.7	10.2
NW	•1	1.4	1.9	1.0	.1	T				T		4.6	8.7
NNW	.7	.9	1.0	•6								3.2	1.0
VARBL						Ī							
CALM		><		><	> <	> <				><		25.6	
	21 (30 (1, ,	7.0				 	1	 		100 0	4 3

TOTAL NUMBER OF OBSERVATIONS

1443

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUC	CKA KYU	SHU JA	PAN/II	AZUKE	AB	48-6	4		rears				AR
STATION		_	SIATION			ALL WE	ATHER			I EARS			0000	-0200
		_				CON	DITION							
	SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
	N	1.3	1.5	• 9	.7	•1							4.4	6.2
	NNE	1.0	1.2	.7	. 3								3.2	5.8
	NE	1.3	•9	.4	.1								2.7	4.8
	ENE	.4	.4										• 8	3.6
	E	•8	•6	•1			i						1.4	3.8
	ESE	1.0	•5	• 3	• 1								1.9	4.6
	SE	4.4	3.7	2.5	. 8	•1							11.4	5.3
	SSE	3.4	5.6	3.0	.9	.1							13.0	5 • 8
	S	2.5	4.2	1.2	•1								8.00	4.7
	SSW	. 4	• 5	•1	• 3								1.2	6.3
	SW	.4	• 5	•1									1.0	4.3
	wsw	• 3	• 3	• 2	• 3								1.1	6.9
	w	•1	•5	1.6	• 9	.1		• 1					3.4	9.8
	WNW	•2	•5	1.0	1.4	. 5	.1						3.7	11.4
	NW	.6	.6	1.3	1.2								3.7	8.4
	NNW	• 5	. 9	.9	.6				<u> </u>				2.8	7.2
	VARBL						ļ,			<u></u>	ļ			
	CALM	$\geq \leq$			$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		36.2	
				I									100 0	2.0

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	<u> FUNU</u>	LNA NYU	SHU JA	<u>LYNY1</u>	ALUKE	AB	48-6	4						IAN
STATION			STATIO	HAME						YEARS				IONTH
						ALL WE	ATHER							-050C
		_				C	LASS						HOURS	\$ (L S.T.)
		_												
						CON	DITION							
		_												
		п									T			
	SPEED (KNTS)	1 - 3	4.6	7 - 10	11 - 16	17 01	00 07		۱ ا	4, 4	40.55	≥56	%	MEAN WIND
	DIR.	1.3	•••	7 - 10	11 - 10	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	۵۵-	/•	SPEED
	N N		1.3	1 4	_								4.4	7.5
	NNE		.9	1.4	•9				 		 		2.3	5.8
	NE	8	•9	<u>.6</u>					 -		·		2.0	4.6
	ENE	5	•3		 						 		-8	3.5
	E	.6	.4	• 2	2				 				1.3	5.4
	ESE	1.3	.6.	.3	• 1	•1			 		t		2.3	4.7
	SE	4.1	4.2	2.8	1.2	.1			 				12.5	5.8
	SSE	3.2	4.2	2.5	1.1	.1	•1		 	 			11.3	5.9
	S	2.1	3.5	1.3	.5		.1		i		T	í———	7.4	5.5
	SSW	- 4	.7	.1									1.2	4.2
	SW	- 4	-4	•2	.2								1.2	5.6
	wsw	3	.4	3_	.3								1.2	1.1
	W	3	.5	1.2	. 5	1	1						2.7	8.6
	WNW	. 3	-6	1.1	1.8	.6	-1						4.4	11.4
	NW	4	1.0	1.1	1.6	2			!		<u> </u>		4.4	9.2
	NNW	6	6	1.3	8_				<u> </u>				3.2	7.6
	VARBL		<u> </u>			<u> </u>				<u></u>	ļ	[]		
	CALM		><	><	\sim	$\triangleright <$	\sim	><	><	><	><	><1	37.4	ĺ
			\leftarrow		 	[[
	1	16.5	20.6	14.5	9.5	1.2	- 3	L	L	l	1	<u>. </u>	100.0	4.1

TOTAL NUMBER OF OBSERVATIONS

1581

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

1

()

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	48-64 YEARS	MAK MONTH						
		ATHER	0600-0800 HOURS (LST)						
CONDITION									

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 47	48 - 55	≥56	%	MEAN WIND SPEED
N	.9	1.3	1.6	. 8								4.7	6.8
NNE	.9	1.6	1.4	. 4								4.3	6.3
NE	1.2	1.4	.7									3.3	4.7
ENE	.4	.4	1									• 9	3.7
E	.9	.4	.1		• 1							1.4	4.1
ESE	•6	6_	1	• 2								1.5	5.2
SE	3.8	2.9	3.1	1.3	-3							11.4	6.2
SSE	3.9	6.5	3.8	1.1	.1	. 2						15.5	6.0
S	3.0	4.7	2.0	. 8			l					10.4	5.5
SSW	4_	4_	.2	.1								1.1	4.9
SW	.4_	4_	1_	1	•1							1.1	5.9
WSW	1	.6	6	. 3	•							1.6	7.7
w		.5	1.0	.5								2.1	8.8
WNW	.1	.4	1.1	1.3	,4	-1	-1	<u> </u>				3.5	11.8
NW	.6	.7	1.4	2.1	.3							5.1	9.8
NNW	• 2	1.1	1.2	. 8								3.3	8.2
VARBL							1	L					
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	\geq	28.8	
	17.6	23.8	18.3	9.7	1.3	• 3	.1					100.C	4.7

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

£.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUOKA KYUSHU JAPAN/ITAZUKE AB	48-64	MAR
STATION	STATION NAME	YEARS	HONTH
	ALL W	EATHER	G + CO-1100
		CLASS	HOURS (LST.)
	co	KOITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	9	2.1	3.2	2.2	• 2							8.6	8.6
NNE	.8	. 8	2.7	1.1								5.4	7.8
NE	1.3	1.6	2.1	. 3								5.3	6.1
ENE	3	•6	5	• 1								1.5	6.0
E	8	. 9	.6	.1						<u> </u>		2.5	5.4
ESE	1	.4	.7	. 2								1.5	7.2
SE	1.1	2.5	2.8	3,4	-1				L			9.9	8.6
SSE	1.5	3.3	4.2	3.1	. 3	-1	1					12.5	8.2
S	1.7	2.5	2.4	1.0	-1-			<u> </u>		<u> </u>		7.7	6.6
ssw	.7	. 5	. 3				ļ			<u> </u>		1.5	4.3
sw	.9	3_	4	3_			<u> </u>					2.0	6.2
wsw				2			<u> </u>		<u> </u>			<u> 1.i</u>	8.6
w	7	7_	_1.6	_2.2.1_	1_							5.1	9.5
WNW		. 9	1.6	2.2	4_	3_			<u> </u>			5.9	10.6
NW	6	1.6	3.1	2.7	4		<u> </u>					8.3	9.5
NNW	.8	1.5	2.3	1.8	3_		<u> </u>	<u> </u>	<u> </u>			6.6	8.4
VARBL				<u></u>	ļ	ļ	Ļ	<u> </u>	<u></u>	<u></u>			
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	14.7	
	12.7	2C.8	28.8	20.7	2.0	.3						100.C	6.9

TOTAL NUMBER OF OBSERVATIONS

1581

1210 WS FORM 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE DESOLETE

€

CATA PROCESSING LIVISION ETAC. USAF ASPEVILLE. N. C. 288CI

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKU(KA KYU	SHU JAI		AZUKE	AB	48-6	4		rears				AK
*******			3181108						,					
						ALL HE	AIFER							-14(C
						ÇL	.A53						ROURI	(131)
		-				CON	DITION							
		_												
-								, <u> </u>						
Ì	SPrED	!										1		MEAN
	(KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
Î	N	.6	2.5	5.3	4.C	. 8							13.2	9.5
ľ	NNE	. 3	1.7	2,2	1.9	• 1				· 			6.3	8.7
Ī	NE	• 9	1.8	2.0	.3								4.9	6.3
Ī	ENF	.4	.4	. 6							i		1.5	5.8
Ì	£	• 3	• 3	•6	•1						·		1.3	6.9
ľ	ESE	.1	.4	.6	. 3			ļ -					1.5	7.7
Ì	SE	•1	. 8	1.7	2.0			i — —			<u> </u>		4.5	9.7
ĵ	SSE	.2	1.1	1.6	1.9	• 3				i	1		5.1	9.7
Ī	S	.4	1.2	•9	1.4	•1				i			4.C	8.8
Ī	SSW	.:	• 3	• 3	• 5					ļ ———			1.2	9.1
Ĭ	SW	.4	•1	• 3	• 3								1.1	6.9
ľ	wsw	• 3	.4	• 2	.6	.1			·——	T			1.5	9.0
	W	•6	•8	1.6	2.4	.5	I	1					5.9	10.4
Ť	WNW	•2	. 8	3.7	3.4	. 8	• 3	T	1	i			9.C	11.C
Ī	NW	.8	3.2	8.9	7.3	.3							20.5	9.5
	NNW	.7	2.2	6.8	4.5	.3			i — -	1			14.5	9.3
Ī	VARBL					1		1						
	CALM	><	> <	><	\geq			$\geq <$			$\geq \leq$		4.0	
		6.5	17.9	37.2	30.9	3.3	.3						100.0	ರ.9

TOTAL NUMBER OF OBSERVATIONS

1581

1210 WS JUL 84 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FO

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED -(FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUĽ		SHU JA STATION			ALL WE	48-6 ATHER ASS	4		TEARS			1500	AR ONTH -1766 (6.8 T.)
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
	N	• 3	2.2	6.5	6.7	.4							16.C	10.0
	NNE	• 4	1.2	2.5	1.7	.1							5.8	8.9
ĺ	NE	• 3	1.6	2.0	. 4								4.2	7.0
	ENE	• 3	.4	٥	• 1								1.8	6.7
i	E	• 2	• 3	• 2									.7	5.4
į	ESE		• 3	• 2									. 4	5.9
į	SE	• 3	. 5	• 9	. 8	.1							2.6	9.C
	SSE	. 3	•6	1.8	.4								3.1	8.1
	S	.1	.3	1.8	1.6	. 1	.1			L			4.0	10.3
	SSW	.1	.1	.4	• 3			<u> </u>	<u> </u>	<u> </u>	<u> </u>		• 8	9.1
	SW	• 2	.3	.1	. 3				<u> </u>				. 9	7.6
	wsw	.1	-1	. 8	- 3	• 2							1.4	10.2
	w	.2	.7	2.0	3.6	. 3	• 3	l		<u> </u>			7.1	11.6
	WNW	.3	1.3	3.0	3.8	.4	ļ		<u> </u>	<u> </u>	<u> </u>		8.9	10.5
	NW	.6	3.4	9.6	5.4	.4	ļ		ļ	<u> </u>	ļ	<u> </u>	19.4	9.2
j	NNW	-9	3.7	10.0	5.3	- 3			<u> </u>	<u> </u>	ļ	<u> </u>	20.2	9.0
	VARBL		ļ		ļ	<u> </u>	<u></u>	Į	Ļ		ļ		ļ	
			\sim	i> /	_		i _	1	\sim	\sim	\sim		2 7	l

TOTAL NUMBER OF OBSERVATIONS

1581

9.1

100.0

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 28501

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

4331C	<u>FUKU(</u>	KA KYU	SHU JAI	I I VAA	AZUKE	AB	48-6	4						AR
STATION			STATION	NAME					1	EARS				ONTH
						ALL WE	ATHER						1800	-200C
						CL	A55						HOURS	(L S T.)
						CON	POLLIC							
		_												
۲	SPEED													MEAN
1	(KNTS)	1.3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
}	DIR.													SPEED
Ĭ	N	2.7	5.6	4.9	1.1		.1	•1					14.4	6.5
ľ	NNE	2.7	3.0	2.8	. 8	• 2							9.5	6.2
Ī	NE	1.9	2.3	. 9	.1								5.2	4.7
Ī	ENE	1.4	.8	• 3									2.5	4.0
Ī	E	1.0	.8	•1									1.9	3.8
Ĭ	ESE	•6	• 2	•1							<u> </u>		• 8	3.7
Ī	SE	.7	1.5	1.3	.4								3.9	6.3
ľ	SSE	•6	1.5	1.0	.4			l			 		3.6	6.6
Ì	\$.7	1.7	.9	•5	• 1_	•1						4.0	7.C
Ī	ssw	.4	.7	• 3	•1		•1						1.5	6.3
ſ	SW	-8	1.5	_ 3	•2								2.7	5.2
Ī	WSW	• 3	1.1	1.1	• 3	.1							2.9	7.2
Ī	W	.6	2.0	2.8	1.6	• 1							7.1	8.2
Ī	WNW	.5	1.0	2.2	1.6	.1							5.5	9.C
ſ	NW	1.3	2.7	2.7	•9	• 2							7.9	6.8
Ĭ	NNW	2.0	4.7	2.8	• 8	•1	•1	-1					10.5	6.3
Ţ	VARBL													
Ī	CALM												15.9	
		18.0	31.2	24.7	8.8	.9	3	1	<u></u>	<u> </u>]	100.0	5.5

TOTAL NUMBER OF OBSERVATIONS

1581

CATA PROCESSING DIVISION ETAL. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	48-64		MAK
STATION	STATION HAME		YEARS	HONTH
	ALL	WEATHER		2100-2300
		CLASS		HOURS (LST)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.4	2.6	1.7	• 6	• 2							6.5	6.4
NNE	.9	1.8	.9	• 4				•				4.C	5.9
NE	1.8	1.3	.9	• 1								4.1	4.9
ENE	.7	•6	.1									1.4	3.8
E	1.5	•6	•2									2.3	3.4
ESE	1.3	.4	•2	. 1						Ī		2.0	3.8
SE	4.2	3.0	1.8	.6								9.7	5.C
SSE	3.5	4.6	2.5	. 8	• 1		i .					11.4	5.5
S	3.8	3.2	1.1	.4	• 1	•1						8.7	4.8
ssw	.7	• 3	.1									1.1	3.8
SW	.4	•7	.4	• 1								1.6	5.6
wsw	• 3	•5	.6	• 1								1.6	6.5
w	• 5	.7	1.5	• 9		•1						3.7	8.6
WNW	• 3	.7	1.0	1.0	. 3	. 1						3.4	9.8
NW	•6	-8	.7	• 9	.1		İ					3.1	8.3
NNW	1.1	.9	.4	. 3								2.8	5.C
VARBL													
CALM		><	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		32.7	
	23.0	22.7	14.3	6.4	.7	.2						100.C	3.9

TOTAL NUMBER OF OBSERVATIONS

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

> NNW VARBL

CALM

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

SURFACE WINDS

APR

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

JIA III			PINITO							12049			-	VA 1117
		_				ALL WE							<u> </u>	-020C
			_			c	LASS						HOURS	(L.S T.)
		_				CON	DITION				_			
		_												
		8											,	
	SPEED (KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND
	DIR.	'-0	4-0	/ - 10	1, 10	,, - 2.		10-00	04.40	4, 14,	10-05	_50] "	SPEED
	N	1.1	2.1	•7	3_				 				4.2	5.3
	NNE	,7	.5	.5									1.6	4.8
	NE	1.1	. 7								<u> </u>		1.9	3.7
	ENE	. 8			<u> </u>				ļ				. 8	2.3
	E	1.3	• 3	2				<u> </u>	<u></u>		<u> </u>		1.8	3.5
	ESE	1.0	.5	.4	. 3]	<u> </u>]	<u> </u>		2.2	5.7
	SE	4.0	4.2	2.9	1.4	1		<u> </u>		<u> </u>			12.6	6.C
	SSE	3.5	5.6	2.8	1.5	.4	-1	<u> </u>	·	<u> </u>	<u> </u>		13.9	6.5
	S	2.7	2.9	1.0	.7	<u> </u>				<u></u>	<u> </u>	<u> </u>	7.3	
	SSW	. 6	5					L		<u> </u>	<u> </u>		1.1	3.5
	sw	.9	3	.1	.1								1.3	3.7
	wsw	. 3	.5	3							<u> </u>	L	1.C	5.2
	W	.1	-7	3	.7	1							1.9	8.4
	W" 'V	.6	.3	.4	. 5	.2							2.C	8.4
		6	8	3	6	. 1			1		[2.4	

TOTAL NUMBER OF OBSERVATIONS 153C

41.8

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

4331C FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

		NAME.						ILAND				VA.1.1
				ALL WE								-0500
				CL	ASS						HOURS	(L.S.T.)
				CONI	NOITION -							
SPEED								_			·	MEAN
(KNTS) 1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
DIR.											 -	
N les		1.2	6					ļ	 		4.6	6.2
NNE		3_						 -	 		1.4	5.C
NE ENE		2						 	 -		1.4	4.C
		1							 		1.2	4.C 2.9
		<u> </u>						 			2.5	5.6
		-4	4-				 	 	 		12.2	6.3
		3.5	1.2	.3			 -		 		15.C	6.6
		4.1	1.6	.3	•1	 	 	 			7.5	5.2
		1.3	6				 -				1.4	4.8
		-4						 			1.3	4.7
				ļ		 	 	 			1.1	5.5
w 1.		-4	-2								2.9	6.0
	7 4	.5	. 8								2.4	8.2
	3 1.4	1.3	.4			<u> </u>	<u> </u>				3.4	6.9
	6 1.3	6		-1							2.7	6.1
VARBL												
CALM			> <	> <	> <	><		$\supset <$	><	$\supset <$	38.5	
	4 20.7	1.6 /	6.1	.7	•1	1		[100.C	3.7

TOTAL NUMBER OF OBSERVATIONS 1530

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

musing terms to be the set

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	EUKUCKA KYUSHU JAPAN/ITAZUKE AB	48-64	APR
STATION	STATION NAME	YEARS	нтиси
	ALL N	WEATHER	060 0 -1800
		CLASS	HOURS (LST)
		CONDITION	

SPEED (KNTS) DIR	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.4	1.2	1.9	1.0					· · · · · ·			5.6	6.9
NNE	. 8	• 8	•6	• 2								2.4	5.4
NE	. 9	• 5	• 1									1.4	3.6
ENE	.5	.3	.1	.1								1.0	4.9
E	•6	•1		.1								• 8	3.8
ESE	1.0	• 8	1.1	• 3	.1							3.3	6.1
SE	2.1	3.5	4.1	2.5	• 1	.1						12.4	7.6
SSF	2.7	4.9	5.6	1.5	• 2							14.8	6.8
S	3.4	3.5	1.3	• 3								8.6	4.8
SSW	. 0	• 3	• 3	.1								1.6	4.2
SW	. 3	• 3	• 2	.1								.8	5.8
wsw	.3	.5	• 3									1.0	5.3
W	1.0	. 8	1.2	• 5	.1							3.5	6.8
WNW	.7	• 3	1.2	.9	.1							3.2	8.7
NW	8	1.2	• 7	• 2								2.9	5.5
NNW	.5	1.0	1.3	• 3								3.1	6.8
VARBL					<u></u>								
CALM	$\geq \leq$	$\geq \leq$	><	$\geq \leq$	><	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq <$	33.7	
	17.8	20.2	19.7	8.0	.6	٠,١						100.C	4.3

TOTAL NUMBER OF OBSERVATIONS 1530

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE. N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	48-64		APR
STATION	STATION HAME		YEARS	MOK-H
	ALL	WEATHER		0900-1100
		CLASS		HOURS (LST.)
		CONDITION		

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.2	3.0	2.8	1.9			i					8.9	7.5
NNE	.7	•9	1.8	• 7				l ———				4.1	7.5
NE	• 9	•9	1.2	• 1								3.1	5.5
ENE	.4	• 3	•6	• l								1.4	6.4
£	. 3	• 5	• 3	.1					i	i — —		1.2	6.1
ESE	. 1	•6	•7	• 5				i				1.9	8.2
SE	1.1	2.0	5.0	3.7	• 3				<u> </u>			12.0	9.1
SSE	1.0	2.4	4.9	4.6	.7							13.6	9.6
S	1.1	2.3	1.6	1.5	• 1							6.7	7.6
ssw	• 5	7	• 3	• 2	• 1							1.8	6.7
sw	• 9	• 3	• 1	. 3								1.6	5.1
wsw	. 3_	.2	•1	• 1								.81	6.3
w	•8	• 9	1.2	.4	• 3					i		3.7	7.8
WNW	•5	1.4	2.4	1.9	• 3							6.5	9.1
NW	1.4	3.7	4.6	1.5	.1							11.3	7.4
NNW	• 9	2.7	2.2	1.2	. 1							7.3	7.4
VARBL													
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		14.3	
	12.0	23.0	30.0	18.8	2.0					1		100.C	6.9

TOTAL NUMBER OF OBSERVATIONS 1529

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

<u>43310</u>	<u>FUKUCKA KYUSHU JAPAN/ITAZUKE AB</u>	48-64	APR
KOITATE	STATION NAME	YEARS	нтиом
	ALL W	EATHER	1200-1460
		CLASS	HOURS (L S.T.)
	cc	ONDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	• 3	2.3	4.6	5.0	.1							12.3	9.7
NNE	• 3	• 7	1.4	• 9	•1			i — —				3.3	9.C
NE	•1	1.3	• 9	• 3								2.6	6.6
ENÈ	• 3	• 5	. 7									1.5	6.C
E	• 1	• 3	. 3	• 1								8.	6.6
ESE	•1	• 3	• 3	.6								1.3	3.6
SE :	•4	1.8	2.4	2.3	• 3							7.2	9.2
SSE	• 3	1.0	2.5	3.3	.4	• 3		Ī ———				7.8	1C.8
S	• 3	.7	2.0	2.0	.4	•1			i			5.6	10.7
ssw	•1	•5	• 5	.9	.1	• 1						2.2	10.7
SW	• 3	•2	.4	• 1								1.0	6.2
wsw	•2	•1	•2		• 1							.6	6.8
W	•2	1.0	1.1	1.2	• 2							3.8	9.5
WNW	• 2	1.2	2.8	2.7	• 5	• 3						7.7	10.7
NW	• 9	4.7	11.1	4.2	• 5						T	21.4	8.7
WNN	3.	3.1	8.1	4.1	-1							16.3	8.8
VARBL													
CALM	> <	$\geq \leq$	$\geq <$	$\geq \leq$	$\geq \leq$	> <	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	4.7	
	5.0	19.8	39.3	27.8	2.7	.7						100.C	8.8

TOTAL NUMBER OF OBSERVATIONS

153C

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

invations.

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKULKA KYUSHU JAPAN/ITAZUKE AB	48-64	APR
STATION	STATION NAME	YEARS	нтком
	ALL W	EATHER	1500-1700
		CLASS	HOURS (LST.)
		ONDITION	

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	•7	3.2	7.3	5.0	•1							16.3	9.1
NNE	•1	•9	1.2	• 8								3.1	8.3
NE	. 7	1.0	1.2	• 1								3.C	6.C
ENE	• 3	• 5	•8	• 3								2 • C	7.3
E	.1	•7	• 3									1.2	6.0
ESE	• 2	•1	.4	.1					<u> </u>			• 8	7.1
SE	.4	1.4	2.1	1.4	•1		<u> </u>					5.4	8.7
SSE	• 3	1.0	1.8	2.2	-1		<u> </u>					5.4	9.9
S	.1	• 7	1.6	2.1	.7	.1	<u> </u>					5.2	11.3
ssw	.1	• 3	.3	.5						L		1.1	9.3
sw	•1	• 3	• 5	.1		<u></u>	<u> </u>	İ				1.0	7.8
wsw	.1	3	.4	. 1	.1			<u> </u>				1.0	7.9
W	• 2	-8	1.7	1.5	•1	1			<u> </u>			4.4	9.8
WNW	.4	1.2	2.5	2.4	.7		.1		<u> </u>	<u> </u>		7.3	10.3
NW	1.6	4.7	11.5	4.2	•1		<u> </u>					21.4	8.3
NNW	.4	4.1	9.5	4.1				<u> </u>				18.1	8.7
VARBL				<u></u>	<u> </u>	ļ		ļ	<u> </u>	<u> </u>			
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	3.4	
	5.1	21.2	43.3	24.8	2.0	.1	.1					100.C	8.6

TOTAL NUMBER OF OBSERVATIONS

1530

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE. N. C. 288C1

and the state of t

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	48-64	APK
STATION	STATION NAME	YEARS	MONTH
	ALL W	FATHER	1800-2000
		CLASS	HOURS (LST)
	C	HOITIGH	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	2.4	5.2	4.6	•5								12.7	6.0
NNE	2.6	2.3	1.6	• 1								6.5	4.9
NE	1.9	1.2	• 5									3.6	4.3
ENE	.7	.7	• 3							L		1.6	4.6
E	1.2	• 8	.1									2.2	3.8
ESE	• 5	.7	• 2	. 3								1.7	6.1
SE	. 8	1.7	1.8	1.0				<u> </u>			<u> </u>	5.4	7.3
SSE	• 8	1.3	2.0	1.4	• 3							5.9	8.6
S	•5	1.0	1.0	.8	.1	-1		<u> </u>		<u> </u>		3.5	8.7
\$\$W	•2	• 3	• 2	-1	.1			<u> </u>	<u> </u>			-8	6.8
SW	7_	.8	.5						l			2.C	5.C
V.2W	-5	• 8	.6	.1		<u> </u>	ļ		ļ			1.9	5.5
W	.7	2.2	2.3	1.4	.3			ļ	ļ			6.9	0.8
WNW	.8	2.0	2.0	1.2	1 .1					<u> </u>		6.1	1.7
NW	2.5	4.9	1.8	.8	<u> </u>	<u> </u>			<u> </u>			10.C	5.7
NNW	1.4	4.7	2.0	.5			<u> </u>		ļ		ļ	8.6	5.7
VARBL			<u> </u>	<u> </u>			<u></u>		ļ,	Ļ	<u></u>		
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	20.7	
	18.2	30.7	21.3	8.1	.9	.1			<u> </u>		<u> </u>	100.C	5.C

TOTAL NUMBER OF OBSERVATIONS

153C

DATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 28801

4331C FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64
STATION MARE

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

	_				ALL WE	ATHER ASS		· · · · · · · · · · · · · · · · · · ·				21 CO	-2300
	_				CON	ROTTIO							
												····	
SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.2	2.1	2.2	•.3								5.7	5.9
NNE	9_	9	. 3	.1								2.2	4.5
NE	_2.C	1.0	.2	.1								3.2	3.8
ENE	.6	• 5	.1									1.2	3.6
E	1.4	•8		• 1								2.3	3.5
ESE	1.4	.7	1	.1	•1	•1						2.6	5.3
SE	4.4	3.3	2.2	1.2								11.2	5.7
SSE	3.5	4.6	3.2	1.2	. 3							12.8	6.1
S	3.0	2.8	1.0	. 8	• 1	.1	-1					7.8	5.7
SSW	9	.6	1	1				<u> </u>				1.6	4.0
SW	1.0	.5	. 4									2.0	4.8
WSW	.2	.4	2			1						1.0	7.5
W	وما	لعلا	8_					<u> </u>				3.2	6.3
WNW	5_	6_	8_	4_								2.3	7.7
NW	.9	9_	6							<u> </u>		2.7	5.6
NNW		_1.1_	5	.4						. _		2.7	6.7
VARBL							<u> </u>		<u></u> .	<u></u>			
CALM				><	\sim			\sim	><	><	><	35.7	

1529

100.0

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS P

THE STATE STATE

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

9.3310	. EUNU	VH VIO	SHU JA	PAN/	ALUNE	<u> </u>	47.0	7						71
STATION			STATIO	3 MAN						YEARS			H-	IONTH
						ALL WE	ATHER						0000	-0200
		_				C	LASS						HOURS	5 (L S T)
		_												
						CON	DITION							
	SPEED						[MEAN
	(KNTS)	1.3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.										<u> </u>			SPEED
	N	.8	•5	5	-1		<u></u>						1.9	5.3
	NNE	.5	•1	1			l				L		. 7	3.4
	NE	. 8	• 5	.1			l L				L		1.4	3.6
	ENE	1.0	• 2	•1	1								1.3	3.3
	E	1.6	8	. 5									2.8	4 . C
	ESE	1.7	.8	.5	• 2								3.2	4.6
	SE.	4.2	3.9	2.9	.8							i	11.9	5.3
	SSE	5.3	3.9	3,1	1.5								13.7	5.7
	S	3.5	3.1	1.5	. 3	• 2		L			L		8.6	5.2
	SSW		.5	.2	• 2								1.4	5.4
	sw	2_	6	.2	-1				<u> </u>	<u> </u>	<u> </u>	lj	1.1	5.3
	WSW	3	.4	4	1_				<u> </u>			}	1.1	5.7
	W	1.0	.5	.4	.2		1	<u> </u>					2.2	5.6
	WNW	.4	.4	.2	.2		<u>L</u>		<u> </u>				1.2	6.1
	NW	•5	1.3	,3	•1								2.2	5.1
	NNW	.8	1.3	.4				<u> </u>	<u> </u>		<u> </u>		2.5	4.6
	VARBL						<u> </u>			<u> </u>	<u> </u>			
	CALM									><			42.8	
			$\vdash \longrightarrow$! 	(≦————————————————————————————————————				ऻ॔	=			
	1	и	1	I				1		1				٠. ١

TOTAL NUMBER OF OBSERVATIONS

1674

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

14

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	MAY
STATION	STATION NAME	YEARS	MONTH
	ALL	WEATHER	0300-05CC
		CLASS	HOURS (LST.)
		CONDITION	
-			

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	• 5	1.1	.7	• 1								2.5	5.8
NNE	•5	•5										1.0	3.7
NE	1.2	•5	.4					I				2.1	4.2
ENE	• 3	•2	• 1									.5	4 • C
E	•9	• 9	.1	.1								2.C	4.4
ESE	1.7	• 8	.9	.1		L				l		3.5	4.7
SE	4.7	5.1	2.6	1.C	.1			<u> </u>	<u></u> .			13.4	5.4
SSE	4.1	5.4	2.6	1.5		<u> </u>	<u> </u>			<u> </u>		13.6	5.8
S	3.1	2.7	1.8	-6	.1	-1	<u> </u>			<u> </u>	<u> </u>	8.4	5.7
ssw	8	.4	.1	•1		İ	<u> </u>		<u> </u>			1.4	4.1
SW	.4	.5	-1		<u> </u>			<u> </u>	<u> </u>	<u> </u>	ļ	1.0	3.9
wsw	- 3	-2	-2	.1			<u> </u>	<u> </u>	<u> </u>]		.8	6.1
w	.6	1.0	.8	.4	.1	<u> </u>	<u> </u>	<u> </u>				3.0	7.0
WWW	3	•2	.4	•1			<u> </u>	ļ	ļ	<u> </u>		1.0	6.4
NW	1.0	- 8	.3	-1	ļ		ļ	<u> </u>	ļ	<u> </u>		2.2	4.8
NNW	1.0	1.4	.8	•2		<u> </u>		<u> </u>	ļ	ļ		3.4	5.3
VARBL		ļ	<u> </u>	<u> </u>		<u> </u>	<u></u>			<u> </u>			
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		40.1	
	21.6	21.8	11.9	4.3	.2	.1		<u> </u>]	100.0	3.2

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 84 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

1:

CAIA PROCESSING DIVISION ETAC. USAF ASFEVILLE. N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-04	MAY							
MOTTATE	STATION NAME	YEARS	MORTH							
ALL WEATHER										
		CLASS	HOURS (LST)							

SPEED (KNTS) DIR	1.3	4 - 6	10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	AIEAN WIND SPFED
N	.7	1.2	1.1	• 2								3.2	6.2
NNE	.4	.4	. 3									1.1	4.8
NE	.9	. 5	•2	.1					!			1.6	4.3
ENF	.4	• 1	.1									• 5	3.6
E	1.3	• 5	• 3									2.1	3.9
ESE	1.5	• 5	. 5									2.6	4.1
SE	4.3	3.9	4.5	1.5	.1							14.4	6.2
SSE	4.4	6.5	5.6	1.7	•1	<u> </u>						18.2	6.4
S	2.5	3.6	1.7	1 + C	• 2	•1						9.1	6.2
SSW	.6	.7	.1									1.4	3.6
SW	.7	•2	•1]				1.0	3.9
wsw	.4	• 2	• 2	•1			T					• 9	4.8
W	• 5	•7	1.1	.4				i				2.8	7.2
WNW	.4	1.0	.8	• 2								2.4	ر ئ
NW	•8	1.1	.4	•1		T			ļ —		l" 	2.3	4.7
NNW	.5	.9	٠7	.2								2.3	6.5
VARBL				<u> </u>									
CALM	$\geq \leq$	><	$\geq \leq$			> <		$\geq \leq$	$\geq \leq$	$\geq \leq$		34.1	
	20.1	22.1	17.7	5.6	.3	.1						100.0	3.8

TOTAL NUMBER OF OBSERVATIONS 1673

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE. N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKU	CKA KYU	SHU JA	PAN/IT	AZUKE	AB	47-6	4					M	'AY
BTATION			STATIO							YEARS			N	ONTH
						ALL WE	ATHER						0900	-11CC
		-					LASS						HOURS	5 (L S.T.)
		-				CON	DITION							
		-												
		н————					1				, 			
	SPEED	ا ا					00 07		ایمار	l <u>.</u>	40 55	>	%	MEAN WIND
	(KNTS) DIR	1 - 3	4 - 5	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	"	SPEED
	N	1.1	1.6	1.7	• 9	.1							5.4	7.2
	NNE	.7	.7	.7	•2								2.3	5.8
	NE	.7	.6	1.0	•1								2.4	6.2
	ENE	.1	.7	- 5									1.3	6.1
	E	.4		.4	• 2								1.4	6.7
	ESE	.4	•6	•7	• 2								1.9	6.4
	SE	1.0	?.6	4.5	2.2	.2	.1						10.6	8.2
	SSE	2.0	3.6	7.0	3.C	.1							15.8	1.9
	S	1.4	2.2	2.6	1.6	• 3	<u> </u>			<u> </u>			8.1	7.8
	SSW	0	a		1 1	1	1		1		1		1.9	4.1

ENE	•1	.7	• 5								1.3	6.1
E	•4	.4	.4	• 2							1.4	6.7
ESE	.4	•6	.7	• 2							1.9	6.4
SE	1.0	2.6	4.5	2.2	• 2	.1					10.6	8∙2
SSE	2.0	3.6	7.C	3.C	.1						15.8	1.9
S	1.4	2.2	2.6	1.6	•3						8.1	7.8
SSW	.9	.9		• 1							1.9	4.1
SW	1.0	.6	.1								1.6	3.6
WSW	.4	-4	•2	•2							1.1	5.7
W	.8	1.4	1.3	• 9	•1						4.5	1.2
WNW	1.3	1.6	2.6	1.3	.1						6.8	7.7
NW	2.0	5.0	3.8	1.0	.1						11.8	6.4
NNW	1.0	3.0	3.4	. 9	•1						8.3	7.C
VARBL												
CALM			\geq	$\geq <$	$\geq \leq$		$\geq <$	$\geq <$	><	$\geq <$	15.1	
	14.9	25.7	30.3	12.8	1.0	.1					100.	1

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 28801

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

SURFACE WINDS

 $\mathbf{M}\mathbf{A}\mathbf{Y}$

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION			STATIO	NAME						YEARS				IONTH
						ALL WE	ATHER						1200	-14(C
		_				CI	ASS						HOURS	(LST)
		_												
						CON	DITION							
		_												
	SPEED	[· · · · · ·			T				MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	26 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.]						}		1		SPEED
	N	.6	2.0	4.6	2.3	• 2							9.7	9.0
	NNE	.4	•6	.7	. 7	•1							2.4	8.5
	NE	• 2	•8	1.0	. 4	• 1							2.6	7.6
	ENE	•2	.4	1.3	.4								2.3	7.9
	E	.4	• 9	1.C	. 2		<u> </u>			L		i	2.5	6.9
	ESE	1.1	-9	.4	.1			<u></u>					1.4	6.2
	SE	.4	1.3	2.3	1.7	• 1					<u> </u>		5.7	ಕಿ.5
	SSE	.5	1.4	3.5	2.0	• 2		<u> </u>	L	<u> </u>	<u> </u>		7.6	9.C
	<u>s</u>	.4	1.2	1.8	2.0	• 2		<u> </u>					5.€	9.1
	SSW		-1	.5	.7					<u> </u>			1.4	10.3
	SW	• 3	.2	-4	.2			ļ	ļ	<u> </u>	ļ	ļI	1.1	7.3
	WSW	. 2	.2	.2	. 2								• 9	6.5
	W	.2	.8	1.2	1.4	•1							3.7	9.4
	WNW	.4	1.3	3.5	3.1	. 3		<u> </u>			ļ		8.5	9.9
	NW		4.8	11.5	5.2	.5							22.7	3.9
	NNW	.8	3.1	10.3	3.0	.4	•1						17.7	8.6
	VARBL	ļ	ļ	<u> </u>	ļ	<u></u>	ļ	<u> </u>	ļ		<u> </u>	<u> </u>	<u> </u>	
	CALM		><	><			!><		><	<u> </u> ><	><		4 • 2	(
		5.9	20 2	43.9	23.7	2.1	.1			T			100.C	8.4
	L	1 2.9	1 60.6	1 43.7	1 6301	1 6.1	<u> </u>	l	l	1	I	įl	I TOO O	, 0.7

TOTAL NUMBER OF OBSERVATIONS

1674

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKU(KA KYU	A KYUSHU JAPAN/1TAZUKE A8 47-64 STATION NAME YEARS											AY
STATION			STATION	NAME					-	YEARS				ONTH
		_				ALL WE	ATHER						<u>1500</u>	-170C
						CI	ASS						HOURS	(LST)
						CON	DITION							
				-										
-														
	SPEED								l		1	i		MEAN
	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.													SPEED
L	N	5	3.0	5.2	2.3	-1				<u> </u>			11.1	8.2
	NNE	• 4		1.1	.7	1							3.C	8.1
l	NE	,7	1.9	1.1	. 4				<u> </u>	<u> </u>			4.2	6.3
Į	ENE	• 8	-4	. 8	.6								2.6	7.1
I	Ε	• 3	1.3	.7	.2								2.5	6.0
	ESE		•2	.4	-1								.7	7.3
	SE	•2	1.2	1.9	• 8	• 2				L			4.2	8.5
ĺ	SSE	.3	1.0	1.8	1.4	• 3							4.8	9.5
	S	.4	• 7	1.3	1.4	•1	.1		<u></u>				3.8	9.4
	SSW	.2	.4	.7	1.1			L					2.3	10.C
Ì	SW	•1	.2	.2	• 2								7	8.C
[wsw	.2	2	2_	• 2			<u> </u>	<u> </u>			H	. 8	7.6
[w	1	1.1	2.2	1.0		L						4.4	8.8
	WNW	3	1.6	3.6	2.9	.2			<u> </u>	<u> </u>			8.5	9.6
į	NW	1.3	4.8	13.3	4.5	.2			<u> </u>	<u> </u>			24.1	8.3
	NNW	. 3	4.9	9.1	3.7	1	Ĺ	L			<u></u> '		18.6	8.3
Ì	VARBL						L	<u> </u>	<u> </u>					
	CALM									\searrow			3.4	
			\leftarrow	 €==	=			 		 				
		6.7	23.7	43.5	21.4	1.2		<u> </u>	<u> </u>		<u> </u>	! <u> </u>	100.C	8.1

TOTAL NUMBER OF OBSERVATIONS

1673

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION STATION HANE TEARS ALL WEATHER CONDITION SPEED	≥56	1800	MEAN WIND SPEED
CONDITION	≥56	НО	MEAN WIND SPEED
CONDITION	≥56	%.	MEAN WIND SPEED
SPEED	≥56		WIND SPEED
SPEED	≥56		WIND SPEED
	250		SPEED
(KNTS) 1 - 3 4 - 6 7 - 10 11 - 16 17 - 21 22 - 27 28 - 33 34 - 40 41 - 47 48 - 55		10.C	
DIR.			C /
N 2.4 4.5 2.6 .5			5.6
NNE 1.9 1.9 1.0 .4	{	5.1	5.4
NE 2.2 2.5 .8	ļ	5.4	4.5
ENE 8 1.3 .4	 	2.5	4.4
E .8 1.0 .5 .2	<u> </u>	2.4	5.2
ESE .5 .5 .5 .1	ĮI	1.7	5.4
SE 1.0 1.6 1.7 .8 .1	ļ'	5.1	6.9
SSE .5 1.4 1.5 1.4 .2 .1	<u> </u>	5.1	8.7
5 1.1 1.3 1.2 1.0 .2		4-8	7.5
ssw .2 .5 .8 .2 .1		1.9	7.7
sw 1.2 .8 .2 .1		2.3	4.1
wsw .7 .6 .7 .2	<u> </u>	2.2	6.0
W .8 2.5 1.7 .6		5.5	6.6
WNW 1.0 1.9 1.6 .4 .2	l	5.1	6.7
NW 3.1 4.1 3.3 .2		10.7	5.4
NNW 2.2 5.7 2.2 .2		10.3	5.3
VARBL		1	
CAIM		20.C	
	¥≦—	 	
20.4 31.9 20.8 6.2 .7 .1	1	100.C	4.7

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

<u>FUKU(</u>	CKA KYU	SHU JAI	PANZLI	AZUKE	AB	47-6	4						AY
		STATION	MAME					•	YEARS				ONTH
					ALL WE	ATHER							-236C
					C	LASS						HOUR	5 (L \$ T.)
					CON	DITION							
				-									
SPEED		-										24	MEAN
(KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
N	1.2	1.1	.6	.2			i	 	 			3.C	5.1
NNE	.6	.4	• 2				1					1.3	4.3
NE	2.2	.8	- 2					 				3.2	3.4
ENE	1.4	.7	• 2				T	1				2.3	3.8
E	2.1	1.6	• 2	. 1		·	<u> </u>					3.9	3.9
ESE	1.7	.6	. 8	•1		<u> </u>						3.2	4.8
SE	4.7	3.0	1.8	. 8		1	1			1		10.3	5.1
SSE	4.4	3.9	2.2	1.4	•1	1						12.1	5.7
S	3.5	2.8	1.4	.6	.1	<u> </u>				1		8.3	5.C
SSW	.4	.5	•1	• 2	.1				 			1.2	6.3
sw	.9	1.1	- 1	1	1		†		1			2.2	4.4
wsw	• 5	.4	• 2		1							1.1	4.8
w	. 7	. 5	. 7	1	<u> </u>	1	1					2.0	5.5
WNW	.4	.1	.2	.1								. 8	5.2
NW	-8	.5	.4			t	<u> </u>	<u> </u>	<u> </u>	<u> </u>		1.7	4.4
NNW	.8	1.1	•2					<u> </u>		<u> </u>		2.1	4.2
VARBL	1								1				
												41.3	

TOTAL NUMBER OF OBSERVATIONS 1674

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

C

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

W WNW NW NNW VARBL

CALM

1.

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

ROITATE			STATIO	H KAMF						YEARS			•	KONTH
						ALL WE	ATHER						0000	0-0200
						C	LASS						HOUR	5 (L \$ T.)
						CON	DITION							
		_												
	SPEED (KNTS)	1.3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 32	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND
	DIR.	1								'' "	" "		,,,	SPEED
	N	1.2	1.4	.7	• 5	<u> </u>	<u> </u>		 	 	i		3.8	5.7
	NNE	.4	•2	.1	• 1								• 8	4 • 8
	NE	.8	• 4	•2]					1.4	4 • C
	ENE	• 9		•1			,						• 9	2.8
	E	1.5	.9	• 2									2.7	3.5
	ESE	1.2	.7	• 7	• 1								2.2	4.2
	SE	3.3	4.3	3.5	1.2	• 1							12.2	5.9
	SSE	4.3	3.8	4.5	1.6	• 2	-1						14.5	6.4
	S	3.2	2.3	1.9	- 8	• 2	•1						8.5	0.1
	SSW	.4	٠٤	•2	• 1								1.3	5.3
	SW	.6	.4	•3	.1								1.4	5.3
	wsw	. 2	- 2	T				ī —	i				. 4	4.1

TOTAL NUMBER OF OBSERVATIONS ______ 1620

100.C

3.2

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64 JUN YEARS MONTH 0300-0500 ALL WEATHER HOURS (LST) CLASS CONDITION

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.4	1.4	1.2	• 2				 				4.2	5.6
NNE	• 3	•6	•2							····		1.1	4.9
NE	1.3	• 4	•2									1.9	3.4
ENE	-4	•3										.7	3.3
Ε	1.4	.8	•2									2.4	3.7
ESE	1.5	.4	•2	• 1								2.1	4 • C
SE	3.8	5.1	4.4	1.6								14.9	6.2
SSE	3.9	3.4	3.6	1.4	• 1							12.5	6.3
S	3.1	2.5	1.2	• 9	• 1	•1	•1					8.0	6.1
ssw	.8	.4	•2	• 3		•1						1.8	6.1
sw	• 9	•6	•2	. 1								1.9	4.6
wsw	.1_	-1	1									. 3	5.0
w	5	.4	.1	. 1	. 1							1.2	5.6
WNW	- 5	.2	. 1									• 7	3.9
NW	.6	• 8	.1		• 1							1.5	4.8
NNW	.5	1.0	.4	1								2.0	5.4
VARBL													
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$		\times		42.8	
	20.9	18.3	12.7	4.9	.3	.1	.1					160.C	3.2

TOTAL NUMBER OF OBSERVATIONS

1620

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUC	KA KYL		PAN/IT	ALUKE	A8	47-6	, 4						JUN
MOITATE		_	STATIO	N NAME			ATHER			YEARS			0600	000TH 0-~80C 5 (LST.)
						CON	DITION							
	SPEED (KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.3	2.1	1.2	• 3								4.9	5.5
NNE	.7	.6	. 4									1.7	4.6
NE	• 8	.7	•5	•1								2.1	5.C
ENE	•6		.1	.1								.7	3.9
E	.8	.2	. 3	.1				ļ				1.4	4.6
ESE	.5	.6	.6	<u>•</u> l_								1.8	5.7
SE	3.4	4.7	5.6	1.7	.1		ļ					15.5	0.5
SSE	3.3	5.3	5.7	1.6	.2	•2	<u></u>					16.4	6.8
S	3.1	3.8	2.0	1.1		•1	<u></u>	ļ	 			10.1	6.2
ssw	.4	.7	.4	• 2				<u> </u>	ļ			1.7	6.4
sw	.6	• 5	.4	•1			<u> </u>	 	<u> </u>	 		1.6	5.4
wsw	.4	.1	.1	• 1			!					.6	2.2
W	.2	.7	• 5	.4	-1		ļ	-1		•1	 	2.1	10.5
WNW	.4	-1	.2		ļ.———						ļ	7	4.4
NW	.6	.5	• 2	-1						<u> </u> -		1.4	4.6
NNW	1.0	.8	-4	• 2			<u> </u>	 	ļ			2.4	5.5
VARBL			ļ	Ļ		<u></u>	· —						
CAL	$\geq \leq$	$\geq \leq$	$\geq \leq$	><	$\geq \leq$	><		$\geq \leq$	<u> >< </u>	$\geq \leq$		34.9	
	18.1	21.4	18.6	6.0	.4	.3		.1	<u> </u>	.1]	100.C	4.1

TOTAL NUMBER OF OBSERVATIONS 1620

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FO

OK OK

EATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 298C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

2210	としない	KA_KYU	SHU JA	PANZII	AZUNE	AD	41-0	4					J	UN
STATION			STATION							YEARS			M	HTHO
						ALL WE	ATHER							-110C
		_					ASS						HOURS	(LST)
		_												
						CONI	MOITION							
				·										
(SPEED										 -			
,	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN UNIW
ļ	DIR.	'''	7.0	,	11.70	17 - 21	22 - 27	20.33	34 - 40	71 - 7/	40.33	-30	'°	SPEED
	N	1.9	2.8	ن. 2	.6					- 	 -		7.3	5.9
1	NNE	.4	7	.6	• 2						<u> </u>		2.C	6.5
İ	NE	1.0	1.3	آگو•	. 3						i		3.4	5.6
ļ	ENE	.4	.4	.4	. 1			i					1.2	5.8
ľ	F	.9	•9	•6	• 2								2.5	5.3
	ESE	.7	• 3	. 8_	• 1								1.9	5.9
j	SE	1.1	2.2	5.6	2.6								11.5	8•i
)	SSE	1.1	3.5	4.8	3.5	• 2							13.1	8.4
	<u> </u>	1.8	2.3	2.5	1,4	.4	•1						8.5	7.7
1	SSW	-6	-4	. 9	.4	-1					<u> </u>		2.3	7.2
	SW	.6	1.1	.2	. 2					<u> </u>			2.2	5.5
	WSW		2_	.4					ļ	ļ	ļ	}	.9	7.8
	W	- 9	1.5		• 5	1	<u>•1</u>		 		<u> </u>		4-1	6.7
	WNW	.9	1.8	1.6	-4		-1		 				4 - 8	6.9
	NW	1.4	3.8	4.0					 		ļ		9.9	6.7
	NNW	1.0	2.9	2.5				ļ	 	 	 		7.2	6.5
ŀ	VARBL						$\dot{-}$						17.2	
	CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$		<u></u>				11.2	
ł			24.0	20.0			•				l		100 0	5 0

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

TATION	EUKUC	<u>KA KYU</u>	SHU JA	PAN/IT	AZUKE	AB	47-6	4						UN
HALION			STATION	MANE						YEARS				
						ALL WE	ATHER							-14CC
						Ç.	.423						NOVA:	(1)
		_				CON	DITION							
											_			
ſ	SPEED								l					MEAN
Į	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.	<u> </u>												SPEED
	N	4	2.3	4.4	1.8				İ		<u> </u>		9.0	8.?
L	NNE	.4	.7	1.0	.7		<u> </u>		<u> </u>				2.8	1.9
- 1	NE	.2.	1.1	1.7							<u> </u>		3.0	6.9
ĺ	ENE	.1	.2	1.4	• 2								1.9	8.2
	E	• 5	1.1	7	1								2.4	6.0
[ESE	.2	.8	1.1	• 1								2.3	6.9
	SE	.5	1.5	3.6	1.4	• 1							7.C	8.2
ĺ	SSE	.6	1.7	2.7	2.1	. 2)	7.2	8.7
I	5	.7	1.4	3.2	2.3	.3	.1						8.0	9.6
Į	SSW	.1	.1	. 4	. 7								1.3	11.1
	SW	1	.4	_4	• 2		<u></u>]]	<u> </u>			1.1	7.7
ĺ	wsw	1_	. 2	4	2	1		<u> </u>	<u> </u>	<u> </u>	<u> </u>		1.1	9.2
- 1	W	1	. 7	5_	-6		1		<u> </u>	<u> </u>			2.0	8.8
1	WNW	4	1.7	2.5	1.2				<u> </u>			}	6.C	8.2
ĺ	NW	1.2	6.0	11.5	4.8	.2							23.6	8.4
[NNW	.6	3.5	8.0	3.8	2_							16.C	8.7
Ī	VARBL				l			<u> </u>	<u> </u>	<u> </u>				
-	CALM	\times	\times	\mathbb{X}		><			><	><	><	><	5 • 2	
		6.0	23.5	43.7	20.2	1.1	.3	 		1			100.C	8.0

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	EUKUI	CKA_KYU	SHU JA	PANZLI	AZUKE	AB	47-6	4		YEARS				UN
PIATON			3141101	NAME.						IEARS				
						ALL WE	ATHER							-17CC
						CI	ASS						HOURS	(L S T.)
						CON	DITION							
Γ	SPEED	<u> </u>									 1		1	MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
Ì	DIR		, -		.,							_55	~	SPEED
	N	.6	3.2	5.1	2.0			.1					11.0	8.1
I	NNE	.4	.7	1.0	.8								3.C	7.8
[NE	.6	2.0	1.5	. 4								4.5	6.3
I	ENE	•2	.6	.7	• 2								1.7	7.3
ĺ	E	.5	.8	.9	•2								2.4	6.3
[ESE	• 3	.4	.4	• 5	.1							1.7	8.6
Ī	SE	2	1.9	2.4	1.1								_ 5.5_	0.6
	SSE	.2	1.0	3.0	1.6	-1							_5.9	9.2
ĺ	S	. 2	• 9	1.7	1.9	•1							4.8	9.7
	SSW	1	.2	. 9	. 8	.1							_ 2 • C_	10.5
Į.	SW	• 2	.4	.4	.1	.1							1.2	7.1
	wsw	1	.2	4	5								1.2	9.7
Į	w		1.0	1.2	1.0	1							3.3	9.1
ĺ	WNW	• 3	1.5	2.8	1.9	.4							6.9	9.5
	NW	8	4.5	11.9	4.6	.2	1		L				22.2	8.6
Ì	NNW	.6	4.1	9.9	4.0	• 2			l				18.7	8.5
	VARBL													
	CALM	><	$\geq <$	$\geq \leq$	$\geq \leq$	$\geq \leq$	\geq	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	4 • C	
		5.3	23.2	44.3	21.7	1.3	•1	.1					100.C	8.1

TOTAL NUMBER OF OBSERVATIONS

1614

CAIA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

		******							LLAND			-	· ·
					ALL WE	ATHER				-			-2000
													. (=
					CON	DIT'ON							
SPEED										[MEAN
(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
DIR.					}	ļ	ļ	1]		4	SPEED
N	2.3	5.5	3.0	1.1	•1					i — i		12.1	6.2
NNE	1.5	2.1	.7	• 1								4.4	4.8
NE	2.3	1.4	• 5	• 1								4.3	4.3
ENE	• 3	.7	.4	• 1								1.5	5.6
E	• 5	• 7	•6	• 2								1.9	6.2
ESE	• 3	•4	.4	.1								1.1	6.1
SE	. 5	2.2	2.4	. 7	• 2							6.1	7.4
SSE	•6	1.3	3.3	.7								5.9	7.8
S	. 7	2.2	1.7	1.4	.1			ĺ				6.0	7.€
ssw	.3	.4	.8	.2	-1							1.9	.7.9
sw	.6	.9	.3	.2	-1							2.0	6.5
wsw	• 6	.8	.3	. 2			<u> </u>	<u> </u>				1.9	5.7
W	7	2.5	1.1.	.3				<u> </u>				4.6	6.0
WNW	1.0	2.2	2.4	.4	ļ	<u> </u>	<u> </u>					6.1	6.4
NW	2.4	5.8	3.6	.4		<u> </u>		ļ				12.2	5.7
NNW	2.0	5.3	4.1	• 5			<u> </u>		L			11.9	5.9
VARBL	1	1	l	i	1	İ	1		l	1		H 1	

TOTAL NUMBER OF OBSERVATIONS

1620

100.0

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

FUKUCKA KYUSHU JAPAN/I TA/UKE AB 47-64

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	JUN
STATION	STATION NAME	YEARS	MONTH
	ALL W	2100-2300	
		CLASS	HOURS (EST.)
•	co	ONDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 19	11 - 16	17 - 21	22 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.7	2.2	1.4	•2	•1							5.6	5.7
NNE	1.4	•8	.3									2.5	4.C
NE	2.4	1.4	.3	_•1								4.1	3.7
ENE	1.3	•1	•1									1.5	2.8
Ę	2.2	•4	.3									2.9	3.4
ESE	1.0	.4	. 4	. 1								1.9	4.3
SE	3.9	4.0	2.2	. 8	• 2					<u> </u>		11.C	5.5
SSE	3.8	3.2	3.8	1.1	.1							12.C	6.2
S	1.9	3.0	1.6	1.C								7.5	€.2
SSW	.5	.7	•6	• 3								2.€	6.2
SW	1.0	.7	- 4					L]	2.0	4.3
wsw	•2	• 3						<u> </u>				.6	3.9
w	.5	•6	• 3	• 1						<u> </u>		1.5	5.3
WNW	.6	•7	.3							l		1.6	4.6
NW	1.0	1.3	• 2	• 1	I				<u> </u>			2.6	4.3
NNW	.8	1.1	.6	• 3								2.8	5.6
VARBL													<u> </u>
CALM			><	$\geq \leq$	$\geq <$	\geq		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	38.C	
	24.2	20.7	12.7	4.1	.4							100.C	3.3

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EJITIONS OF THIS FORM

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

> NNW VARBL

CALM

many the second

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

SURFACE WINDS

JUL 0000-0200

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

47-64

					ALL WE	ATHER							-0300
						ASS						HOUR	(L S.T.)
					CON	DITION							
							 			_			
SPEED	 1						T						MEAN
(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
DIR.					ļ				ļ	i i			SPEED
N	.6	.7	• 1			ļ						1.3	3.9
NNE	.4	•1	• 1									.6	3.9
NE	1.1	• 2	• 2						·			1.5	3.4
ENE	•8	•2		• 2					i			1.2	4.3
E	1.4	1.0	•2									2.6	3.8
ESE	.7	1.1	• 8	• 1	i							2.7	5.7
SE	3.5	7.1	8.5	1.7	•1							21.C	6.6
SSE	2.6	7.0	6.6	1.7								18.0	6.6
s	2.4	3.3	4.0	1.4								11.2	6.7
ssw	.7	.4	.6	.3								1.9	6.6
sw	.7	.8	• 5	• 1								2.2	5.4
wsw	•1	.1	•1									.4	5.0
w	• 3	•4	.2	•1						L		1.0	5.8
WNW	•2	.4	.2	• 1	<u> </u>							• 8	5.8
NIVA/	1 0	3		1			1					1.7	5.4

1674 TOTAL NUMBER OF OBSERVATIONS

30.7

100.C

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

4.3

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

e 💉

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	JUL
STATION	STATION NAME	YEARS	нонти
	ALL W	EATHER	0300-6500
		CLASS	HOURS (L.S.T.)
	co	MOLTION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	• 7	.5	• 1									1.4	3.8
NNE	.4	.4	•2									• 9	4.5
NE	.7	.4	•2									1.3	4.2
ENE	.4	•1	•2	• 1								.7	5.3
E	1.4	.8	• 5	• 1								2.8	4.7
ESE	•6	1.3	1.0	.4								3.3	6.5
SE	3.6	7.6	8.3	2.0	•1							21.7	6.6
SSE	2.4	6.1	7.5	2.0	.1							18.0	7.C
S	2.7	4.0	2.9	1.4								11.1	6.4
ssw	• 2	.7	• 8	.4								2.2	7.1
SW	.1	.7	.4	• 2								1.3	6.8
wsw	• 2	•2	•2									• 6	4.8
w	•2	• 3	.1	.1				i				• 6	5.€
WWW	.1	•3										• 4	5.2
NW	• 5	.4	.4	• 2								1.6	5.8
NNW	• 3	• 3	• 2									- 8	4.7
VARBL													
CALM	><	$\geq <$	$\geq \leq$	$\geq \leq$	><	\geq	><	$\geq \leq$	$\geq \leq$	\geq	><	31.5	
	14.5	24.1	22.9	6.8	•2							100.C	4.4

TOTAL NUMBER OF OBSERVATIONS

1673

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

5,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

4331C STATION	EUKU	KA KYU	SHU JA	PAN/II	AZUKE	AB	47-6	4		YEARS			J	UL
Jinton		_				ALL WE							0000	-0800 (LE.T.)
		_				коэ	DITION							
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 · 21	22 - 27	28 - 33	34 - 40	41 - 47	48 · 55	≥56	%	MEAN WIND SPEED
ĺ	N	.7_	• 7	.4	. 1								1.7	4.9
ļ	NNE	.1	.2										• 4	4.C
į	NE	1.C	.7	.4									2.0	4.4
	ENE	- 2		.2	-1								4	5.7
]	E	1.3	1.1	.4							L		2.8	4.4
j	ESE	1.0	1.3	.8	.4	-1							3.5	6.0
ļ	SE	3.0	6.5	11.1	3.0								23.7	7.3
	SSE	2.4	6.6	8.0	3.1	• 2		ļ <u> </u>		<u> </u>			20.4	7.3
	S	2.6	3.8	3.8	1.8	•1							11.9	6.8
,	ssw			8									2.2	6.3
]	sw	.7		.5	- 2					<u> </u>			1.9	6.1
]	wsw	1_	2	.2	1_	-1_		ļ	ļ		ļ	<u> </u>	.7	7.1
	W		2	2_		ļ				ļ			8.	4.6
	WNW	2_			ļ					<u> </u>			- 4	3.3
	NW	. 2		2_	ļ	<u> </u>					ļ		. 9	5.0
	NNW	4	.8_		-1	ļ		ļ		<u> </u>		<u> </u>	1.3	4.3
	VARBL		<u></u>		<u></u>						<u></u>		<u> </u>	
	CALM	$\geq \leq$	\times	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	25.0	
		14.9	23.8	27.1	8.9	.4							100.0	5 · C

TOTAL NUMBER OF OBSERVATIONS

1674

CATA PROCESSING CIVISION FTAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	EUKU	OKA KYU	SHU JA	PAN/IT	AZUKE	AB	47-6	4						IUL
STATION			STATION	NAME						'EARS				ONTH
		_				ALL WE								-110C
						CI	LASS						HOURS	(L S.T.)
		_												
						CON	MOITID							
		_												
											,,			
	SPEED	l I							1]		,	MEAN
	(KNTS)	1.3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
	DIR.						ļ							
	N	8-	1.6	. 7	2				ļ		<u> </u>		3.3	5.3
	NNE		1.5		•.						İ		2.6	4.4
	NE		- 4	.2	•1		ļ		<u> </u>				1.4	4.8
	ENE	1_	•8	.4	.1		<u> </u>						1.4	6.2
	E	.7	1.0	. 5	• 1			<u> </u>					2.3	5.5
	ESE	.5	1.0	1.0	. 2					Ì	L		2.7	5.9
	SE	1.4	3.9	9.7	3.7	.1	L	L			•		18.8	8.3
	SSE	•9	3.6	8.7	5.1	• 2	-1			<u> </u>			18.7	9.1
	S	1.6	3.3	4.8	3.2	• 3							13.2	8.2
	SSW	.6	•7	1.9	1.0					I			4 • 2	8.2
	SW	.8	• 9	1.0	.4								3.1	6.6
	wsw	.4	. 3		.1								1.1	6.1
	W	.5	.9	.6	. 2								2.2	6.1
	WNW	.4	1.0	.1					1				2.2	5.9
	NW	1.1	3.0	1.7			-1						6.0	5.6
	NNW	1.3	2.2	1.1	• 1				·		1		4.6	5.2
	VARBL	1						i	<u> </u>					
	CALM												12.1	
	CALM													
		12.6	26.1	33.7	14.7	.7	.2	Ì	<u> </u>	<u> </u>			100.C	6.5

TOTAL NUMBER OF OBSERVATIONS 1674

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288G1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

S10 STATION	EUKU	CKA KYU	SHU JA	PAN/IT	AZUKE	<u>AB</u>	47-6	4		TEARS				UL
		_				ALL WE	ATHER						12CO	-140
		<u>-</u> -				CON	DITION							
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	M WII
	N	.7	2.2	2.9	•6								6.4	7
	NNE	.1	.7	.4	•1								1.3	6
	NE	.2	1.0	. 8	.2								2.2	6
	ENE	1	.6	.5	.2			<u> </u>					1.4	6
	E	1	• 8	1.2			ļ	.1_			ļ		2.4	7
	ESE	2_	5_	1.0							ļ <u>.</u>		1.9	7
	SE	.7	2.3	4.1	2.2	•1	ļ	ļ	 		ļ		9.3	<u> </u>
	SSE	3	2.2	5.2	3.9	-6	ļ			<u></u>			12.2	9
	ssw	8	2.3	6.5	5.7	.4	 	 	<u> </u>	 -	 		15.7 5.5	1.0
	SW	2	<u>.7</u>	2.2	2.0	.4	<u> </u>	 	 	 	 		2.4	10
	wsw	•1	.4	1.1					 	 		 	1.1	6
	- W	.4	.8	1.1	.3						-	<u> </u>	2.6	7
	WNW	.2	1.0	1.6	.6	i							3.5	7
	NW	- 8	3.6	10.2	1.2	i	 	 					15.8	7
	NNW	.3	2.1	7.2	1.2		-1						10.9	8
	VARBL													
	CALM	\leq	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		5.5	
		5.4	21.7	46.4	19.3	1.5	.1	.1	· ·	1		\	100.C	8

TOTAL NUMBER OF OBSERVATIONS

1671

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

æ: "≻

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

49910	FUNU	LIA NIO	SUO SH	LWIALT I	ALUNE	AU	71-0	7					•	O.C.
MOITATS			STATIO	NAME						YEARS				ONTH
						ALL WE	ATHER						1500	-170C
		_		· · · · · · · · · · · · · · · · · · ·			ASS						HOURS	(LST)
						CON	MOLTIC							
											_			
	SPEED							Ϊ						MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.							<u> </u>			li			SPEED
	N	1.0	3.3	4.4	1.1								9.8	7.2
	NNE	•3	•6	.7	• 3								1.9	7.1
	NE	• 5	1.3	1.0	1								2.9	6.1
	ENE	• 5	.4	• 9	1	. 1			•1				2.0	8.4
	E	•2	•9	1.5	.4								2.9	7.4
	ESE	• 2	•6	• 5	• 2								1.5	7.1
	SE	•6	1.4	3.0	1.5	.1							6.6	8.5
	SSE	• 3	1.2	4.2	2.9	.4	.2						9.3	10.3
	S	•2	1.8	6.6	4.9	• 2	.1						13.7	9.9
	SSW	•1	1.1	1.7	1.6	L							4.4	9.3
	SW	• 3	•5	1.2	• 9					l			2.9	8.7
	wsw	.1	.4	•2									. 8	5.6
	W		1.1	1.3	_ • 5								3.C	7.8
	WNW	•1	1.1	1.1	. 8								3.0	8.3
	NW	•6	4.1	10.3	2.3					l			17.2	8.1
	NNW	•6	3.3	8.4	1.6								13.8	7.9
	VARBL				l									
	CALM												4.2	
	1	_	_	_		_	_	\sim	_	\sim				

TOTAL NUMBER OF OBSERVATIONS 1674

100.G

8.0

DATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

6. %

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	JUL
STATION	STATION HAME	YEARS	итиом
	ALL W	EATHER	1800-2000
		CLASS	HOURS (LST.)
	co	NOITION	

SPEED (KNTS) DIR.	1 . 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	2.3	4.4	2.3	•2					i			9.3	5.2
NNE	.7	1.3	.4									2.5	5.C
NE	1.3	1.6	.4									3.4	4.3
ENE	.7	-8	-4			•1	•1					2.1	6.7
E	. 8	1.9	1.3	• 1								4.0	5.5
ESE	.6	1.0	.7	• 2								2.4	5.8
SE	1.0	3.1	4.3	1.0	• 1							9.5	7.3
SSE	8	3.1	5.7	2.6	• 2	• 1						12.6	8.4
S	. 8	2.9	4.9	2.3	.3							11.1	8.3
SSW	.3	1.0	1.2	. 8								3.3	8.1
sw	•5	1.1	1.0	.1								2.8	6.0
wsw	.1	. 5	.4									1.0	5.6
W	7	1.6	1.0	.1	.1							3.4	5.9
WNW	6	1.3	.8	<u> </u>	.1							2.8	5.6
NW	1.6	4.7	3.3	• 2								9.8	5.7
NNW	• 9	5.1	3.5			<u> </u>						9.6	5.7
VARBL													
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		10.7	
	13.8	35.4	31.6	7.6	.7	.1	.1					100.0	5.9

TOTAL NUMBER OF OBSERVATIONS 1671

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLET

located in a

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUGKA KYUSHU JAPAN/ITAZUKE AB 47-64	JUL
STATION	STATION NAME YEARS	HONTH
	ALL WEATHER	21 CC-230C
	CLASS	HOURS (LST)
	CONDITION	

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	•9	1.7	• 3	•1			i		i			2.9	4.7
NNE	•5	• 5	•1									1.1	4.1
NE	1.3	1.1	•1									2.6	3.7
ENE	.8	.4	•2	.1	i							1.4	4.2
Ε	1.9	1.1	•5	• 1						i		3.7	4.1
ESE	1.0	•6	•7	• 2	•1							2.6	5.9
SE	2.6	4.7	6.6	1.8			<u> </u>		1			15.7	6.8
SSE	2.6	6.3	6.2	2.2	•1	•1	1					17.5	7.0
S	1.6	3.9	3.4	1.5								10.4	6.8
SSW	•5	•5	•4	•2								1.7	6.0
SW	1.2	.7	•7	•2								2.8	5.2
wsw	• 5	•2	•1									• 8	3.8
W	• 5	•3	•1		i							1.0	3.8
WNW	• 3	•5		•1								-8	4.6
NW	1.4	1.3	• 3	.1								3.1	4.3
NNW	.4	.8	•2	•1	•1							1.6	5.7
VARBL	1				1								
CALM	>	\geq	\geq	><	><		\geq	\geq	\geq	$\geq \leq$	$\geq <$	30.3	
	18.1	24.9	19.8	6.6	.2	.1						100.C	4.2

TOTAL NUMBER OF OBSERVATIONS

1671

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

oK.

SURFACE WINDS

٠.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64	AUG
STATION	STATION NAME YEARS	HONTH
	ALL WEATHER	0000-0200
	CLASS	HOURS (L S.T.)
	CONDITION	

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	.3	. 8	• 2	•1								1.4	5.2
NNE	.7	.1_		• 1								• 8	4.5
NE	. 8	• 4	• 3	1								1.5	4.7
ENE	5	.4	. ?.	. 3		• 2	• 1			.1		1.7	10.6
E	1.1	1.1	• 5	•5	_ • l							3.2	6.1
ESE	1.3	. 8	- 8	.2								3.C	5.4
SE	4.7	5.0	5.1	1.0	-,2							15.9	5.9
SSE	3.7	5.0	3.0	.8	• 3	•1	.1					13.0	6.1
S	4.1	3.8	1.0	.4	•2							9.4	4.7
SSW	.3	• 5	. 3	.2								1.3	5.9
SW	.4	.4	.1	-1								. 8	4.4
WSW				1	l				Ĺ			.1	11.0
W	3_	2										.5	3.6
WNW	.3	.1	.1	Ĺ	L							5	3. /
NW	5_	.3	1					1				. 9	4.3
WWW	.4	3_	.2	4				<u> </u>		L		1.3	7.3
VARBL					L								
CALM		><	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	\times	44.5	
	19.2	19.2	11.9	4.0	.7	.2					}	100.C	3.2

TOTAL NUMBER OF OBSERVATIONS 1674

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

The State Company of the State

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

	_				ALL NE	ATHER						03CO	<u>- (</u>
	_				CON	DITION							
SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	,
N	5_	.4	.2									1.2	
NNE	4	2				ļ						. 8	<u> </u>
NE	5_	5_	2_			ļ		 		 _		1.3	L_
ENE		4		3_	1_	1		ļ	ļ			1.7	<u> </u>
E	1.4	1.0	9_	4		ļ		1		 		3.8	<u> </u>
ESE	_1.1.	_1.1_				ļ			 	ļ		2.9	<u>Ļ</u> _
SE	4.4	5.0	5.2	8_		ļ <u>-</u>	-1	-1	ļ	 	<u> </u>	15.6	
SSE	4.2	5.9	4.7									16.0	-
S	3.3	2.9	1.5	4_		 	 	 	 -			8.1	
SSW	7_	5_	2_				ļ		 	 	 	1.4	
WSW	4_	2_	2				 -	 	 			• 9	
W			-2	 		 		 				.8	-
WNW	4_	2			ļ	 	 	 		 		• 5	-
NW	-2	-1	1	 	 	 	 -	 	 			• 5	-
NNW		2	1	-2		 -		 		\vdash $-$	 	1.C	
VARBL						 	 	 				<u> </u>	
CALM	\geq	$\geq \leq$	$\geq <$	>	\geq	\geq	$\geq \leq$	\geq	> <	$\geq \leq$		43.4	
	19.0	18.7	14.8		.5	.1	.1	•2				100.C	

TOTAL NUMBER OF OBSERVATIONS

167

1210 WS JUL 14 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64

CATA PRCCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

۲; <u>X</u>.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64												AUG		
STATION	STATION NAME YEARS													HTROM	
	ALL WEATHER												0600-6800		
		CLASS											HOURS	(LST.)	
		_													
			CONDITION												
		_													
												a			
	SPEED (KNTS)											~	۰,	MEAN	
	DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED	
		 						 	 	 					
	N Auto	6	4	2	1_			 	 	 -	ļ		1.4	6.1	
	NNE	5_	2_	.2	2		 	 	ļ	 			1.1	5.9	
	NE	4_	5_	.5					ļ	 	ļ		1.6	6.6	
	ENE	3	3_	.4	.4	-1	<u> </u>	1	<u> </u>	<u> </u>			1.6	9.3	
	E	1.5	.7	1.0				1			ļ		3.9	6.6	
	ESE	7	. 5	. 9	2_								2.2	6.1	
	SE	4.2	5.2	6.5	1.6			<u> </u>		<u> </u>	<u> </u>		17.7	6.6	
	SSE	3.3	6.4	5.7	2.2	-1	-1						17.7	6.9	
	٥	3.3	4.1	1.3	5				l		<u></u>		9.2	4.9	
	ssw	.4	.7	.2									1.4	4.8	
	SW	.7	•2		•1			.1	1				1-1	7.2	
	wsw		1	.1	1		l						• 2	8.0	
	W	.2	.1	. 1	- 1				<u> </u>				• 5	6.9	
	WNW	.2	- 2	. 1	-1			1				1	• 5	5.4	
	NW	- 5	.5	- 2	.1								1.2	4.8	
	NNW	.4	- 4		1		- 1					1	1.1	6.5	
	VARBL				1	i				1	<u> </u>				
	CALM				> <	$\supset <$							37.5		
		17.2	20.4	17.4	6.5	.4	.4	•2					100-C	4.C	

TOTAL NUMBER OF OBSERVATIONS

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS ADITIONS OF THIS FORM ARE ORSOLETT

AND THE RESERVE

DATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

€.

SURFACE WINDS

AUG

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	. EUKU(FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64													
STATION			STATION	NAME					1	TEARS				HTMO	
		ALL WEATHER											09C0-11CC		
		CLASS											HOURS (L S.T.)		
		_	CONDITION												
		_													
	SPEED]											Ì	MEAN	
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND	
	DIR.													SPEED	
	N	1.9	2.2	2.0	. 3								6.4	5.6	
	NNE	1.6	1.3	.6	• 2	2							3.3	6.2	
	NE	8	1.6	1.0	• 5								3.3	6.5	
	ENE	.2	•3	1.3	• 5			.1		L			2.4	9.0	
	Ε	• 5	1.0	1.5	• 5	.2			L				3.8	8 • C	
	ESE	.7	.4	1.3	• 5	• 2							3.€	8.3	
	SE	1.6	3.0	6.3	2.7	• 1	• 1						13.7	7.9	
	SSE	1.4	4.2	6.2	3.0	.2	•1						15.2	8.1	
	S	1.3	3.4	2.6	1.3	.2	•1	•1_	•1				9.C	7.7	
	SSW	.7	1.5	•5	.4								3.0	5.9	
	SW	•8	• 8	.4	.1								2.2	4.8	
	WSW	-1	•2	- 3									• 5	6.4	
	W	.8	•7	•2	• 2		•1	•1					2.0	7.2	
	WNW	.4	1.2	.8	. 2								2.6	6.3	
	NW	2.0	2.4	1.6	.5		Ī						6.5	5.8	
	NNW	1.1	2.6	1.9	.5								6.1	6.1	
	VARBL			Ī											
	CALM												17.2		
							\leq				\leq				
		11	t .	1	1	I .	1	1		1	1				

TOTAL NUMBER OF OBSERVATIONS 1674

DATA PROCESSING LIVISION ETAC. USAF ASFEVILLE. N. C. .88C1

SURFACE WINDS

1673

PERCENTAGE FREQUENCY OF WIND O RECTION AND SPEED NOOM HOURLY OBSERVATIONS)

A1	43310	<u>FUKu(</u>	FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64											AUG	
SPEID 1 - 3	BOITATE			STATION	N M						YEARS				
SPEID 1-3							ALL WE	LIMER							
SPEID 1-3							CI	.A52						HOURE	(L S T.)
SPEID 1-3															
N							C.4.	OM							
N															
N															
(i' its)	1	ene: o	·			- 7				ı			 -	, 	
DIR. N	į		1.3		7.30		.7 . 21	22 27	28 . 22	24 40	41 . 47	40	>64	9/	
NNL			1 - 3	1.0	- 10	1. 10	17 - 21	22 . 2/	20.33	34.40	41 . 7/	""	-30	"	SPEED
NNL	ļ	N	.7	2.6	4.6	•6	- 2					 		9.7	8.C
ENE		NNL	• 3	1.1		.4		•2						2.9	8 • C
ENE		NE	.5	1.3	1.7	• 4								4.0	7.0
ESSE .2 .7 1.1 .5 .1 .2 .5 .1 .7 .8 .2 .7 .7 .4 .8 .5 .1 .7 .2 .5 .1 .7 .2 .5 .1 .7 .4 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1		ENE		• 5	1.4	. 8	. 1							2.9	9.4
ESE		E	•2	.,	1.7	- 8									8.3
SSE		ESE		.2		, 5	ν I							2.0	9.C
SSE		SE	. 7	1.7	3.1	1.7	• 2							7.4	8.5
SSW .1 .6 1.3 .5 .1 .2 .6 8. SW .2 .6 .5 .3 .1 .1 .1 .7 8. WSW .1 .2 .3 .1 .1 .1 .7 9. WNW .1 1.0 1.4 .8 .1 .1 .1 .1 .1 .1 .1 .7 9. NNW .8 5.1 10.2 2.4 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1 .1		SSE	• 2					.1	.1					8.2	10.1
SW .2 .6 .5 .3		\$	• 5	1.9	3.0	2.0	. 5	• 1							9•0
SW .2 .6 .5 .3		SSW	• 1	۰,6	1.3	• 5	•1							2.6	8.8
W .2 .3 .7 .4 .1		SW		•6		• 3								1.6	6.8
WNW .1 1.0 3.4 .8		wsw	.1	• 2	. 3	• 1	. 1		L					.7	8.3
WNW		w	•2	. 3	.7	• 4	.1	1							9.C
NNW 1.0 4.2 9.5 3.8 18.4 8. VARBL CALM 4.4	,	WNW	.1	1.0	1.4	<u>. 8</u>		<u> </u>							8.4
VARBI CALM 4.4		' NW	.8	5.1	10.2	2.4	.1		<u> </u>	<u></u>					7.9
CALM 4.4		NNW	1.0	4.2	9.5	3.8				ļ				18.4	8.4
		VARBL]	<u> </u>						
5.8 23.2 45.1 19.3 1.7 .4 .1		CALM				\geq	><		$\geq \leq$	$\geq <$	><	$\geq <$	><	4.4	
	!		5.8	23.2	45.1	19.3	1.7	.4	.1					100.0	8.1

TOTAL NUMBER OF OBSERVATIONS

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

£

(1

11

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUŰ	CKA KYU	SHU JA	PAN/IT	AZUKE	AB	47-6	4					Д	UG
STATION			STATIO							YEARS				ONTH
						ALL HE	ATHER						15C0	-17CC
		_				c	LASS						HOURS	(L S.T.)
		_												
						CON	MOITIG							
		_												
	SPEED	1				·	· · · · · ·			·				MEAN
	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR	,			}		ļ				, ,	1		SPEED
	N	• 7	2.4	7.1	2.0	• 3							12.5	8.4
	NNE	• 3	-8	1.3	.7	. 1	• 1						3.3	ું ક
	NE	• 4	1.3	1.7	.4								3.8	7.C
	ENE	.4	1.0	1.7	1.0	• 2	•1						4.3	8.8
	E	•2	1.1	1.9	• 3	.1							3.6	1.6
	ESE	. 3	• 1	• 8	.4	.1	ļ						1.7	8.8
	SE	.1	1.0	2.1	.8	.2	11	.1					4.4	9.5
	SSE	.5	•7	2.2	1.1	.1	<u> </u>					<u> </u>	4.6	8.8
	<u>s</u>	4	1.5	3.0	1.6	.7_	<u> </u>		.1		<u> </u>		7.2	9.1
	SSW		•5	1.4	1.0	.1				<u> </u>			3.1	9.0
	\$W	.1	.3	-4	-1		 						- 8	7.6
	WSW		.4	. 5	-1	ļ	ļ	ļ	ļ	ļ. ——	ļ	ļ	1.0	7.6
	w	-1	-4	1.1	.1						<u> </u>		1.7	7.6
	WNW	.3	1.6	1.4	1.C		<u> </u>		 		ļ	 	4.3	7.9
	NW	.7	4.9	11.4	2.2				<u> </u>		ļ		19.2	7.8
	NNW	.5	3.5	12.0	4.4	•1	 	 	 	 	 	 	20.5	8.8
	VARBL													
	CALM	$\geq \leq$			<u> -><</u>								4.0	
		5.0	21.5	50.2	17.2	1.9	.2	.1	-1		T		100.C	8.1

TOTAL NUMBER OF OBSERVATIONS 1666

1210 WS JUL 84 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PARADO:

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE. N. C. 288C1

Á.

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AŁ	47-64	<u>AUG</u>
STATION	STATION NAME	YEARS	HONTH
•	ALL	WEATHER	1800-2000
		CLASS	HOURS (LST.)
		CONDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.6	6.8	3.3	•2	.4							12.3	6.2
NNE	1.6	2.0	.8	.4	<u>`</u>						1	4.7	5.3
NE	1.6	1.7	1.0	• 2		.1						4.6	5.3
ENE	•8	1.1	-1.0	•4	.1	•1						3.0	7.C
ENE	.8	1.3	1.3	• 3	• 1	 -		 	 			3.8	6.4
ESE		- 1.3	• 7	• 1			 	 				1.9	6.C
	1.3		2.6	•2	•1	•1	 	 -	 			7.0	6.4
SE	1.2	2.5	2.9	1.1	••		•1	.1	 			7.8	7.7
SSE	1.2		2.2	• 5	•2		 -	<u> </u>	 	 	1	6.4	6.8
S	1.1	2.3					 		 	†		2.2	6.0
SSW	.6	. 8	.7	•1		 	 	 -	 	 	1	1.9	4.8
SW	- 6	8_	- 5	<u> </u>	 	 	┼	 		 		.7	5.C
WSW	•2	.4	-1		 	 	1	 	 	<u> </u>		2.1	5.5
W	•5	. 9	.7	├─ ,	 	 		 	├	 	1	2.5	6.0
WNW	.3	1.3	.8	-1	 	├──	 	 	 	 	1	9.5	5.5
NW	1.7	5.0	2.8	-1	├─ ़	 -	 	 		 -	1	11.8	5.8
NNW	2.0	5.7	3.6	-4	1	 		 	 	 	 		
VARBL	ļ		ļ					* -	+	 		17.6	
CALM	><	><	><		<u> </u>		<u> </u>	<u> </u>					
	16.1	36.2	24.6	4.1	1.0	•2	.1	.1				100.C	5.C

TOTAL NUMBER OF OBSERVATIONS

1668

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

Ж.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	O FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-04 TION STATION NAME YEARS										AUG			
STATION			STATION	NAME						YEARS				ONTH
						ALL WE								-2306
						CI	ASS						HOURS	(LST)
						CONI	DITION							
								 .						
	SPEED											 }		MEAN
	(KNTS)	1 - 3	4.6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.		4.0	,				1000	1.	1 71 - 77	10.00	_,,	1 " 1	SPEED
	N	1.2	1.0	• 3	•1	-1							2.6	4.7
	NNE	.9	• 3	.1	• 2						ii		1.6	5.3
	NE	1.5	1.1	. 4			-1						3.1	4.6
	ENE	1.3	.7	. 4	• 2	•1							2.7	5.8
	E	1.7	1.2	•8	•1	•1							4 • C	5.2
	ESE	.8	1.0	•3	• 2		•1						2.4	5.3
	SE	4.8	4.9	3.1	• 5	.1	•1						13.5	5.3
	SSE	3.1	4.3	3.8	1.0	• 2	•1	.1					12.5	6.6
	S	3.2	4.3	1.3	• 2	• 2							9.0	5.C
	SSW	1.0	. 8	• 2	•1								2.1	4.3
	SW	•8	• 1								<u> </u>		. 9	2.9
	WSW	.4	• .?	-1	.1	<u> </u>		<u> </u>	<u> </u>	ļ	<u> </u>		. 8	4.5
	W	•2	.2	1_	<u> </u>								- 5	3.9
	WNW		.2	<u> </u>							ļ		•6	4.0
	NW		-8	-1	-1				ļ				1.4	4.4
	NNW	.7	.8	.4	.4	-1		<u> </u>					2.3	6.8
	VARBL	<u> </u>		<u></u>	ļ	<u></u>	<u> </u>	ļ	<u></u>	<u> </u>	<u> </u>			
	CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	<u> ><</u>	$\geq \leq$	$\geq \leq$	4C.C	
		22.4	21.9	11.3	3.1	.9	•3	.1					100.C	3.3

TOTAL NUMBER OF OBSERVATIONS 1670

DATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

SEP

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	EUKU	KA KYU	CU 211U JAPAIN 11 TOUKE AB 46-64										SEP MONTH	
						ALL he	ATHER				_		0000 ENUON	-02CC
		-				CON	DITION				_			
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
Ī	N	8	9	1.0	3	• 2							3.3	7.4
[NNE	.6	. 5	• 4	2	• 1							1.8	6.4
[NE	1.1	. 9	.5									2.7	5.0
Į	ENE	. 4	3_					<u> </u>		<u> </u>			.7	3.4
l	E	1.1	.5	2_	-1			L	L	1	L	<u> </u>	2.0	4.0
	ESE	_1.8	. 3	2	2	1						l	2.5	4.6
ļ	SE	5.6	5.3	2.7	8_	•1				<u> </u>			14.6	5.1
	SSE	4.1	4.1	2.8	_1.1								12.0	5.6
	<u> </u>	4.4	2.6	1.4	2_	ļ				 			8.5	4.4
	ssw		6_	2_							<u> </u>		1.7	4.4
Į	SW	5_				 	ļ	ļ		 	<u> </u>	<u> </u>	- 9	5.1
	WSW	ļ		 		<u> </u>	 		 	ļ		I		4.C
ļ	W	2_	5_	3_	ļ	 		 	 	 	 	 -	1.C	5.6
	WNW	2_		2	1_	 -	 		 	 	 	 	5	6.4
ļ	NW	2_	5_	2			 	 	 	 		 	1.1	6.7
	NNW VARBL	. 8	4_	6_				 	 	 			2.C	6.9
İ				 		 - - - - - - - - - - - - - 				$\overline{}$	\leftarrow		44.5	
	CALM												44.5	
		H		1	2 2	-	·						100 0	2 0

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64	SEP
HOITATE	STATION NAME YEARS	NONTH
	ALL WEATHER	0300-0500
	CLASS	HOURS (L E.T.)
	COMDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 · 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	. 8	1.1	•6	• 5		.1	•1					3.1	1.6
NNE	•2	.4	• 7	.4								1.6	8.1
NE	1.0	1.1	•3		.1	• 1	•1					2.5	5.5
ENE	•2	• 2	• 2	• 1								• 8	6.5
E	1.1	•4	• 1									1.5	3.4
ESE	1.4	• 7	•1	•1								2.2	4.5
SE	5.7	4.6	3.7	8		1						14.9	5.3
SSE	4.8	4.8	2.2	•6		.1						12.5	5.0
S	3.3	3.3	1.1	2			•1					7.9	4.7
SSW	.7	5	.1									1.4	4.0
sw	• 9	.2		1_	-1				<u> </u>			1.2	4.4
wsw	.1	• 2	.1	.1									5.8
W	5	4	1	1						<u></u>		1.0	5.5
WNW	.1	•2	.3	1_					<u> </u>			8	6.6
NW	.1	1	.4	1_	-1	.1						. 8	9.4
NNW	.5	5_	. 5	. 3								1.8	6.4
VARBL									1				
CALM	$\geq <$	><		$\geq \leq$	$\geq <$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$		45.6	
	21.4	18.5	10.3	3.4	•2	.4	.2					100.0	2.9

TOTAL NUMBER OF OBSERVATIONS 1689

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

lengton | . we

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

SYSTEMS

SURFACE WINDS

×,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64	SEP
- INTION	SIATION TARE / LEARS	WORTH
	ALL WEATHER	0600-0800
	CLASS	HOURS (LST)
	CONDITION	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	.7	1.1	1.1	• 5		•2	•2					3.9	9.2
NNE	•5	• 9	_ • 5	.4	• 1							2.5	7.1
NE	1.2	1.1	• 2	• 2								2.8	4.7
ENE	.4	•1	1_	• 1								- 7	4.1
E	1.1	• 3	.3	.1								1.8	4.4
ESE	1.1	• 8	.4									2.3	4.0
SE	5.4	5.6	3.7	1.3	•1	• 2						16.2	5.8
SSE	4.2	5.0	2.9	• 9	• 1							13.2	5.6
\$	3.1	3.1	8	.4		.1		L				7.5	4.9
SSW	. 9	•5	1	1_	• 1							1.7	4.7
SW	1.1	• 5	.1	• 2								1.9	4.4
wsw	.2	•2	.1	.1	<u></u>	L						. 5	6.1
w	• 3	•2	.2		<u> </u>			<u> </u>				• 8	5.3
WNW	.2	•2	<u> </u>	.1			<u> </u>	<u></u>		L		.4	4.7
NW	5	• 3	-1			<u> </u>		.1	<u> </u>			1.C	6.6
WWW	• 2	-6	.4	. 2			<u> </u>					1.4	6.6
VARBL						L			l				
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		41.5	
	21.2	20.4	11.0	4.7	-4	.5	•2	.1				100.C	3.3

TOTAL NUMBER OF OBSERVATIONS

1688

BATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

x,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.9	2.5	2.2	• 5	.4	•2	1					7.7	7.2
NNF	• 9	2.1	1.2	• 6	.1	•1						4.9	6.8
NE	1.2	2.0	2.2	. 8								6.1	6.9
ENE	.4	• 8	.7	.1								2.0	6.3
E	• 8	• 8	.4									1.9	4.6
ESE	.7	.7	• 5	• 1								2.C	5.5
SE	1.7	4.0	4.0	1.7			•1					11.3	7.1
SSE	1.8	3.7	5.3	1.8	. 1	•1	•1	.1				12.9	7.6
S	2.1	2.5	2.0	. 5		.1						7.1	6.0
SSW	. 8	1.4	.7	. 1		l						3.1	5.5
SW	.5	•6	.4	•2								1.7	6.1
wsw	•2	•2	.2	.1								• 8	5.8
w	1.0	.9	.9			.1						2.9	5.9
WNW	.4	1.1	. 8	.1					<u> </u>			2.3	6.0
NW	1.2	2.4	1.2	. 2				.1				5.1	5.8
NNW	.9	1.8	1.6	.6		.1						5.0	6.8
VARBL						<u></u>	<u> </u>						
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		23.1	
	16.5	27.5	24.1	7.4	• 5	.5	.2	.1				100.C	5.1

TOTAL NUMBER OF OBSERVATIONS

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64											SEP		
STATION			STATIO	. HANE						YEARS			•	HTHO
						ALL WE	ATHER						1200	-14CC
							L/SS						HOUR	(L S T.)
								_						
		_				CON	DITION							
		_												
i	SPEED								Γ					MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.	Ĺ]				SPEED
	N	1.1	3.3	6.1	2.7	• 4	.1						13.7	8.5
	NNE	•6	2.2	2.4	1.2	•1	•1						6.7	7.9
	NE	- 8	3.0	3.1	• 7	• 1							7.6	6.9
	ENE	.4	•8	1.2	• 5								2.9	7.3
	E	• 3	1.5	.4									2.2	5.4
	ESE	• 2	•4	•4	•2								1.2	7.3
	SE	•2	2.1	3.1	•6	•1	1			i			6.0	7.7
	SSE	.4	.9	2.7	1.4	•1							5.4	9.1
	S	.4	1.6	1.5	1.1	•1	•1	•1	•1				4.9	9.1
	SSW	•2	.4	• 5	.5	.1	•1						1.9	9.6
	SW	.4	.5	•1	• 2	•1	•1						1.2	7.3
	WSW	.4	• 3	• 2	• 2								1.2	6.9
	w	.4	.9	•5	• 3	•1							2.1	6.7
	WNW	.7	1.9	2.4	•6				i				5.6	7.1
	NW	1.1	5.9	7.4	1.1			1					15.5	6.9
	NNW	.8	4.1	6.9	2.2	.1	.1	Γ					14.1	8.0
	VARBL	<u> </u>	 		 -	* -		<u> </u>						
			ヤ ▽										7.9	

TOTAL NUMBER OF OBSERVATIONS

1692

7.1

100.C

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	46-64	SEP
STATION	STATION NAME	YEARS	HTHOM
	ALL	WEATHER	1500-1700
		CLASS	HOURS (L S.T.)
		CONDITION	

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.0	6.3	8.6	4.2	• 2	.1						20.4	8.2
NNE	.8	1.9	3.3	• 9	• 1	•1						7.C	7.7
NE	1.2	3.5	2.7	• 5		•1						8.C	6.5
ENE	•2	•6	1.1	•2								2.1	7.2
E	•5	• 9	1.0	_•1								2.5	5.7
ESE	.3	• 5	. 3	• 1								1.1	5.3
SE	.4	1.4	1.3	4	•1							3.5	7.C
SSE	•2	1.1	1.4	1.0	• 1	• 2						4 • C	9.1
S	-3	•9	1.1	. 9	•1							3.3	8.8
SSW	•2	2	.7	• 2	•1		.1					1.4	10.3
SW	.3	• 5	.4	1					<u> </u>			1.3	6.0
WSW	•2	.3	• 5	• 1								1.1	6.6
W	•2	1.0	1.4	2								2.8	7.1
WNW	• 2	1.4	1.8	• 5								3.9	7.8
NW	1.6	6.0	6.2	1.2								15.0	6.7
WNN	•9	5.5	8.9	1.2					ĺ			16.5	7.4
VARBL													
CALM	\times	$\geq \leq$	$\geq <$	$\geq \leq$	$\geq <$	\geq	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		6.1	
	8.6	31.9	40.6	11.6	.7	.4	.1					100.0	7.0

TOTAL NUMBER OF OBSERVATIONS 1691

EATA PRUCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

EUKU C	UCKA KYUSHU JAPAN/1 TAZUKE AB 46-64 STATION HAME YEARS												
		STATION	HAME			_			YEARS				HTHO
					ALL WE	ATHER							-200 <u>C</u>
					CI	ASS						HOURS	(LST)
	_				CON	DITION							
SPEED				_									MEAN
(KNTS) DIR.	1 · 3	4-6	7 - 10	11 - 16	17 · 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
N	2.9	5.6	2.7	.7	. 3	•1	 		 	 		12.1	6.0
NNE	3.0	3.5	2.0	.4		•1						8.9	5.3
NE	3.8	3.3	1.2	• 3	.1							8.6	4.5
ENE	•9	1.1	.3		•1		.1		1			2.4	5.3
E	1.3	.9	.4	• 1								2.8	4.7
ESE	.7	. 8	.2	•1	.1		i			<u> </u>		1.8	5.C
SE	1.8	2.2	1.1	.4	.1		i		1	T		5.6	5.4
SSE	1.8	2.3	1.5	• 8	•2	-4						6.9	7.4
5	1.5	2.1	.7	•2						!		4.5	5.0
ssw	.7	. 9	•2	.2			 					2.1	5.5
SW	.6	-6	.2	•1				1				1.4	4.9
wsw	6	-4	• 3	1								1.4	4.8
w	- 8	1.0	•7	.1								2.5	5.3
WNW	.4	.8	•2	.2								1.7	5.4
NW	2.4	2.6	.8									5.8	4.3
NNW	1.6	2.7	. 9	•2	.1				1			5.6	5.3
VARBL						1							
CALM	><	> <	> <	> <	> <	>>			\geq			26.0	
	24.7	31.0	13.2	3.7	.8	•5	-1					100.0	4.0

TOTAL NUMBER OF OBSERVATIONS

1691

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

A STATE OF THE STA

1

SURFACE WINDS

E.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	EUKUI	CKA KYU	KYUSHU JAPAN/ITAZUKE AB 46-64 STATION NAME YEARS													
						ALL WE	ATHER						<u>21 CO</u>	-2300		
						C	LASS						HOURS	((21)		
						CON	DITION	··								
						•••										
		_														
j	SPEED								<u> </u>					MEAN		
- [(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 . 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND		
į	DIR.	ļ											5.C	SPEED 7.2		
	N		1.7													
	NNE	1.0	.9	.9 .5 .3 .1												
	NE	1.3	1.3	1.3 .5 .1												
	ENE		.3			<u> </u>			ļ	ļ	<u> </u>		. 9	3.3		
	E	2.4	.7	1					 	ļ	[i		3.3	3.3		
	ESE	1.5	.7	.4		-1	<u> </u>		ļ <u>-</u>	 	<u> </u>		2.7	5.C		
	SE	6.0	8	1.7	- 6	<u> </u>	<u></u>	<u> </u>	<u> </u>	<u> </u>	[i		13.1	4.5		
	SSE	4.8	3.5	2.3			<u> </u>	ļ	ļ	ļ	ļ		11.8	5.5		
	S	3.9	2.6	.8			<u> </u>	 	ļ	 	ļ		7.4	4.1		
	ssw	1.2		1_		 	ļ	ļ	 	<u> </u>			2.0	3.6		
	SW	6	5_		ļ	<u> </u>	ļ		ļ	 -	<u> </u>		1.2	4.C		
	wsw		.2		<u> </u>			 	 				- 5	4.8		
	w	4_	4_		<u> </u>		 	 -	ļ	ļ	ļ		- 9	4.4		
	WNW		.2	1_	<u> </u>	 		ļ	 	<u> </u>	 		- 4	4.6		
	NW					<u> </u>	ļ		 	 			1.1	4.2		
	NNW	5	6_	6	2_		ļ		 	 			2.0	7.C		
1	VARBL	<u> </u>		 		 										
	CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	<u> </u>	<u> > </u>	$\geq \leq$		<u> ><</u>	<u> ><</u>		$\geq \leq$	41.9			
		26.1	19.6	8.6	3.1	.7	.1						100.0	2.9		
										TOTAL NUM	BER OF OBSI	RVATIONS		1692		

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUC	CKA KYU			AZUKE	AB	46-6	4						CT
STATION			STATION	NAME		-				YEARS			4	ONTH
						ALL WE	ATHER							-620C
							ASS						HOURS	(LST)
		_				CON	DITION							
		_												
	SPEED													MEAN
	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR.							}	ļ		Í l			SPEED
	N	•9	•5	.9	• 5	• 2		•1					3.C	7.7
	NNE	1.0	.9	_ • 5	•2								2.5	5.5
:	NE	1.0	1.3	•2	.1								2.6	4.2
	ENE	•6	• 3	_ •2					i ———				1.1	4.1
	E	1.8	.5	.1	.1			i — —	i ———				2.4	3.4
	ESE	1.5	.6	•1	• 2								2.3	4.C
	SE	5.7	4.5	.8	• 3								11.2	4.C
	SSE	6.5	3.9	1.2	• 3	.1		ì		\vdash			11.9	4.1
	\$	4.8	2.8	•5	•1	i — —							8.2	3.9
	SSW	.7	• 3	•1						i			1.1	3.6
	sw	• 5	.2	1				T	Γ –				• 8	4.4
	WSW	•1				Γ							.1	2.5
	w	• 3	.4	_•2_	• 2								1.1	6.5
	WNW	•1		.1	•1	.2							5	10.8
	NW	.3	• 5	.4	•1	. 2							1.5	7.8
	NNW	.3	.4	.5		.1		•1	.1				1.3	8.6
	VARBL													
	CALM												48.4	
						$\vdash \longrightarrow$	\leq	 	\vdash	\vdash	\vdash			
		26.0	17.1	5.7	2.0	.6	L	1	.1		L		100.0	2.4

TOTAL NUMBER OF OBSERVATIONS

1706

DATA PROCESSING CIVISION ETAC, USAF ASPEVILLE, N. C. 288C1

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	<u>FUKUCK</u>	A KYUSH	JAPAN	/I TAZUKE	AB	46-6	54		YEARS				OC T
						CLASS	<u>-</u>	-				0300)-(50C
					co	NOITION							
	SPEED (KNTS) DIR.	1 - 3	-6 7-	10 11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	•6	1.1	1.1	• 3	•2	.1						3.5	1.6
NNF	.4	•6	•6	• 3	.1							1.9	7.C
NE	1.0	•5	.3									1.8	4.1
ENE	•2	•2										.4	3.4
E	1.4	•5	1									1.9	3.2
ESE	1.9	.5	.1		.1		L	ļ . <u></u>				2.5	3.4
S.E	5.0	3.5	•6	.3	.1							9.5	4.1
SSE	5.7	4.2	1.2	.4			<u> </u>					11.5	4.3
S	4.2	4.4	•6					;				9.2	4.C
SSW	.7	1.0										1.7	3.7
sw	•5	• 2	.1									- 8	3.4
wsw	• 3	•2	.1				L				<u> </u>	.6	4.5
w	.2	•2	• 2	.2			<u> </u>					. 8	6.3
WNW	•2	• 2	.1	• 2	.1							. 7	8.7
NW	•1	.3	.5	. 8					<u> </u>			1.7	9.8
NNW	• 3	5	. 7	.2	.1		L	•2	<u> </u>			1.8	9.9
VARBL				<u></u>		ļ,	Ļ,		<u> </u>				
CALM		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		49.9	
	22.6	18.0	6.1	2.6	• 5	.1	<u> </u>	.2				100.0	2.4

TOTAL NUMBER OF OBSERVATIONS 1767

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

100

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUC	UCKA KYUSHU JAPAN/ITA/UKE AB 46-64												<u>C 1 </u>
STATION			STATION	MAME					'	rears				HTH
						ALL WE	ATHER							-08CC
		_				Ct	ASS						HOURS	(L \$.T.)
		_				CON	MOLTIO							
												·		
	SPELD										1 [Į		MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND Str. D
	DIR.	l												
	N	•5	1.0	1.0	• 3	. 2	.1	l	L	L			3.1	1.4
	NNE	•6	1.1	•6	• 2	•1	l						2.5	6.2
	NE	1.0	1.4	•2					<u> </u>				2.5	4.2
	ENE	•5	•2	•2					<u> </u>	<u></u>			.9	4.3
	£	•8	•5		• 1								1.3	3.5
	ESE	1.3	.6	•1	•1								2.0	3.6
	SE	5.0	3.6	1.3	• 5								10.3	4.4
	SSE	6.2	4.2	1.3	•1	.1							11.9	4.1
	S	4.1	3.9	1.1	.3								9.5	4.5
	SSW	1.4	•5	-1	.1								2.0	3.5
	SW	• 5	.3	1.1									. 9	3.8
	wsw	• 3	•2	.1	1								.6	4.1
	W	•2	.4	.3	• 2						<u> </u>	<u></u>	1.1	7.6
	WNW	.1	•2	.2	. 3	.1							- 9	9.C
	NW	•1	.6	.8	• 3								1.8	8.1
	NNW	• 3	.3	.8	.3	.1	.1		.1				2.0	10.1
	VARBL	1	1	1									!	
	CALM		1						$1 \leq 2$	152	152		46.5	
	CVDA			*	$\leq \geq$	\vdash	⊭≟	$ \leftarrow $	*	*===	*	\vdash		
]	22.9	18.9	8.3	2.8	.5	1.1	L	.1	<u> </u>		<u> </u>	100.C	2.7
	L	<u> </u>												

1767

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING DIVISION ETAC, USAH ASHEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

<u>43310</u>	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	46-64		OC 1
STATION	STATION NAME		YEARS	MONTH
	AL	L WEATHER		0900-1160
		CLASS		HOURS (L S T.)
		CONDITION		

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.2	2.7	2.8	1.3	•2		•1					8.9	7.2
NNE	1.1	1.2	3.3	1.0	• 1							6.6	7.5
NE	1.1	3.1	4.4	•5								9.1	€.7
ENE	•2	.7	1.8	•3	•1				; ———			3.1	7.6
E	• 5	•8	.7						T			2.C	5 . d
ESE	• 5	•9	.3	• 2				1				1.9	5.5
SE	1.1	1.6	2.5	•5					1			5.7	6.6
SSE	2.1	2.9	3.1	.4						T		8.4	5.9
S	2.8	2.7	2.0	•7								8.2	5.6
SSW	1.0	.4	.3	• 1								1.7	4.5
SW	•8	• 3	.1									1.2	3.9
WSW	•5	• 3	.2	.1								1.0	4.9
w	• 8	.6	.7	• 3								2.5	6.5
WNW	•8	1.0	1.1	. 8					T			3.8	7.3
NW	1.1	1.8	1.5	1.2	•1							5.7	7.4
NNW	1.1	. 8	1.7	1.4	•1							5.0	8.2
VARBL													
CALM	> <			><	><			$\geq <$	><	$\geq <$		25.1	
	17.3	22.0	26.4	8.7	.5		.1					100.0	5.0

TOTAL NUMBER OF OASERVATIONS

1767

1210 WS FORM 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

and the same the same of the

rosida D

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

SURFACE WINDS

<u>.</u>

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

+3310	FUKUI	<u>.KA KYU</u>	SHU JAI	PAN/II	ALUKE	AB	46-6	4						IC I
STATION			STATION	MAME						YEARS			- - 	нтко
						ALL WE	ATHER						1200	-1400
						Ç	ASS						HOURS	(L.S.T.)
						CON	NOITION							
													 -	
{	SPEED (KNTS)	1-3	4.6										۸,	MEAN
1	DIR.	1-3	4.0	7 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
+	N N	ļ			·			 -		 	 		17.0	9.C
ŀ	INNE	.7	4.1 2.0	4.1	2.6	•2		 -	 		 		9.6	8.9
}	NE	1.4	3.6	5.3	1.1	• 2		 		 -	 		11.4	7.1
ŀ	ENE	.3	1.1	2.0	• 2	• •					 		3.6	7.1
	E	•6	1.3	1.0				 			 		2.8	5.7
ł	ESE	•5	. 3	• 3	.1	i		 	 	 	 		1.1	5.3
1	SE	.7	1.5	1.4	• 5						 		4.1	6.7
Ì	SSE	•3	1.0	1.2	• 3		·				1		2.8	7.1
	5	.7	1.1	1.4	• 2				·		l		3.3	6.5
j	SSW	•2	•5	•2	• 1	•1		1			1		1.0	7.4
l	sw	• 3	.3	• 5						1			1.0	5.6
İ	wsw	• 3	•.5	. 3	• 1								1.1	5.5
	w	• 3	•6	. 8	.6	-1							2.4	8.3
	WNW	• 3	1.4	2.3	1.1	•2							5.3	8.5
	NW	.7	4.0	6.7	2.7	.1							14.2	8.1
	NNW	•6	3.3	6.0	2.9								12.8	8.4
	VARBL	ļ				<u></u>	<u> </u>	<u></u>	<u></u>	<u></u>				
		· _	· -		·	\sim	<u>`</u>	\sim	\sim	·		\sim	(3	1

TOTAL NUMBER OF OBSERVATIONS

1767

7.4

100.C

CATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 288C1

WNW

NW

NNW

£.

SURFACE WINDS

÷ . *

¥.,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	EUKUL	JKA KYU	SHU JA	PAN/II	AZUKE	<u> </u>	46-6	.4		YEARS				C I
			•••••			ALL WE	ATHER			· can				-1700
							LASS						HOURS	(LST)
							DITION							
						COR	DITION							
		_												
i														
	SPEED							l					۰,	MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	'28 - 33 	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
		1.4	5.5	12.1	4.8		 -		 	 	 		23.8	8.2
	NNE	1.0	3.5	5.2	2.4	•1	 	!			·		12.2	8.1
	NE	1.1	3.7	4.5	.8			 					10.1	6.9
	ENE	.4	1.6	1.4									3.4	6.C
	E	.6	1.1	.4	• 1		1		 				2.2	5.2
	ESE	•2	• 5	•1									.7	4.5
	SE	.3	.6	•8	• 2								1.9	6.6
	SSE	. 3	.6	.6		<u></u>	L						1.5	6•℃
	\$.3	.9	.7	.1								2.C	6.0
	SSW	• 2	• 3		•1	ļ <u>.</u>	Į						6	5.4
	SW	.2	.3	.2	-1	ļ			<u> </u>	<u> </u>	<u> </u>		3.	6.1
	wsw		.2	.3	.2	<u> </u>		ļ		<u> </u>	<u> </u>		- 8	7.9
	1 w	11 3		1 1 2		I	1	1	1	1		1	2 8	8 3

TOTAL NUMBER OF OBSERVATIONS 1766

5.1 12.2 13.3

6.6 100.0 9.0 7.2 7.6

7.0

1210 WS FORM G-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

1.5

1.4

DATA PROCESSING CIVISION . ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

BIATION		STATIO	T RAME						TEARS			-	ORIH
					ALL WE	ATHER							-2G0C
	_					LASS						HOURS	(L S.T)
	_												
					CON	DITION							
	-												
SPEED		1				1					 -		/AEAN
(KNTS		4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
DIR.			,]]							SPEED
N	2.7	5.8	2.2	. 7	.2							11.5	5.6
NNE	3.8	4.8	1.6	• 2								10.5	4.7
NE	4.1	3.0	1.4									8.6	4.3
ENE	1.9	1.4	• 3	.1								3.6	3.7
E	1.4	.8	.1	. 1								2.4	3.8
ESE	1.2	.5	• l						l			1.7	3.3
SE	1.9	1.7	. 3									3.9	3.9
SSE	2.3	3.3	.6	.1	L]						6.2	4.3
S	2.7	2.0	.6]								5.3	4.0
SSW	8_	.7	.1	<u> </u>	<u></u>	<u> </u>			<u> </u>			1.5	3.9
sw	.2	.5	.2		<u> </u>	<u> </u>	<u> </u>	<u> </u>		<u> </u>		1.0	5.1
wsw		.2	.2	<u> </u>		<u> </u>	<u> </u>	<u> </u>				- 8	4.8
W	.6	.3	.5	.4	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>		1.8	6.8
WNW		.7	.6					<u> </u>	ļ	Į		1.8	6.1
NW	1.0	2.0	.6	.2	-1		<u> </u>	<u> </u>	<u> </u>	<u> </u>		3.9	5.6
NNW		1.8	.5	<u> </u>	<u> </u>	ļ	<u> </u>	<u> </u>	<u> </u>			3.5	4.5
VARB	L	<u> </u>	<u></u>		<u></u>	<u> </u>	ļ	<u></u>		Ļ _	L	 	
CALN			$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	32.0	
	26.6	20 5	9.0	1.8	3							100.C	3.2

TOTAL NUMBER OF OBSERVATIONS

1765

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

, CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

action the second section with the second section of the section of the secti

OK

ALLIED/EGNY BUTINESS

(1

()

0

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUCKA KYUSHU JAPAN/ITALUKE AB 46-64 STATION NAME YEARS	OC I MONTH
	ALL WEATHER CLASS	21CO-23CO
	CONDITION	

SPEED (KNTS) DIR,	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.2	1.1	• 7	• 5	• 2			•1				3.7	6.8
NNE	1.0	1.2	• 5	•1			1		•1			2.9	5.6
NE NE	1.8	1.4	• 3				1					3.5	3.9
ENE	•8	• 2	.1									1.1	3.4
E	1.2	• 5	.1								<u> </u>	1.7	2.9
ESE	2.C	.8									<u> </u>	2.8	2.9
SE	4.6	3.3	.9	•2						<u></u>		9.1	4.1
SSE	5.7	4.3	.6	-1								10.7	3.8
S	4.0	4.0	.5		1		<u> </u>			<u> </u>		8.4	3.9
SSW	1.0	.3	.1_						<u></u>			1.4	3.5
SW	.6	.5		T					<u> </u>			1.C	3.6
WSW	• 3	•2						<u> </u>	<u> </u>			• 5	3.6
W	.2	.1	.1	•2				<u> </u>			<u>i</u>	. 5	7.1
WNW	•2	•3_	• 2	. 3	. 2		<u> </u>		L			1.1	10.6
NW	1.0	•5_	.2	-1_	• 2			<u> </u>	ļ	<u> </u>		1.9	5.5
NNW	• 3	1.1	.2		.1		<u> </u>	<u> </u>	ļ			1.7	5.8
VARBL									<u></u>	ļ	<u></u>		
CALM					><			$\triangleright <$	$\supset <$	$\geq \leq$	$\geq \leq$	48.0	
	25.7	19.6	4.4	1.5	.7	-		•1	.1			100.C	2.3

TOTAL NUMBER OF OBSERVATIONS 1764

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

in it

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUC	KA KYU	SHU JA	T I \ NA 9	AZUKE	AB	46-6	4					N	CV
STATIC 4			STATIO	N NAME						YEARS				NTH
		_				ALL WE	ATHER						0000	-C20C
						c	LASS						HOUR	\$ (L S T.)
			·											
						CON	DITION							
	SPEED	1			I	_ -	Γ	T			т т			MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 . 2	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR	[(1					· · · · · · · · · · · · · · · · · · ·	' '	SPEED
	N	.7	1.2	1.1	.6	.1		1		†			3.7	7.C
	NNE	6	1.0	.4	.1								2.2	5.2
	NF	1 2	- 4	4	1					1			2.2	4.4

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 2	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	.7	1.2	1.1	•6	• 1							3.7	7.0
NNE	6	1.0	. 4	. 1								2.2	5.2
NE	1.2	•6	•4	. 1								2 • 2	4.4
ENE	.4	• 2	.1									.6	3.5
E	1.2	.4	.2	.1						<u> </u>		1.9	3.9
ESE	1.6	• 9	• 2	• 1							<u> </u>	2.9	3.9
SE	7.3	4.7	1.9	. 3								14.2	4.2
SSE	6.2	5.8	1.9	.4	.1						<u> </u>	14.4	4.5
S	3.7	5.0	. 8	.1								9.6	4.2
ssw	- 8	.4	.1]	1.3	3.7
SW	.5	• 2	. 3					<u> </u>		<u> </u>	<u> </u>	1.0	5.1
WSW	• 2	•2	. 5	.1			<u> </u>		<u> </u>			. 9	7.1
W	.4	• 5	. 9	- 3	-1	<u> </u>				<u> </u>		2.1	7.6
WNW	• 2	•2	.6	-6	.1	•1			L	<u> </u>	<u> </u>	1.8	10.3
NW	3	• 2	. 8	. 9				L		<u> </u>		2.2	9.7
NNW	.2	.4	. 5	.8	.1			<u> </u>			1	1.8	9.6
VARBL	<u></u>								<u> </u>				
CALM	$\geq \leq$	\times	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$		37.1	
	25.5	21.8	10.6	4.6	. 4	.1						100.0	3.2

TOTAL NUMBER OF OBSERVATIONS 1710

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB

ķ.

SURFACE WINDS

NOV

10 m

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

46-64

- INTIVE			BIATIO	N NAME						YEARS			¥	HTHO
						ALL WE	ATHER						0300	0-050C
		_				c	LASS						HOUR	5 (L S.T.)
		_												
						CON	DITION				_			
		_												
										· -	<u></u>			
			,							· · · · · · · · · · · · · · · · · · ·				
	SPEED (KNTS)	1 - 3		١	l							_		MEAN
	DIR.	1.3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
	N N				 			<u> </u>	ļ	ļ	<u> </u>			
	NNE	• 7	1.4	-8	•6	•2	<u> </u>			<u> </u>	<u> </u>		3.7	7.2
	NE NE	.7	.8	•5	•2	<u> </u>			ļ				2.2	5.7
	ENE	9-	1.1	.3	ļ —	 			<u> </u>	<u> </u>			2.2	4.2
	E	.8	•5	•2	ļ	 	ļ		<u> </u>	<u> </u>			1.5	4.3
	ESE	1.3	•7	•2	• 1	<u> </u>				 			2.3	3.6
	SE	1.5	6.5	.3	• 2	 				 			2.5	4.4
	SSE	6.3	5.8	1.4	• 2	<u> </u>				ļ			13.8	4.2
	S S	6.0	6.5	1.8	• 3	<u> </u>	ļ	ļ					14.6	4.4
	SSW	4.2	3.7	.7	-4	ļ	<u> </u>						9.0	4.4
	SW	.6	.9	.2	 	 -		!	 -			ļ	1.7	4.3
	WSW	- • 4	.5	-1		 	<u> </u>			———			.9	4.2
	W W	-4	2	-4					 		_	ļ.—	1.1	5.8
	WNW	•7	-3	-6	•2	.1	 -	 		{ -			2.0	7.2
	NW	.2	•2	.8	.9	-2	-1						2.3	10.9
	NNW	2	-6	1.6	1.3	•1	 -		 	 	 		3.9	9.2
	VARBL	•2	-2	.8	•6	 	 -	 	——	 	<u> </u>		1.9	9.2
		·		 _		\vdash		<u></u>		\vdash				
	CALM		$\geq \leq$	<u> ><</u>		<u> </u>	ackslash		<u> </u>	!><	><	$\triangleright\!\!<$	34.5	
		25.2	23.9	10.8	5.0	- 6	1			i ——			100 0	3 5

TOTAL NUMBER OF OBSERVATIONS

1709

CATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

j.

日本の一般の一個の一人

C

SURFACE WINDS

.. T.

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHL JAPAN/ITAZUKE	AB	46-64		NOV
STATION	STATION NAME			YEARS	MONTH
		ALL	WEATHER		0600-0800
			CLASS		HOURS (LST)
			CONDITION		

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	• 5	•9	.7	• 8	•1							3.0	7.6
NNE	•5	.8	•6	• 5								2.4	6.9
NE	1.0	.9	• 3									2.2	4.1
ENE	•8	•3	•1									1.2	3.8
E	•8	.3	•2	•1								1.3	4.1
ESE	1.1	.4	• 3	•1								1.8	4.2
SE	6.5	5.9	1.3	.7								14.4	4.4
SSE	5.6	6.3	2.8	•5	.1							15.2	4.8
S	4.8	5.3	1.5	• 2				1				11.7	4.4
ssw	1.2	1.0	.1_									2.2	3.6
sw	• 5	.4	•2	• 1								1.1	5.1
wsw	2	•6	.4		.1							1.3	5.9
w	•3	.7	.4	• 4	.1	• 1						1.9	8.3
WNW	•2	•2	.8	.4	• 2_	1						1.9	9.9
NW	• 5	• 8	1.3	1.4	• 1							4.1	8.9
WNN	•2	.4	.9	_8_	• 2							2.5	9.6
VARBL											<u> </u>		
CALM	> <	> <		><	$\geq \leq$	\geq	><	$\geq \leq$	$\geq \leq$	$\geq \leq$		31.7	
	24.7	25.1	11.9	5.8	.7	.1						100.C	3.7

TOTAL NUMBER OF OBSERVATIONS

1710

CATA PROCESSING DIVISION ETAC, USAH ASHEVILLE, N. C. 288C1

SURFACE WINDS

6. 44

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	EUKUC	KA KYU			UV									
MOLTATE			STATION	NAME		ALL WE	ATLICD		,	rEARS				-110C_
		_					ATTIEN ASS						HOURS	(L.S T.)
		_												
						CONI	DITION							
		_			 									
	SPEED	<u> </u>												MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
<u> </u>	DIR.										 			
<u> </u>	_ N	1.3	1.7	2.0	1.6	1							6.7	7.6
	NNE	6	1.0	2.2	.7				<u> </u>				4.4	7.8
<u> </u>	NE	. 9	1.7	1.9	. 3								4.9	6.2
	ENE	5	. 8	.7	2_								2.2	6.3
	E	8	.7	8	1				<u> </u>		ļ		2.3	5.6
L	ESE	.6	.6	3	. 3					ļ	<u> </u>		1.8	5.7
L	SE	2.6	3.9	3.4	1.1					<u> </u>		L	11.0	6.3
Ĺ	SSE	4.0	5.6	4.8	1.2	.1				<u> </u>	<u> </u>		15.6	6.1
[S	2.9	4.0	1.8	.5								9.2	5.2
	SSW	1.2	.5	1					<u> </u>		<u> </u>		1.8	3.2
	sw	1.3	.9	_4					<u> </u>				2.6	4.0
	wsw	.5	.4	.4					<u> </u>				1.3	4.7
	w	.7	.6	1.4	. 8	1	<u> </u>						3.6	8.C
	WNW	. 3	.5	. 9	.9	. 4					<u> </u>		3.1	10.2
Ī	NW	•6	1.2	2.1	1.8	.1	.1						5.7	8.7
	NNW		.9	1.5	1.5								4.4	8.6
T	VARBL		1				1							
	CALM	> <		><	><	><	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	19.3	
-		19.4	25.0	24.8	10.8	.7							100.0	5.4

TOTAL NUMBER OF OBSERVATIONS

17C9

1210 WS FORM 0-8-5 (Det 50) PREVIOUS KOITIONS OF THIS FORM ARE OBSOLET

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	EUKUC	KA KYU	SHU JAI		AZUKE_	AB	<u>46-6</u>	4	 ,	rears .				UV
		_			 	ALL WE	ATHER						12C0	-14CC
		-				CON	NOTION							
	SPEED (KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND
ļ	DIR N NNE	1.2	3.4 1.9	4.9	3.6	.3							13.3	8 • 6 1 • 8
	NE ENE	1.2	3.5	3.1		.1							8.9	6.9
	ESE	.5	.6 .4	6_	.2								1.9	6.8
	SE SSE S	8 9	1.6 1.2	2.3 1.6 .8	6 8	-1	1						5.2 4.7 3.5	7.2 7.5 7.0
	SSW SW	2	.8	5	1	î							1.7	6.8 4.9
	WSW W	.4 .5	1.2	2.0	1.2	2							5.0 8.0	8.8 9.1
	NW		1.4 4.2 3.0	3.6 6.2 5.6		.2	2						15.0 12.9	8.6
	VARBL CALM	>	\times	\times	>	><	>		>		>		7.4	
ļ			24.	2, 2	10.2	, ,		,			—		100 0	7 4

TOTAL NUMBER OF OBSERVATIONS 1710

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKU	CKA KYU	SHU JA	PAN/IT	AZUKE	AB	46-6	4		YEARS				ICV
•						ALL WE	ATHER			TEARS	_		1500	1-1700 (L.\$ T.)
		-				CON	MOITION				_			
{	SPEED (KNTS) DIR.	1 - 3	4 · 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
[N	2.3	6.0	6.3	2.3	• 2			<u> </u>				17.0	7.2
	NNE	. 9	2.3	4.0	1.2								8.4	7.7
j	NE	1.0	3.1	2.8	1.2								8.2	7.2
	ENE	<u></u>	1.8	1.3	-1					i			3.6	5.8
Į	E	•5	1.1	.5	-1			[2.2	5.4
Į	ESE	3	5	2_					<u> </u>	L	II		1.0	5.4
[SE		2.0_	1.2	3_			ļ	<u> </u>				4.0	6.4
Į	SSE	2_	_1.5	1.3	2_	.1		ļ <u>.</u>	ļ	ļ			3.3	7 • C
	5	2_	5_	6_	1				 	<u> </u>			1.5	6.7
ļ	SSW			5			ļ		 -				1.1	7.2
	SW WSW	4_	64_	2_		 -	 -	<u> </u>	 -	 	 -		- 9	5.3
	W	2	2_	5_		<u> </u>	 	ł	 	 	 -		1.1	6.6
į	WNW	8	1.0	2.3	1.5	3_	 	 	 	 	 		5.9	8.5
	NW	1.7	. 9	3.2	1.7	 -		 	├	 	 i		5.7	8.6
	NNW	1.1	4.3	8.2					 -	 	 		14.6 15.4	7.2
	VARBL			-0.2	1.6.		 	 	 	 	 		1204	7.6
	CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	\geq	$\geq \leq$	$\geq \leq$	$\geq \leq$	\geq		6.2	
		11.0	30.7	39.5	11.6	و	1	1					100 · C	6.8

TOTAL NUMBER OF OBSERVATIONS 1710

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

NOV

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

3310	FUKU	KA KYU			AZUKE	AB	46-6	4						CV
STATION			STATION	NAME						TEARS				ONTH
		_				ALL WE	ATHER							-200C
						CI	A55						HOURS	(LST)
		_												
						CON	DITION							
		_												
	SPEED	1										1		MEAN
	(KNTS)	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
	DIR								i '		1	1		SPEED
	N	2.2	2.4	1.1	• 7	• 2							6.5	6.1
	NNE	2.0	2.5	1.1	• 3							22.2	5.9	4.9
	NE	4.5	4.0	1.1	• 1								9.7	4.4
	ENÉ	1.9	1.4	•2	•1								3.6	4.0
	E	2.0	•8	• 2									3.1	3.5
	ESE	1.8	•9	• 3									3.0	3.6
	SE	3.9	3.1	• 5	• 2								7.7	4.0
	SSE	3.9	3.4	•6	• 2	• 1						22.7	8 • 2	4.3
	S	3.0	3.6	. 3				<u> </u>		<u> </u>			6.8	3.8
	SSW	- 8	.5	.1						<u> </u>			1.5	_3. გ
	SW	.6	• 5		.1	-1		l					1.2	4.3
	WSW	• 2	.7	•2	• 1				<u> </u>	···		ļ	1.3	5.6
	W	.4	1.0	1.0	• 2	.1			<u> </u>		<u> </u>	ļ	2.6	6.7
	WNW	.4	5	• 9	• 5	•2		<u></u>	<u> </u>				2.5	8.8
	NW	1.1	1.2	. 8	.5	-1		ļ				!	3.7	6.3
	NNW	1.1	1.1	.6	-1	-1	!	ļ	<u> </u>			 	2.9	1•دَ
	VARBL	ļ				Ļ—		<u> </u>	<u> </u>	L	<u> </u>			
	CALM		><	$\geq \leq$	><	><	$\geq \leq$,><	$\geq \leq$	><		$\geq \leq$	29.8	
		29.8	27.6	9.1	3.0	.8							100.0	3.3

TOTAL NUMBER OF OBSERVATIONS

1710

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

C

SURFACE WINDS

£.,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	46-64		NOV
STATION	STATION NAME	YEARS		MONTH
	ALL W	EATHER	2	1 CG-230 C
		CLASS		HOURS (LST)
	Co	MOITION		

SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.4	.5	• 5	• 5								3.C	6.C
NNE	• 3	1.2	• 8	.4				i				2.6	7.0
NE	1.4	1.6	-4	•1								3.5	4.5
ENE	1.1	.4	-1									1.6	3.2
E	1.6	• 9	• 2					l	[2.8	3.8
ESE	1.9	.4	.2	• 1								2.6	3.5
SE	6.7	4.7	•8	.4				i				12.5	3.9
SSE	6.3	6.7	1.3	. 3	• 1					·		14.6	4.2
S	4.0	4.0	• 6	1	• 1							8.7	4.1
SSW	•8	•8	ءَ ۔									1.7	4.1
SW	.4	• 5	.1									1.0	4.3
WSW	•2	. 3	.1	.1								.7	6.2
w	3	. 5	•6	• 2	.1							1.8	7.4
WNW	•1	.4	•6	.5	• 1							1.8	9.1
NW	. 4	• 6	1.1	. 8	.1							2.9	8.3
NNW	•2	.4	. 3	5								1.5	8.6
VARBL													
CAIM		\geq	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	36.8	
	27.0	24.0	8.0	4.0	.4							100.C	3.0

TOTAL NUMBER OF OBSERVATIONS

171C

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE. N. C. 26801

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUL	KA KYU			AZUKE	AB	46-6	4						EC
BOITATE			STATION		·	ALL WE	ATHER			rears			0000	-620C
						CONI	DITION				_			
	SPEED (KNTS) DIR.	1 - 3	4-6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
	N	.4	.7	.6	.5	•1	• 1						2.3	8.C
i	NNE	•2	• 5	.1	•1								. 8	5.C
	NE	•5	• 5	.1	• 1								1.2	4.0
Į	ENE	.6	• 2								1	7	.7	2.8
	E	.7	• 3										1.0	3.2
[ESE	1.2	•6	•1	• 1								2.0	3.5
	SE	5.5	6.6	2.3	• 3								14.6	4.7
ľ	SSE	5.6	9.1	4.7	.7	•1	.1						20.2	5.4
	S	3.1	5.4	1.8	- 3								10.6	4.9
[SSW	-8	•6	.1				l					1.5	3.7
	SW	.6	•6	• 2	• 2								1.6	5.8
	wsw	.1	. 3	.7	• 2	•1							1.4	7.9
	W	.3	.7	. 8	1.0	.2	•1		<u> </u>				3.1	9.6
	WNW	.2	.2	1.2	3.2	.9	.3	<u> </u>					6.1	12.9
	NW	.2	1.0	1.5	3.0	• 3	.1			<u> </u>	<u> </u>		5.9	11.2
	MnM	.3	<u> </u>	.7	1.1	.1	.1		<u> </u>	<u> </u>		<u> </u>	2.5	16.7
	VARBL					<u> </u>	ļ	ļ	<u></u>	<u> </u>	<u> </u>			
	CALM	$\geq \leq$	$\geq \leq$		$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	24.6	
		20.2	27.4	14.8	10.7	1.8	.6						100.0	4.9

TOTAL NUMBER OF OBSERVATIONS

1765

CATA PROCESSING DIVISION ETAC. US'F ... ASHTVILLE, N. C. 288C1

43310 FUKUCKA KYUSHU JAPAN/ITALUKE AB

SURFACE WINDS

DEC

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

46-64

					ALL WE	ATHER						0300	-05CC
	_				ci	ASS						HOURS	(LST)
					CONT	NOTTON							
	_												
SPEET,	<u> </u>			 1						· · · · · · · · · · · · · · · · · · ·			MEAN
(KNTS)	1.3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
21P.	11 1		/ 10	'''	,,	/	20 00	04 1 40	11.54	10 55		"	SPEED
- N	.2	1.1	.9	•6	•1							2.9	7.9
NNE	• 3	.6	• 2	• 1								1.2	5.2
NE	.8	4.3	•1	•1							i	1.3	3.9
ENE	.3	• 2										. 5	3.7
Ε	.7	.4	•1									1.2	3.3
ESÉ	. 3	.7	• 1	• 1								1.2	5.1
SE	5.1	7.2	2.6	. 5								15.4	4.8
SSE	4.0	8.8	5.2	. 8		•1						18.8	5.7
S	3.2	5.9	1.6	.2					<u> </u>			10.9	4.8
ssw	8	- 8_	1		<u> </u>			ļ	<u> </u>	<u> </u>		1.7	4.C
sw	.5	.6	.3	-1	<u> </u>						 	1.5	5.3
wsw	.2	.5	.9	-2	 _		<u> </u>	ļ	 	ļ	 	1.7	7.3
	•3	5_	9	1.3	2	1	 	 	 	 		3.3	10.4
WNW		-4	1.4	2.6	.8	3	ļ	 	ļ	 		7.3	12.5
NW	<u>}3</u>	6	2.1	3.8	- 4	-1		 		 	 -	3.1	11.3
VARBL	-2	3	1.2	1.1	1	2	1	 	 	ļ	 	3.1	1103
<u> </u>	+-											22.3	
CALM				<u> </u>									
	17.4	28.8	17.7	11.4	1.6	•7	.1				}	100.C	5.3

TOTAL NUMBER OF OBSERVATIONS

1765

1210 WS JUL 64 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

t

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 288C1

Marie Del Della

SURFACE WINDS

TOTAL NUMBER OF OBSERVATIONS

1767

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310 STATION	FUKUC	KA KYU	SHU JA	PAN/IT	AZUKE	A4	46-6	4		'EARS				EC
		_				ALL WE	ATHER ASS	·			 -		0600	-C8C0
		_				CON	DITION							
	SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
-	N	.1	.7	.8	,9 ,1	- 1							2.5	9.3 5.2
Į	NE	.7	. 8	2	1								1.9	4.8
	ENE	.2	.2										.4	4.4
1	E	.7	.3	.1									1.1	3.5
1	ESE	1.0	• 5							<u> </u>		<u> </u>	1.8	4.1
Ļ	SE	4.2	6.5	_3.3	- 5			!	<u> </u>	ļ			14.5	5.3
Ļ	SSE	4.4	8.7	5.7	9					 	 		19.8	5.7
Ļ	s	2.7	2.1	2.0	5_			<u> </u>	L	 		<u> </u>	10.9	5.3
ļ-	ssw	1.0	6	.3			ļ			 -			1.9	4.3
+	SW	3_	9_	2				 	 	 	 	 	1.5	4.9
Į.	wsw		•7	- 3	4	 		ļ	 -	ļ			1.6	7.6
ŀ	WNW	5	2		1.7	2_	-	 	 	 	 		3.3	10.6
<u> </u>	NW			1.1	2.3	6_		 	 	 	 	 	7.6	10.9
ŀ	NNW	.3	8_	2.5	3.5	4				<u> </u>	 	 	3.6	11.7
ŀ	VARBL							-	 	 -				
	CALM	$\geq \leq$	$\geq \leq$	><	><	$\geq \leq$		><	\geq				21.3	
		17.1	28.3	18.7	12.5	1.6	5_	<u> </u>	<u> </u>	<u> </u>	<u> </u>]	100.c	5.5

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

()

()

1 ;

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

	_				ALL WE	ATHER						09C0	-110 (4 * T.)			
		CONDITION														
SPEED (KNTS) DJR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 • 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAI WINI SPEE			
N	6	1.4	1.4	1.2	• 1		<u> </u>	T				4.8	8.			
NNE	• 2	. 3	•6	.3			T					1.4	ಚ			
NE	.6	.4	.8	.3	•1		l —					2.2	6			
ENE	.1	.1	• 2									• 3				
E	3_	•2	. 3									. 7	ر.			
ESE	3	.5	.3									1.1	4			
SE	1.9	4.6	5.0	1.5								13.0	(
SSE	2.9	6.8	11.5	1.8	. 2	.1						23.4	Ĺ (
\$	2.8	5.1	2.5	• 7	• 1							11.2				
SSW	5	• 6	3_	.1								1.4	5			
SW	.6	• 9	. 3						<u> </u>	<u> </u>	<u> </u>	1.8				
WSW	2_	.6	. 8	3				<u> </u>				1.9	7			
W	ن و	.6	1.5	1.5	3_		<u> </u>	<u> </u>		<u> </u>		4.2	10			
WNW	3_	5	1.9	2.8	.5	-1			<u> </u>		<u> </u>	6.2	11			
NW	1_	1.0	2.8	4.8	.5			ļ	ļ			9.2	11			
MNM	2	l <u>6</u>	2.4	2.1	. 3			ļ	ļ			5.6	10			
VARBL	ļ	ļ	<u> </u>	ļ	<u> </u>	ļ	ļ	<u></u>	Ļ	Ļ	<u> </u>		ļ			
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$				$\geq \leq$	11.9				
	11.9	24.0	32.5	17.5	2.0	.2]				100.0	_ 1			

DATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

SURFACE WINDS

DCC

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

						ALL WE	ATHER						12CO	-1400
		_					.ASS						HOURS	(L S T.)
		_												
						CON	017101							
		_									_			
r														
i	SPEED												ا ر	MEAN
	(KNTS) DIR	1 - 3	4-6	7 - 10	11 - 16	17 - 21	:2 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
	N N		1.8	3.1	3.4	-1		 			ļ		9.1	9.1 8.2
	NNE	-3	1.0	1.2	.7	.1		<u> </u>						
	NE	.7	1.2	1.0	. 2						ļ	l	3.2	6.C
	ENE	- 5	- 2	•2	.1				ļ			ļ	1.0	5.2
į.	E		5				<u> </u>	ļ			ļ	l	1.1	5.7
!	ESE	-3	•2	•2	1				ļ				.7	6.0
	SE	8	2.0	3.2					ļ		ļ		6.5	1.2
	SSE	1.0	3.6	3.6	. 9	.1	.1					<u> </u>	9.2	7.1
i	S	.7	2.2	1.7	.6	-1			<u></u>				5.3	6.9
	SSW	- 8	.3	.3	•1		L		<u></u>	<u> </u>	<u> </u>		1.5	5.C
	SW	. 3	.8	-6	• 1								1.9	6.2
	W\$W	•2	6	. 8	• 5	.1							2.1	8.5
	W	.7	1.4	3.0	3.1	•2	.2						8.7	₹.8
	WNW	.7	1.6	3.7	4.2	1.2	•2	.1]}	11.7	10.8
	NW	1.0	4.0	6.5	5.5	. 8	•1					[}	17.8.	9.4
	NNW	• 5	2.0	4.4	2.6	.3	.1						9.7	9.2
	VARBL													
	CALM												7.2	
			\vdash	$\models \rightarrow$				⊭	 					
	1	ll 🕳							1	I	1	1 1	300 0	1 00

TOTAL NUMBER OF OBSERVATIONS 1767

1210 WS FORM 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLFTE

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 45-64

CATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

SURFACE WINDS

S

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

EUKU	CKA KYU	SHU JAI	PAN/IT	AZUKE	AB	46-6	4		YEARS			. _	EC
					ALL WE	ATHER			•			1500	-1700
						ASS							(L S.T.)
	_				CON	DITION							
SPEED (KNTS)													MEAN
DIR.	1 - 3	4 - 6	7 · 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
N	1.3	4.1	4.5	1.4								11.3	7.C
NNE	.6	1.8	1.6	• 5								4.5	6.7
NE	.9	1.8	1.0	. 2								3.9	5.6
ENE	- 3	.3	- 3	. 2						<u> </u>		1.1	5.8
E	•2	3							<u> </u>		j	.6	4.2
ESE	.3	.3	• 2					<u> </u>		<u> </u>		- 8	4.6
SE	1.0	1.9	1.4	.2				 	 			4.6	6.1
SSE	8	1.5	1.6	- 8	1_			 -				4.8	7.4
SSW	6	1.6	1.2		 -			 	 	 		3.5	6.2
SW	•3	- 3						<u> </u>	<u> </u>			1 7	4.8 6.1
wsw	•1	<u>•7</u>	1.1		•1					 		2.4	9.2
w	•6	1.8	3.8	2.9	-4	-1			 	 	 	9.6	9.3
WNW	1.1	1.9	4.3	4.0	.9		•1		 			12.3	9.8
NW	1.6	5.3	6.3	4.6	.4	•1		 		 		18.4	8.5
NNW	1.3	3.7	4.9	2.7	.1			 				12.7	8.0
VARBL													
CALM	><	\geq	\times	$\geq <$	$\geq <$	\geq	$\geq <$	$\geq \leq$	$\geq <$	\geq	><	7.1	
	11.4	27.8	33.1	18.3	2.2	•1	.1					100.0	7.3

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

. 6

ť.

()

SURFACE WINDS

DEC

<u>x</u>,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

YEARS

		_				ALL WE	ATHER							-2000
		_				CON	DITION							
1	SPEED												<u> </u>	MEAN
	(KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND SPEED
	N	1.0	2.5	1.4	•1	•1							5.C	5.6
	NNE	1.0	1.6	• 5	•1								3.1	4.8
	NE	2.3	2.3	•1									4.7	3.8
	ENE	- 5	• 5	. 1									1.1	4.4
	E	1.6	.7	. 1						•			2.4	3.4
	ESE	1.1	.7										1.8	3.2
i	SE	4.3	4.2	.8	• 2	.1							9.6	4.4
	SSE	3.8	4.8	1.4	• 2	.1							10.2	4.6
	S	2.4	3.6	.8	.1		<u> </u>				<u> </u>		6.9	4.5
	ssw	6	1.0	.3	<u> </u>	<u> </u>	<u></u>	<u> </u>	<u> </u>				1.9	4.4
	SW	.6	1.5	.5	.1		<u> </u>		ļ	<u> </u>			2.6	5.C
	wsw	.4	1.2	-5	.2	.1	.1			<u> </u>	ļ		2.4	6.7
	W	.7	1.0	2.2	1.7	.3				[5.8	9.1
	WNW	.2	1.1	1.9	2.2	.8		ļ	ļ <u> </u>		<u> </u>		6.2	10.9
	NW	.2	1.6	2.5	2.5	.4	.2	ļ				<u> </u>	7.4	1C.C
	NNW	.2	1.1	1.5	1.2	1	<u> </u>	L	ļ	[[4.C	8.6
	VARBL	ļ	<u> </u>	ļ		<u></u>	ļ	<u> </u>	<u> </u>	<u> </u>	[-			ļ
	CALM	><	><	><]><		<u> ><</u>	><		24.7	ĺ

TOTAL NUMBER OF OBSERVATIONS

1767

100.0 4.7

1210 WS FORM 0-8-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

20.9 29.3 14.4

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

DATA PROCESSING DIVISION ETAC, USAH ASHEVILLE, N. C. 28801

43310 STATION

SURFACE WINDS

5~ *x

* 3 *

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

	FUKU	CKA KYU	SHU JA	PAN/II	AZUKE	AB	46-6	4					D	EC
			STATIO	NAME						YEARS				ONTH
						ALL WE	ATHER						2100	-2300
		_					A55						HOURS	(L \$ T)
						CON	DITION							
					·									
		H						·			,			
	SPEED	((Į.			MEAN
	(KNTS)	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	WIND
į	DIR.	<u> </u>								l	L	L		SPEED
Į	N	.8	• 3	.5	.1	• 1				[1.9	6.C
i	NNE	• 3	• 5	• 3	• 1						l		1.2	5.4
	NE	1.0	• 5	•2						l		i	1.7	3.7
	ENE	.5	•2	•1						i			• 8	3.9
1	Ē	.7	.5	•1								 	1.4	3.5
	ESE	1.2	1.0	•2							 		2.3	3.9
	SE	6.1	7.8	1.5	• 2						 	i ———	15.5	4.3
Ì	SSE	5.5	7.5	3.0	• 3	•1							16.5	5.0
	S	3.2	5.9	1.4	•2						 		10.7	4.7
	SSW	.7	•8	•2							1	1	1.8	4.3
	SW	•5	• 5	• 3	• 2			i					1.5	6.2
	wsw	.5	.8	.4	•2	•1		T			<u> </u>		2.0	6.4
	w	.3	•6	1.8	. 8	.2	•1	i —					3.7	9.1
	WNW	.2	.7	1.5	1.4	.7	• 3	i	i —		1		4.8	11.4
	NW	.4	.7	2.0	2.3	• 5				1			5.9	10.3
	NNW	•1	.7	.8	1.0	• 2		T					2.8	9.5
	VARBL	1	1			T								
	CALM												25.5	
	CAUN													
		22.1	29.2	14.3	6.6	1.8	.4				1		100.0	4.5

TOTAL NUMBER OF OBSERVATIONS

1767

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

€.

SURFACE WINDS

×,

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

43310	FUKUCKA KYUSHU JAPAN/1 TAZUKE AB 46-64	ALL
	INSTRUMENT	ALL
	CLASS	HOURS (L S.T.)
	CIG 20C IC 140C FI W/ VSEY 1/2 MI OR MORE.	
	AND/OR VSBY 1/2 TC 2-1/2 MI W/CIG 20) FT CR MORE	

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥56	%	MEAN WIND SPEED
N	1.5	2.5	1.8	. 9	.3	•1	•0					7.1	7.2
NNE	. 8	8_	. 5	. 3	.0	•0			• C			2.4	5.8
NE	1.4	.9	.4	1	•0		•0					2.8	4.5
ENE	.7	.3	1	.0		0						1.0	3.8
E	1.0	.5	.2	.0	• 0						<u> </u>	1.7	4.C
ESE	1.1	. 5	. 2	.0	.0							1.8	4.3
SE	3.1	2.7	1.0	. 5	1_	0	.0	0				7.4	5.1
SSE	3.0	2.6	1.2	3_	1	.0	0	.0	ļ		<u> </u>	7.3	5.3
<u> </u>	2.0	1.8	5_	3_	0	0	0	0				4.7	
ssw	6	5_	1_	0	0_	0						1.3	4.2
SW	8	6_	.2	0	0		0	.0				1.7	4.6
wsw	5_	-4	2	1	0_	0_			<u> </u>		<u> </u>	1.3	5.7
w		1.0	.7	5_		0_	م	0_		0_	ļ	3,3	7.2
WNW	9	1.2	. 8	-4								3.5	7.C
NW	1.8	2.8	1.6	5_		0_	0	-0				6.9	6.1
NNW	1.3	2.4	1.9	7_	1_	0_		0	ļ			6.6	6.9
VARBL			ļ <u>.</u> .				Ļ	ļ	Ļ	Ļ	<u> </u>		
CALM	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	$\geq \leq$	39.2	
	21.5	21.3	11.6	4.8	1.0	4	2	1	.0	.0		100.C	3.5

TOTAL NUMBER OF OBSERVATIONS 16672

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA

PART D

CEILING VERSUS VISIBILITY

200 May

5.

This summary is a bivariate percentage frequency distribution by classes of ceiling from zero to equal to or greater than 20,000 feet and as a separate class "no ceiling", versus visibility in 16 classes from zero to equal to or greater than 10 miles. Data are derived from hourly observations, and three sets of tables are presented as follows:

- 1. Annual all years and all hours combined
- 2. By month all years and all hours combined
- 3. By month by standard 3-hour groups

Due to the cumulative nature of this presentation, it is possible to determine the percentage frequency occurrence for any given limit of ceiling or visibility separately, or in combination of ceiling and visibility. The totals progress to the right and downward. Ceiling may be determined independently by referring to totals in the extreme right hand columns. Also, visibility may be determined independently by reference to the horizontal row of totals at the bottom of the page. The percentage frequency for which the station was meeting or exceeding any given set of minima may be determined from the figure at the intersection of the appropriate ceiling column and visibility row. Several examples in the use of these tables are shown on pages 2 and 3 below.

U. S. Weather Bureau and Navy stations did not report ceilings within the range 10,000 feet and higher prior to January 1949. Summaries prepared from data for these stations using the earlier period will be eliminated from the summary for short periods or be limited to ceilings at or below 10,000 feet. For Air Force stations, the "no ceiling" category includes clear and scattered conditions, and ceilings above 20,000 feet for period through June 1948. Beginning in July 1948 for Air Force stations and January 1949 for USWB and US Navy stations the "no ceiling" category consists of observations with less .han 6/10 total sky cover and those cases where total sky cover is 6/10 or more, but not more than 1/2 of the sky cover is opaque.

Summary sheets are omitted when stations maintaining limited observing schedules did not report certain three-hour periods for any particular month during the available period of record. Such missing sheets are listed below:

JANUARY	APRIL	JULY	OCTOBER
FEBRUARY	MAY	AUGUST	NOVEMBER
MARCH	JUNE	SEPTEMBER	DECEMBER

EXAMPLES FOR USE OF CEILING VERSUS VISIBILITY TABLES IN THIS TABULATION

CEILING							\1S	IBILITY (ST	ATUTE MI	LES)					•	
(FEET)	≥ 10	≥ 6	≥ 5	≥4	≥ 3	≥ 2 1/2	≥ 2	≥1%	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING																
				\sim					~	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	\supset	$\check{\smile}_{7}$				
≥ 1800 ≥ 1500					91.0											92.6
≥ 1200 ≥ 1000																
≥ 900 ≥ 800		•								·						
≥ 700 ≥ 600																
≥ 500 ≥ 400										97.4						98.1
≥ 300 ≥ 200																
≥ 100 ≥ 0					95.4		96.9			98,3						100.

- EXAMPLE # 1 Read ceiling values independently of visibility under column at right headed > 0. For instance, from the table: Ceiling > 1500 feet = 92.6%. Ceiling > 500 feet = 98.1%.
- Read visibilities independently of ceilings on bottom line opposite ≥ 0 . From the table: Visibility ≥ 3 miles = 95.4%. Visibility ≥ 2 miles = 96.9%. Visibility ≥ 1 mile = 98.3%. EXAMPLE # 2
- To obtain combinations of ceiling with visibility, read figure at intersection of the two categories; ie: Ceiling \geq 1500 feet with visibility \geq 3 miles = 91.0%. EXAMPLE # 3
- EXAMPLE # 4 Values below minimums stated in the table may be obtained by subtracting the value given in the table from 100%. Thus, to obtain the percentage of observations with ceiling < 1500 feet and/or visibility < 3 miles, subtract the value read from the table at the intersection, which is 91.0, from 100.0. The answer 9.0 is the percentage of observations with ceiling < 1500 ft and/or vaby < 3 miles.

Likewise, the percentage of observations with ceiling < 500 ft and/or vsby < 1 mile is 2.6, obtained by subtracting 97.4 from 100.0.

ADDITIONAL EXAMPLES

EXAMPLE # 5 To find the percentage of observations falling within the two categories given in example above, subtract the value read from the table for the first set of limits from the value in the table for the second set of limits. The difference will be the percentage of observations meeting the lower set of limits, but not meeting the higher set of limits.

The value 91.0 read from the table at the intersection of \geq 1500 feet with \geq 3 miles, subtracted from 97.4 read from the table at the intersection of \geq 500 feet with \geq 1 mile is equal to 6.4%. Thus; 6.4 percent of the observation meet the criteria: "ceiling \geq 500 feet with vsby \geq 1 mile, but < 3 miles; or ceiling \geq 500 feet, but < 1500 feet with vsby \geq 1 miles."

ئ ماللىد

Since these tabulations are prepared in several ways including by month, by 3-hour groups it is possible to determine diurnal variations of ceiling and visibility limits as well as probabilities of various ceiling-visibility combinations.

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUUKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VIS	IBILITY (ST.	ATUTE MIL	ES)		· -				
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ½	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	12.4 16.0	27.2 34.4	29.9 37.9	32 • 2 41 • 1	33.5 42.9	34.0 43.6	34.5 44.3	34.8 44.7	34.8 44.7	35.0 44.9	35.0 44.9	35.0 45.0	25.0 - 5.0			35.€ 45.€
≥ 18000 ≥ 16000	16.2 16.5	35.0 35.6	38.6 39.3	41 • 8 42 • 6	43.6	44.3	45.1 45.9	45.5	45.5 46.4	45.7	45.7 46.6		47.8 43.7	46.7	43.7	45.8
≥ 14000 ≥ 12000	17.2 18.0	37•2 39•3		44.6	46.6 49.3	50.2	48.2 51.1	48.6 51.6	48.7 51.7	48.9 51.9	52.0	48.9 52.0	49.0 52.0	52.0	52.1	52.1
≥ 10000 ≥ 9000 ≥ 8000	18.8	41.5 42.3	46.9	50.1 51.2	52.5 53.7	53.5 54.7	54.5 55.8		55.2 56.5	55.5 56.7	56.8			56.9		55.6 57.6
≥ 7000 ≥ 6000	19.6 20.0 20.3	43.8 44.8 45.8	50.0	53.3 54.7 56.0	56.0 5 7. 5	57.0 58.6 60.0	58.2 59.8 61.4	58.9 60.5 62.1	59.0 60.7 62.2	59.3 61.0 62.6	61.1	59.4 61.1	54.5 61.2 62.8	61.2	61.2 62.8	59.5 61.2 62.8
≥ 5000 ≥ 4500	21.4	48.3	53.8	58.0 58.9	62.C	63.3 66.0	64.7	65.5	65.6 68.4	66.0	66.1	66.1	66.2	I i		66.3 69.1
≥ 4000 ≥ 3500	25.5	56.5 60.9	62.6	68.2	71.6	73.6 78.6	74.6	75.5	75.6 81.4	76.1 81.9	76.3	76.3	76.4 82.2	76.4	76.4	76.4
≥ 3000 ≥ 2500	29.4 30.2	64.9 67.2		78.2 81.2	82.2 85.5	83.8		86.8	86.9 90.5	87.5 91.1	87.7 91.3		87.8 91.5			
≥ 2000	30.6 30.7	68.9	76.6	83.2 83.6	88.3	90.1	92.3	93.6	93.2 93.8	93.9 94.5	94.7	94.8	94.3 94.9	94.9	94.9	95.0
≥ 1500 ≥ 1200 ≥ 1000	30.8	69.7	77.7	84.4 85.0	90.0		94.3	95.8	95.0 96.0	95 • 8 96 • 8		97.1	96.2 97.3 98.0	97.3		
≥ 900 ≥ 800	30.8 30.8	70.0	78.0		90.5		95.1	96.6		97.5 97.7 98.0		98.1	98.3 98.6	98 - 3	98.3	98.4
≥ 700 ≥ 600	30.8	70.1		85 • 7 85 • 8	90.8		95.5	97.1	97.3	98 • 2 98 • 5	98.6	98.6	98.8			
≥ 500 ≥ 400	30.8 30.8		78.3 78.3	85 • 9 85 • 9	91.0 91.1	93.1 93.2	95.8 95.9			98.8 98.9		99.2	99.4 99.6	1		99.5 99.7
≥ 300 ≥ 200	30.8 30.8	70.2	78.3	85.9	91.1	93.2 93.2	96.0 96.0	97.7	98.0	99.0	59.5	99.5		99.8		99.9
≥ 100 ≥ 0	30.8		78.3 78.3	85 • 9 85 • 9		93.3		97.7 97.1	1		1					99.9 106.0

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS PO

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310	FUKUCKA KYUSHU JAPAN/ITAZUKE AB	47-64	NAL
STATION	STATION NAME	YEARS	MONTH
		JENCY OF OCCURRENCE LY OBSERVATIONS)	ALL ROURS (LST)

CEILING							VISI	BILITY (STA	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6 ☐	≥ 5	≥4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 ¼ j	21	≥ ¾	≥ %	≥ %	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	8.1 9.1	18.1	20.2	22.2	23.5		T I	24.4	24.4	- 1	24.5	24.5		24.5 27.8	24.5	
≥ 18000	9.2	20.5	23.0	25.2	26.7	27.2	27.7	27.9	28.0	28.0	28.1	28.1	28.1	28.1	28.1	25. 1
≥ 16000	9.3		23.2	25.5	27.0	27.4		28.2	28 - 2			28.3	28.4		28.4	20.4
≥ 14000 ≥ 12000	9.6	21.4 22.7	23.9	26.3	27.9	28-4	28.9 30.8	29.2	29.2 31.1	29.3 31.2	29.3 31.3	31.3			31.3	
≥ 10000	10.4	24.1	27.2	30.2		32.6	- 1		33.6	33.7	33.8	33.8	33.8		33.9	33.9
≥ 9000	10.6		27.9			33.5		34.5				34.8		34.8		
≥ 8000	10.9		1 1	32.6		35.4	36.2	1	36.6	- 1	36.8	36.9	•		37.0	
≥ 7000	11.1		30.1	33.7	35.9 37.0		$\frac{37.5}{38.7}$	37.9 39.1	37.9		38.2				38.4	39.7
≥ 6000 ≥ 5000	13.1	1 1	35.4	39.5		42.9	1		44.6	- ;				1 1	45.1	45.1
≥ 4500	16.0			45.2	48.1	48.9	5C.0		50.6			51.1			51.2	21.2
≥ 4000	23.5	51.5	57.0	62.1	65.5	66.6	67.8	68.3	68.4	68 . 8	68.9	69.0	69.1	69.1	69.1	69.2
≥ 3500	27.6	61.0	67.3	73.C		78.2	-	80.2	-	- 1		81.0		81.1	81.2	81.2
≥ 3000	29.3	66.0			84.C		87.0		88.0							
≥ 2500	29.9				88.1	89.6	- :		92.6	93.2		93.4		1 1	'	93.7
≥ 2000	30.1	69.4			90.2	91.9		95.1	95.3	96.0		96.4			96.6	
≥ 1800 ≥ 1500	30.1	69.5	1 1	85.1 85.6	90.4	92.1 92.9	. }	95.5 96.5	_1	96 • 4 97 • 5	96.7 97.8				98.2	38.2
≥ 1200	30.1	69.7	77.9			93.2	95.5			98.0						98.7
≥ 1000	30.1				91.6	–	1	97.3				1) _ 1	99.2	99.2
≥ 900	30.1	69.8	78.0	86.0	91.6	93.5	95.9	97.3	97.5	98.4	98.8	98.9	99.1	99.1	99.2	99.3
≥ 800	30-1	69.8	78.0	86.0	91.7			97.4		98.5		99.0			99.3	
≥ 700	30.1			86.0		_						_				1
≥ 600	30.1										99.1					
≥ 500	30.1	1		86.1										1		1
	30.1	69.8		86.1 86.1	91.8			97.6			99.3					99.5
≥ 300	30.1	1		86.1		93.7					99.3		1	1		icc.cl
≥ 100	30.1			86.1	91.8			97.6			99.3				99.9	
≥ 0	30.1	1	1		91.8	93.7					99.3		99.7	99.7	99.9	ice.cl

TOTAL NUMBER OF OBSERVATIONS 13390

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETI

دگ

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 48-64

STATION NAME

YEARS

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

		-					VIS	BILITY (51)	ATUTE MIL	ES)						
CEILING	7	,-		+		,		,			,			,		
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 11/3	≥ 1%	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING	9.5	21.5	23.9	26.6	27.9	28.5	29.0	29.4	29.4	29.5	29.5	29.5	29.5	29.6	29.6	29.6
≥ 20000	11.5	26.0	29.1	32.5							36.2			36.3	36.3	36.3
≥ 18000	11.7	26.4	29.6	33.C		35.5			36			37.C			37.0	37.1
≥ 16000	11.7	26.7	29.9	33.4	35.1	35.9			3/.1	37.3	37.4	37.4	37.4	37.4	37.5	37.5
≥ 14000	12.1	27.6	31.1	34.6	36.4	37.2	38.0	38.4	38.+	38.6	38.8	38.8	38.8	38.8	38.8	38.9
≥ 12000	12.8	29.3	33.0	36.8				40.9	41.0	41.2				41.3	41.4	41.4
≥ 10000	13.4	31.1	35.2	39.3	41.4	42.3	43.3	43.8	43.7	44.1	44.3	44.3	44.3	44.3	44.3	44.4
≥ 9000	13.5	31.6	35.7	40.0	42.2	43.1			44.7	45.0	45.1	45.1	45.2	45.2	45.2	45.4
≥ 8000	13.7	32.5	36.9	41.3	43.7	44.7	45.8	46.3	46.4	46.6	46.8	46.8	46.8	46.9	46.9	46.9
≥ 7000	13.8	33.2	37.8	42.5	44.9	46.1	47.2	47.9	48.0	48.2	48.4	48.4	48.4	48.5	48.5	48.5
≥ 6000	14.0	34.0	38.8	43.9	46.4	47.5	48.9	49.6	49.6	49.9	50.1	50.1	50.1	50.1	50.1	20.2
≥ 5000	15.8	37.9	43-1	48.3	51.0	52.3	53.7	54.5	54.5	54.8	55.0	55.1	<u>5</u> 5.1	55.1	55.1	25.2
≥ 4500	19.0	43.3	48.9	54.4	57.2	58.5	60.0	60.9	60.9	61.2	61.4	61.4	61.5	61.5	61.5	61.6
≥ 4000	24.1	53.4	59.9	65.8	69.1	70.5	72.2	73.1	73.2	73.6	73.8	73.8	73.9	73.9	73.9	73.9
≥ 3500	27.2	59.8	66.8	73.5	77.2	78.6	80.4	91.5	81.6	82.0	82.2	82.2	82.3	82.3	82.3	82.4
≥ 3000	28.7	63.7	71.2	78.4	82.5	84.1	86.1	87.3	87.5	88.0	88.3	88.4	88.5	88.5		88.6
≥ 2500	29.1	65.8	73.6	81.1	85.5	87.2	89.5	90.8	91.0	91.7	92.1	92.1	92.3			42.3
≥ 2000	29.2	66.7	74.8	82.7	87.3	89.1	91.6	93.2	93.4	94.3	94.7	94,7	94.9	94.9		95.0
≥ 1800	29.2	67.0	75.2	83.2	88.C	89.8	92.3	93.9	94.2	95.0	95.5	95.5	95.7	95.8	95.8	95.8
≥ 1500	29.2	67.4	75.8	<u>83.9</u>	88.9	90.7	93.4	95.0	95.3		96.7				97.1	97.2
≥ 1200	29.2					91.0		95.5			97.3			1	ı	
≥ 1000	29.2	67.6	76.1	84.3	89.3	91.3	94.1				97.9					
≥ 900	29.2						1	1 '			97.9		1	1	•	98.5
≥ 800	29.2	67.6	76.1								98.2					
≥ 700	29.2	67.6				91.5		96.2						· ·	ı	ι.
≥ 600	29.2	67.6	76.2								98.5			99.0		
≥ 500	29.2	1			89.5						98.7				L	1
≥ 400	29.2										98.8					
≥ 300	29.2										98.8				1	1 1
≥ 200		67.6													99.7	
≥ 100		67.6														
≥ 0	1 29.2	67.6	76.2	84.4	89.5	91.5	94.5	96.4	96.8	98.2	99.0	99.0	99.6	99.7	99.8	noc.u

TOTAL NUMBER OF OBSERVATIONS 11543

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PFRCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VISI	BILITY (STA	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ½	≥1%	ا د≤	≥ ¾	≥ %	≥ % °	≥ 5/16	≥ ¼	> 0
NO CEILING ≥ 20000	12.6		32.6		36.2			37.4			37.6	37.6	37.6	37.6	37.6	- 1
≥ 18000		35.1 35.6	38.6	41.5 42.1	43.8	43.6		45.3		45.5		45.6	45.6	45.6	45.6	45.7
≥ 16000	15.0	36.3	}	43.1	44.8			46.4	46.5	1	46.6	46.6	46.7	1 - 1 - 1		46.1
≥ 14000	15.7	37.8		44.9	46.7			48.3	48.4	48.5		48.6	48.6		48.6	48.7
≥ 12000	16.3	39.5		47.2	49.1	49.7	- 1		1	51.1	51.1	51.1	51.2		51.2	51
≥ 10000	16.8			49.7	51.8		53.3		53.9	54.0		54.2	54.2	54.2	54.2	54.3
≥ 9000	17.0	42.1	46.7	50.6	52.8	53.5	54.4	54.9	55.0	55.2	55.3	55.3	55.4	55.4	55.4	55.4
≥ 8000	17.4	43.3	48.1	52.2	54.5	55.2	56.2	56.7	56.9	57.1	57.2	57.2	57.3	57.3	57.3	57.3
≥ 7000	17.6	44.1	49.0	53.2	55.7		57.6		58.3			58.7	58.7		58.8	58
≥ 6000	17.9	45.2		54.7	57.3		59.3		60.0	60 • 3		60.4	60.5		60.5	60.5
≥ 5000	19.0	48.0		58.1		61.9		63.9	64.1	64.4			64.6		64.7	64.7
≥ 4500	20.0	50.5		61.1	64.1			67.3	67.5	67.9		68.0	68.1	68.1	68.1	68.4
≥ 4000	23.4			68.3	71.5			75.2	75.4			76.0	76.1			76.1
≥ 3500 ≥ 3000	25.5			73.8				81.2				82.1	82.2	: 1	82.2	
≥ 2560	27.0				81.7			86.2	90.0	87.0 90.6		87.2 90.9	87.3 91.0			
≥ 2000	27.7		1 1	- 1	84.9 87.6		88.4		93.0			94.0	94.2		94.2	94.2
≥ 1800	28.0			83.6	88.1		92.0		93.6			94.7	94.9			
≥ 1500	28.1					1 .			94.9		1 I	,	96.3	;		
≥ 1200	28.2					91.5	94.2			96.9		97.2	97.4	97.4		
≥ 1000	28.2					92.0			96.5				98.0		98.1	98.1
≥ 900	28.2	70.5	78.1	85.5	90.4	92.1	94.9	96.5	96.8	97.7	98.0	98.1	98.3	98.3	98.3	98.4
≥ 800	28.2	70.6	78.2	85.6	90.6	92.3	95.0	96.7	97.0	97.9	98.2	98.3	98.5	98.6	98.6	98.6
≥ 700	28.2	70.6	78.2	85.7				1	97.2		1			1 1	1	
≥ 600	28.2	70.6	78.3	85.8		92.6								99.3		
≥ 500	28.2					92.7			-			99.2	99.5			. ,
≥ 400	28.2					92.7					99.3		99.6			
≥ 300	28.2								98.0		1			1		
	28.2		78.3			92.8				99.1		99,6		99.9		
≥ 100	28.2	1	1			92.8		97.6		99.1	99.5	99.5		99.9	5	150.5
	28.2	70.7	78.3	85.9	91.0	76.0	72.1	71.0	700	77.2	1 77.2	77.3	77.0	77.7	7707	H JO O Y

TOTAL NUMBER OF OBSERVATIONS_

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 48-64

APR

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

ALL

CHILING							VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEcT)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ ¾	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING	14.0	29.3	32.0	34.7	36.2		37.4		37.6	37.7	37.7	37.7	37.8	37.8	37.8	37.8
≥ 20000	16.7	36.0		42.9	44.8				46.6	46.8	46.8		46.9		46.9	46.9
≥ 18000	16.9	36.7	40.2	43.8	45.8		47.4	47.7	47.7	47.9	47.9	47.9	48.0	48.0	48.0	48.0
≥ 16000	17.2	37.5	41.0	44.7	46.7	47.6	48.4	48.6	48.7	48.9	48.9	48.9	49.0	49.0	49.C	49.
≥ 14000	17.7	38.8	42.6	46.5	48.7	49.6	50.5	50.8	50.8	51.1	51.1	51.1	51.2	51.2	51.2	51.2
≥ 12000	18.C	40.3	44.4	48.6	51.1	52.2	53.2	53.5	53.5	53.8	53.9	53.9	53.9	54.0	54.0	54.0
≥ 10000	18.8	42.8	47.3	51.9	54.7	55.8	57.0	57.5	57.5	58.0	58.1	58.1	58.2	58.2	58-2	58.2
≥ 9000	18.9	43.3	48.0	52.6	55.5	56.7	57.9	58.4	58.5	59.0	59.1	59.1	59.2	59.2	59.2	59.4
≥ 8000	19.5	44.7	49.6	54.4	57.4	58.7	60.0	60.6	60.6	61.1	51.2	61.3	61.3	61.3	61.4	61.4
≥ 7000	19.9	46.1	51.3	56.4	59.5	60.8	62.3	62.9	63.0	63.5	63.6	63.6	63.7	63.7	63.8	63.0
≥ 6000	20.1	47.0	52.4	57.6	60.8	62.2	63.8	64.5	64.6	65.1	65.3	65.3	65.4	65.4	65.4	65.5
≥ 5000	21.0	49.4	55.0	60.6	63.9	65.4	67.1	67.8	67.9	68.5	68.6	68.7	68.8	68.8	68.8	68.b
≥ 4500	21.4	50.4	56.1	61.7	65.2	66.7	68.4	69.2	69.3	69.9	70.1	70.1	70.2	70.2	70.2	10.4
≥ 4000	22.9	53.9	59.9	65.8	69.5	71.1	72.9	73.8	73.9	74.5	74.8	74.8	74.9	74.9	74.9	74.9
≥ 3500	િ23∙ શૈ	56.7	62.9	69.1	73.0	74.7	76.6	77.6	77.8	78.4	78.7	78.7	78.8	78.8	78.8	78.₺
≥ 3000	24.7	59.4	65.9	72.5	76.7	78.5	80.7	81.8	81.9	82.7	82.9	83.0	83.1	83.1	83.2	83.4
≥ 2500	25.4	61.7	68.5	75.4	79.9	81.8	84.0	85.3	85.5	86.3	86.6	86.6	86.8	86.8	36.8	86.8
≥ 2000	25.9	63.6	70.8	77.9	82.6	84.6	87.2	88.5	88.7	89.6	89.9	90.0	90.1	90.2	90.2	90.2
≥ 1800	26.1	64.1	71.4	78.6	83.3	85.3	87.9	89.3	89.5	90.4	90.8	90.8	91.0	91.0	91.0	91.1
≥ 1500	26.2	64.7	72.2	79.6	84.6	86.7	89.5	91.0	91.3	92.3	92.7	92.7	93.0	93.0	93.0	93.1
≥ 1200	26.3	65.4	73.1	80.6	85.8	88.0	90.9	92.5	92.8	93.9	94.2	94.3	94.6	94.6	94.6	94.7
≥ 1000	26.3	65.8	73.6	81.3	86.5	88.8	91.8	93.5	93.8	94.9	95.3	95.4	95.6	95.7	95.7	95.7
≥ 900	26.3	65.9	73.7	81.5	86.8	89.1	92.1	93.8	94.1	95.3	95.7	95.8	96.0	96.1	96.1	96.1
≥ 800	26.3	65.0	75.9	81.8	87.1	89.5	92.6	94.3	94.6	95.8	96.3	96.3	96.6	96.6	7	96.1
≥ 700	26.3	66.1	74.0	82.	87.4	89.9	93.0	94.8	95.1	96.3	96.7	96.8	97.1	97.2	,7.2	97.2
≥ 600	26.4	66.2	74.1	82.2	87.6	90.2	93.4	95.2	95.5	96.8	97.3	97.3	97.6	97.7	97.7	97.8
> 500	26.4	66.3	74.3	82.4	88.0	90.7	93.9	95.9	96.3	97.6	98.1	98.2	98.5	98.6	98.6	98.6
≥ 400	26.4	66.3	74.3	82.5	88.1	90.8	94.1	96.1	96.5	98.0	98.5	98.5	98.9	98.9	99.0	99.6
≥ 300	26.4	65.3	74.4	82.6	88.2					98.2		98.8	99.2	99.3	99.3	99.4
≥ 200	26.4	66.3	74.4	82.6	89.2	90.9	94.3			98.3	98.9	99.0	99.4	99.4	99.5	99.5
≥ 100	26.4		74.4											99.5	99.7	99.0
≥ 0	26.4	66.3			i	!	1	1	i		,	99.0	99.4	1	99.7	100.0
									<u></u>							·

TOTAL NUMBER OF OBSERVATIONS

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

MALES A.

CAIA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

ALL

MAY

										u-						
CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						1
(FEET)		≥ 6	≥ 5	I. T	1	S !	!	٠ I	×	1	I	I	~			≥ 0
	≥ 10	= 0	= 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	21/2	≥ 1 1/4	۱ ا =	≥ ¾	≥ %	< ½	≥ 5/16	≥ ¼	< 0
NO CEILING	11.4	26.6	29.5	31.8	33.2	33.6	34.0	34.2	34.3	34.4	34.4	34.4	34.4	34.4	34.4	34.4
≥ 20000	15.6	36.4	40.7	44.2	46.2	46.8	47.5	47.9	47.9	48.0	48.1	48.1	48.1	48-1	48.1	48 . 2
≥ 18000	15.8	37.1	41.4	45.1	47.2	47.9	48.6	49.0	49.0	49.2	49.2	49.2	49.2	49.3	49.3	49.3
≥ 16000	16.1	37.9	42.4	46.1		49.1		50.2				50.5			50.5	50.5
≥ 14000	16.7	1	44.4	48.4	50.7		,		52.9					1	53.2	53.2
≥ 12000	17.4		46.9	51.3		54.7			56.4							56.8
≥ 10000	18.1	44.0	49.6	54.3		1			60.1					60.6	1 1	1
≥ 9200	18.3			55.7					61.8					62.2		02.3
≥ 8000	19.0			58.2		62.6			64.8					65.2	, ,	65.3
≥ 7000	19.4		54.4						67.0					67.5	·	
≥ 6000	19.7		;	- 1		66.5			68.9					69.4	1	69.5
≥ 5000	20.3			63.7					71.4					72.0		72.1
≥ 4500 ≥ 4000	20.6	1		64.6	68.3	1	- (73.0		73.1	1		73.2
 	21.5			67.4		72.9		78.9			76.3 79.7					
≥ 3500 ≥ 3000	22.2			70.3		76.1		82.6		83.3		1		1		
≥ 2500	23.5		66.3		80.2	79.5 82.2										86.5
≥ 2000	24.1					84.7			88.5						1 1	
≥ 1800	24.2		70.7	78.3				89.0								30.3
≥ 1500	24.3								91.0						92.1	92.1
≥ 1200	24.4		72.7	80.7					92.6							93.8
≥ 1000	24.5					89.2		93.7				95.0				95.2
≥ 900	24.5											95.6				95.8
≥ 800	24.5	64.4	73.5						95.0		96.1	96.2	96.3	96.4	96.4	96.4
≥ 700	24.5	64.5	73.7	82.2					95.6					97.1	97.1	97.1
≥ 600	24.5	64.6	73.9	82.4	88.3	90.9			96.4	97.3	97.7	97.7	97.9	97.9	98.0	98.0
≥ 500	24.5	64.7	73.9	82.5	88.5	91.2	94.6	96.6	97.0	98.0	98.4	98.4	98.6	98.6	98.7	98.7
≥ 400	24.5	64.7	73.9	82.6	88.6	91.3	94.8	96.9	57.3				99.1		+	
≥ 300	24.5	64.7							97.5		99.2		1	1	, ,	- 1
≥ 200	24.5	64.7	74.0	82.6	88.7	91.5	95.0	97.2	97.6	98.8	99.4	99.5	99.7	99.7	99.8	99.8
≥ 100	24.5	1	74.G	82.6	88.7	91.5	95.0	97.2	97.6	98.8	99.4	99.5	99.7	99.8	99.8	99.9
≥ 0	24.5	64.7	74.0	82.6	88.7	91.5	95.0	97.2	97.6	98.9	99.4	99.5	99.7	99.8	99.8	100.0

TOTAL NUMBER OF OBSERVATIONS 13389

CATA PROCESSING DIVISION ETAL, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

ALL HOURS (LST)

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 %	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING	7.1	16.6	18.6	20.7	21.9	22.7	23.4	23.9		24.2	24.2	24.2	24.2	24.2	24.2	24.2
≥ 20000	11.1	25.6	29.2	32.8	35.1	36.3	37.6	38.5	38.7	39.1	39.1	39.1	39.2	39.2		39.2
≥ 18000	11.5	26.6	30.2	34.0	36.5	37.7	39.C	40.0	40.2	40.6	40.7	40.7	40.8	4C.8	40.8	40.8
≥ 16000	11.9	27.4	31.3	35.2	37.7	39.1	40.5	41.6	41.7	42.2	42.3	42.3	42.3	42.3	42.3	42.4
≥ 14000	12.6	29.3	33.5	37.8	40.6	42.0	43.6	44.8	45.0	45.6	45.7	45.7	45.8	45.8	45.8	45.8
≥ 12000	13.1	31.0	35.5	40.2	43.3	44.8	46.6	48.0	48.2	48.8	49.0	49.0	49.1	49.1	49.1	49.1
≥ 10000	13.7	32.8	37.7	42.9	46.2	47.9	49.9	51.3	51.6	52.3	52.5	52.5	52.7	52.7	52.7	52.7
≥ 9000	13.8	33.4	38.3	43.6	47.1	48.9	51.0	52.5	52.8	53.5	53.8	53.9	54.1	54.1	54.1	54.1
≥ 8000	14.1	34.6	39.9	45.6	49.3	51.2	53.4	55.1	55.4	56.2	56.6	56.7	56.9	56.9	56.9	56.9
≥ 7000	14.3	35.7	41.2	47.2	51.1	53.1	55.4	57.1	57.4	58.4	58.7	58.8	59.1	59.1	59.1	59.1
≥ 6000	14.5	36.3	42.0	48.1	52.2	54.3	56.7	58.5	58.8	59.8	60.1	60.2	60.5	60.5	60.5	66.5
≥ 5000	15.0	37.7	43.5	49.9	54.1	56.3	58.9	60.7	61.1	62.1	62.5	62.6	62.8	62.8	62.8	62.9
≥ 4500	15.3	38.6	44.6	51.0	55.4	57.7	60.3	62.2	62.6	63.6	64.0	64.1	64.3	64.4	64.4	64.4
≥ 4000	16.7	41.5	47.8	54.5	59.1	61.4	64.2	66.2	66.6	67.7	68.0	68.1	68.4	68.4	68.4	68.5
≥ 3500	18.1	44.6	51.2	58.2	63.1	65.6	68.5	70.5	70.9	72.0	72.4	72.5	72.8	72.8	72.8	72.8
≥ 3000	20.0	48.7	55.8	63.1	68.3	70.9	74.0	76.2	76.6	77.7	78.2	78.3	78.6	78.6	78.6	78.€
≥ 2500	21.3	52.1	59.6	67.3	72.9	75.7	78.9	81.2	81.6	82.9	83.3	83.4	83.7	83.8	83.8	83.8
≥ 2000	22.1	54.6	62.6	70.6	76.7	79.7	83.1	85.6	86.0	87.4	87.8	88.0	88.3	88.4	88.4	88.4
≥ 1800	22.3	55.4	63.5	71.6	77.7	80.8	84.3	86.8	87.3	88.6	89.1	89.2	89.6	89.6	89.6	89.6
≥ 1500	22.6	56.5	64.9	73.3	79.7	82.8	86.6	89.2	89.7	91.1	91.6	91.8	92.1	92.2	92.2	92.2
≥ 1200	22.7	57.6	66.3	75.1	81.5	84.8	88.8	91.6	92.1	93.6	94.2	94.3	94.7	94.8	94.8	94.8
≥ 1000	22.7	58.0	66.9	75.8	82.4	85.8	89.9	92.9	93.4	95.1	95.7	95.8		96.3	96.3	
≥ 900	22.7	58.1	67.0	76.0	82.7	86.1	90.2	93.3	93.8	95.5	96.1	96.3	96.7	96.7	96.7	96.8
≥ 800	22.7	58.3	67.4	76.4	83.2	86.6	90.9	94.0	94.5	96.3	97.0		97.6		97.6	97.1
≥ 700	22.7	58.4	67.5	76.7	83.5	87.0	91.3	94.4	95.0	96 . 8	97.5	97.7	98.1	98.1	98.2	1
≥ 600	22.7	58.5	67.7	76.9	83.9	87.4	91.8	95.0	95.5	97.4	98.1	98.3		98.8	98.8	
≥ 500	22.7		67.8	77.0	84.C	87.5	92.0	95.2	95.7	97.7	98.5	98.6			99.2	
≥ 400	22.7	58.6	67.8			87.7		95.5								
.≥ 300	22.7	58.6	67.9				1	95.6		1	1		1	1		-
≥ 200	22.7	58.6	67.9	77.2	84.2	87.9	92.3	95.6	96.2	98.2		99.2				
≥ 100	22.7	58.6	67.9						96.2			99.2			1	100.
≥ 0	22.7	58.6	67.9	77.2	84.2	87.9	92.3	95.6	96.2	98.2	99.1	99.2	99.8	99.8	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS

1210WS JUL 64 Q-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE ORSOLETE

ye out the the

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUUKA KYUSHU JAPAN/ITAZUKE AB 47-64 PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS) ALL HOURS (L S.T.)

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ½	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ ½	≥ 5/16	≥ ¼	≥ 0
NO CEILING	13.1	24.7	26.7	28.1	28.6	28.8	29.1	29.2	29.2	29.2	29.2	29.2			29.3	29.3
≥ 20000	19.2	34.2	36.7	38.5		39.6			40.1	40.2	40.2	40.2			40.2	40.3
≥ 18000	19.5	34.9	37.5	39.3	40.0	40.4	40.7		40.9	40.9	40.9	40.9	41.0		41.0	41.
≥ 16000	20.0	35.7	38.2	40.1	40.8	41.2	41.5		41.7	41.7	41.8	41.8			41.8	41.8
≥ 14000	21.4	37.8	40.5	42.5	43.3	43.6	44.0	44.2	44.2	44.2	44.3	44.3	44.3	44.3	44.3	44.3
≥ 12000	23.0	40.5	43.4	45.5		46.8	47.1	47.3	47.3	47.4	47.4	47.4	47.4		47.4	47.5
≥ 10000	24.7	43.4	46.6	49.0	50.0	50.4	50.8		51.1	51.1	51.1	51.1	51.2	51.2	51.2	51.2
≥ 9000	25.3	44.5	47.8	50.2		51.7	52.2		52.4	52.5	52.5	52.5		52.5	52.5	52.6
≥ 8000	26.1	46.3	49.7	52.3	53.5	53.9	54.4		54.7	54.7	54.8	54.8			54.8	54.8
≥ 7000	26.8	47.6	51.0	53.9		55.5			56.4	56.4	56.4	56.4			56.5	56.5
≥ 6000	27.4	48.5	52.1	54.9		56.6	57.2		57.5	57.6	57.6	57.6			57.6	57./
≥ 5000	28-1	50.1	53.8	56.7		58.4			59.4	+	59.5	59.5	59.5			59.6
≥ 4500 ≥ 4000	28.6	1	55.2	58.2		60.0	60.6	1	60.9	61.0	61.0	61.0		1		61.1
	31.1	55.7		62.9		64.9				66.0	66.0	66.0			66.1	66.1
≥ 3500 ≥ 3000	34.1	60.8		68.7	70.2	70.8		1	72.0	72.1	72.1	72.1	72.1	72.2	72.2	12.2
	38.6		72.9			79.6			81.0	81.2	81.3	81.3				81.4
≥ 2500 ≥ 2000	40.6		77.7	82.1		85.1	86.3	. ,	86.8	87.1	87.1	87.1	87.2		87.2	87.2
	41.6					89.1	90.4		91.1	91.5	91.5	91.5	91.6		91.6	91.6
≥ 1800 ≥ 1500	41.6					90.0			92.1	92.4	92.5		92.5			94.7
	41.8					91.7	93.2		94.1	94.5	94.6	94.6			96.0	96.1
≥ 1200	41.9			88.6		92.8			1	1			97.1	97.1	97.2	97.3
	41.9					93.6			96.3	96.9	97.1 97.5	97.1			97.6	97.7
≥ 900	42.0		84.0 84.2			94.3		96.7 97.1	97.1					98.1	98.1	98.4
	42.0					94.5			97.5		98.3				98.5	98.6
≥ 700	42.0		84.5	l			l				98.9			1		99.1
≥ 500	42.0			90.4			97.0		98.3		99.3				99.5	99.6
≥ 400	42.0	1	1 '		1		1	98.3								99.1
≥ 300	42.0							98.4			99.6				99.8	99.9
≥ 200	42.0	1	1	1	'	_	-	•					1			
≥ 100	42.0			1							99.6	_			•	
≥ 100	42.0				1			98.5								nóc it
	72.0		04.0	70.0	77.0	7303	7102	. ,,,,	70.0	7707	- , , , ,	,,,,,,	, , , , , ,	1 77.00	- / - /	<u> </u>

TOTAL NUMBER OF OBSERVATIONS_

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1 .	≥ ¾	≥ 3/6	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING	16.9	35.3	38.1	40.2	41.2	41.5	41.9	42.1	42.1	42.2	42.2	42.2	42.2	42.2	42.2	42.2
≥ 20000	24.2	47.6	51.7	54.8	56.6	57.0	57.5	57.8	57.8	57.9	57.9	57.9	57.9		57.9	57.9
≥ 18000	24.6	48.1	52.3	55.4	57.2	57.6	58.1	58.4	58.4	58.5	58.5	58.5	58.5	58.5	58.5	58.5
≥ 16000	24.9	48.8	53.0	56.1	58.0	58.4	58.9	59.2	59.2	59.3	59.3	59.3	59.3		59.3	59.3
≥ 14000	26.2	51.1	55.6	58.8	60.7	61.1	61.7	62.0	62.0	62.1	62-1	62.1	62.1	62.1	62.1	62.1
≥ 12000	27.5	53.2	58.0		63.4	63.8	64.4	64.7	64.7	64.9	64.9	64.9	64.9		64.9	64.9
≥10000	28.7	55.6	60.6	64.2		66.9	67.5		67.8	68.0	68.0	68.0	68.0		58.0	68.0
≥ 9000	29.1	56.5		65.2		68.0	68.6		68.9	69.1	69.1	69.1	69.1	69.1	69.1	69.1
≥ 8000	29.8	58.0	63.3	67.1	69.4	69.9	70.6		70.9	71.1	71.1	71.1	71.1		71.1	71.1
≥ 7000	30.4	59.1	64.5		70.7	71.2	71.9		72.3		72.4	72.4	72.5	72.5	72.5	72.5
≥ 6000	30.8		65.5			72.2	72.9	73.3	73.3	73.5	73.5	73.5	73.5	73.5	73.5	
≥ 5000	31.4		67.1	71.0	73.4	74.0	74.7	75.1	75.1	75.3	75.3	75.3				75.3
≥ 4500	31.7	62.4	68.0		74.5	75.1	75.8	76.2	76.2	76.4	76.4	76.4	76.4		76.4	76.4
≥ 4000	33.4	65.8			78.2	78.8	79.6		80.1	80.2	80.3	80.3	80.3			
≥ 3500	34.9		75.0			82.6	83.4	83.9	83.9	84 - 1	84.1	84.1	84.1	84.1	84-1	84.1
≥ 3000	37.6					88.1	89.1	89.6	89.7	89.8	89.8	89.8	89.9			
≥ 2500	38.9			1		91.5	92.5		93.2	93 • 3	93.4	93.4	93.4		93.4	
≥ 2000	39.5		84.9			93.9	95.0		95.7	95.9		95.9	96.0			
≥ 1800 ≥ 1500	39.6		85.3			94.3	95.5		96.2	·	96.4	96.4	96.4			
	39.7			90.9		95.1	96.3		97.0			97.3			97.4	
≥ 1200 ≥ 1000	39.7	79.0		91.5		95.8	97.1		97.9	- 1	98.3	98.3	98.3		98.3 99.0	
	39.7					96.4	97.7		98.7	98.9	99.0	99.0	99.0		99.2	
≥ 900 ≥ 800	39.7	79.2 79.3	86.5	l .	(96.5 96.6	97.8 97.9				99.4	99.4		1		_
≥ 700	39.7					96.7	98.0		99.0			99.5	99.6			
≥ 600	39.7						98.1	99.0							99.7	
≥ 500	39.7					96.7	98.1	99.1	99.2	99.6						
≥ 400	39.7							–				99.8				
≥ 300	39.7				95.8											
≥ 200	39.7	(99.7		99.9		99.9	l .	
≥ 100	39.7		,		95.8										100.0	
≥ 0	39.7		1					99.2						99.9		1

TOTAL NUMBER OF OBSERVATIONS____

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUUKA KYUSHU JAPAN/I TAZUKE AB 46-64 PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS) ALL HOURS (L S T.)

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	ן ≤	> 3/4	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	14.3	29.4	31.9	33.6	34.3	34.5	34.7	34.8	34.8	34.9	34.9	34.9	34.9			34.9
≥ 20000	19.2	38.7	42.0	44.7	45.7	46.1	46.4				46.7	46.7	46.7		46.7	46.7
≥ 18000	19.7	39.5	42.9	45.6	46.6	47.0	47.4		47.6	47.6	47.6	47.6		1 1		47.7
≥ 16000	20.1	40.4	43.9	46.7	47.8	48.2	48.5		48.7	48 - 8	48.8	48.8	48.8		48.9	48.9
≥ 14000	21.1	43.1	47.0	50.0	51.2	51.6	52.0		52.2	52.3	52.3	52.3	52.3			52.4
≥ 12000	22.4	46.1	50.4	53.6		55.6	56.0		56.4	56.5	56.5	56.5	56.5			56.5
≥ 10000	23.6	49.7	54.4	57.9	59.6	60.3	60.9		61.3	61.4	61.5	61.5	61.5	61.5		61.5
≥ 9000	24.2	51.0	55.9	59.7	61.4	62.1	62.7	63.1	63.2	63.3	63.3	63.3	63.4			63.4
≥ 8000	25.6	54.2	59.5	63.5	65.5	66.2	66.9		67.4	67.6	67.6	67.6				67.7
≥ 7000	26.2	55.7	61.2	65.4			69.0					69.7	69.7		69.7	69.7
≥ 6000	26.6	57. q	62.6	67.0		69.8	70.6		71.1	71 • 3	71.3		71.3		71.4	11.4
≥ 5000	27.2	58.9	64.7	69.3	71.5		73.1	73.5			73.9		73.9		73.9	74.
≥ 4500	27.6	59.8	65.7	70 - 3	72.6	73.4	74.3		74.8	75.0	75.1	75.1	75.1	75.1	75.1	75.1
≥ 4000	28.8	62.5	68.5	73.4		76.7	77.7			78.5	78.5				78.6	
≥ 3500	29.9		71.6	76.8	79.3	80.3			_	82 • 2			82.2		82.2	82.3
≥ 3000	31.7	69.2		81.7											87.9	
≥ 2500	32.5	71.9	79.3	85.3			90.7			92.0			i e	1	92.1	92.1
≥ 2000	32.9			87.5					94.4							95.C
≥ 1800	33.0	- 1		88.0	6	,	94.1	The state of the s	1	95.5					. i	95.7
≥ 1500	33.1		82.3	88.9						97.0			97.1	97.1	97.1	97.2
≥ 1200	33.2		82.8	89.6	- 1	94.7)	97.6	1	98.3			1 1	1 1	98.3
≥ 1000	33.2			89.9			96.9		98.2	98 • 8						99.0
≥ 900	33.2	75.0		90.0					98.4				99.1	1 1		99.2
≥ 800	33.2	75.0		90.0					98.6				99.3			99.4
≥ 700	33.2			90 • 1					1 1	99.3		1	1	1		99.5
≥ 600	33.2			90.1	93.9					99.4	99.6					99.7
≥ 500	33.2	75.1		90.1	94.0				98.9	99.5			99.8			1 1
≥ 400	33.2			90.1	94.0				98.9	99.6		99.7	99.8			99.5
≥ 300	33.2	1	83.2	90.1				,	1	1	99.8			1		1 1
≥ 200	33.2										99.8				·	100.0
≥ 100	33.2	75.1	83.2						1		99.8		1		-	100.0
≥ 0	33.2	75.1	83.2	90.1	94.0	95.5	97.5	98.8	99.0	99.7	99.8	99.9	99.9	99.9	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS,_

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

S

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

1 30

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

ALL

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	18.0	38.0	41.0	43.5	44.5	44.9	45.3	45.6	45.6	45.8	45.8	45.8	45.8	45.8	45.8	45.0
≥ 20000	21.9	46.0	49.9	53.1	54.9	55.6	56.2	56.6		56.8		1		56.9	56.9	
≥ 18000	22.4	46.8	50.8	54 . C	55.9	56.5	57.1	57.5	57.6	57.8	57.8	57.8		. 1	57.8	57.9
≥ 16000	22.7	47.7	51.8	55.2	57.2	57.8	58.5	58.9		59.2	59.2				59.3	59.3
≥ 14000	23.8	5C - 2	54.5	58.1	60.2	60.9	61.7	62.1	62.1	62.3	62.3	62.3	62.4	62.4	62.4	62.4
≥ 12000	25.1	53.6	58.4	62.3	64.7	65.5	66.3			67.1	67.1	67.1			67.2	67.2
≥ 10000	26.0	56.2	61.4	65.8	68.4	69.3	70.3	70.9	71.0	71.2	71.2	71.2	71.3	71.3	71.3	71.3
≥ 9000	26.3	57.4	62.7	67.1	69.9	70.8	71.9	72.5	72.6	72.8	72.8	72.8	72.9	72.9	72.9	72.5
≥ 8000	27.C	59.6	65.1	69.9	72.8	73.8	75.C	75.7	75.8	76.1	76.1	76.1	76.2	76.2	76.2	
≥ 7000	27.4	60.6	66.3	71.1	74.2	75.2	76.4		77.3	77.6	77.6			77.7	77.7	
≥ 6000	27.8	61.7	67.5	72.5	75.7	76.8	78.1		79.0	79.3	79.3	79.3	79.4			
≥ 5000	28.7	63.7	69.8	74.9	78.2	79.4	80.8	81.6	81.7	82.0	82.1	82.1	82.2		82.2	82.2
≥ 4500	29.2	64.8	71.0	76.3	79.7	81.0	82.3	83.1	83.3	83.6	83.7	83.7	83.7	83.8		83.8
≥ 4000	30.7	67.8	74.2	79.7	83.3	84.6	86.0	86.9	87.0		87.5	87.5		1	87.5	87.6
≥ 3500	32.1	70.6	77.3	83.0	86.8	88.1		90.5	90.6		91.1	91.1	91.2		91.2	3
≥ 3000	33.2	73.0	79.9		89.8	91.2	92.8	93.7	93.9		94.4	94.4			94.5	94.6
≥ 2500	33.5	73.9	81.0	87.1	91.3	92.7	94.3		95.5	1		96.1	96.2	1 1	96.2	
≥ 2000	33.7	74.7	81.9	88.2	92.6	94.1	95.8	96.9	97.0	97.5	97.7	97.7	97.8		97.8	97.9
≥ 1800	33.7	74.8	82.0	88.3	92.8	94.3	96.0	97.1	97.3		98.0	98.0		98.1	98.1	98.1
≥ 1500	33.8	74.9	82.2	88.6	93.2	94.7	96.6		97.8			98.6				<u> </u>
≥ 1200	33.8	75.1	82.4	88.9	93.5	95.1	96.9	98.1	98.3	98.8	99.0	99.0	99.1	99.2	99.2	99.2
≥ 1000	33.8	75.1	82.4	89.0	93.6	95.2	97.1	98.4	98.6	99.2	99.4	99.4	99.5	99.5		نـــــــــــــــــــــــــــــــــــــ
≥ 900	33.8	75.1	82.4	89.0	93.7	95.3	97.2	98.5	98.7	99.2	99.4	99.5	99.6	99.6	99.6	99.7
≥ 800	33.8	75.1	82.5	89.0	93.7	95.3	97.3					99.5	99.7			
≥ 700	33.8	75.2	82.5	89.0	93.8		97.3						99.7	1 1		1 1
≥ 600	33.8	75.2	82.5	89.0	93.8	95.4			98.9	99.4		99.7	99.8			99.9
≥ 500	33-8	75.2	82.5	89.C	93.8	95.4	97.4	98.7	98.9	99.5	99.7	99.7	99.8	99.8	99.9	99.9
≥ 400	33.8	75.2	82.5	89.0	93.8	95.4	97.4		98.9	99.5	99.7	99.7	99.9	99.9	99.9	100.r
≥ 300	33.8	75.2	82.5	89.0	93.8	95.4			98.9			99.7	99.9	1 1	1	100.0
≥ 200	33.8	75.2	82.5	89.0	93.8	95.4	97.4	98.7	98.9	99.5	99.7	99.7	99.9	99.9	99.9	100.0
≥ 100	33.8	75.2	82.5	89.0	93.8	95.4	97.4	98.7	98.9	99.5	99.7	99.7	99.9	99.9	99.9	100.0
≥ 0	33.8	75.2	82.5	89.0	93.8	95.4	97.4	98.7	98.9	99.5	99.7	99.7	99.9	99.9	99.9	100.0
	1					, ,	•									Ţ

TOTAL NUMBER OF OBSERVATIONS_

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

leuischie!

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

-64

NUV

ALL HOURS (LST.)

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

10 14.3 16.5	≥ 6 32.8 38.0	≥ 5 36•5	≥ 4	≥ 3	≥ 2 ½		BILITY (ST	ATUTE MI	.ES)						
4.3	32.8			≥ 3	> 21/										
6.7		36.5		,	- 272	≥ 2	≥ 1 1/3	≥1¼	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
16.7	38. d	2002	40.2	42.4	43.6	44.7	45.4	45.5	45.8	45.8	45.8	45.9	45.9	45.9	45.9
- 1	30.0	42.5	47.3	50.2	51.6	52.9	53.8	53.9	54.3	54.3	54.3	54.4	54.4	54.4	54.5
	38.3	42.9	47.6	50.6	52.1	53.4	54.2	54.3	54.7	54.8	54.8	54.8	54.8	54.8	54.9
16.9	38.7	43.4	48.2	51.2	52.7	54.1	55.0	55.1	55.4	55.5	55.5	55.5	55.6	55.6	55.6
17.1	39.6	44.4	49.4	52.5	54.1	55.5	56.4	56.5	56.9	57.0	57.C	57.0	57.0	57.1	57.1
17.6	41.2	46.3	51.7	55.1	56.8	58.3	59.3	59.4	59.9	60.0	60.0	60.1	60.1	60.1	67.1
18.3	43.2	48.8	54.9	58.7	60.5	62.3	63.4	63.5	64.0	64.1	64.1	64.2	64.2	64.2	64.3
18.5	43.7	49.4	55.7	59.6	61.5	63.3	64.5	64.6	65.1	65.3	65.3	65.4	65.4	65.4	65.5
18.8	44.9	51.0	57.7	61.8	63.9	65.9	67.1	67.2	67.8	68.0	68.C	68.1	68.1	68.1	68.2
18.8	45.5	51.7	58.6	62.9	65.C	67.2	68.4	68.5	69.1	69.3	69.3	69.4	69.5	69.5	69.5
19.1	46.5	52.8	59.9	64.2	66.4	68.7	70.0	70.1	70.7	70.9	71.0	71.1	71.1	71.1	71.2
20.5	49.3	55.9	63.2	67.7	70.1	72.5	73.9	74.0	74.7	74.9	74.9	75.1	75.1	75.1	75.2
22.1	52.1	58.8	66.3	71.0	73.4	75.9	77.3	77.5	78.1	78.4	78.4	78.5	78.6	78.6	78.6
25.3	57.7	64.7	72.6	77.5	80.0	82.7	84.2	84.4	85 - 2	85.5	85.6	85.7	85.7	85.8	85 - გ
27.1	60.9	68.3	76.6	81.8	84.3	87.2	88.8	88.9	89.8	90.2	90.2	90.4	90.4	90.4	90.5
28.3	63.7	71.5	80.1	85.7	88.3	91.3	93.0	93.2	94.2	94.5	94.5	94.7	94.7	94.7	94.0
28.9	65.1	73.1	82.0	87.7	90.4	93.6	95.3	95.5	96.5	96.8	96.8	97.0	97.0	97.0	97.1
29.1	65.7	73.9	82.9	88.9	91.6	94.8	96.6	96.8	97.8	98.1	98.2	98.3	98.4	98.4	98.5
29.1	65.8	74.0	83.0	89.0	91.8	95.0	96.8	97.0	98.0	98.3	98.3	98.5	98.5	98.5	98.6
29.1	65.9	74.1	83.2	89.3			97.2			98.8	98.8	99.0	99.0	99.0	99.1
29.1	66.0	74.2	83.3	89.5	92.4	95.7	97.5	97.8	98.8	99.1	99.1	99.3	99.3	99.4	99.4
29.1	66. d	74.2	83.4	89.6	92.5	95.8	97.8	98.0	99.0	99.3	99.4	99.6	99.6	99.6	99.7
29.1	66.0	74.2	83.4	89.6	92.5	95.8	97.8	98.0	99.0	99.4	99.4	99.6	99.6	99.7	99.7
29.1	66. q	74.2	83.4	89.6	92.5	95.8	97.8	98.0	99.1	99.4	99.4	99.6	99.7	99.7	99.8
29.1	66.0	74.2	83.4	89.6	92.5	95.9	97.8	98.1	99.1	99.4	99.5	99.7	99.7	99.7	99.8
29.1	66.d	74.2	83.4	89.7	92.6	95.9			99.1	99.5	99.5	99.7	99.7	99.8	99.9
29.1	66.0	74.2	83.4	89.7			97.9		99.2	99.5			99.8	99.8	99.9
29.1	66. d	74.2	83.4	89.7	92.6	95.9	97.9	98.1	99.2	99.5	99.6	99.8	99.8	99.8	99.9
29.1	66.0	74.2	83.4												99.5
29.1	66.0	74.2	- 1												136.
29.1															
29.1	· ·													1	
	7.6 8.3 8.5 8.8 8.8 9.1 0.5 7.1 7.1 8.3 8.9 9.1 9.1 9.1 9.1 9.1 9.1 9.1 9.1 9.1	7.6 41.2 8.3 43.2 8.5 43.7 8.8 44.9 8.8 45.5 9.1 46.5 C.5 49.3 2.1 52.1 5.3 57.7 7.1 60.9 8.3 63.7 8.9 65.1 9.1 65.7 9.1 65.8 9.1 65.9 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0 9.1 66.0	7.6 41.2 46.3 8.3 43.2 48.8 8.5 43.7 49.4 8.8 44.9 51.0 8.8 45.5 51.7 9.1 46.5 52.8 C.5 49.3 55.9 2.1 52.1 58.8 5.3 57.7 64.7 7.1 60.9 68.3 8.3 63.7 71.5 8.9 65.1 73.1 9.1 65.7 73.9 9.1 65.8 74.0 9.1 65.9 74.1 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2 9.1 66.0 74.2	7.6 41.2 46.3 51.7 8.3 43.2 48.8 54.9 8.5 43.7 49.4 55.7 8.8 44.9 51.0 57.7 8.8 45.5 51.7 58.6 9.1 46.5 52.8 59.9 63.2 2.1 52.1 58.8 66.3 57.7 64.7 72.6 71.1 60.9 68.3 76.6 71.5 80.1 8.3 63.7 71.5 80.1 8.9 65.1 73.1 82.0 9.1 65.7 73.9 82.9 9.1 65.8 74.0 83.0 9.1 65.9 74.1 83.2 9.1 66.0 74.2 83.4	7.6 41.2 46.3 51.7 55.1 8.3 43.2 48.8 54.9 58.7 89.6 8.5 43.7 49.4 55.7 59.6 8.8 44.9 51.0 57.7 61.8 8.8 45.5 51.7 58.6 62.9 9.1 46.5 52.8 59.9 64.2 67.7 2.1 52.1 58.8 66.3 71.0 55.3 57.7 64.7 72.6 77.5 8.3 57.7 64.7 72.6 77.5 8.3 63.7 71.5 80.1 85.7 73.9 82.9 88.9 88.9 65.1 73.1 82.0 87.7 89.1 65.7 73.9 82.9 88.9 99.1 65.9 74.1 83.2 89.3 89.1 65.9 74.1 83.2 89.3 89.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.6 99.1 66.0 74.2 83.4 89.7	7.6 41.2 46.3 51.7 55.1 56.8 8.3 43.2 48.8 54.9 58.7 60.5 8.5 43.7 49.4 55.7 59.6 61.5 8.8 44.9 51.0 57.7 61.8 63.9 8.8 45.5 51.7 58.6 62.9 65.0 9.1 46.5 52.8 59.9 64.2 66.4 60.5 52.8 59.9 64.2 66.4 60.5 52.8 59.9 64.2 66.4 60.5 52.8 59.9 64.2 66.4 60.5 52.8 59.9 64.2 66.4 60.5 52.8 59.9 64.2 66.4 60.5 52.8 59.9 63.2 67.7 70.1 60.5 49.3 55.9 63.2 67.7 70.1 60.9 68.3 76.6 81.8 84.3 63.7 71.5 80.1 85.7 88.3 8.3 63.7 71.5 80.1 85.7 88.3 8.3 63.7 71.5 80.1 85.7 88.3 8.9 65.1 73.1 82.0 87.7 90.4 91.1 65.8 74.0 83.0 89.0 91.8 91.6 65.7 73.9 82.9 88.9 91.6 91.1 65.9 74.1 83.2 89.3 92.1 91.1 66.0 74.2 83.4 89.6 92.5 91.1 66.0 74.2 83.4 89.6 92.5 91.1 66.0 74.2 83.4 89.6 92.5 91.1 66.0 74.2 83.4 89.6 92.5 91.1 66.0 74.2 83.4 89.7 92.6	7.6 41.2 46.3 51.7 55.1 56.8 58.3 8.3 43.2 48.8 54.9 58.7 60.5 62.3 8.5 43.7 49.4 55.7 59.6 61.5 63.3 8.8 44.9 51.0 57.7 61.8 63.9 65.9 8.8 45.5 51.7 58.6 62.9 65.0 67.2 9.1 46.5 52.8 59.9 64.2 66.4 68.7 70.1 72.5 52.1 52.1 58.8 66.3 71.0 73.4 75.9 53.3 57.7 64.7 72.6 77.5 80.0 82.7 77.1 60.9 68.3 76.6 81.8 84.3 87.2 83.3 57.7 64.7 72.6 77.5 80.0 82.7 77.1 60.9 68.3 76.6 81.8 84.3 87.2 88.3 63.7 71.5 80.1 85.7 88.3 91.3 89.1 65.7 73.9 82.9 88.9 91.6 94.8 91.3 65.9 74.1 83.2 89.3 92.1 95.4 99.1 65.9 74.1 83.2 89.3 92.1 95.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 99.1 66.0 74	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 88.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 85.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 88.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 8.8 45.5 51.7 58.6 62.9 65.0 67.2 68.4 91.4 6.5 52.8 59.9 64.2 66.4 68.7 70.0 60.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 72.1 52.1 58.8 66.3 71.0 73.4 75.9 77.3 57.7 64.7 72.6 81.8 84.3 87.2 88.8 83.3 57.7 64.7 72.6 81.8 84.3 87.2 88.8 83.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 82.7 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 89.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 91.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 91.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 91.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.9 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.9 97.8 99.1 66.0 74.2 83.4 89.6 92.5 95.9 97.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 97.9 97.9 97.9 97.9 97.9 97.9	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 88.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 88.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 67.2 88.8 45.5 51.7 58.6 62.9 65.0 67.2 68.4 68.5 91.4 66.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 72.5 73.9 74.0 70.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 74.0 70.1 52.1 52.1 58.8 66.3 71.0 73.4 75.9 77.3 77.5 53.5 7.7 64.7 72.6 77.5 80.0 82.7 84.2 88.8 88.9 77.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 89.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 99.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 99.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 97.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 59.9 88.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 64.0 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 65.1 8.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 67.2 67.8 8.8 45.5 51.7 58.6 62.9 65.0 67.2 68.4 68.5 69.1 9.1 46.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 70.7 70.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 74.0 74.7 72.1 52.1 58.8 66.3 71.0 73.4 75.9 77.3 77.5 78.1 53.3 57.7 64.7 72.6 77.5 80.0 82.7 84.2 84.4 85.2 77.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 89.8 8.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 89.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 97.8 99.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 97.4 98.4 99.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 97.4 98.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.1 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.2 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.2 99.2	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 59.9 60.0 88.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 64.0 64.1 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 65.1 65.3 8.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 67.2 67.8 68.0 8.8 45.5 51.7 58.6 62.9 65.0 67.2 68.4 68.5 69.1 69.3 9.1 46.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 70.7 70.9 0.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 74.0 74.7 74.9 2.1 52.1 58.8 66.3 71.0 73.4 75.9 77.3 77.5 78.1 78.4 55.3 57.7 64.7 72.6 77.5 80.0 82.7 84.2 84.4 85.2 85.2 85.5 77.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 89.8 90.2 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 88.3 63.7 73.1 82.0 87.7 90.4 93.6 95.3 95.5 96.5 96.8 99.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 97.8 98.1 99.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 97.4 98.4 98.8 99.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 97.4 98.4 98.8 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.1 66.0 74.2 83.4 89.6 92.5 95.9 97.8 98.1 99.1 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.2 99.2 99.5 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.2 99.2 99.5 99.1 66.0 74.	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 59.9 60.0 60.0 8.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 64.0 64.1 64.1 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 65.1 65.3 65.3 8.8 44.9 51.0 57.7 61.8 63.9 65.0 67.2 68.4 68.5 69.1 69.3 69.3 99.1 46.5 51.7 58.6 62.9 65.0 67.2 68.4 68.5 69.1 69.3 69.3 99.1 46.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 70.7 70.9 71.0 0.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 74.0 74.7 74.9 74.9 74.9 2.1 52.1 58.8 66.3 71.0 73.4 75.9 77.3 77.5 78.1 78.4 78.4 55.3 57.7 64.7 72.6 77.5 80.0 82.7 84.2 84.4 85.2 85.5 85.6 71.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 89.8 90.2 90.2 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 94.5 94.5 94.5 94.5 94.5 94.5	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 59.9 60.0 60.0 60.1 8.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 64.0 64.1 64.1 64.2 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 65.1 65.3 65.3 65.4 8.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 67.2 67.8 68.0 68.0 68.1 8.8 44.9 51.7 58.6 62.9 65.0 67.2 68.4 68.5 69.1 69.3 69.3 69.4 9.1 46.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 70.7 70.9 71.0 71.1 60.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 74.0 74.7 74.9 74.9 75.1 72.1 52.1 52.1 58.8 66.3 71.0 73.4 75.9 77.3 77.5 78.1 78.4 78.4 78.5 5.3 57.7 64.7 72.6 77.5 80.0 82.7 84.2 84.4 85.2 85.5 85.6 85.7 71.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 89.8 90.2 90.2 90.4 83.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 94.5 94.7 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 94.5 94.7 88.9 65.1 73.1 82.0 87.7 90.4 93.6 95.3 95.5 96.5 96.8 96.8 97.0 99.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 97.8 98.1 98.2 98.3 98.1 99.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 97.0 98.0 98.3 98.3 98.5 99.1 65.9 74.1 83.2 89.3 92.1 95.4 97.2 97.4 98.4 98.8 98.8 99.0 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.0 99.4 99.5 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.0 99.4 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.1 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.1 99.4 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.9 97.9 98.1 99.1 99.2 99.5 99.5 99.7 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.5 99.7 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.5 99.7 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.5 99.6 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.6 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.5 99.6 99.6 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 59.9 60.0 60.0 60.1 60.1 60.1 8.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 64.0 64.1 64.1 64.2 64.2 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 65.1 65.3 65.3 65.4 65.4 8.8 44.9 51.0 57.7 61.8 63.9 65.0 67.2 68.4 68.5 69.1 69.3 69.3 69.3 69.4 69.5 91.1 46.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 70.7 70.9 71.0 71.1 71.1 71.1 52.1 52.1 52.1 58.8 66.3 67.7 70.1 72.5 73.9 74.0 74.7 74.9 74.9 75.1 75.1 75.1 52.1 52.1 58.8 66.3 77.5 80.0 82.7 84.2 84.4 85.2 85.5 85.5 85.6 85.7 85.7 71.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 89.8 90.2 90.2 90.2 90.4 90.4 83.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 94.7 94.7 88.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 94.7 94.7 99.1 65.7 73.9 82.9 88.9 91.6 94.8 96.6 96.8 97.0 98.0 98.3 98.3 98.5 98.5 99.1 65.9 74.0 83.0 89.0 91.8 95.0 96.8 97.0 98.3 98.3 98.3 98.5 98.5 99.1 65.9 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.4 99.6 99.6 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.0 99.3 99.4 99.6 99.6 99.6 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.4 99.6 99.7 99.7 99.1 66.0 74.2 83.4 89.6 92.5 95.8 97.8 98.0 99.1 99.4 99.5 99.5 99.7 99.7 99.7 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.6 99.8 99.8 99.8 99.8 69.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.6 99.6 99.8 99.8 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.6 99.6 99.8 99.8 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.6 99.6 99.8 99.8 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.6 99.6 99.8 99.8 99.8 99.1 66.0 74.2 83.4 89.7 92.6 95.9 97.9 98.1 99.2 99.6 99.6 99.8	7.6 41.2 46.3 51.7 55.1 56.8 58.3 59.3 59.4 59.9 60.0 60.0 60.1 60.1 60.1 8.3 43.2 48.8 54.9 58.7 60.5 62.3 63.4 63.5 64.0 64.1 64.1 64.2 64.2 64.2 8.5 43.7 49.4 55.7 59.6 61.5 63.3 64.5 64.6 65.1 65.3 65.3 65.4 65.4 65.4 65.4 8.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 67.2 67.8 68.0 68.0 68.0 68.1 68.1 68.1 8.8 44.9 51.0 57.7 61.8 63.9 65.9 67.1 67.2 67.8 68.0 68.0 68.0 69.3 69.4 69.5 69.5 9.1 46.5 52.8 59.9 64.2 66.4 68.7 70.0 70.1 70.7 70.9 71.0 71.1 71.1 71.1 71.1 72.5 49.3 55.9 63.2 67.7 70.1 72.5 73.9 74.0 74.7 74.9 74.9 75.1 75.1 75.1 75.1 53.3 57.7 64.7 72.6 77.5 80.0 82.7 84.2 84.4 85.2 85.5 85.6 85.7 85.7 85.8 71.1 60.9 68.3 76.6 81.8 84.3 87.2 88.8 88.9 89.8 90.2 90.2 90.4 90.4 90.4 90.4 83.3 63.7 71.5 80.1 85.7 88.3 91.3 93.0 93.2 94.2 94.5 94.5 94.5 94.7 94.7 94.7 94.7 94.7 94.7 94.7 94.7

OTAL NUMBER OF OBSERVATIONS 1368

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

DEC

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VIS	BILITY (ST.	ATUTE MIL	ES)						ļ
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ½	≥11/4	≥ 1 ,	≥ ¾	≥ 3/6	≥ ½	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	9.4 10.7	23.3 27.2	26.4 30.8	29.1 34.1	30.6 36.1	31.3 37.2	32.0 38.1	32.4 38.5	32.4 38.5	32.6 38.7	32.6 38.8	32.6 38.8	32.7 38.8	32.7 38.8	32.7 38.8	32.7 38.9
≥ 18000 ≥ 16000	10.9	27.4 27.8	31.1 31.4	34.4 34.8	36.4 36.8		38.4 38.7	38.8 39.2	38.8 39.2	39.0 39.4	39.1 39.5	39.1 39.5	39.1 39.5	39.1 39.5	39.2 39.6	
≥ 14000 ≥ 12000	11.4	28.6 29.8		35.9 37.6	38.0 39.8		40.0	40.5 42.4	40.5 42.5	40.7 42.7	40.8 42.8	40.8 42.8	40.9 42.8		40.9 42.8	40.9
≥ 10000 ≥ 9000	12.1 12.4	31.2 32.0	36.4	39.5 40.5	42.0 43.1	44.4		44.9	44.9 46 2	45.2		45.3 46.6		46.6	46.7	
≥ 8000 ≥ 7000	12.7 12.9	33.2 33.9	38.9	42.4	45.2 46.5					48.8 50.2	49.0 50.4			50.4	50.5	
≥ 6000 ≥ 5000	13.3 15.0	35.0 39.1	44.6	45.1 49.8	48.3 53.4	54.8		51.8 57.1	57.2	52.2 57.6	57.8	57.8		57.9	57.9	57.9
≥ 4500 ≥ 4000	17.4 24.1	43.7 55.7	62.4	55.2 68.5	58.9 72.6	74.3		77.1	77.2	63.3 77.6	77.8	63.5 77.8	77.9		78.0	78.ú
≥ 3500 ≥ 3000	27.5 29.2	63.1 67.4		77.2 82.8		89.8	91.9	93.0	86.5 93.1	87.0 93.7	93.9			94.1	94.2	94.2
≥ 2500 ≥ 2000 ≥ 1800	29.7 29.7	68.9 69.5	77.3 78.0	84.9 85.8	90.2	93.4	94.5 95.9		95.8 97.2	96.4 97.8	96.7 98.2		96.9 98.4	98.4		97. 98.5 98.7
≥ 1500 ≥ 1500	29.8 29.8 29.8	69.6	78.2	85.9 86.0	91.6	93.8		97.4 97.7 97.9	97.5 97.8	98.1 98.4 98.7	98.4 98.8 99.0	98.4 98.8	98.6 99.0	99.0		99.1
≥ 1000	29.8 29.8	69.7	78.3 78.4 78.4	86.1 86.2 86.2	91.8 91.9 92.0	94.1	96.5 96.7 96.7	98.1 98.1	98.0 98.2 98.3	98.9	99.3	99.3	99.5	99.5	99.6	
≥ 800	29.8	69.7		86.2 86.2	92.0	94.3		98.2	98.4 98.4	99.1	99.4	99.5	99.6 99.7		99.7	99.8
≥ 600	29.8 29.8	69.7		86.2 86.3	92.0	94.3		98.3	98.4 98.5	99.1 99.2	99.5	99.5	99.7 99.8	99.7	99.8	99.8
≥ 400	29.8	69.7	78.4		92.1	94.3	96.9	98.3	98.5	99.2	99.6	99.6	99.8	99.8	99.9	99.9
≥ 200 ≥ 100	29.8	69.7	78.4	86.3	92.1	94.3	ومهو	98.3	98.5	99.2	99.6	99.6	99.8	99.8	99.9	
≥ 0	29.8		78.4	86.3		94.3	96.9		98.5	99.2	99.6	99.6		I * .		r i

TOTAL NUMBER OF OBSERVATIONS_

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

and regard the gas for the

DATA PROCESSING WISION ETAC, USAF ASHEVILLE, N. C 28801

CEILING VERSUS VISIBILITY

0

(

FUKUGKA KYUSHU JAPAN/ITAZUKE AB

47-64

JAN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

MONTH HOURS (LST)

CEILING							VISI	BILITY (ST.	ATUFE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2		≥ 11/3	≥ 1 1/4	≥ 1	≥ ¾	≥ %		≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	7.4 7.6	23.2 24.1		28.9 30.6	30.0 32.0	30.2 32.2	30.5 32.7		30.7	30.8 33.0	30.8 33.0	30.8 33.0			31.0 33.2	31.1 33.3
≥ 18000 ≥ 16000	7.6	24.2	-	30.7	32.1 32.3	32.3	32.9 33.0	33.0 33.2	33.1 33.3	33.2	33.2 33.4	33.2 33.4	33.2	33.4 33.6	33.4 33.6	33.5
≥ 14000 ≥ 12000	7.6 8.1	24.7	28.3	31.2	32.7	32.9	33.5 34.9	33.7 35.1	33.8 35.1	33 · 8 35 · 2	33.9	33.9 35.2	33.9 35.2		34.1 35.4	34.1 35.5
≥ 10000 ≥ 9000	8.2	26.8		34.9 35.8	36.4 37.3	36.6	37.2 38.1	37.4 38.3	37.5 38.4	37.5 38.5	37.6 38.5	37.6 38.5	37.6 38.5	37.8	37.8 38.7	
≥ 8000 ≥ 7000	8.5	28.7	33.8	37.8	39.5	39.7	40.3	40.4	40.5	40 . 6	40.7	40.7	40.7	40.9	40.9	40.9
≥ 6000	8.5	29.5 30.3	35.7	39.1 40.2	40.8	42.2	41.8	43.2	43.2	42.2	42.3	42.3	43.5		43.7	43.8
≥ 5000 ≥ 4500	13.9	35.7 41.8		53.2	48.6 55.8	56.3	57.2	57.5	57.6	50 • 6 58 • 0	58.1	50.7 58.1	50.7	50.8	50.8 58.2	58.3
≥ 4000 ≥ 3500	19.5 21.1	56.2	63.1 72.0	69.1 78.6	72.2	72.9 83.0	74.0 84.1	74.3	74.4 84.5	74 • 8 84 • 9	74.9 85.0	74.9 85.0	74.9 85.0	85.2	75.0 85.2	85.2
≥ 3000 ≥ 2500	22.3	67.9	78.6	83.8	91.3	92.1	89.8 93.4	93.8	94.0	90.7	90.9	90.9	90.9	95.0	91.1	
≥ 2000 ≥ 1800	22.5	70.4	1	88.C	93.1	93.9	95.5	95.9	96.0	96.8	96.9 97.1	97.0 97.2	97.0 97.2	97.4	97.1 97.4	97.2 97.4
≥ 1500 ≥ 1200	22.5	70.7	80.3 80.4	88.6	94.0	95.4	96.9	97.1 97.5	97.3	98 • 0 98 • 4	98.1 98.6	98•2 98•6	98.2 98.6	98.8		
≥ 1000	22.5	70.7	80.4 80.4	88.9	94.5	95.7	97.3	98.0	98.1 98.1	99.0	99.1	99.2	99.2	99.3	99.3	99.4
≥ 800	22.5	70.7	80.4	88.9	94.6	95.8	97.4		98.3	99 • 1 99 • 1	99.2	99.3	99.3	99.5	99.5	99.5
≥ 600 ≥ 500	22.5	70.7	80.4 80.5	88.9	94.6	95.8 95.9	97.5		98.4	99.2	99.3 99.4	99.5	99.5			
≥ 400	22.5	70.8		89.0 89.0	94.7	95.9 95.9	97.7	98.4 98.4	98.6 98.6	99.5	99.6		99.6			
≥ 200 ≥ 100	22.5	70.8	 		94.7	95.9 95.9		98.4 98.4	98.6 98.6	99.5 99.5						
≥ 0	22.5	70.8	80.5	89.0	94.7	95.9	97.7	98.4	98.6	99.5	99.6	99.6	99.6	99.8	99.9	100.

TOTAL NUMBER OF OBSERVATIONS_

1210W5 FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

mais 8

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

ķ.

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

JAN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

3300-350

CEILING							VISI	BILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥٠	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	6.5	20.3	22.3	24.4	26.0	26.5	26.6		26.8	26.9		27.0	27.0		27.1	27.1
≥ 20000	6.5	21.4		25.9	27.6	28.1	28.3		28.4	28.6			28.6			28.1
≥ 18000	6.5	21.4	23.5	25.9	27.6	28.1	28.3		28.4	28.6		28.6	28.6	1 1	28.7	28.7
≥ 16000	_6.6	21.5		26.0		28.1	28.3		28.5			28.7	28.7	1	28.7	28.7
≥ 14000	6.6	22.0	24.1	26.5	28.4	28.9	29.1	29.3	29.3	29.4	29.5	29.5	29.5	i I	29.5	29.5
≥ 12000	6.9	23.0	25.5	28.0	30.0	30.6	30.8	30.9	30.9	31.1	31.1	31.1	31.1	31.1	31.2	31.2
≥ 10000	7.4	24.9	28.0	31.3	33.3	33.9	34.1	34.2	34.2	34.3	34.4	34.4	34.4		34.5	34.5
≥ 9000	7.5	25.3	28.6	32.1	34.2	34.7	34.9	35.1	35.1	35.2	35.2	35.2	35.2	35.2	35.3	35.3
≥ 8000	7.5	26.2	29.9	33.5	35.9	36.4	36.6	36.8	36.8	36.9	37.0	37.0	37.0	37.0	37.0	37.0
≥ 7000	7.6	26.8	30.9	34.9	37.3	37.8	38.0	38.2	38.2	38 • 4	38.4	38.4	38.4		38.5	38.5
≥ 6000	7.7	27.7	32.0	36.0	38.4	39.0	39.2	39.4	39.4	39.5	39.6	39.6	39.5	39.6	39.7	39.1
≥ 5000	10.d	33.6	38.3	42.8	45.5	46.1	46.4	46.6	46.6	46.7	46.8	46.8	46.8	46.8	46.8	46.€
≥ 4500	13.3	39.6	44.8	49.6	52.6	53.2	53.5	53.8	53.8	53.9	53.9	53.9	53.9	53.9	54.0	54.0
≥ 4000	19.2	56. Q	62.2	68.0	71.7	72.6	72.9	73.2	73.2	73.4	73.5	73.5	73.5	73.5	73.5	73.5
≥ 3500	21.6	65.0	72.2	78.7	82.8	83.8	84.4	84.7	84.7	84.9	85.0	85.0	85.0	85.0	85.1	85.1
≥ 3000	22.8	69.7	77.5	84.9	89.5	90.5	91.3	91.6	91.6	91.8	91.9	91.9	91.9	91.9	92.0	92.
≥ 2500	23.0	71.4	79.6	87.5	92.4	93.6	94.6	95.0	95.0	95.2	95.3	95.3	95.3	95.3	95.4	95.4
≥ 2000	23.2	72.2	80.7	88.8	94.0	95.5	96.7	97.2	97.3	97.6	97.7	97.7	97.7	97.7	97.7	97.7
≥ 1800	23.2	72.2	80.8	88.9	94.2	95.6	96.9	97.4	97.5	97.8	97.9	97.9	97.9	97.9	98.0	98.C
≥ 1500	23.4	72.6	81.3	89.4	94.8	96.2	97.5	98.0	98.1	98.4	98.5	98.5	98.5	98.5	98.6	98.6
≥ 1200	23.4	72.6	81.3	89.4	94.9	96.4	97.7	98.2	98.3	98.6	98.7	98.7	98.7	98.7	98.7	98.7
≥ 1000	23.4	72.6	81.3	89.5	95.d	96.5	97.8	98.3	98.4	98.7	98.8	98.8	98.8	98.8	98.9	98.9
≥ 900	23.4	72.6	81.3	89.5	95.C	96.5	97.8	98.4	98.4	98.7	98.9	98.9	98.9	98.9	98.9	99.0
≥ 800	23.4	72.6	81.3	89.5	95.d	96.5	97.8	98.4	98.4	98.7	98.9	98.9	98.9	98.9	98-9	99.0
≥ 700	23.4	72.6	81.3	89.5	95.0	96.5	97.8	98.4	98.5	98.9	99.0	99.0	99.0	99.0	99.1	99.2
≥ 600	23.4	72.7	81.4	89.5	95.2	96.6	98.0	98.6	98.7	99.1	99.2	99.2	99.2	99.2	99.3	99.3
≥ 500	23.4	72.7	81.4	89.7	95.4	96.9	98.3		99.0	99.4	99.5	99.5	99.5	99.5	99.6	99.6
≥ 400	23.4	72.7	81.4	89.7	95.4	96.9	98.3	98.9	99.0	99.5	99.6	99.6	99.6	99.6	99.6	99.7
≥ 300	23.4	72.7	81.4	89.7	95.4	96.9	98.3	98.9	99.0	99.5	99.6	99.6	99.6	99.6	99.6	99.8
≥ 200	23.4	72.7	81.4			96.9	98.3	98.9	99.0	99.5	99.6	99.6	99.6	99.6	99.8	99.9
≥ 100	23.4	72.7	81.4	89.7	95.4	96.9	98.3	98.9	99.0	99.5	99.6	99.6	99.6	99.6	99.8	99.9
≥ 0	23.4		81.4	89.7	95.4	96.9	98.3	98.9	99.0	99.5	99.6	99.6	99.6	99.6	99.8	100.0

TOTAL NUMBER OF OBSERVATIONS 1674

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-0800

CE'LING							VISI	BILITY (ST	ATUTE MIL	FS)						i
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ⅓	≥ 1 ¼ j	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	4.1		15.4 17.8	17.5	19.3	19.8	20.6		21.0	21.0	21.0	21.0	21.1	21.1	21.1	
≥ 18000	4.6	14.6	17.8	20.2	22.3	22.9	23.7		24.1	24.3	24.3	24.3	24.4		24.5	
≥ 16000	4.7	14.7	17.9	20.3	22.4	23.0	23.8		24.3	24.4	24.4	24.4	24.6	_	24.6	
≥ 14000	4.8	15.1	18.3	20.7	22.9	23.5	24.4	24.8	24.9	25.0	25.0	25.0	25.1	25.1	25.2	
≥ 12000	5.1	16.2	20.0	22.5	24.8	25.5	26.5	26.9	27.0	27.3	27.3	27.3	27.5	27.5	27.5	27.5
≥ 10000	5.5	17.3	21.1	23.9	26.4	27.2	28.2	28.7	28.8	29.1	29.1	29.1	29.3	29.3	29.3	29.3
≥ 9000	5.6	17.5	21.4	24.4	26.9	27.8	28.8	29.3	29.4	29.7	29.7	29.7	29.9	29.9	29.9	29.9
≥ 8000	5.8	18.6	23.0	26.2	29.6	29.9	30.9	31.5	31.5	31.8	31.8	31.8	32.C	32.0	32.1	32.1
≥ 7000	5.9	19.3	23.7	27.1	29.9	30.8	31.8	32.5	32.6	32.9	32.9	32.9	33.0		33.1	33.1
≥ 6000	6.2	19.8		27.8	30.9	31.8	32.8	33.6	33.6	34.1	34.1	34.1	34.2	34.2	34.3	34.3
≥ 5000	8.0			33.4		37.6	38.6		39.5		40.0	40.0			40.3	
≥ 4500	11.5	30.4	777	39.6		44.2	45.3		46.2	46.8	46.8	46.8	47.0		47.1	47.2
≥ 4000	18.6			58.8	62.8	+	65.1	66.1	66.1	66 • 7	66.7	66.7	66.9		67.0	
≥ 3500	22.2			71.6	76.3	77.6	79.0		t	81.0	81.1	81.1	81.3		81.4	
≥ 3000	23.2		70.7	77.8	83.8		87.2			89 - 6	89.8	89.8	90.1	90.1	90.1	90.3
≥ 2500 ≥ 2000	23.5			81.1	87.5	89.3	91.2		92.8	93.7	93.9	93.9	94.2	94-2	94.3	94.4
	23.6			82.4	89.2	91.3	93.2	95.0		96 - 1	96.3	96.3		96.7 97.1	96.8	
≥ 1800 ≥ 1500	23.6		74.5	82.4	89.2	91.3	93.5	95.3		96.5	96.7	96.7 97.7	97.1		98.2	
≥ 1200	23.6		74.7	82.7	90.0	91.9	94.6	96.1 96.5	96.4	98.0	98.2	98.2	98.1 98.6	98.1 98.6	98.7	98.8
≥ 1000	23.6		75.0	83.4	90.3					98.4	98.7	98.7	99.2	99.2	99.3	99.5
≥ 900	23.6	64.2	75.0	83.4	90.3	92.6	94.9	97.0	97.2	98.4	98.7	98.7	99.2	99.2	99.3	99.5
≥ 800	23.6		75.0	83.5	90.4		95.0	97.0	97.3	1	98.8	98.8		99.2	99.4	
≥ 700	23.6		75.0	83.5	90.4	92.7	95.0	97.0	97.3	98.4	98.9	98.9	99.3	99.3	99.5	
≥ 600	23.6	64.2	75.0	83.5		- 1	95.0		97.3		98.9	98.9	99.3	99.3	99.5	99.7
≥ 500	23.6	64.2	75.0	83.5	90.4	92.7	95.0	97.1	97.4	98.6	99.0	99.0	99.5	99.5	99.6	99.8
≥ 400	23.6	64.2	75.0	83.5	90.4	1	95.0	97.1	97.4		99.1	99.1	99.5	99.5	99.7	99.9
≥ 300	23.6	64.2	75.0	83.5	90.4	92.7	95.0	97.1	97.4	98.6	99.1	99.1	99.5	99.5	99.7	99.9
≥ 200	23.6	64.2	1 1		90.4	92.7	95.0	97.1	97.4	98.6	99.1	99.1	99.5	99.5	99.8	100.0
≥ 100	23.6	64.2	75.0	83.5	90.4	92.7	95.0	97.1	97.4	98.6	99.1	99.1				100.0
≥ 0	23.6	64.2	75.0	83.5	90.4	92.7	95.0	97.1	97.4	98.6	99.1	99.1	99.5	99.5	79.8	100 c

1210W5 FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

£

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/1 TAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-11CC

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)	-					
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/3	≥ 5/16	≥ ¼	≥ 0
NO CEILING	5.8					17.4									18.2	18.2
> 18000	6.9	15.4	17.3	19.5	20.8	20.8	22.2	22.6	22.6	22.6	22.6	22.6	22.7	22.7	22.7	22.1
≥ 16000	7.2				21.2	21.8		24.5	23.0			23.1	23.1	24.5	23.1	24.5
≥ 12000	7.8 8.4	17.6		22.8		25.2	26.1		26.5	26 · 8 29 · 3		26.8	26.9		26.9	26.9
0008 ≤	8.6 9.1	19.8	22.5	25.4	27.3	28.2	29.3	30.1	30.1	30.5	30.5		30.6	30.6		,
≥ 7000	9.1	21.2	24.3	28.1	30.4	31.7	33.2	34.0	34.0	34.6	34.6	34.6	34.8	34.8	34.8	34.5
≥ 6000 ≥ 5000	9.3 10.9		, – ,	28 • 8 32 • 9	-)	32.4 37.0	34.2 38.8		,	35.7 40.3	,	35.7 40.3	35.8 40.4	1	35.9 40.5	36.(40.6
≥ 4500 ≥ 4000	13.4		11	38 • 1 55 • 3		42.4	44.3 62.7		45.1	45.8		45.8	45.9 64.8	45.9 64.8	46.0	46.1
≥ 3500 ≥ 3000	27.4		1 7 7 7 7	66.2	70.4		74.6 83.8	,	75.6 85.2	76.6 86.3		76.9	77.2 86.8	77.2 86.8	77.3 87.0	77.4 87.1
≥ 2500 ≥ 2000	30.9		70.6	77.4	83.2	85.8	89.1 91.9	90.6	90.9	92.4		92.8	93.0	93.0	93.2	93.3
≥ 1800	31.1	64.2	72.4	79.6	85.7	88.4	92.1	94.0	94.3	95.)	96.4	96.4	96.7	96.7	96.9	97.6
≥ 1500 ≥ 1200	31.1		72.7 72.8		36.4	89.2	93.2	95.0 95.3	95.8	97.7	98.2	98.2	98.5	98.6		98.6
≥ 1000	$\frac{31.1}{31.1}$	64.5	72.8 72.8					95.6 95.6				98.7		99•1 99•2	99.4	99.5
≥ 800	31.1	, 	72.8 72.8			89.3		95.6 95.6			98.7 98.7	98.7 98.7	99.1			
≥ 600	31.1	,	72.8	80.0	86.5	89.3	93.4	95.6 95.6	96.1	98.1	98.7 98.8		99.1	99.2		99.6
≥ 400	31.1	64.5	72.8	80.1	86.6	89.4	93.5	95.6	96.1	98.1	98.8	98.8		99.5	99.8	99.9 100.0
≥ 300 ≥ 200	31.1	64.5		80.1	رد و	89.4	93.5	95.6 95.6	96.1	98.1	98.9	98.9	99.4	99.6	99.9	100.0
≥ 100 ≥ 0	31.1					69.4 89.4									99.9	

TOTAL NUMBER OF OBSERVATIONS...

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

BUSINESS

CEILING VERSUS VISIBILITY

FUKUC'.A KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-1400 HOURS (LST)

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/2	≥ 1 ¼	≥ 1	≥ ¾	≥ 5/0	≥ 1/3	≥ 5/16	≥ %	≥ 0
NO CEILING ≥ 20000	15.1	20.1	20.4	20.7		20.7 25.1						20.7 25.1			20.7	
≥ 18000	17.7	24.6	25.3									25.8		25.8		
≥ 16000	18.0	25.0	25.7		26.2							26.2	26.2	26.2	26.2	26.2
≥ 14000 ≥ 12000	18.6	25.9 28.1	26.7 29.0	27.1	27.2		27.2 29.6		27.2	27.2 29.6			27.2			27.2
≥ 10000	20.2	3C. 0	31.0	31.7	32.0			32.3		32.3			32.4			
≥ 9000	20.3	30.9	31.9	32.8					33.6				33.7			33.7
≥ 8000	21.0	32.8		35.1	35.6	35.7	36.2	36.2	36.2	36.3	36.3	36.3	36.3		36.3	- 1
≥ 7000	21.3	33.7	34.7						37.4			37.6	37.6			37.6
≥ 6000 ≥ 5000	21.6	34.8	35.8 39.1	37 · 3	38.0 41.6	38.2	1		38.8		L L	39.0 42.8	39.0 42.8	-	39.0 42.8	39.ú
≥ 4500	27.1	42.5		45.9	46.8				47.8	47.9			48.0			48.0
≥ 4000	38.0	58.1	60.3		(:	64.6			65.0			1	65.1
≥ 3500	45.5	69.5	72.0	74.6	76.2	76.5	77.3	77.5	77.5			78.0	78.1	78.1	78-1	78.1
≥ 3000	48.6	76.0							85.8			86.4				
≥ 2500 ≥ 2000	49.8	78.7	82.3						90.6				91.4			
≥ 1800	50.4	80.3 80.5	84.5						95.4			95.8	96.6			96.8
≥ 1500	5C-4	80.7	1	89.7											97.9	
≥ 1200	5C.4	80.7	84.9		93.3				97.1				98.3			
≥ 1000	50.4	80.7	84.9	89.8											99.0	
≥ 900	50.4	80.7		- 1					97.4					98.9		
≥ 800	50.4	80.7			93,4				97.5 97.7			98.8			99.4	
≥ 600	50.4	80.7	85.0 85.1									99.2		99.4		
≥ 500	50.4	80.7	85.1		93.7				98.0				99.5			
≥ 400	50.4	80.7							98.0			1			99.9	
≥ 300	50.4	80.7	85.1	90.0	93.7	94.5	96.5	97.8	98.0	98.6	99.3	99.5	99.6			99.9
≥ 200	50.4		85.1												99.9	
≥ 100 ≥ 0	50.4	80.7	85.1 85.1	90.0 90.0								99.5				99.9
	50.4	0V.	07.1	70.00	77.1	77.7	70.7	71.0	70.U	70.0	77.0	77.0	77.0	77.1	99.9	AUC • C

TOTAL NUMBER OF OBSERVATIONS_

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

JAN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700 HOURS (LST)

CEILING							VIS	BILITY (ST.	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1%	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	15.9	20.9	21.2	21.2	21.2	21.2	21.2	21.3	21.3	21.3	21.3	21.3	21.3	21.3	21.3	21.3
≥ 20000	19.2	25.2	25.9	26.1	26.1	26.1	26.1	26.1	26.1		26.2				26.2	
≥ 18000	19.4	25.7	26.4	26.6	26.6	26.6	26.7	26.7	26.7	26.7	26.8	26.8		1 1	26.8	26.8
≥ 16000	19.7	26.1	26.8	27.0	27.0	27.0			27.1			27.1			27.1	27.1
≥ 14000	20.6	27.4	28.2	28.4	28.5	28.5			28.6			28.6			28.6	
≥ 12000	21.3	29.3	30.1	30.4	30.5	30.5					30.7	30.7				30.7
≥ 10000	21.9		32.1	32.9	33.3	33.4	33.5		33.5		33.6	33.6			33.6	33.6
≥ 9000	22.2	31.9	32.9	33.9	34.3	34.4	34.5	34.7	34.7	34.7	34.7	34.7	34.7	34.7	34.7	34.7
≥ 8000	22.5	32.8	33.8	35.0	35.6	35.7	35.9	36.0	36.0		36.2	36.2		1 1	36.2	36.2
≥ 7000	22.8	33.5	34.8	36.0	36.9	37.0	37.2	37.4	37.4	37.5	37.7	37.7	37.7		37.7	37.7
≥ 6000	23.1	34.4	35.7	37.1	37.9	38.0	38.3	38.6	38.6	38.7	38.9	38.9			39.0	39.€
≥ 5000	24.4	37.0	38.8	40.2	41.2	41.4	41.7	42.0	42.0		42.3	42.3	42.4		42.4	42.4
≥ 4500	27.2	40.9	43.0	44.5	45.5	45.7	46.1	46.4	46.4			46.7			46.8	- 1
≥ 4000	39.0	57.6	60.5	62.4	64.0	64.1	64.6	65.1	65.1	65.2		65.5				
≥ 3500	46.1	68.7	72.1	74.2	76.4	76.8	77.6	78.3	78.3	78.5	78.8	78.8	78.9		78.9	78.9
≥ 3000	48.7	74.4	78.5	81.2	83.7	84.3	85.2	86.1	86.1	86.5	86.8	86.8				86.9
≥ 2500	49.6	77.6	82.4	85.6	88.3	88.9	89.9	91.0	91.0	91.4	91.8	91.8	l .			91.9
≥ 2000	50.0	78.6	84.1	88.0	91.1	91.8	93.3	94.6	94.6	95.0	95.5	95.5	95.6		95.6	
≥ 18C0	50.0	78.6	84.1	88.2	91.3	91.9	93.5	94.7	94.8	95.2	95.8				96.0	96.0
≥ 1500	50.0	78.8	84.5	89.1	92.3	93.0	94.6	96.2	96.3	96.8					97.8	97.8
≥ 1200	50.0	79.1	84.9	89.7	92.9	93.7	95.3	97.1	97.1	97.8	98.4	98.5				
≥ 1000	50.0	79.1	85.1	89.8		93.8				98.0					99.2	99.2
≥ 900	50.0	79.1	85.1	89.8	93.1	93.8	95.5	97.3	97.3			98.8		•		1
≥ 800	50.0	79.1	85.1	89.8	93.2	93.9	95.6	97.4		98.2					99.4	
≥ 700	50.0	79.2	85.2	90.0	93.3	94.0	95.8	97.6	ľ.	98.4			l .	1	ı	1 1
≥ 600	50.0	79.2	85.2	90.0	93.3	94.0	95.8	97.6	97.7							
≥ 500	50.0	79.2	85.2	90.0	93.4	94.1	96.0	97.8	97.8		99.4		1	1		100.0
≥ 400	50.7	79.2	85.2		93.4			97.8			99.4		<u> </u>			130.5
≥ 300	50.0	79.2	85.2	90.0	93.4	94.1	1	97.8	1	1	1	ţ.		(100.
≥ 200	50.0	79.2	85.2	90.3	93.4	94.1	96.0	97.8	97.8	98.6		·		4	ļ	100.3
≥ 100	50.0	79.2	85.2			·		97.8								100.C
1 ≥ 0	50.0	79.2	85.2	90.0	93.4	94.1	96.0	97.8	97.8	98.6	99.4	99.5	99.9	99.9	99.9	1000

TOTAL NUMBER OF OBSERVATIONS 1673

1210WS JUL 84 0-14-5 (Det 50) PREVIOUS EDITIONS OF

> 1/4/4 2.3

(

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

JAN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-2000 HOURS (LST)

CELLING						-	VISi	BILITY (STA	TUTE MILE	(S)						
CEILING (FEET)	≥ 10	_ ≥ 6	≥ 5	≥ 4	≥ 3	1		1	≥ 11/4	ĺ	- 1	≥ 3/0	≥ 1/2		≥ ¼	≥ 0
NO CEILING	4.5	15.7			24.3		25.5	25.9	26.0	26.0	26.0	26.0	26.0	26.0	26.0	26.u 29.5
≥ 20000	5.0		21.0		27.1	27.8	28.9	29.3	29.5	29.5	29.5	29.5	29.5	29.0	29.5	20 (
≥ 18000	5.0	17.3	21.0		27.2	28.0			29.6	29.6	29.6,	29.6	29.6	29.0	29.0	29.6
≥ 16000	5.0	17.4	21.3		27.6	28.3	29.4		29.9	29.9	30.0	30.0	20.0	30.0	30.0	
≥ 14000	5.1	18.0	21.9		28.3	29.2	30.4			30.9	31.0		31.0			- 1
≥ 12000	5.4	19.2	23.2	27.0		30.8				32.7	32.7		32.7		32.7	
≥ 10000	5.7	20.3	24.7	28.9	32.9	33.0	34.6		35.2	35.2	35.3	35.3				
≥ 9000	5.8	20.8	25.3	29.5	32.8	34.0	35.7		36.5	36.7	36.7	36.7		36.7	36.7	
≥ 8000	6.2	21.8	26.6	31.0	34.3	35.5	37.3		38.2	38 - 4	38.5	38.7			38.7	!
≥ 7000	6.4	22.3	27.2	31.8	<u>35.</u> 3∤	36.7	38.7		39.7	40.0		40.3				
≥ 6000	6.7	22.7	27.7	32.6	36.2	37.6	39.7	40.4	40.6	41.1	41.2	41.4			41.5	i i
≥ 5000	8.4	25.9	31.2	36.7	40.9		44.7				46.5		46.9		47.0	
≥ 4500	9.5	29.6	35.2	41.1	45.5	47.1	49.5								51.7	51.7
≥ 4000	15.8	43.1	49.8	56.6	61.5	63.6			67.3							
≥ 3500	18.9	51.7	59.4	66.6	72.0	74.6			78.8	79.4						• :
≥ 3000	20.5	56.5	65.1	73.4	79.2	82.0		86.7	86.9						88.2	
≥ 2500	20.8	59.5	69.0	78.0	83.9			91.9			92.8			_ !		1 1
≥ 2000	20.9	60.0	70.0	79.4	85.5	88.4				95.5			~			
≥ 1800	20.9	60.1	70.1	79.6	85.6	88.8				95.8	-	96.2	f .		96.7	96.7
≥ 1500	20.9	60.1	70.1	79.9	86.4	89.5	93.7			96.8		97.2				
≥ 1200	20.9	60.2	70.3	80.1	86.6	89.8	94.0	95.9		97.1	- 1		1	98.1	98.2	98.2
≥ 1000	20.9	60.3	70.5	80.4	87.1	90.3	94.5			97.8		4			99.1	
≥ 900	20.9	60.3	70.5	80.5	87.2	90.3	94.6	96.7			1		1			
≥ 800	20.9	60.3	70.6	80.5	87.3	90.4	94.7	96.8								
≥ 700	20.9	60.3	70.6	80.5	87.3	90.5	94.7	97.0				99.0	b .	1	l .	1 1
≥ 600	20.9	60.3	70.6	80.5	87.3	90.6		97.1								 -
≥ 500	20.9	60.3	70.6					97.1							I	
≥ 400	20.9	60.3	70.6	80.5	87.3	90.6			97.3					+		
≥ 300	20.9	60.3	70.6						97.3					1	1 '	99.9
≥ 200	20.9	60.3	70.6	80.5	87.3	90.6	94.8	97.1	97.3		99.0			99.8		100.
≥ 100	20.9	60.3		80.5	87.3	90.6	94.8	97.1	97.3	98.4				1	1	ico.c
≥ 0	20.9	60.3	70.6	80.5	87.3	90.6	94.8	97.1	97.3	98.4	99.0	99.3	99.8	99.8	99.9	100.C

TOTAL NUMBER OF OBSERVATIONS_

7210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF

CATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

47-64

JAN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-2300 HOURS (LST)

(FEET)	Т						*10	1011111 (31)	ATUTE MIL	.E3)						
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	5.7	19.4	23.0	26.8	29.3	30.0	30.3	30.6	30.8	30.8	3C.8	3C.8	30.8	30.8	30.8	3€.8
≥ 20000	5.9	20.8	24.7	28.8	31.5	32.4	32.9		33.4	33.5	33.5	33.5	33.5	33.5	33.5	
≥ 18000	5.9	20.8	24.7	28.8	31.5	32.4	32.9	33.2	33.4	33.5	33.5	33.5	33.5	33.5	33.5	
≥ 16000	5.9	21.0	24.9	29.1	31.8	32.7	33.2	33.5	33.7	33.8	33.8	33.8	33.8	33.8	33.8	_33.გ
≥ 14000	5.9	21.6	25.6	29.9	32.7	33.7	34.2	34.5	34.7	34.8	34.8	34.8	34.8	34.8	34.8	34.8
≥ 12000	6.3	22.8	27.1	31.7	34.4	35.4	36.0	36.3	36.5	36.5	36.5	36.5	36.5	36.5	36.5	36.5
≥ 10000	6.3	23.6	27.8	33.3	36.2	37.2	37.9	38.2	38.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5
≥ 9000	6.4	23.7	28.2	33.7	36.7	37.8	38.6	38.9	39.0	39.2	39.2	39.2	39.2	39.2	39.2	39.2
≥ 8000	6.8	24.6	29.3	35.0	38.1	39.3	40.0	40.3	40.5	40.7	40.7	40.7	40.7	40.7	4C.7	40.7
≥ 7C00	6.9	25.6	30.4	36.3	39.7	40.8	41.7	42.0	42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4
≥ 6000	7.4	26.4	31.4	38.1	41.7	42.9	43.8	44.1	44.4	44.6	44.7	44.7	44.7	44.7	44.7	44.7
≥ 5000	9.0	30.6	35.9	43.0	46.9	48 - 2	49.1	49.6	49.9	50.1	50.2	50.2	50.2	50.2	50.2	50.2
≥ 4500	11.8	37.0	42.4	49.9	54.2	55.5	56.6	57.1	57.4	57.6	57.7	57.9	57.9	57.9	57.9	57.5
≥ 4000	16.4	50.1	56.2	64.4	69.4	71.0	72.2	72.7	73.^	73.2	13.4	73.5	73.5	73.5	73.5	73.5
≥ 3500	17.8	57.9	64.6	73.7	79.2	80.9	82.1	82.7	83.0	83.1	83.3	83.4	83.4	83.4	83.4	83.4
≥ 3000	18.5	61.9	69.0	79.1	85.3	87.0	88.5		89.3	89.5	89.7	89.8	89.8	89.8	89.8	89.8
≥ 2500	18.9	64.6	72.4	83.1	89.6	91.5	93.1	93.7	94.0	94.1	94.3	94.4	94.4	94.4	94.4	94.4
≥ 2000	19.1	65.5	73.6	84.6	91.6	93.5	95.1	95.8	96.1	96.5	96.7	96.8	96.8	96.8	96.8	96.8
≥ 1800	19.2	65.5	73.7	84.8	91.8	93.7	95.3	96.1	96.4	96.8	97.1	97.2	97.2	97.2	97.2	97.2
≥ 150	19.2	65.7	74.1	85.3	92.5	94.4	96.3	97.1	97.4	97.9	98.1	98.3	98.3	98.3	98.3	98 • 3
≥ 1200	19.3	65.8	74.2	85.6	92.8	94.8	96.8	97.7	98.0	98.4	98.7	98.8	98.8	98.8	98.8	98.8
≥ 1000	19.3	65.8	74.2	85.6	92.8	95.0	97.1	98.1	98.4	98.9	99.2	99.3	99.3	99.3	99.3	99.3
≥ 900	19.3	65.8	74.2	85.8	93.0	95.2	97.3	98.3	98.6	99.1	99.3	99.5	99.5	99.5	99.5	99.5
≥ 800	19.3	65.8	74.2	85.8	93.1	95.3	97.3	98.4	98.7	99.2	99.5	99.6	99.6	99.6	99.6	99.6
≥ 700	19-3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.8	99.8	99.8	99.8
≥ 600	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	99.9
≥ 500	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	99.9
≥ 400	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	99.9
≥ 300	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	100.0
≥ 200	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	10C.C
≥ 100	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	10C-C
≥ 0	19.3	65.8	74.2	85.9	93.1	95.3	97.4	98.4	98.7	99.3	99.6	99.8	99.9	99.9	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS

CATA PROJESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0000-020

CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	6.2	26.7	30.5	33.8	35.3	35.8	36.C	36.2	36.2	36 • 2	36.2	36.2	36.2	36.3	36.3	36.4
≥ 20000	6.5	29.6	33.7	38.0	39.4	40.1	40.5	40.8	40.8	40 • 8	40.8	40.8			40.9	41.6
≥ 18000	6.5	29.8	34.3	38.6	40.1	40.7	41.2	41.4	41.4	41.4	41.4	41.4	41.4	1	41.5	41.6
≥ 16000	6.5	3C.1	34.6	38.9	40.4	41.1	41.5		41.8	41.8	41.8	41.8	41.8	41.9	41.9	41.9
≥ 14000	6.5	30.4	34.9	39.3	40.8	41.5	41.9	42.2	42.2	42 . 2	42.2	42.2	42.2	42.3	42.3	42.3
≥ 12000	6.7	31.7	36.5	41.0	42.7	43.4	43.8	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.2
≥ 10000	6.9	33.3	38.5	43.6	45.5	46.2	46 • 6	- 1	46.8	46 . 8	46.8	46.8		, ,	46.9	47.0
≥ 9000	6.9	33.7	39.1	44.3	46.2	46.9	47.3	47.6		47.6	47.6	47.6			47.7	47.7
≥ 8000	7.1	34.3	40.0	45.3	47.5	48.2	48.6	48.9	48.9	48.9	48.9	48.9		1 1	48.9	49.0
≥ 7000	7.1	34.8	40.7	46.6		49.5	50 · C		50.3	50 • 3	50.3	50.3				50.5
≥ 6000	7.3	35.8		48.0	50.3	51.1	51.8		52.1	52.1	52.1	52.1	52.1		52.2	52.3
≥ 5000	9.0	41.4	47.7	54.1	56.6	57.5	58.2		58.5	58 • 5	58.5	58.5				58.7
≥ 4500	12.1	47.9	54.5	61.1	63.9	64.8	65.6	65.9	65.9	65.9	65.9	65.9	66.0	1 1		66.1
≥ 4000	14.7	55.5	62.9	70.4	73.9	74.9			76.2	76 • 2	76.2	76.2	76.2			76.4
≥ 3500	16.2	61.5	69.7	77.8	81.5	82.6	83.6	83.9	83.9	83 - 9	83.9	83.9	84.0	1	84-1	84.1
≥ 3000	16.8	64.7	73.4	82.0	86.3	87.5	88.7	89.1	89.1	89.1	89.3	89.3	89.4			89.5
≥ 2500	17.0	67.3	76.3	85.4	89.8	91.0	92.6	93.0	93.1	93 • 2	93.3	93.3	93.5	1 -	93.6	93.6
≥ 2000	17.0	68.3	77.4	86.8	91.5	92.7	94.4	94.9	95.1	95.3	95.4	95.4				95.7
≥ 1800	17.1	69-1	78.2	87.7	92.4	93.6			96.0	96.2	96.4	96.4	t .	ŧ :	96.6	96.7
≥ 1500	17.1	69.4	78.7	88.3	93.1	94.2	96.0	96.6	96.9	97.0		97.2				97.5
≥ 1200	17.1	69.8	79.0	88.7	93.5		96.6		97.6	97.8		98.0			98.3	98.3
≥ 1000	17.1	69.9	79.1	88.8	93.6			97.9		98 • 3		98.6				99.C
≥ 900	17.1	69.9		88.8					98.2	98 • 4		98.7				99.1
≥ 800	17.1	69.9		89.1						98 • 8						99.4
≥ 700	17.1	69.9	79.2	89.1	93.8		l			98.8					99.4	99.4
≥ 600	17.1		79.2		93.8									<u> </u>	99.4	
≥ 500	17.1	69.9	79.2	89.1	93.8						1		1	1	99.5	1 1
≥ 400	17.1					95.2									99.7	99.7
≥ 300	17.1	69.9			1	1	1		l.	Į.	99.4		[1	99.7	99.8
≥ 200	17.1	69.9	79.2	89.1	93.8	95.2									·	
≥ 100	17.1			89.1	93.8	•							1	1	t	1
≥ 0	17.1	69.9	79.2	89.1	93.8	95.2	97.6	98.5	98.8	99.2	99.4	99.4	99.8	99.9	99.9	loc.ul

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-050L

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						1
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	5.1 5.6	23.6	26.2 29.4	28.3 32.2	29.0 33.3		30.4 35.0	30.7 35.3	30.7 35.3	30 · 8 35 · 3		30.8 35.3		30.8	30.9 35.5	
≥ 18000	5.7	26.5	29.9	32.8	33.9	34.6	35.6	35.9	35.9	36.0	36.0	36.0	36.0	36.C	36.1	36.2
≥ 1 ₀ C00	5.8	26.6		33.3			36.1	36.4	36.4	36.5	36.5	36.5	36.5	36.5	36.6	
≥ 14000	5.8	27.3		34.1	35.2	35.9	36.9	37.2	37.2	37.3	37.3	37.3	37.3	37.3	37.4	_
≥ 12000	6.4	29.0		36.3	37.5		39.3	39.6	39.6	39.6				39.6	39.8	
≥ 10000 ≥ 9000	6.7	30.4		38.5	39.7	40.5	41.6	41.9	41.9	42.0		42.0	42.0	42.0	42.1	42.2
	6.7	30.8		38.9			42.4		42.7	42.8			42.8	42.8	42.9	
≥ 8000 ≥ 7000	6.9	31.9		40.3			43.9	44.1	44.1	44 • 3	44.3	44.3	44.3	44.3	44.4	44.5
	6.9			41.6		44.1	45.4		45.7	45.8	45.8		45.8	47.8		
≥ 6000 ≥ 5000	7.3 8.7	33•7 38•3	38.7 43.7	43.6	45.1 50.3	46.1 51.5	47.4 52.8	47.7 53.1	47.7 53.1	47.8 53.2	47.8 53.2	47.8 53.2	47.8 53.2	53.2	48.0 53.4	
≥ 4500	10.8		49.6		56.5		59.0		59.3	59.5		59.5	59.5	59.5	59.6	
≥ 4000	14.6	55.9		68.6			73.3	73.5	73.5	73.7	73.7	73.7	73.7	73.7	73.8	
≥ 3500	16.3	61.6	69.0	76.0			81.4	81.6	81.6	81.8		81.8	81.8	81.8	81.9	
≥ 3000	17.0		- 1	80.8		85.6	87.2	87.6	87.6	87.8	-		87.9	87.9	88.C	1
≥ 2500	17.1	68.6		85.0			91.7	92.2	92.2	92.4	92.5	92.5	92.5	92.5	92.7	92.7
≥ 2000	17.1	69.8		86.8			94.2	95.1	95.1	95.6		95.7	95.7	95.7	95.8	
≥ 1800	17.1	70.0	1	87.3		92.8	94.7	95.6	95.6	96.1	96.3	96.3	96.3	96.3	96.4	96.5
≥ 1500	17.1	70.5		88.4	92.2	93.9	95.8	96.7	96.7	97.2	97.4	97.4	97.4	97.4	97.6	97.0
≥ 1200	17.1	70.7	80.5	88.5	92.4	94.0	96.0	97.0	97.0	97.4	97.6	97.6	97.6	97.6	97.8	97.9
≥ 1000	17.1	70.7	80.5	88.6	92.5	94.2	96.5	97.5	97.5	98.0	98.2	98.2	98.2	98.2	98.3	98.4
≥ 900	17.1	70.7	80.5	88.6	92.5	94.2	96.6	97.6	97.6	98.1	98.3	98.3	98.3	98.3	98.4	ر. 98
≥ 800	17.1	70.7	80.5	88.6			96.7			98.3		98.5		98.6	98.8	
≥ 700	17.1	70.7	80.5	88.6		1	96.7	97.8		98.3		98.5	98.6	98.6	98.8	
≥ 600	17.1	70.7				,	96.7					98.6		98.8		
≥ 500	17.1	70.7	80.5	88.6			96.7	97.9			98.8	98.9	99.1	99.1	99.2	
-	17.1	70.7				· · · · ·								99.2	99.4	
`≥ 300 ,≥ 200	17.1	70.7	80.5	88.6			96.8	-	98.1	98,6		1	99.4	99.4		
	17.1	70.7	7						98.1	98.7						
≥ 100	17.1	70.7							98.1 98.1	98.7 98.8				99.6		100.0
	1 1 1 • 1	70.7	80.5	88.6	76.1	94.4	96.8	98.1	70.1	70.8	77.5	77.4	34.1	77.1	77.7	<u>п ЭО • С</u>

TOTAL NUMBER OF OBSERVATIONS_

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Service and a

CATA PROCESSING DIVISION ETAC. USAF ASPEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-0800 HOURS (LST)

CEILING							VIS	IBILITY (ST	IIM ETUTA	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ½	≥11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	3.7 4.2	14.5		20.0 24.0	22.1 27.0	22.6 27.7	23.6		24.5		25.0 30.9	25.0 30.9	25.1 31.1	25.1 31.1	25.1 31.1	25.3 31.3
≥ 18000	4.3	17.5	20.6	24.4	27.5	28.2	29.7	30.7	30.8	31.3	31.4	31.4	31.6	31.6	31.6	31.8
≥ 16000 ≥ 14000	4.3 4.9	17.5 18.4	20.8	24.7		28.6 30.0		31.1	31.3	31.8	31.9	31.9	32.1	32.1	32.1 33.6	32.3 33.6
≥ 12000	5.3	19.4	23.4	27.7	31.3	32.0	33.8	35.0	35.1	35.6	35.7	35.7	35.9	35.9	35.9	
≥ 10000 ≥ 9000	5.9 6.0			30.0 30.4		34.6 35.3		38.0 38.7	38.1 38.8		38.8 39.6					39.2 40.0
≥ 8000 ≥ 7000	6.2			31.1	35.2	36.3	38.4	39.9	40.1	40 - 7	40.8	40.8	41.1	41.1	41.1	41.3
≥ 6000	6.4			32.4 33.7	36.5 37.9	37.7 39.2	41.7	41.5		42.4	44.2		44.5			42.9
≥ 5000 ≥ 4500	8.0		32.9	33.1 45.1	42.5	43.8 51.0					49.0 56.4	49.0 56.4	49.3 56.7			_
≥ 4000	15.6	44.0	52.4	58.5	63.8	65.3	68.3	70.4	70.6	71.6	71.8	71.8	72.1	72.1	72.1	72.3
≥ 3500 ≥ 3000	18.0	-	59.2	66.0	ı .	73.6 80.0	-		-				80.8 88.1			
≥ 2500 ≥ 2000	19.4		66.5 67.1	75.0 75.9			87.2	, ,			91.9 94.2	91.9 94.2	92.4			
≥ 1800	19.4	57.2		76.6				92.2	92.6	94.5	95.0	95.1	95.7	95.7	95.7	96.0
≥ 1500	19.4		68.5 68.6	77.7 77.8			91.1 91.3	93.7			96.8 97.2					
≥ 1000	19.4	58.0	68.8	78.1	85.6	87.4	91.5	94.2	94.7	96.9	97.6	97.6	98.3	98.3		
≥ 900 ≥ 800	19.4 19.4		68.8 68.8	78.2 78.2			91.7 91.7		94.9 94.9			97.8 97.9		1		1 .
≥ 700 ≥ 600	19.4	58.0 58.0	68.8 68.8	78.2 78.2	1		91.7			97 • 3 97 • 4	98.1 98.2	98.1 98.3	98.8 99.0	1		
≥ 500	19.4	58.0	68.8	78.2	85.8	87.7	91.8	94.7	95.1	97.4	98.5	98.5	99.3	99.3	99.4	99.7
≥ 400 ≥ 300	19.4			78.2 78.2	85.8 85.8		91.8				98.5 98.5					
≥ 200	19.4	58.0	68.8	78.2	85.8	87.7	91.8	94.7	95.2	97.5		98.7	99.4			
≥ 100	19.4				85.8 85.8			94.7		97.5 97.6				II .		100.11

TOTAL NUMBER OF OBSERVATIONS

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

(

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						
(FEFT)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	8.0 9.7	16.4				20.8							22.2		22.2	22.2
≥ 18000 ≥ 16000	10.0	21.8	23.8	27.2				30.8 31.5			31.4	,	31.5 32.4	1	31.5	31.5
≥ 14000 ≥ 12000	10.7 10.9		25.0 26.2	28.6 30.2	29.9 31.7	30.7 32.6		32.5 34.7	32.6 34.9	33 • 1 35 • 6	33.4 35.9			33.5 36.0	33.5 36.0	33.5 36.
≥ 10000 ≥ 9000	11.6 12.1	26.7			34.5 35.7	36.7	37.9	37.8 39.2	38.0 39.3			40.6	40.6	39.2 40.6		39.2 40.6
≥ 8000 ≥ 7000	12.3 12.3	28.8	30.8	36.7	37.2 38.5	39.7	41.1	41.0	41.1 42.8	41 · 9 43 · 6		44.1	44.1	42.4	42.4	42.4
≥ 6000 ≥ 5000	12.4 14.4	33.2	32.4 36.8	37.6 42.1	39.4 44.1	45.6	47.1	48.6	43.9 48.9		50.5	50.6	50.7	45.3 50.7	45.3 50.7	45.3
≥ 4500 ≥ 4000 ≥ 3500	18.8 25.4	51.1	43 • 3 55 • 6		51.1 64.7		68.3	70.3	56.1 70.7	71.9	57.8 72.6	72.6	72.7	57.9 72.7 81.0	57.9 72.7 81.0	57.9
≥ 3000 ≥ 3000	29.2 31.3 31.9	61-2	61.7 67.0	68.3 74.0 76.8	72.1 78.1 81.1	73.9 80.2 83.4	82.7	78.4 85.1 88.6	78.9 85.7 89.1	1	80.9 87.8 91.5	87.9	88.1	88.1 92.1	88.1 92.1	81.6 88.1 92.1
≥ 2000 ≥ 1800	31.9	63.7	70.1 70.5		82.3	84.5	87.4	90.2				93.8	94.3	94.3	94.3	95.4
≥ 1500 ≥ 1200	31.9	64.4	71.1 71.2	79.2	84.4	86.4	89.2	92.1	93.0	94.9	96.0 97.0	96.2	96.8	96.9 97.9	96.9	
≥ 1000 ≥ 900	31.9		71.4 71.4		84.5 84.5	87.0	90.0	93.1	94.0		97.4 97.4	97.5	98.3	98.5 98.5	98.5 98.5	98.5 98.5
≥ 800	31.9 31.9		71.4 71.4		84.5 84.6	87.0 87.0			94.1	96.3 96.3	97.6	97.8	98.6	98.7 98.8	98.7 98.8	98 • 8 98 • 8
≥ 600 ≥ 500 ≥ 400	31.9	64.5	71.4	79.8	84.6		90.1	93.3	94.2	96.6	98.1	98.2		99.0	99.2	99.2
≥ 400 ≥ 300 ≥ 200	31.9	64.5	71.4	79.8	84.6	87.0	90.1		94.2		98.1			99.5	99.6	99.7
≥ 100 ≥ 0	31.9 31.9 31.9	64.5		79.8	84.6	87.0	90.1	93.3 93.3 93.3	94.2	96.7		98.3	99.4	99.6	99.7	99.8

TOTAL NUMBER OF OBSERVATIONS

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUGKA KYUSHU JAPAN/I TAZUKE AB 48-64

FEB NONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140 HOURS (LST.)

CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 %	≥11/4	≥ı	≥ ¾	≥ ¾	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	17.3 22.0	23.3		24.3	24.4	24.4	24.4	24.4	24.4		24.4	24.4	_	, –	_	_
≥ 18000	22.7	31.0		32.3	32.4	32.4	32.4	32.4	32.4	32.4	32.4	32.4	32.4	32.4		32.4
≥ 16000	22.9	32.0		34.1	34.2	34.2				-	34.2		_	34.2		i
≥ 14000	24.1	34.1	35.6	36.3	36.6	36.7	36.7		36.7	36.7	36.7	36.7	36.7	36.7	36.7	36.7
≥ 12000	25.2	36.6		39.0	39.3	1						39.8		1 - I		
≥ 10000	26.Q	38.8	·	41.6	42.1	42.3	42.6	$\overline{}$	42.8		42.8	42.8				
≥ 9000	26.d	39.1	40.7	42.1	42.6			43.4	43.4							ı
≥ 8000	26.5	40.3		43.9	44.6				45.4							
≥ 7000	26.7	41.2	43.2	45.1	,	į.	46.7	46.9		47.0	, ,	47.0		47.0	47.0	47.0
≥ 6000	27.0	42.3	44.4	46.6	47.5	48.0	48.4	48.6	48.6	48.7	48.7	48.7	48.7	48.7	48.7	48.7
≥ 5000	29.3	45.7	48.1	50.3	51.4	_51.8	52.3	52.7	52.7	52.8	52.8	52.8	52.8	52.8	52.8	52.8
≥ 4500	34.0	51.9	54.4	56.7	57.8		58.9	59.3	59.3	59.4	59.5	59.5	59.5	59.5	59.5	59.5
≥ 4000	43.2			69.5		71.4	72.0	72.4		72.5	72.6	72.6		72.6	72.6	72.6
≥ 3500	48.8	71.1	1 1	77.9	(í			- 1					81.5	81.5
≥ 3000	51.8	76.0			85.7	+		88.1								
≥ 2500	52.5	77.8		- 1		89.0		- 1								
≥ 2000	52 <u>.</u> 9	78.9		87.1					93.3							
≥ 1800	52.9	79.3						93.8					94.9			
≥ 1500	52.9	79.6		88.2				94.9								
≥ 1200	52.9	79.7	,,	88.	91.2	92.4	,		95.4			,		, ,	i	
≥ 1000	52.9	79.7	·	88.4	91.3		94.3	95.5	95.6			96.9	97.2			97.5
≥ 900 ≥ 800	52.9	79.7	1	88.4	91.3	92.6					96.B					
	52.9	79.8		88.5	91.4	92.7	94.5						97.4			
≥ 700 ≥ 600	52.9	79.8	1 ' ' [88.5	- 6	92.8								97.8		
	52.9	79.8	 -	88.5	91.4						97.7	97.9		98.2		
≥ 500 ≥ 400	52.9 52.9	79.8	,		91.5						_	98.3		: L		99.2
	52.9	79.8		88.6	91.5	92.9										
≥ 300	52.9	79.8	1 1		91.5	-		96.3								
≥ 100	52.9		84.3					96.3			98.3			99.4		
≥ 100	52.9										98.5					100.0
	7607	17.0	0703	30.0	7400		37.07	7043	70.0	7100	70.0	30.0	77.47	77.00	77.0	<u> </u>

TOTAL NUMBER OF OBSERVATIONS

DATA PROCESSING LIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

8-64

FEB MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-17C(

CEILING							VISI	BILITY (ST	ATUTE MILI	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ı	≥ ¾	≥ 3/6	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	21.2	26.4 34.9	1		1	27.5	1	27.6		27.6	27.6		27.6	27.6	27.6 36.9	27.6
≥ 18000	27.4	35.2	36.2	36.8	37.3	37.3	37.4	37.4	37.4	37.4	37.4	37.4	37.4	37.4	37.4	37.4
≥ 16000 ≥ 14000	27.4		36.2	38.9			37.4 39.6		39.6	39.6	37.4		37.4 39.6	39.6	37.4 39.6	37.4
≥ 12000 ≥ 10000	30.1				43.1		43.4		43.4	43.4	43.4		i	43.4	43.4	43.4
≥ 9000	31.7		45.7	46.5	-			47.9	48.0	48.0	48.0		48.0 49.6	48.0		
≥ 7000	32.2	45.3	48.1	49.3	50.5	51.0	51.3	51.4	51.4	51.4	51.5	51.5	51.5	51.5	51.5	,
≥ 6000 ≥ 5000	32.5	48.1	51.3	53.1	54.5		52.6 55.7	56.0		52.7 56.1	56.1	52.8 56.1	52.8 56.1	56.1	56.1	56.1
≥ 4500 ≥ 4000	38.0 46.1		56.0 68.3	(1	60.3	61.0	•	74.1	61.5 74.1		61.6	61.6 74.2	61.6 74.2		61.6 74.2
≥ 3500 ≥ 3000	51.1			1	80.0 85.1	80.9 86.1	81.8 87.1	82.4 87.9		82.7 88.4			82.8 88.7	82.8 88.7	82.8 88.7	82.8 88.7
≥ 2500 ≥ 2000	54.5	78.2	. 1		87.6 89.4	1	90.2		91.3	91.7			92.0	92.0	92.0	92.1
≥ 1800 ≥ 1500	54.5	78.9	84.0	87.2	90.0		93.1	94.4	94.7	95.0	95.1		95.4 96.7	95.4	95.5 96.8	95.5 96.8
≥ 1200	54.5	79.2	84.4	87.9	90.9	92.4		95.6	95.9	96.5	96.7	96.7	97.0	97.0	97.1	97.1
≥ 1000 ≥ 900	54.5	79.2	84.5	88.0	91.1		94.5	96.0		97.0	97.2	97.2	97.6	97.6	97.8	97.9
≥ 800	54.5				91.3	92.8		96.3 96.6	96.6			97.7	98.3 98.7			98.5
≥ 600	54.5		-				95.1 95.1		97.2 97.2			98.4	99.0		99.4	99.2
≥ 400	54.5		84.5	88.2	91.4	93.1	95.1 95.1	96.9	97.2 97.2	98.3	98.6	98.6 98.7	99.4	99.4		99.7
≥ 200	54.5	79.2	84.5	88.2	91.4	93.1	95.1	96.9	97.2	98.3	98.7	98.8	99.6	99.7	99.8	99.9
≥ 100 ≥ 0	54.5	1	84.5 84.5			93.1 93.1	95.1 95.1		97.2 97.2			98.8 98.8				100.0

TOTAL NUMBER OF OBSERVATIONS

1443

1210W5 FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

. . mande and annual section is

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCIKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-200.

NO CELLING 9.7 20.8 24.3 28.6 30.8 31.7 32.7 33.1 33.2 33	CEILING							VISI	IBILITY (ST	ATUTE MIL	LES)						
≥ 20000 11.6 25.6 30.2 35.1 37.6 38.8 39.9 40.6 40.7 41.0 41.	(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/3	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
≥ 18000	NO CEILING	9.7	20.8	24.3	28.6	30.8	31.7	32.7	33.1	33.1	33.2			-		33.2	33.2
≥ 10000 11.6 26.0 30.9 35.8 38.4 39.6 40.8 41.6 41.8 42.1 43.0 43.0 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.4 43.6 46.5 47.1 47.1 47.9 48.2 48.6	≥ 20000	11.6	25.6	30.2	35.1	37.6	38.8	39.9	40-6		40.7				<u> </u>	41.0	41.0
≥ 14000	≥ 18000	11.6	25.8	30.7	35.6	38.2	39.4	40.6	41.4	41.4	41.6	41.9	41.9			41.9	41.9
≥ 12000	≥ 16000	11.6	26.0	30.9	35.8	38.4	39.6	40.8	41.6	41.6	41.8					42.1	42.1
≥ 10000	≥ 14000	11.6	26.6	31.7	36.7	39.5	40.7	42.1	42.8	42.8	43.0	43.4	43.4	43.4	43.4	43.4	43.4
≥ 9000 13.0 30.2 35.9 41.7 44.8 46.2 47.9 48.6 48.6 48.9 49.3 49.3 49.3 49.3 49.3 49.3 49.3 49	≥ 12000	12.2	28.0	33.5	38.6	41.6	42.8	44.2	45.0	45.0	45.2	45.5	45.5	45.5	45.5	45.5	45.5
≥ 8000	≥ 10000	12.8	29.6	35.3	41.0	44.1	45.4	47.1	47.9	47.9	48.2	48.6	48.6	48.6	48.6	48.6	48.6
≥ 7000	≥ 9000	13.0	30.2	35.9	41.7	44.8	46.2	47.9	48.6	48.6	48.9	49.3	49.3	49.3	49.3	49.3	
≥ 6000	≥ 8000	13.0	30.8	37.0	43.0	46.5	47.7	49.6	50.5	50.5	50.9	51.3	51.3	51.3	51.3	51.3	51.3
≥ 5000	≥ 7000	13.q	31.3	37.8	44.0	47.3	48.7	50 - 8	52.0	52.0	52.3	52.9	52.9	52.9	52.9	52.9	52.9
≥ 4500	≥ 6000	13.3	31.7	38.5	45.0	48.4	49.8	52.2	53.4	53.4	53.7	54.3	54.3	54.3	54.3	54.3	54.5
	≥ 5000	14.7	34.7	42.1	48.9	52.5	54.0	56.7	57.9	57.9	58.3	58.8	58.8	58.8	58.8	58.8	58.8
	≥ 4500	16.4	37.8	45.8	52.9	56.9	58.4	61.1	62.4	62.4	62.8	63.3	63.3	63.3	63.3	63.3	63.3
	≥ 4000	20.2	45.8	54.5	62.0	66.5	68.0	70.9	72.2	72.2	72.6	73.1	73.1	73.1	73.1	73.1	73.1
	≥ 3500	23.0	53.Q	62.3	70.5	75.2	76.8	79.9	81.3	81.4	81.8	82.4	82.4	82.4	82.4	82.4	82.4
	≥ 3000	24.1	56.2	65.6	74.6	79.8	81.4	84.8	86.3	86.3	87.1	87.9	87.9	88.1	88.1	88.1	88.1
	≥ 2500	24.3	57.8	67.5	76.7	82.1	83.9	87.7	89.4	89.5	90 . 4	91.3	91.3	91.4	91.4	91.4	91.4
$ \begin{array}{c} \geq 1800 \\ \geq 1800 \\ \geq 4.4 \\ \leq 59.2 \\ \leq 69.5 \\ \leq 69.5 \\ \leq 79.5 \\ \leq 1000 \\ \geq 4.4 \\ \leq 59.5 \\ \leq 69.9 \\ \leq 69.9 \\ \leq 69.0$	≥ 2000	24.4	58.8	69.0	78.9	84.5	86.5	90.6	92.7	92.9	94.0	94.8	94.8	94.9	94.9	94.9	94.9
	≥ 1800	24.4	59.0	69.2	79.1	85.0	87.0	91.3	93.5	93.6	94.7	95.6	95.6	95.7	95.7	95.7	95.7
	≥ 1500	24.4	59.2	69.5	79.5	85.4	87.7	92.3	94.6	94.7	95.9	96.7	96.7	97.0	97.0	97.6	97.6
	≥ 1200	24.4	59.3	69.7	79.8	86.0	88.1	92.9	95.2	95.5	96.7	97.6	97.6	97.9	97.9	97.9	97.9
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	≥ 1000	24.4	59.5	69.9	80.0	86.1	88.3	93.3	95.6	95.8	97.4	98.3	98.3	98.7	98.7	98.7	48.1
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	≥ 900	24.4	59.5	69.9	80.0	86.2	88.4	93.3	95.6	95.9	97.4	98.4	98.4	98.8	98.8	98.8	98.8
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	≥ 800	24.4	59.5	69.9	80.0	86.2	88.4	93.3	95.6	95.9	97.5	98.5	98.5	98.8	98.8	99.0	99.0
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	≥ 700	24.4	59.5	69.9	80.2	86.3	88.6	93.6	95.8	96.1	97.8	98.8	98.8	99.1	99.1	99.2	99.2
$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	≥ 600	24.4	59.5	69.9	80.2	86.3	88.6	93.6	95.8	96.1	97.8	98.8	98.8	99.2	99.2	99.3	99.3
\geq 300 24.4 59.5 69.9 80.2 86.3 88.6 93.6 96.0 96.3 98.0 99.1 99.2 99.6 99.7 9 \geq 200 24.4 59.5 69.9 80.2 86.3 88.6 93.6 96.0 96.3 98.0 99.1 99.2 99.6 99.7 9	≥ 500	24.4	59.5	69.9	80.2	86.3	88.6	93.6	95.9	96.2	97.9	99.0	99.0	99.4	99.4	99.6	99.6
\geq 200 24.4 59.5 69.9 80.2 86.3 88.6 93.6 96.0 96.3 98.0 99.1 99.2 99.6 99.7 9	≥ 400	24.4	59.5	69.9	80.2	86.3	88.6	93.6	96.0	96.3	98.0	99.1	99.1	99.5		99.7	99.7
	≥ 300	24.4	59.5	69.9	80.2	86.3	88.6	93.6	96.0	96.3	98.0	99.1	99.2	99.6	99.7	99.8	150.
	≥ 200	24.4	59.5	69.9	80.2	86.3	88.6	93.6	96.0	96.3	98.0	99.1	99.2	99.6	99.7	99.8	100.0
≥ 100 24.4 59.5 69.9 80.2 86.3 88.6 93.6 96.0 96.3 98.0 99.1 99.2 99.6 99.7 9	≥ 100	24.4	59.5	69.9	80.2	86.3	88.6	93.6	96.0	96.3	98.0			99.6	99.7	99.8	160.0
		24.4	59.5	69.9	80.2						98.0	99.1	99.2	99.6	99.7	99.8	roc.cl

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

{ I

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

FEB

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-230

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ 1/0	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	4.6				33.7				36.6	36.7		36.8		1		36.€
≥ 20000	5.1	23.4	28.6			41.0		42.2		42.3						42.4
≥ 18000	5.1		28.8	35.8				42.7	42.7	,	43.0					l í
≥ 16000	5.1	23.5	28.9	35.9				42.8		42 . 8			43.0			
≥ 14000	5.1		29.7	36.7	40.4	42.5	43.6	43.8	43.8	43.9	44.1	44.1	44.1	44.1	44.1	44.1
≥ 12000	5.3	25.7	31.7	38.9	42.7	44.8	45.9	46.1	46.1	46 • 2	46.4	46.4	46.4	46.4	46.4	46.4
≥ 10000	5.5	27.0	33.2	41.0	44.9	47.0	48.2	48.4	48.4	48.5	48.7	48.7	48.7	48.7	48.7	48.7
≥ 9000	_ 5.6	27.7	33.9	41.8	45.8	47.9	49.1	49.4	49.4	49.5	49.7	49.7	49.7	49.7	49.7	49.7
≥ 8000	5.8	28.8	35.5	43.6	47.7	50.0	51.2	51.5	51.5	51.6	51.8	51.8	51.8	51.8	51.8	51.8
≥ 7000	6.0	29.6	36.5	44.6	48.8	51.1	52.5	52.9	52.9	53.0	53.2	53.2	53.2	53.2	53.2	53.2
≥ 6000	6.2	30.6	37.8	46.2	50.6	53.0	54.5	55.0	55.0	55.1	55.3	55.3	55.3	55.3	55.3	55.3
≥ 5000	8 - 2	34.8	42.6	51.4	56.1	58.6	60.2	61.0	61.0	61.1	61.3	61.3	61.3	61.3	61.3	1.3
≥ 4500	10.5	39.7	47.8	57.3	62.2	64.7	66.5	67.2	67.2	67.4	67.6	67.6	67.6	67.6	67.6	67.6
≥ 4000	13.1	46.7	55.6	65.9	71.1	73.7	75.4	76.2	76.2	76.3	7(5	76.5	76.5	76.5	76.5	76.5
≥ 3500	15.C	52.6	62.2	72.9	78.5	81.2	83.0	83.8	83.8	83.9	84.1	84.1	84.1	84.1	84.1	84.1
≥ 3000	16.0	55.6	65.8	77.2	83.0	85.6	87.6	88.7	88.7	88.8	89.3	89.3	89.3	89.3	89.3	89.3
≥ 2500	16.1	57.2	67.8	79.2	85.2	88.1	90.3	91.5	91.5	92.1	92.5	92.5	92.5	92.5	92.5	92.5
≥ 2000	16.1	58.4	69.0	81.2	87.3	90.3	92.7	94.1	94.2	94.8	95.2	95.2	95.2	95.2	95.2	95.2
≥ 1800	16.1	58.7	69.5	81.8	88.1	91.1	93.5	94.9	94.9	95.6	96.0	96.0	96.0	96.C	96.0	96.0
≥ 1500	16.1	59.1	70.0	82.3	88.8	92.0	94.5	95.9	96.0	96.6	97.0	97.0	97.1	97.1	97.1	97.1
≥ 1200	16.1	59.3	70.2	82.7	89.3	92.5	95.2	96.7	96.8	97.7	98.1	98.1	98.2	98.2	98.2	98.2
≥ 1000	16.1	59.5	70.5	83.1	89.7	93.0	95.8	97.3	97.4	98.5	99.0	99.0	99.0	99.0	99.0	99.0
≥ 900	16.1	59.5	70.5	83.1	89.8	93.1	95.9	97.4	97.5	98.7	99.1	99.1	99.2	99.2	99.2	99.2
≥ 800	16.1	59.5	70.5	83.1	89.8	93.1	95.9	97.4	97.6	98 - 8	99.2	99.2	99.3	99.3	99.3	99.3
≥ 700	16.1	59.5	70.5	83.1	89.9	93.1	96.0	97.5	97.6	98 • 8	99.2	99.2	99.4	99.4	99.4	99.4
≥ 600	16.1	59.5	70.5	83.1	89.9	93.1	96.0	97.6	97.7	98.9	99.4	99.4	99.5	99.5	99.5	99.5
≥ 500	16.1	59.5	70.5	83.1	89.9	93.2	96.1	97.6	97.9	99.0	99.5	99.5	99.7	99.7	99.7	99.7
≥ 400	16.1	59.5	70.5	83.1	89.9	93.3	96.2	97.7	97.9	99.1	99.6	99.6	99.7	99.7	99.7	99.9
≥ 300	16.1	59.5	70.5	83.1					97.9	99.1	99.6	99.6	99.8	99.8	99.8	99.5
≥ 200	16.1	59.5	70.5	83.1	1	93.3			97.9			99.7	99.9	99.9	99.9	100.
≥ 100	16.1		70.5										99.9	99.9	99.9	100.0
≥ 0	16.1	59.5	70.5	83.1	89.9	93.3		97.7		99.2				99.9		
															<u>-</u>	·

TOTAL NUMBER OF OBSERVATIONS____

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	Γ		1	T. T	1	!	!	!							J 1	
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	211/2	≥ 1%	≥1	≥ ¾	≥ % '	≥ 1/2	≥ 5/16 '	≥ 1/4	≥ 0 `
NO CEILING	5.4	31.7	36.4	40.0	41.7	42.2	43.3	43.3	43.3	43.4	43.4	43.4	43.4	43.4	43.4	43.4
≥ 20000	5.9	35.0	40.5	44.7	46.6	47.1	48.3	48.3	48.3	48.4	48.4	48.4	48.4	48.4	48.4	48.4
≥ 18000	5.9	35.4	41.0	45.2	47.1	47.7	48 . 8	48.9	48.9	49.0	49.0	49.0	49.0	49.0	49.0	49.0
≥ 16000	5.9	35.7	41.4	45.9	47.8	48.3	49.5	49.5	49.5	49.6	49.6	49.6	49.6	49.6	49.6	49.C
≥ 14000	6.5	36.9	42.8	47.4	49.4	50.0	51.1	51.2	51.2	51.2	51.2	51.2	51.2,	51.2	51.2	51.4
≥ 12000	6.6	38.0	44.3	49.2	51.2	51.8	52.9	53.0	53.0	53.1	53.1	53.1	53.1	53.1	53.1	53.1
≥ 10000	7.0	39.6	46.1	51.2	53.5	54.1	55.2	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3
≥ 9000	7.3	40.2	46.7	51.9	54.1	54.8	<u> 56 - 0</u>	56.0	56.0	56.1	56.1	56.1	56.1	56.1	56.1	56.1
≥ 8000	7.3	41.4	48.0	53.2	55.6	56.2	57.5	57.6	57.6	57 . 7	57.7	57.7	57.7	57.7	57.7	57.7
≥ 7000	7.5		49.3	54.5	57.1	57.9	59.2	59.3	59.3	59.4	59.4	59.4	59.4	59.4	59.4	59.4
≥ 6000	7.8	43.8	50.7	56.3	59.1	60.0	i		- 1	1	61.7	61.7	. 1	61.7	61.7	61.7
≥ 5000	8.9	46.9	54.0	60.2	63.1	64.1	65.8		65.9	65.0	66.0		66.0			
≥ 4500	9.5	49.5	56.7	63.1	66.2				. 1	69.6	69.6	69.6				
≥ 4000	11.7	56.7	64.3	70.8	74.1	75.3				77.7	77.7	77.7	77.7	77.7	77.7	77.7
≥ 3500	12.8	61.5	69.5	76.5	79.9				83.7		83.9	83.9		83.9	83.9	
≥ 3000	13.5	64.6		80.5	84.2			88.0			88.2					88 - 3
≥ 2500	13.7	66.4	75.4	82.9	86.9	- 1	90.6		90.8	91.0	91.0	91.0		91.1	91.1	91.1
≥ 2000	13.7	68.4		85.6						94.5	94.6			94.7	94.7	94.7
≥ 1800	13.7	68.4	77.8	85.7	90-3					94.7	94.8	94.8	94.9	94.9	94.9	94.9
≥ 1500	13.7	68.7	78.4		91.5					96.1	96.2		96.3	96.3		
≥ 1200	13.7	68.8	1 1		91.8		1 1		96.7	97.0	97.1	97.1	97.2	97.2	97.2	97.2
≥ 1000	13.7			87.6				97.2			97.7			97.8		
≥ 900	13.7	_			92.4									98.0		
≥ 800	13.7					94.3		97.7			98.2					
≥ 700	13.7	69.3	–	i i	92.9			98.0			98.7			98.8		
≥ 600	13.7	69.3		88.2	93.0		97.7				99.1	99.1	99.2	99.2		
≥ 500 ≥ 400	13.7	69.3														
	13.7	69.3					98.1	98.9		99.6		99.7		99.9		99.9
≥ 300	13.7	69.3		88.4	93.3		1 1	i i		99.6				100.0		
	13.7	69.3			93.3	95.1		99.0						100.0		
≥ 100	13.7				_			99.0		99.6				100.0		
≥ 0	13.7	69.3	79.3	88.4	<u>93.3</u>	95.1	98.2	0.0	99.0	99.6	99.8	99.8	100.0	100.0	10C-0	H JC • L

TOTAL NUMBER OF OBSERVATIONS___

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-650

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						ļ
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 %,	≥ '%	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ %	≥ 0
NO CEILING ≥ 20000	5.4	,	33.0		37.8	38.1	38.2 43.5				38.3 43.6			38.3 43.6		38.5 43.6
≥ 18000 ≥ 16000	5.6	33.6	38.0	46	43.3	43.6	43.8	44.0	44.0	44.0	44.0	44.0	44.0	4:1.0	44.0	44.1
≥ 14000	5.6	34.0 35.7			·		45.2		45.3				45.3	45.3		45 • 3
≥ 12000	6.1	36.8		· .							49.7		49.7	49.7		49.7
≥ 10000	6.3	38.4					52.1		52.2	52.2	52.2		52.2	52.2		52.2
≥ 9000	6.5	38.6						52.6					52.6			52.6
≥ 7000	6.5	39.9 41.2						54.1 55.9	54.1		54.1		54.1 55.9		55.9	
≥ 6000	6.a	42.8						58.1	59.1	58.1	58.1		58.1		58.1	58.1
≥ 5000	7.7		54.3					64.3					64.3			
≥ 4500 ≥ 4600	8.6		57.9		1	,		68.6			1 1		68.6 76.5	1	1	1 1
≥ 3500	10.6							76.5 82.7	82.7					·		82.3
≥ 3000	12.5	1				1		86.7			87.0		_			87.0
≥ 2500	12.7	1				i 1	i e	89.3	89.4		89.8			1	1	1)
≥ 2000	12.8					91.3		93.2			93.8					94.6
≥ 1500	12.8					93.0					95.8			l :	1	
≥ 1200	12.8			87.7	92.9	94.3	96.1	96.6	96.7	97.0				ł		
≥ 1000	12.8		79.2			94.7					68.0				98.0	
≥ 900 ≥ 800	12.8	1	79.3 79.3	,	1			97.5 97.5			98.2			(98.2
≥ 700	12.8	4				·		97.5			98.4				·	
≥ 600	12.8	·			+			97.7				98.6			1	
≥ 500	12.8	1	' ' '		1	1		98.1			•		99.1			
≥ 300	12.8				93.7			98.3			99.2				· — — —	
≥ 200	12.8		1	,	1	95.8					99.7		•			99.1
≥ 1c3	12.8					95.8								99.7	l .	99.8
	<u> </u>	70.1	1 14.6	88.	93.5	95.8	41.6	48.	78.	99.4	779.1	77.	1 77.	777.	777.	H OO + CI

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/LTAZUKE AR 48-64 PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

MAK 0600-080(

i i																
CEILING	VISIBILITY (STATUTE MILES)															1
(FEET)	T	1	ī		1	1	1	1			1	1		7	7	
1120	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥11/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16 ¹	≥ 1/4	≥ 0
NO CEILING	6.6	20.3	23.5	26.9	28.7	29.3	31.0	31.8	31.9	32.1	32.3	32.5	52.7	32.8	32.8	33.
≥ 20000	7.1	23.8	28.3	32.2	34.5	35.4	37.3	38.5	38.6	39.0	39.2	39.4	39.7	39.7	39.7	39.7
18000	7.2	24.2	28.8	32.7	35.0	35.9	37.8	39.0	39.2	39.5	39.7	39.9	40.2	46.2	40.2	4(.4
≥ 16000	7.3	24.9	29.9	34.1	36.7	37.6	39.5	40.7	40.9	41.2	41.4	41.6	41.9	41.9	41.9	42.1
≥ 14000	7.6	25.6		35.5	38.3		41.3			43.1		43.5	43.7	43.8	43.8	44.0
≥ 12000	8.0	27.3			40.7			45.1	45.2			46.0		46.4		46.6
≥ 10000	8.3	28.5		39.5	43.3		46.8	48.3	48.5	1	49.3	49.5	49.8		49.8	5C.U
≥ 9000	8.3	28.7				45.3	47.6		49.3	49.8		50.3	50.6		50.7	50.9
≥ 8000	8.8		35.9	41.6	45.5	t t	49.5		51.4			52.4	52.8			53.
≥ 7000	9.0	30 . 8		42.9		48.5	51.2		53.3	53.9		54.3	54.7	54.8		55.0
≥ 6000	9.2	32.1	_	44.5	48.7	50.3	53.1	55.1	55.4			56.5	56.9			57.1
≥ 5000	10.4	35.2	41.7	48.5	52.8		57.4						61.6			
≥ 4500	11.5	- 9	44.9	51.9	56.4			63.4	63.8		1		65.5			65.8
≥ 4000	13.7	43.6		58.6	63.3		68.6		71.3				73.3			73.6
≥ 3500	15.2	48.8			69.8		75.4					- 1	80.3			
≥ 3000	16.4	52.1	60.7	69.2	74.6		80.7						86.1		86.1	86.3
≥ 2500	16.8	53.1	62.0		77.0		83.7				,		89.6		89.6	89.3
≥ 2000	16.8						87.1						93.5			93.8
≥ 1800 ≥ 1500	16.9		64.0		80.4		87.6			92.5	93.1		94.2		94.3	94.5
	17.C				81.6		89.1		92.9		94.7		95.8			96.1
≥ 1200 ≥ 1000	17.0			74.8 75.1	82.1	84.9	89.8					96.0 96.7	97.7			98.
	17.0 17.0	55.1 55.1	65.1	75.1	82.5		90.3	93.5		95.6 95.7			97.7			
≥ 900 ≥ 800	17.1	55.2			82.5		,		94.6				98.1			- , 4
≥ 700	17.1	55.2	65.3		82.7		90.6			95.1	96.9		98.3			'•-
≥ 600	17.1	55.2			82.8		90.7			- 1						9.0
≥ 500	17.1	55.2	65.4		82.9		90.9	94.4	95.4	-			99.2	99.2		
≥ 400	17.1	55.2	_		83.1	85.9	91.1		95.8			-			99.6	
≥ 300	17.1	55.2			83.0		91.1	94.8	15.9						99.7	99.9
≥ 200	17.1	55.2	1		83.0				95.9					1		
≥ 100	17.1	55.2			83.0				95.9							
] ≥ 0	17.1		65.5		_									1	99.7	

TOTAL NUMBER OF OBSERVATIONS_

CEILING VERSUS VISIBILITY

FUKUGKA KYUSHU JAPAN/ITAZUKE AB 48-64

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-110c

												,				
CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						}
(FEFT)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 %	≥ 1%	≥ 1	≥ 1/4	≥ ⅓	≥ ½	≥ 5/16	≥ ¼	≥ 0
NO CHILING	14.8	28.1	29.6	31.3	31.8	32.4	33.C	33.1	33.1	33.3	33.3	3 . 3	33.3	33.3	33.3	33.3
≥ 20000	17.3	33.6	35.7	38.0	39.2	40.2	40.9	41.3	41.4			• 6				
≥ 18000	17.4	34.1	36.2	38.5	39.9	40.9	41.6	42.0	42.1	42.3	42.3	42.3	42.3	42.3	42.3	42.3
≥ 16000	17.8	35.2	37.3	39.6		42.1	42.7		43.2			43.5			43.5	
≥ 14000	18.0	36.4	38.7	41.3		43.8	44.5		45.0	45.2	45.2	45.3	45.3		45.3	
≥ 12000	19.3	38.8	41.6	44.3	45.9	47.0	47.7	48.3	48.3	48 .5	48.5	48.6			48.6	
≥ 10000	19.5	40.5	43.5	46.5	1	49.4	50 • 2		51.0	51.3	51.5	51.6		1 1	51.6	
≥ 9000	19.5	41.4	44.4			51.0	51.8	52.4		53.1		53.4			53.5	
≥ 8000	20.3	43.3	46.4	50.0	51.9	53.2		54.8	55.1	55.6	1	55.9	1	1 1	56.0	1 1
≥ 7000	20.4	43.9	47.0		52.9	54.2		55.9		56.7		57.0		4	57.1	5/.1
≥ 6000	20.7	44.9	48.2	52.1	54.3	55.7	56.7		- }	58 • 2	58.4	58.5	,	•	59.6	1 1
≥ 5000	21.8	47.1	50.9			59.0										
≥ 4500	22.9		53.2	57.3			62.8			64.6		65.0	i	1	65.1	65.1
≥ 4000	27.0	55.7	59.9	64.4								73.2		4		
≥ 3500	29.7	60.3	64.9	69.6	72.5	74.1	75.8		1	78.8			1			1 1
≥ 3000	31.6	64.3	69.1	74.3	77.6											85.7
≥ 2500	32.5	67.4	72.4	_								90.4	1			90.6
≥ 2000	32.8	68.5	73.8	79.5	83.5							92.6				
≥ 1800	32.8	68.9	74.3	80.1		86.4			1			93.7				33.9
≥ 1500	33.0	69.5		81.2					93.2		1.	95.6		1		
≥ 1200	33.0				1 1	1		1 '	94.6	-	1 1	97.3	5	1		
≥ 1000	33.0							94.3		96.9		97.8				98.1
≥ 900	33.1		76.1		87.0			94.4		97.1	97.8	98.0	1	1	1	1
≥ 800	33.1		-					94.9		97.5						
≥ 700	33.1	l.	l .					95.1		97.8			i			1 .
≥ 600	33.1				87.5			95.6		98.3					99.5	
≥ 500	33.1		1		87.6			95.7	,	98 • 4		_	1		99.6	
≥ 400	33.1							95.8							99.7	
≥ 300	33.1	1	1	1)		l .	96.0	1	1	99.6			100.0	V	
≥ 200	33.1	70.2						96.0			99.6			100.0	·	
≥ 100	33.1	70.2	76.3	3	87.7	1					99.6			100-0	1	1 1
≥ 0	33.1	70.2	76.3	82.7	87.7	90.3	93.0	96.0	96.8	98.8	99.6	99.7	99.9	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS

CEILING \ ERSUS VISIBILITY

<u>43310 FUK</u>

FUKUUKA KYUSHU JAPAN/ITAZUKE AB

48-64

MAR

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1230-140.

CEILING							VISI	BILITY (STA	ATUTE MIL	ES)						
(FEET)	≥ 10	_ ≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%;	≥i į	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	24.5	34.5	34.8	35.6	1	36.0			36.0	1	36.0		36.0	1	36.0	
≥ 18000	28.9 29.0	42.8	42.8	44.4	44.8	44.3	44.3 45.0		44.3	44 • 3	44.3	44.3	L	44.3	44,3	
≥ 16000	29.4	43.6	44.1	45.2	45.7	45.8	45.9		45.9	45.9	45.9	45.9		45.9	45.9	45.9
≥ 14000	29.9	45.6	46.2	47.3		47.9	48.1	48.1	48.1	48.1	48.1	48.1			48.1	48.1
≥ 12000	31.3	47.9	48.8	49.8		50.5	50.7	- 1	50.8	50.8	50.8	50.8		1	5C.8	
≥ 10000	32.3	50.5	51.8	52.9	53.6	53.6	53.8		54.2	54.2	54.2	54.2	i		54.2	
≥ 9000	32.6	51.3	52.7	54.d	54.8	55.0	55.3	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	50.7
≥ 8000	33.0	52.3	53.8	55.4	56.2	56.4	56.7	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.6
≥ 7000	33.3	53.1	54.8	56.4	57.2	57.4	57.9	58.4	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5
≥ 6000	33.8	54.0	55.7	57.4	58.3	58.4	58.9	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5
≥ 5000	35.4	56.2	58.2	60.0		61.4		62.6					62.6			62.6
≥ 4500	36.6	i -	60.3	62.3	1	63.9	1	65.2	65.3		65.4	65.4	1 1	1 1))
≥ 4000	42.4			70.1	71.4						73.7					L i
≥ 3500	47.0		74.0	76.5					80.4			80.5				
≥ 3000	49.8		79.1	81.8				86.0		86.2	86.2	86.3				
≥ 2500	51.1		82.4			88.4	-	90.2	90.3		90.4		F 1			
≥ 2000	51.9		84.4	88.2			92.3		93.5		93.7	93.7		93.7	93.7	
≥ 1800	51.9	1 1	84.9	88.7	91.1	91.9	1	94.2	94.3	94.5	94.5		1 1			1 1
≥ 1500	52.1		85.6	89.6		93.1				96.2	96.2					1
≥ 1200	52.4	11	86.4	90.3	93.1	94.0			97.0	1	97.4	97.5	1 1			
≥ 1000	52.4		86.7	91.0	93.9	94.8					98.3				98.4	
≥ 900	52.4		86.9	91.3	94.2	95.1	96.6	1	,	98.7	98.7	98.8	1 .			98.8
	52.4		87.0 87.1	91.3	94.6	95.4	96.6				99.4				99.1 99.5	
≥ 700	52.4	1 "1	87.1	91.7	94.6	- 1				99.6	99.7		1 1	1	99.7	1
≥ 500	52.4		87.1	91.7	94.6			98.9		99.7	99.8					
≥ 400	52.4		87.1	91.7	94.6			99.0		99.9			100.0			
≥ 300	52.4		87.1	91.7	94.6			99.0		99.9			10.00			
≥ 200	52.4		87.1	91.7	94.6		97.1						100.0	l		
≥ 100	52.4		87.1	91.7	94.6								100.0			
≥ 0	52.4															100.0
										كبتنت						

TOTAL NUMBER OF OBSERVATIONS_____

1581

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

MAR

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700

CEILING							VISI	BILITY (ST.	AYUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/3	≥1%	≥ I	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	24.6	32.6	33.1	33.7	33.8		34.C	34.0	34.0	34.0	34.0	34.C	34.C	34.0	34.2	34.2
	30.9	42.7	43.5	44.3	44.6			44.9	44.9	44.9		44.9	44.9		45.0	
≥ 18000	31.4	43.6	44.3	45.2	45.5	45.5	45.7	45.8	45.8	45.8	45.8	45.8	45.8	, ,	45.9	45.9
≥ 1(000	31.9	44.6	45.4	46.4	46.6			46.9		46.9		46.9	46.9	L	47.1	47.1
≥ 14000	33.1	46.7	47.4	48.5	48.7	48.7	48.9	49.0	49.0	49.0	,	49.0	49.0		49.1	49.1
≥ 12000	34.3	49.3	50.2	51.5	52.0			52.4	52.4	52.4		52.4	52.4		52.5	52.5
≥ 10000	35.5	51.9	52.9	54.5	55.0	55.0	55.3	55.4	55.4	55.4		55.4	55.4		55.5	55.5
≥ 9000	35.9	52.8	53.8	55.4				56.5	56.5	56.5		56.5	56.5		56.6	
≥ 8000	36.8	54.3	55.5	57.1	57.7	57.8	58.2	58.4	58.4	58.5		58.5	58.5		58.6	58.6
≥ 7000	36.8	54.9	56.3	58.0	58.7	58.8	59.5	59.8	59.8	59.8	59.8	59.8	59.8	59.8	60.0	60
> 6000	37.3	56.0	57.4	59.2	60.0	60.1	60.8	61.0	61.0	61.1	61.1	61.1	61.1	61.1	61.2	61.4
≥ 5000	38.4	57.9	59 4	61.6	62.4	62.6	63.4	63.8	63.8	63.9	63.9	63.9	63.9	63.9	64.1	64.1
≥ 4500	40.4	60.8	62.8	64.8	65.7	65.8	66.7	67.2	67.2	67.3	67.3	67.4	67.4	67.4	67.5	67.5
≥ 4000	46.8	69.0	71.2	73.7	74.9	75.3	76.2	76.7	76.7	76.8	76.8	16.9	76.9		77.0	17.
≥ 3500	50.0	73.4	75.8	78.6	79.8	80.3	81.3	82.0	82.1	82.2	82.2	82.2	82.2	82.2	82.4	62.4
≥ 3000	52.5	77. d	79.4	82.8	84.0	84.8	86.1	87.0	87.0	87.2	87.2	87.3	87.3	87.3	87.4	87.4
≥ 2500	54.1	80.0	82.8	86.5	88.0	89.0	90.3	91.3	91.4	91.8	91.8	91.9	91.9	91.9	92.0	92.1
≥ 2000	55.d	81.8	84.7	88.9	90.7	91.7	93.0	94.2	94.2	94.8	94.8	94.9	94.9	94.9	95.0	95.5
≥ 1800	55.2	82.1	85.1	89.4	91.2	92.2	93.6	94.8	94.9	95.4	95.5	95.6	95.6	95.6	95.7	45.7
≥ 1500	55.2	82.5	85.7	90.3	92.2	93.2	94.8	96.0	96.0	96.6		96.7	96.7	96.7	96.8	96.8
≥ 1200	55.5	82.9	86.1	90.8	92.8	93.8	95.4	96.8	96.9	97.5	97.5	97.6	97.6	97.6	97.7	97.7
≥ 1000	55.5	83.1	86.4	91.1	93.2	94.2	96.0	97.4	97.5	98.0	98.1	98.2	98.2	98.2	98.3	98.3
≥ 900	55.5	83.2	86.5	91.1	93.2	94.4	96.2	97.7	97.7	98.3	98.4	98.4	98.4	98.4	98.5	98.5
≥ 800	55.5	83.2	86.5	91.1	93.2	1		97.8	97.8	98.4	98.5	98.5	98.5	98.5	98.7	98.7
≥ 700	55.5	83.2	86.5	91.2	93.3	94.5	96.3	97.8	98.0	98.5	98.6	98.7	98.7	98.7	98.8	98.8
≥ 600	55.5	83.2	86.5	91.2	93.3	94.6	96.5	I	98.5	99.2	99.3	99.4	99.4	99.4	99.5	39.5
≥ 500	55.5	83.2	86.5	91.2	93.3	94.6	96.5	98.4	98.5	99.2	99.4	99.5	99.5	99.6	99.8	99.8
≥ 400	55.5	83.2	86.5	91.2		1			98.5	99.2	1	99.5	99.5	99.6	99.8	99.0
≥ 300	55.5	83.2	86.5	91.2					98.5	99.2			99.6	99.7	99.9	99.7
≥ 200	55.5		85.5	91.2	. 1				98.5		l .		_		99.9	99.5
≥ 100	55.5		86.5						98.5	99.2		99.6				
≥ 0	55.5				93.3		96.5		1					99.7	1	
L			3000	/202												

TOTAL NUMBER OF OBSERVATIONS _____

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-2001

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	à. 1	≥ ¾	≥ ¾	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	13.1	30.2 36.3		35.7 43.3	37.1 45.1	37.8 45.8	38.2	38.5 47.1	38.7	38 . 8	_	38.9		38.9 47.7	38.9 47.7	38.4 47.7
≥ 18000	16.0	37.1	41.6		46.2	46.9	47.8	48.2	48.4	48.5	48.7	48.7			48.8	46.8
≥ 16000	16.1	37.9		45.2	47.1	47.8	48.7	49.1	49.3	49.5	49.7	49.7	49.7			49.7
≥ 14000	16.8	39.6	44.4	47.2	49.3	50.0	50.9	51.4	51.5	51.7	51.9	51.9	51.9	51.9	51.9	51.7
≥ 12000	17.1	40.8		49.1	51.4	52.2	53.2	53.6	53.8	54.1	54.3	54.3	54.3		54.3	54.3
≥ 10000	17.5	42.8		52.1	54.6	55.4	56.5	57.0	57.2	57.5	57.7	57.7	57.7		57.7	57.1
≥ 9000	17.5	43.3		53.2			57.7	58.4		59.0	59.2	59.2	59.3		59.3	59.3
≥ 8000 ≥ 7000	17.9	44.2	, ,	54.9	57.7	58.6	59.7	60.4	60.7	61 - 2	61.4	61.4	61.5		61.5	61.5
≥ 6000	18.5	44.8		56.9	58.8	59.6	62.2	61.6	61.9	63.9	62.6	64.1	64.1	62.7	62.7	62.1
≥ 5000	19.4	47.6	1	59.4	62.7	63.8	65.2		66.5	67.6	67.7	67.7		67.9		67.9
≥ 4500	20.2	49.7	56.5	62.0	65.5	66.6	68.2	+		70.7	70.8	70.8	70.9		/1.0	71.
≥ 4000	22.8	55.1	62.2	68.1	71.9	73.1	75.0	76.3	76.6	77.9	78.1	78.1	78.1	78.2	78.2	78.2
≥ 3500	24.7	58.6	66.2	72.5	76.7	77.9	79.8	81.3	81.7	83.0	83.3	83.3	83.4	83.4	83.4	83.4
≥ 3000	25.8			76.7				86.3		88.2	88.6				88.7	88.7
≥ 2500	26.5		1	79.6	84.3		88.0			91.7	92.1	92.1	92.2		92.3	92 - 3
≥ 2000	26.9			81.4	86.5			92.4		94.2		94.8	95.0		95.1	95.1
≥ 1800 ≥ 1500	26.9 27.0			82.0	87.1	88 - 4	91.3	1	93.5	94.9	95.4	- 1	95.7		1 1	95.8
≥ 1200	27.0			82.5	87.8		92.9			95.9	96.4		96.7 97.8	96.8		96.8
≥ 1000	27.0		1 1	83.2	88.7	90.1	93.3	95.4		97.3		97.8	98.2			98.2
≥ 900	27.0			83.4	88.9					97.5	98.0		98.4			98.4
≥ 800	27.0	67.4	76.1	83.5	89.0	1	93.5	95.6		97.5	98.0		98.5		98.5	98.5
≥ 700	27.0	67.4	76.1	83.6	89.1	90.5	93.7	95.8	96.3	97.7	98.2	98.3	98.7	98.7	98.7	98.7
≥ 600	27.0	67.4		83.6	89.3	90.8	94.2	96.5	96.9	98.4	98.9	99.0	99.4	99.4	99.5	99.5
≥ 500	27.0			83.6		90.8				98.5	99.0		99.4			
≥ 400	27.0		76.1	83.6	89.3			96.5		98.5	99.0		99.4			
≥ 300	27.0		1	83.6	89.3		94.2	96.5		98.6	99.1	99.2	99.6			
≥ 100	27.C			83.6 83.6	89.3 89.3			96.5 96.5		98.7 98.7	99.4				100.0 100.0	
≥ 100	27.0		1 1	83.6	89.3		94.2			98.7	99.4	1	99.9	1	100.0	
			1001	0,00	2,4,5	70.01	74.6	,,,	<u> </u>	30 - 11	7707	7907	2707	77.7	2000	<u> </u>

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-230.

CEILING							VIS	BILITY (ST.	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	= 1 1/2	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	6.6	30.9	36.6	40.1	42.8	43.3	43.8	44.0	44.1	44.2	44.2	44.2			44.2	44.2
≥ 20000	7.2			44.5	47.6	48.1	48 • 6		49.0			49.0				
≥ 18000	7.2	34.3	40.9	45.2	48.3	48.8	49.7		50.0	50.0	50.0	50.0			50.0	
≥16000	7.2	34.9	41.5	46.0		49.6			50.7	50.8	50.8	50.8				
≥ 14000	7.8	36.1	42.7	47.4		51.2	52.0	52.1	52.3	52.4	52.4	52.4			52.4	
≥ 12000	8.0	37.3	43.9	49.1	52.4	53.2	54.0	54.1	54.3	54.4	54.4	54.4		54.4	54.4	
≥ 10000	8 - 3	39.4	46.2	51.7	55.2	56.0	56.9	57.0	57.2	57.4	57.4	57.4) i	57.4	57.4
≥ 9000	8.5	40.2	47.1	52.9	56.6	57.4	58.3	58.4	58.6	58.9	58.9	58.9	58.9	58.9	58.9	
≥ 8000	8 • 7	41.2	48.2	54.1	58.2	59.1	60.0		60.3	60.5		60.5)) ;	60.5	60.5
≥ 7000	8 • 8	41.6	48.7	55.C	59.3	60.3	61.3	61.5	61.7	61.9	61.9	61.9	61.9	61.9	61.9	
≥ 6000	8.9	42.5	49.9	56.9	61.2	62.2	63.3	63.5	63.7	63.9	63.9	63.9	63.9	63.9	63.9	63.9
≥ 5000	9.9	45.5	53.3	60.5	65.5	66.4	67.6	67.9	68.1	68 • 4	68.4	68.4	68.4	68.4	68.4	68.4
≥ 4500	10.4	48.0	56.1	63.0	68.8	69.9	71.4	71.9	72.0	72.4	72.4	72.4	72.4	72.4	72.4	72.4
≥ 4000	11.8	53.1	61.5	69.6	75.1	76.3	78.0	78.6	78.8	79.1	79.1	79.1	79.1	79.1	79.1	79.1
≥ 3500	12.7	57.9	66.6	75.0	80.5	81.8	83.8	84.4	84.6	84.9	84.9	84.9	84.9	84.9	84.9	
≥ 3000	13.5	61.4	70.5	79.1	84.7	86.0	88.0	88.7	88.9	89.2	89.2	89.2	89.2	89.2	89.2	89.2
≥ 2500	13.9	63.6	72.9	81.6	87.4	88.8	91.1	91.8	92.0	92.3	92.3	92.3	92.3	92.3	92.3	92.3
≥ 2000	14.0	65.0	74.5	83.4	89.7	91.1	93.7	94.3	94.6	94.9	94.9	94.9	94.9	94.9	94.9	94.5
≥ 1000	14.0	65.3	74.8	83.7	90.0	91.5	94.1	94.8	95.0	95.4	95.4	95.4	95.4	95.4	95.4	95.4
≥ 1500	14.0	66.0	75.5	84.5	91.0	92.5	95.2	95.8	96.1	96 • 6	96.6	96.6	96.6	96.6	96.6	96.6
≥ 1200	14.0	66.1	75.7	84.8	91.3	93.1	96.1	96.8	97.0	97.6	97.6	97.6	97.6	97.6	97.6	97.6
≥ 1000	14.0	66.2	75.8	84.9	91.5	93.4	96.3	97.2	97.5	98.0	98.0	98.0	98.0	98.0	98.0	98.0
≥ 900	14.0	66.4	76.0	85.1	91.8	93.7	96.8	97.7	97.9	98.5	98.5	98.5	98.5	98.5	98.5	98.5
≥ 800	14.0	66.5	76.2	85.3	92.1	94.0	97.1	98.0	98.3	98.9	98.9	98.9	98.9	98.9	98.9	98.4
≥ 700	14.0	66.5	76.2	85.3	92.1	94.0	97.2	98.2	98.4	99.0	99.0	99.0	99.1	99.1	39.1	79.1
≥ 600	14.0	66.6	76.3	85.6	92.5	94.4	97.7	98.7	99.0	99.6	99.6	99.6	99.7	99.7	99.7	99.7
≥ 500	14.0	66.6	76.3	85.6	92.5	94.4	97.7	98.8	99.1	99.6	99.6	99.6	99.7	99.7	99.8	99.8
≥ 400	14.0	66.6	76.3	85.6	92.5	94.4	97.7	98.8	99.1	99.6	99.7	99.7	99.8	99.8	99.9	39.5
≥ 300	14.0	66.6	76.3			94.5	97.8	98.9	99.2	99.7	99.8	99.8	99.9	99.9	100.0	100.0
≥ 200	14.0	66.6	76.3	85.6	92.5	94.5	97.8	98.9	99.2	99.7	99.8	99.8	99.9	99.9	100.0	100.
≥ 100	14.0	-	76.3	85.6	92.5	94.5	97.8	98.9	99.2	99.7	99.8	99.8	99.9	99.9	100.0	LUC .
≥ 0	14.0	1		l .	1	94.5	97.8	90.9	99.2	99.7	99.8	99.8	99.9	99.9	100.0	100.
					man against the great factor of the contract o			•								

TOTAL NUMBER OF OBSERVATIONS

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING		_					VIS	BILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1%	≥1%	≥ 1 ¯	≥ ¾	≥ %	≥ ½	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	6.9 8.0	30.7 36.5	34.6 40.8	38.5 45.7	40.5	41.0 48.6	41.9 49.7	42.1	42.2	42.2 50.1	42.2 50.1	42.2 50.1	42.2 50.1	42.2 50.1	42.2 50.1	42.2 50.1
≥ 18000	8.0	36.7	41.0	45.9	48.C	48.8	49.9	50.1	50.2	50.3	50.4	50.4		50.4	50.4	50.4
≥ 16000	8.1	37.1	41.4	46.3	48.5	49.3	50.5	50.8	50.9	51.0	51.1	51.1	51.1	51.1	51.1	51.1
≥ 14000	8.2	38.3	43.1	48.4	50.7	51.6	52.7	53.1	53.1	53.3	53.3			53.3	53.3	53.3
≥ 12000	8.3	39.9		50.5	53.3			55.8	55.9		56.1			56.1		
≥ 10000 ≥ 9000	8.5	42.4	48.0 48.3	54.0 54.3	57.2 57.5	58.3 58.6	59.8	60.2	60.3 60.7	60 • 5 60 • 8	60.5		60.5 60.9	60.5		1 1
≥ 8000	9.0	43.9	49.7	55.9	59.3		62.1	62.5	62.5		62.8	62.8				
≥ 7000	9.0	45.5		58.2	61.8			65.2	65.2							1
≥ 6000	9.1	46.2	52.8	59.2	62.7	63.9	65.8	66.2	65.3	66.5	66.5	66.5	66.5			
≥ 5000	9.7	49.2				67.3	69.2			69.8						
≥ 4500 ≥ 4000	9.7 9.9			63.5	67.3		70.5		70.9				·	71.2	71.2	1 1
≥ 3500	10.5	53.1 56.0		67.0 71.0	70.8		74.3 78.8	74.8 79.3	75.0 79.5	75 • 2 79 • 7	75.3 79.8	75.3	75.3 79.8			
≥ 3000	11.2	58.5		74.6	78.8		82.9	83.7	83.8		84.1	84.1	84.1	84.1	84.1	1
≥ 2500	11.6	61.2	69.2	77.6	82.1		86.5	87.5								
≥ 2000	11.8	63.0		80.3	85.1	86.9	90.1	91.0	91.2	91.6	91.7	91.7	91.8			
≥ 1800 ≥ 1500	12.0			80.8	85.6		90.7	91.6	91.8	1	92.3	92.3	92.4	92.4		
≥ 1200	12.0	64.6		81.4	86.4		91.6	92.5	92.7	93.1	93.2	93.2	93.3			
≥ 1000	12.2			82.7			93.3	94.4	94.8		95.4	94.5	94.6	94.6		
≥ 900	12.2			83.Q	88.2		93.7	94.8	95.2		95.8	95.8	95.8			
≥ 800	12.2	65.3	74.2	83.1	88.5	90.5	94.0	95.1	95.5		96.1	96.1	96.1	96.1	96.1	96.1
≥ 700	12.2	65.4	74.3	83.4	88.8		94.5	95.6	96.0		96.6	96.6	96.7	96.7		
≥ 600	12.2			83.7	89.1	91.3		96.1		97.1	97.1	97.1	97.2			
≥ 500 ≥ 400	12.2			34.1 84.3	89.7 89.9	91.9 92.1		96.8 97.0	97.2 97.5			97.8 98.3				
≥ 300	12.2			84.4		92.4		97.3			98.3 98.8	98.9		99.1	99.1	
≥ 200	12.2		75.1	84.4	90.2			1	98.0			99.0		99.2		;
≥ 100	12.2	65.7	75.2	84.5			96.3		98.0							
≥ 0	12.2	65.7	75.2	84.5	90.3	92.5	96.3	97.5	98.0	98.8	99.C	99.0	99.3	99.3	99.7	100.5

TOTAL NUMBER OF OBSERVATIONS

CEILING VERSUS VISIBILITY

#3310 FUKUUKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

APR
NONTH
0300-050,
HOURS (LST)

				·			. – Visi	- 121 Y 1111	ATUTE MIL							
CEILING							¥131	DIEIT (31.	HIOTE MIL	£3)						1
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	6.9	30.3	33.9	37.1	39.3	39.9	40.5	40.5	40.5	40.7	40.7	4C.7	40.8	4C.8	40.8	46.0
≥ 20000	8.d	35.3	39.3		45.6	1	,	1	47.1	1		47.3		- }	47.4	_ 1
≥ 18000	8.0	35.5	39.5	43.6			47.4			47.6		47.8			47.9	
≥ 16000	8. c	35.9	39.9	44.1	46.7	47.2	- 1	48.2	48.2	48.3		48.4	4	1	48.6	48.6
≥ 14000	8.2	37.4		45.8	48.4			49.9				50.2				
≥ 12000	8.4	38.9		48.1	51.2	51.8		52.8		53.0		53.1	53.2	53.2	53.3	1
≥ 10000	8.4	41.2		50.8	54.1	54.7		55.8		55.9		56.1			56.2	
≥ 9000	8.4	41.6		51.3	54.7	55.4		56.6		56.8	56.9	56.9			57.1	57.1
≥ 8000	8.5	42.7		52.7	56.2		58.1			58.5		58.6			58.8	
≥ 7000	8.8	44.6	[55.0			60.8		61.2	61.4			61.6		· ·	
≥ 6000	8.9	46.0		57.1	60.7					64.1		64.2			64.3	
≥ 5000	9.1	48.5		60.0		64.5	ı	66.8	- 1	67.1	_	_i			67.4	67.4
≥ 4500	9.3	49.7	55.9	61.4				68.6					69.1		69.2	69.2
≥ 4000	9.5	53.1	59.3	65.0	69.2		72.5					-	73.5		73.5	73.0
≥ 3500	10.0	55.9	62.5	68.4	72.9		76.2				77.5	77.5		77.5	77.6	77.6
≥ 3000	10.9	59.3	66.5	72.5	77.5	78.4	81.2	81.9	82.0	82.4	82.5	82.5	82.5	82.5	82.6	82.€
≥ 2500	11.2	61.6	68.9	75.3	80.3	81.3	84.1	85.0		85.6				85.9	85.9	85.9
≥ 2000	11.4	62.7	71.0	77.6	82.6	83.7	86.9	87.8				88.8	89.0	89.0	89.0	89.6
≥ 1800	11.6	63.2	71.5	78.2	83.3		87.7	88.8	88.9	89.5	89.7	89.7	89.9	89.9	89.9	89.9
≥ 150C	11.6	64.0	72.5	79.5	85.0	86.5	89.7	90.8			91.9	91.9	92.0	92.0	92.1	92.1
≥ 1200	11.6	64.2	72.9	80.1	85.8	87.3	90.6	91.8	92.0	92.9	93.1	93.1	93.3	93.3	93.3	93.3
≥ 1000	11.6	64.5	73.3	80.5	86.3	87.9	91.4	92.5	92.8	93.7	93.9	93.9	94.1	94.1	94.1	94.1
≥ 900	11.6	64.5	73.4	80.6	86.5	88.1	91.6	92.	3.0	94.0	94.2	94.2	94.4	94.4	94.4	94.4
≥ 800	1.6	64.9	73.8	81.2	87.1	88.7	92.3	93.	93.7	94.8		95.0	95.2	95.2	95.2	95.2
≥ 700	11.6	64.9	73.8	81.3	87.3	89.0	92.5	93.7	94.0	95.1	95.4	95.4	95.5	95.5	95.6	95.6
≥ 600	11.6	65.0	74.1	81.8	87.9	89.5	93.2	94.4	94.6	95.8	96.0	96.0	96.1	96.1	96.2	16.2
≥ 500	11.6	65.4	74.5	82.4	88.8	90.7	94.4	95.6	95.9	97.0	97.3	97.3	97.5	97.5	97.5	97.5
≥ 400	11.6	65.4	74.6	82.5	89.0	90.8	94.6	95.8	96.0	97.2	97.5	97.5	97.6	97.6	97.7	97.7
≥ 300	11.6	65.5	74.8	82.7	89.2	91.0	94.8	96.1	96.4	97.6	97.9	97.9	98.0	98.0	98.1	98.1
≥ 200	11.6	65.5	74.8	82.7	89.2	91.0	94.9	96.3	96.7			98.2	98.3	98.3	98.4	98.4
≥ 100	11.6	65.6	74.9	82.8	89.3	91.2	95.0	96.5	96.8	98.0	98.5	98.5	98.7	98.7	99.0	79.1
≥ 0	11.6	65.6	74.9	82.8	89.3	91.2	95.0	96.5	96.8	98.0	98.5	98.5	98.7	98.7	99.0	100.

TOTAL NUMBER OF OBSERVATIONS___

1530

toricken j

CEILING VERSUS VISIBILITY

()

{ '

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-0800 HOURS (LST)

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥1%	≥1%	≥ 1	≥ ¾	≥ 3/6	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	7.2	20.7	25.2	28.4	31.0	32.5	34.4	35.1	35.2	35.9	36.1	36.1	36.1	36.2	36.3	36.3
≥ 20000	8.3	24.5	29.7	34.1	37.4		41.7	42.5		43.4	43.5	43.6	43.7	43.7	43.9	43.5
≥ 18000	8.3	24.7	29.9	34.4	37.8	39.7	42.4	43.1	43.3	44 • 1	44.2	44.2	44.4	44.4	44.6	44.5
≥ 16000	8.3	25.0	30.2	34.7	38.1	40.0	42.7	43.5	43.6		44.6	44.6	44.8			45.
≥ 14000	8 • 3	25.6	31.0	35.8	39.3		44.1	44.9	45.1	45.9	46.1	46.1	46.3	46.3	46.5	46.5
≥ 12000	8.4	27 3	33.1	38.1	41.6	43.8	46.9									49.5
≥ 10000	8.8	29.2	1	41	44.7	47.1	50.7			53.1	53.3		53.7		1 1	54
≥ 9000	9.0	29.5	<u> 36 '</u>	41.6	45.3		51.5		52.9	53.9	54.1		54.5			54.0
≥ 8000	9.0	30.9	37.0	47.4	47.5		53.7			56.1	56.4	- 1	56.8	i :	1	57.4
≥ 7000	9.1	31.9	39.0	45.C	49.2		55.5		57.3		58.5					59.3
≥ 6000	9.3	32.5	39.7	46.0	50.4	53.1	56.9	58.7	58.9	59.9	60.3	60.4	60.7	60.8	61.0	61.1
≥ 5000	<u> </u>	34.6	47.2	48.6	53.1		59.8				63.3		63.7	63.9	l	64-1
≥ 4500	10-3	35.9	43.6	50.0	54.6	57.5	61.4	63.3			65.0	65.0	65.4			65.0
≥ 4000	11.2	<u> 39.3</u>	47.5	54.1	58.9		65.8				69.7	69.7	70.1	70.2	70.4	70.5
≥ 3500	11.8	41.5	50.0	57.3	62.4	- 1	69.7				73.9		74.4		74.7	74.8
≥ 3000	12.2	43.6		60.3	65.8	69.0	73.4				78.2		78.9			79.3
≥ 2500	12.9	46.3	55.6	63.9	69.8		77.6			81.7	82.7		83.5			83.4
≥ 2000	13.5	47.9	57.5	66.1	72.3		80.4	82.8					86.9			87.3
≥ 1800	13.5	48.2		66.5	72.7	76.1	80.8	•		85.5			87.6		87.9	88.0
≥ 1500	13.6	49.0	59.4	68.2	75.0		83.1	85.8	86.3				90.7	90.8		91.1
≥ 1200	13.8	49.7	60.3	69.2	76.4		84.7	3 - 5	88.0	/			92.5		92.9	93.
≥ 1000	13.8	50.0	60.5	69.6	76.9		85.6			91.0			93.9			94.4
≥ 900	13.8	50.1	60.7	69.9	77.3	80.9	86.0		89.7	91.6		93.4	94.4	94.5	94.8	94.9
≥ 800	13.8	50.3	60.8			81.4	86.6		90.3			94.2	95.2		95.6	95.7
≥ 700	13.8	50.5	61.1	70.5	78.2	81.8	87.1	90.2	90.8			-	95.8		1	95.3
≥ 600	13.8	50.5	61.2	70.8	78.7	82.4	87.6	90.7	91.3	93.5	95.2	95.5	96.5			97.1
≥ 500	13.8	50.6	61.3	70.9		- (87.8				-	_	97.3			97.8
≥ 400	13.8	50.6				82.5										98.2
≥ 300	13.8	50.6			,	82.6	88.0		92.1	94.4					98.4	98.6
≥ 200	13.8	50.6				82.4				94.6					·	
≥ 100	13.8	50.6			,	82.6										
≥ 0	13.8	50.6	61.3	70.9	78.8	82.6	88.0	91.4	92.1	94.6	96.5	96.8	98.3	98.7	99.2	100.

TOTAL NUMBER OF OBSERVATIONS

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

APR HONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-110 HOURS (LST)

CEILING							VIS	BILITY (ST.	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	18.9	30 · 2	31.6 38.5	33.8	35.4 43.6		36.5 44.8	36.7 45.2	36.7 45.2	36.7 45.2		36.7 45.2	36.7 45.2	36.7 45.2	36.7 45.2	36.7
≥ 18000 ≥ 16000	22.2	37.7 37.9	39.7 39.9	42.8	45.1 45.4	45.8 46.1	46.5	1	46.8	46.8	. 1	46.8		1	46.8	
≥ 14000 ≥ 12000	22.7	39.1 40.9	41.0	46.9	47.0	47.9	48.6	49.0	49.0	49.2 51.9	49.2	49.2	49.2	49.2	49.2	49.2
≥ 10000 ≥ 9000	24.6	43.9	46.1	50.3	53.2 54.1	54.2	55.1 56.2	55.9	56.0 57.3	56.3	56.3	56.3	56.4	56.4	56.4 57.7	
≥ 8000 ≥ 7000	25.4	45.9	48.2	52.8	55.9	57.1	58.1	59.0	59.2	59.5	59.6	59.6	59.7	59.7	59.7	59.7
≥ 6000 ≥ 5000	25.9	47.9		55.2 58.0	58.6	60.2	61.4	62.5	62.7	63.2	63.4	63.5	63.5	63.5	63.5	63.5
≥ 4500 ≥ 4000	27.6	50.8	53.7	58.8		64.1	65.4	66.5		67.3	67.6		67.7	67.7	67.7 12.9	67.7
≥ 3500 ≥ 3000	31.2	58.6	62.0		71.7	73.4		76.1	76.3 81.4	76.9	77.2	77.3	77.3	77.3	77.3	17.3
≥ 2500 ≥ 2000	33.4	64.8	- 1	75.2	80.1	82.3	84.1	85.4	85.7	86.5	86.9	86.9	87.0	87.0	87.C	87.0
≥ 1800 ≥ 1500	34.0 34.2	67.4	72.1	78.5 79.7	83.8	86.1	88.2	89.7	89.9 91.4	90.8	91.2	91.2	91.3	91.4	91.4	
≥ 1200 ≥ 1000	34.2	68.7	74.0	80.9	86.3	88.7	91.1	92.7	92.9	94.1	94.4	94.5	94.6	94.6	94.6	
≥ 900 ≥ 800	34.4		74.7	81.9	87.4 87.6	90.1	92.7	94.4	94.6	95.8	96.2	96.3	.96.3		96.4 97.1	96.4
≥ 700 ≥ 600	34.4	69.5	75.0	82.5	88.C 88.1	90.8	93.9			97.4	97.8		98.0	98.2	98.2	98.2
≥ 500 ≥ 400	34.4	69.7	75.2	82.8	88.4	91.3	94.4	96.5	97.0	98.4	98.8	98.9	99.1	99.2	99.2	99.2
≥ 300 ≥ 200	34.4	69.8	75.3	82.9	88.4	91.4	94.6	96.9	97.4	98.9	99.5	99.5	99.7	99.9	99.9	99.9
≥ 1(≥ (34.4	69.8	75.3	82.9	88.4	91.4	94.6	96.9	97.4	98.9	99.5	99.6	99.9	100.0	100.0	10

1210WS JUL 04 0-14-5 (Det 50) PREVIOUS EDITIONS OF

CEILING VERSUS VISIBILITY

FUKUUKA KYUSHU JAPAN/1 TAZUKE AB

48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140 .

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 11/4	≥1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	25.7	32.6	33.4	34.4	34.7	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9
≥ 20000	31.d	42.7	43.8	45.1	45.6	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9
≥ 18000	32.0	44.3	45.4	46.9	47.5	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.6
≥ 16000	_33.0	45.7	46.9	48.4	49.0	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3			49.3
≥ 14000	34.4	47.8	49.1	50.8	51.4	51.7	51.8	51.9	51.9	51.9		52.0	52.0		52.0	52.
≥ 12000	35.2	49.9	51.4	53.2	53.9	54.2	54.5	54.6		54.6		54.7	54.7	54.7	54.7	54.7
≥ 10000	36.7	52.9	54.7	56.9	57.8	58.2	58.5	58.7	58.7	58 - 8	58-9	58.9	58.9	58.9	58.9	58.9
≥ 9000	37.1	53.7	55.6	57.9	58.8	59.2	59.5	59.8	59.8	59.9		60.1	60.1	60.1	60.1	5-1
≥ 8000	38.0	55.2	57.1	59.7	60.7	61.0	61.6	1	1	62.0	,	62.2	62.2		62.2	
≥ 7000	39.0	56.7	58.9	61.8	62.8	63.3	63.9	64.2		64.2	64.5	64.5	64.5	64.5	64.5	
≥ 6000	39.2	57.3	59.5	62.5			64.8	65.3				65.8			65.8	
≥ 5000	40.8	60.1	62.6	65.6	66.9	67.5	68.3				69.3		69.3			<u> </u>
≥ 4500	41.9	60.7	63.3	66.5	67.8		69.,4		. ,			70.5	70.5		70.5	: 1
≥ 4000	44.5	64.8	67.5	71.0											75.3	
≥ 3500	46.1	67.3	70.1	73.7	75.2	76.1	77.0	77.7	77.7	77.9		78.2	78.2			
≥ 3000	47.7	70.1	73.2	77.1	78.8	79.9	80.9	81.7					82.2			
≥ 2500	48.8	72.4	75.7	79.9	81.7	82.8	84.0			,		85.5		i .		
≥ 2000	50.4	75.6	79.2	83.8	85.8	86.9	88.3	89.3				89.9				
≥ 1800	50.7	70.6	80.2	84.9	86.9	88.1	89.7	90.7				91.3		(•	
≥ 1500	51.2	78.2	81.8	86.7	88.8	89.9		93.0				93.9				
≥ 1200	51.4	79.2	83.3	88.3	90.5	92.0	93.9	95.2				96.1	96.1	96.2		
≥ 1000	51.4	79.7	83.9	89.0	91.2	92.7	94.8	96.1				97.1	97.2			
≥ 900	51.4	79.9	84.0	89.3	_		95.1	,						1		١ ١
≥ 800	51.4	79.9	84.1	89.4	91.6	93.3	95.4	96.7		97.3		97.8				
≥ 700	51.4	80.0	84.2										98.3	1	-	ì
≥ 600	51.4	8/ . 0	84.2	89.5	91.8	93.6	95.9		97.6			98.6				
≥ 500	51.4	80.0	84.2	89.6	92.0								,	i		
≥ 400	51.4	80-0	84.2	R4 . 7					98.4							
≥ 300	51.4	80.0	84.2	89.7	92.1	94.0		98.2						99.9		
≥ 200	51.4	8C.0	84.2	84.7					98.5	99.3	99.9	99.9	99.9	100-0	moc.o	Luca.
≥ 100	51.4	80.0	84.2	89.7	92.1	940	96.5	98.2	98.5	99.3	99.9					100.0
≥ 0	51.4	80.0	84.2	89.7	92.1	94.0	96.5	98.2	98.5	99.3	99.9	99.9	99.9	00°0	10C • 0	150.

TOTAL NUMBER OF OBSERVATIONS ...

CEILING VERSUS VISIBILITY

FUKUGKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700 HOURS (LST)

CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						i
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ % '	≥ 1/2	≥ 5/16	≥ 1/4	. ≥ 0
NO CEILING	24.8	32.7		34.1	34.1	34.1	34.1			34.1	,	34.1	34.1	34-1	-	34 . i
≥ 20000	3C.9	43.1	44.3	45.4	45.5	45.5	45.5	45.5	45.5			45.5	45.5	45.5	+	45.0
≥ 18000	31.3	44.6	45.9	47.0	47.1	47.1	47.1	47.1	47.1,	47.1	47.1	47.1	47.1		47.1	1
≥ 16000	32.5	46.5	47.8	48.9	49-0	49.0	49.0	49.0	49.0	49.0	49.0	49.0	49.0		49.0	49.
≥ 14000	33.5	48.3	50.0	51.2		51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4		51.4	51.4
> 12000	34.2	50.1	51.8	53.5	53.8	53.9	54.1	54.1	54.1	54.1	54-1	54.1	54.1	54.1	54.1	54.1
≥ 10000	35.9	52.9	54.8	56.7	57.1	57.3	57.5	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6
≥ 9000	36.3	53.9	56.1	58.1	58.6	58.8	59.1	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.4
≥ 8000	37.3	55.6	58.0	60.2	60.8	61.2	61.8	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.
≥ 7000	38.0	57.1	59.6	61.9	62.5	62.9	63.5	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
≥ 6000	38.5	58.0	60.7	63.2	63.8	64.2	65.0	65.2	65.2	65 . 2	65.2	65.2	65.2	65.2	65.2	65.2
≥ 5000	40.5	60.9	63.7	66.3	67.2	67.8	68.5	68.8	68.8	69.0	69.0	69.0	69.0	69.0	69.0	69.L
≥ 4500	41.1	62.1	64.9	67.6	68.6	69.3	70.0	70.4	70.4	70.6	70.7	70.7	70.7	70.7	70.7	70.7
≥ 4000	44.6	66.5	69.4	72.7	73.9	74.6	75.4	75.8	75.8	76.1	76.1	76.1	76.1	76.1	76.1	76.1
≥ 3500	46.1	69.5	72.7	76.4	77.5	78.3	79.2	79.7	79.7	79.9	80.0	80.0	80.0	80.0	80.C	8C.
≥ 3000	47.8	72.2	75.5	79.5	81.1	82.0	82.9	83.9	83.9	84.4	84.4	84.4	84.4	84.4	84.4	84.4
≥ 2500	48.8	74.2	78.0	82.5	84.3	85.2	86.2	87.3	87.3	87.8	87.8	87.8	87.8	87.8	87.8	87.5
≥ 2000	49.5	76.3	80.2	85 • C	87.2	88.1	89.2	90.3	90.3	90.9	91.0	91.0	91.0	91.0	91.0	91.
≥ 1800	49.9	76.9	80.8	85.8	88.0	89.0	90.2	91.3	91.3	91.9	92.0	92.0	92.0	92.0	92.0	92.0
≥ 1500	50.0	77.6	81.6	86.7	89.3	90.6	91.9	93.3	93.5	94.4	94.5	94.5	94.5	94.5	94.5	94.5
≥ 1200	50.0	78.1	82.4	87.6	90.2	91.8	93.2	94.8	95.0	95.9	96.0	96.0	96.0	96.0	96.0	96.0
≥ 1000	50.0	78.3	82.6	87.8	90.5	92.2	93.7	95.3	95.5	96.5	96.6	96.6	96.6	96.6	96.6	96.6
≥ 900	50.0	78.4	82.9	88.2	90.8	92.6	94.1	95.7	95.9	96.9	97.1	97.1	97.1	97.1	97.1	97.1
j ≥ 800	50.0	78.5	83.0	8° 5	91.1	92.9	94.5	96.2	96.4	97.5	97.6	97.6	97.6	97.6	97.6	97.6
≥ 700	50.0	78.6	83.1	86	91.2	93.2	94.8	96.5	96.7	97.8	97.9	98.0	98.0	98.0	98.0	98.0
≥ 600	50.0	78.6	83.1	86.6	91.4	93.5	95.2	96.9	97.2	98 - 3	98.4	98.5	98.6	98.6	98.6	38.6
≥ 500	50.G	78.6	83.1	88.6	91.5	93.7	95.4	97.5	97.8	99.0	99.2	99.2	99.3	99.3	99.3	39.3
≥ 400	50.0	78.6	83.1	88.6	91.5	93.7			98.0	99.3	99.6	99.7	99.8	99.8	99.8	99.8
≥ 300	50.C	78.6	83.1	88.6	91.5	93.7	95.5	97.7	98.1	99.5	99.7	99.8	99.9	99.9	39.9	99.9
≥ 200	50.0	78.6		88.6	91.5	93.7	95.5	97.7	98.2	99.5	99.8	99.9	100.0	100.0	100.0	100.6
≥ 100	50.0			88.6	91.5	93.7	95.5	97.7	98.2	99.5	99.8	99.9	100.0	10C.O	100.0	100.0
≥ 0	50.0	ı		88.6	1	93.7	95.5		98.2	99.5	99.8	99.9	100.0	100.0	hoo.o	LOC.

CEILING VERSUS VISIBILITY

ķ,

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-200_

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 %	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ 1/4	> 1/6	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	14.2	28.4	30.8	32.4	33.8	34.4	34.5	34.5	34.6	34.7	34.7	34.7	34.7	34.8	34.8	34.8
≥ 20000	17.1	35.8	39.5		44.7	45.6		46.1	46.2			46.6			46.7	46.1
≥ 18000	17.3	36.5	40.7	43.5	46.3		47.5	47.7	47.8	48 • 0	48.2	48.2	48.2	48.3	48.3	48.3
≥ 16000	17.3	37.2	41.8	44.8	47.8	:	-	49.3		49.6	49.7	+				49.9
≥ 14000	18.9	38.6	43.5	47.C	50.5		52.2	52.5		52.9			53.1	53.2	53.2	53.2
≥ 12000	18.1	39.3	44.6								55.8					
≥ 10000	18.4	41.7	47.8	52.0	56.3			59.3	,	60.5		60.7	60.8	1 - :		60 · c
≥ 9000	18.5		48.6			59.0					61.8		61.9		62.0	
≥ 8000	19.0	43.2	50.3		59.4					63.9	1			1 1	- !	
≥ 7000	19.3								65.5			67.0				
≥ 6000	19.5	- 1	53.1	58.4	63.1	1		67.0			68.6			68.8		68.0
≥ 5000	20.2					67.6								71.8		
≥ 4500	20.6		55.6						71.2	-			73.0			73.1
≥ 4000	21.4													77.5		
≥ 3500	22.2	52.7							78.6					: 1		
≥ 3000	22.9													84.3		
≥ 2500 ≥ 2000	23.5								85.4		87.3				87.7	
ļ 	23.7													90.3		
≥ 1800 ≥ 1500	23.7							88.2						91.0		
<u> </u>	23.7													92.9		
≥ 1200 ≥ 1000	23.9				83.1			91.1		93 • 5					94.6	
	24.0													36.C		
≥ 900 ≥ 800	24.0				84.7				93.1			95.7				
-	24.0				85.3									97.0		
≥ 700 ≥ 600	24-0								94.2					97.6		
		60.3							94.7							
≥ 500 ≥ 400	24.0				85.7				95.4			98.2			99.0	
≥ 300	24.0		70.1	78.2										99.4		
≥ 300	24.0													99.8		
≥ 100														99.9		
≥ 100		60.3														
	24.0	65.3		10.2	02.8	07.5	76.2	72.4	7.2.9	70 06	77.	77.6	77.1	99.9	27.7	<u> </u>

121OWS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-230(

CEILING							VISI	BILITY (STA	ATUTE :AIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	> 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ %	≥ ⅓ '	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	7.5	28.8		38.6	40.5	41.6	42.4		42.5	42.5	42.5	42.5		42.5	42.5	
≥ 18000	8.4	33.4 34.0		46.5	48.1 48.8	49.4 50.2	50 · 1	50.3	50.3	50.5	50.5	50.5	50.5 51.3	50.5	50.5	51.3
≥ 16000 ≥ 14000	8.4	34.5 35.2		47.2	49.6 50.9	51.0 52.5	51.7	51.9 53.5	51.9	52.1	52.1	52.1 53.7	52.1	52.1 53.7	52.1 53.7	52.1
≥ 12000	8.6	36.1	43.1	50.4	53.3	55.0	55.9	56.1	56.1	56.3	56.3	56.3	56.3	56.3	56.3	
≥ 10000 ≥ 9000	9.0 9.0	38.4 38.6	45.9 46.0	53.6 53.7	57.1 57.5	58.9 59.3	60.1 60.8	60.5	61.1	61.2 61.8	61.8	61.2	61.2	61.2	61.9	61.7
≥ 8000 ≥ 7000	9.9	39.9 41.2		55.6 57.8	59.7 62.0	61.6	63.1	63.4	63.4	64.1	64.1	64.1	64.2	64.2 66.5	64.2	64.2
≥ 6000 ≥ 5000	10.5	42.4	50.9	59.4	63.7	65.6	67.1	67.6	67.6	68.4	68.4	68.4	68.4	68.4	68.4	68.4
≥ 4500	10.8 11.4	46.3	55.2	64.4	67.4	71.0	71.0	71.6	71.6	73.9	72.3	72.3	72.4	74.0	74.0	74.0
≥ 4000 ≥ 3500	12.0	49.1 51.6	58.5 61.5	68.0 71.2	72.9 76.5	75.0 78.6	76.7 80.5	77.3 81.3	77.4	78 • 2 82 • 4	78.2 82.4	78.2 82.4	78.3 82.4	78.3 82.4	78.3 82.4	
≥ 3000	12.5	53.8 55.9		73.9 76.4	79.4 82.1	81.6	83.5 86.3	84.5	84.6	85 - 8	85.8	85.8	85.8 88.6	85.8	88.6	
≥ 2000	13.1	57.3	67.8	78.4	84.3	86.6	89.5	90.7	90.8	91.9	91.9	91.9	92.0	92.0	92.0	92.0
≥ 1800 ≥ 1500	13.1	57.6 57.8	1	78.8 79.5	84.7 85.4	87.0 87.6	89.9 90.7	91.0 91.8	91.2 92.0	92.3 93.1	92.3 93.1	92.3 93.1	92.4 93.4	92.4 93.4	92.4	92.4 93.4
≥ 1200 ≥ 1000	13.3	58.5 59.3	69.3 70.1	80.5 81.6	86.5 87.6	89.0 90.2	92.0	93.2	93.3		94.6	94.6	94.9	94.9	94.9	
≥ 900 ≥ 800	13.3	59.3	70.1	81.6	87.7	90.3	93.5	94.6	94.8	96.1	96.1	96.1 96.5	96.5	96.5	96.5	96.5
≥ 700	13.3	59.5	70.4	82.C	88.2	90.8	94.1	95.3	95.4	96.8	96.8	96.8	97.1	97.1	97.1	97.1
≥ 600 ≥ 500	13.4							95.8 96.7	95.9 96.9		97.3 98.4	97.3 98.4	97.6 98.7	97.6 98.7	97.6 98.7	97.6
≥ 400	13.4			83.0 83.1	89.6 89.7	92.6 92.7	95.9 96.1	97.5			98.8	98.8	99.2	99.2		
≥ 200	13.4	60.1	71.2	83.1	89.7	92.7	96.1	97.5	97.6	99.2	99.3	99.3	99.7	99.7	99.7	99.1
≥ 100 ≥ 0	13.4		71.2	83.1 83.1	89.7 89.7			97.5	97.6 97.6				99.7 99.7	99.8 99.8	-	

TOTAL NUMBER OF OBSERVATIONS_

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0000-J20 HOURS (LST)

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	_≥ 6	≥ 5	≥4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 ⅓,	≥1%	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	4.4	29.5		39.1	41.2	41.6	42.2	1	42.4	· - i	42.5	,	42.6	1	42.7	1
-	4.9	33.9	41.4	46.7		49.7	50.4	50.7	50.7		50.9	50.9			51.0	
≥ 18000	4.9	34.2		47.0	1	50.1	51.0	51.2	51.3	51.4	51.4	51.4		1	51.6	51.6
	4.9 5.C	34 · 8	42.5	47.8	50.4	50.9	51.8 53.8	52.0 54.1	52.1	54.5	54.5	54.5	54.6	54.7	52.4	54.7
≥ 14000 ≥ 12000	5.3	38.7	47.0	52.9		1	57.6	57.9	58.0		58.4	58.4	58.4	58.5	58.5	
≥ 10000	5.6	40.5	49.3	55.5	59.1	56.6	61.2	61.5		62.1	62.1	62.1	62.2	62.2	62.2	62.3
≥ 9300	5.6	41.6		57.2			63.1	63.4	61.6	1		64.0			64.1	64.2
≥ 8000	5.9	43.1	52.3	59.0	62.8	63.9	65.1	65.5	65.6	66.1	66.1	66.1	66.1	66.2	66.2	66.2
≥ 7000	6.2	44.6	! [61.3		66.5	68.0					69.0		69.1	69.1	69.2
≥ 6000	6.4			62.5	66.5	67.8	69.4	69.8	69.9		70.4	70.4	70.5			70.6
≥ 5000	6.8			64.9	68.9	70.1	71.7	72.2	72.3	i	72.9	72.9	72.9	73.0	73.0	
≥ 4500	7.2	48.6		66.2	70.3	71.6	73.2		73.7	74.3	74.3	74.3	74.4		74.5	
≥ 4000	7.5		1	68.6	72.7	74.0	75.6	76.0	76.1	76.9	76.9	76.9	77.0	1	77.1	7/.1
≥ 3500	8.1	52.2		71.6	75.7	77.1	79.0	79.5	79.6		80.4	80.4				
≥ 3000	8.5		1	74.2			82.0	82.6	82.7	83.6	83.6	83.6		83.8		1 ?
≥ 2500	8.8	55.7	67.1	76.3	80.6	82.3	84.7	85.4	85.5		86.3	86.3	86.4	86.5	86.5	86.6
≥ 2000	9.0	56.8	68.3	77.6	82.2	83.9	86.4	87.1	87.3	88 - 2	88.2	88.2	88.3	88.4	88.4	88.4
≥ 1800	9.2	57.3	69.1	78.5	83.2	84.9	87.5	88.2	88.4	89.2	89.2	89.2	89.4	89.4	89.4	89.5
≥ 1500	9.2	57.8	69.8	79.5	84.5	86.3	88.9	89.7	89.8	90.9	90.9	90.9	91.0	91.1	91.1	91.2
≥ 1200	9.2	59.0	71.1	80.9	86.1	87.8	90.7	91.6	91.8	92.9	93.0	93.0	93.1	93.1	93.1	93.2
≥ 1000	9.2	59.3	71.4	81.5	86.9	88.6	91.7	92.7	92.9	94.1	94.1	94.1	94.3	94.3	94.3	94.4
≥ 900	9.2	59.4	71.6	81.7	87.2	89.1	92.2	93.2	93.4	94.6	94.7	94.7	94.8	94.9	94.9	94.9
≥ 800	9.2	59.6	71.9	82.2	87.8	89.7	93.0	94.0	94.1	95.3	95.4	95.4				95.7
≥ 700	9.2		72.0	82.4		-	93.4	94.6	94.7	96.0	1	96.1	96.2			
≥ 600	9.2			82.8			94.1	95.5	95.8			97.1	97.3			
≥ 500	9.2	60.2	72.5	83.1		91.2	94.8	96.4	96.6			98.0	98.1	98.2	98.2	
≥ 400	9.2		72.7	83.3					97.1	98 • 6						
≥ 300	9.2			83.4	89.4	91.7	95.4		97.3			99.2	99.3			1
≥ 200	9.2		+	83.4		91.8		97.1	97.4		99.5			99.8		
≥ 100	9.2			83.4	89.4	91.8			97.4			99.5		99.8	1	
≥ 0	9.2	60.5	72.8	83.4	89.4	91.8	95.5	97.1	97.4	98.9	99.5	99.5	99.7	99.8	99.8	ncc.cl

TOTAL NUMBER OF OBSERVATIONS_

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

of a solution of the second

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

MAY

STATION

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-0500 HOURS (LST)

CEILING							VIS	IBILITY (S)	ATUTE MII	LES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 1 1/2	£ 1 1/4	≥1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 2C000	4.3	26.3	31.1	34.6	37.5	38.3	39.2	39.4	39.5	-	39.7	39.8	39.8			39.0
	4.5	30.8	36.9	41.8		46.1	47.1					47.8				47.8
≥ 18000	4.5	31.1	37.5	42.4	45.8	46.9	47.9	48.3	48.4			48.7	48.7	48.7	48.7	48.7
≥ 16000	4.5	31.9	38.4	43.4	46.8		48.9		49.4	49.6	49.6	49.7	49.7	49.7	49.7	49.8
≥ 14000	4.5	33.0	39.8	44.8	48.3	49.4	50.5	51.1	51.2	51.4	51.4	51.5				51.6
≥ 12000	4.6	35.4		48.6	52.3		54.8		55.6			55.9				56.
≥ 10000	4.7	37.5	45.6	51.9	55.9	57.4	58.7	59.4	59.5		59.9	59.9	59.9			6C • u
≥ 9000	4.8	38.4		53.2	57.2	58.8	60.1	60.8						61.4	61.4	61.4
≥ 8000	4.8	39.7	48.4	55.3	59.6		62.7	63.4	63.6		63.9	64.0			64.C	64
≥ 7000	5.1	40.9	49.9	56.8	61.1	63.0	64.5	65.3			65.8	65.8	65.8	65.8	65.8	65.3
≥ 6000	5.4	42.1	51.2	58.2	62.6		66.2	67.0	67.1	67.4	67.5	67.6		67.6	67.6	67.6
≥ 5000	5.6	43.7	53.3	60.5	65.1	67.1	68.9	69.8	69.9	70.2	70.3	70.3	70.3	70.3	70.3	70.4
≥ 4500	5.7	44.0	53.8	61.1	65.7	67.7	69.7	70.5	70.6	70.9	71.0	71.0	71.0	71.0	71.0	71.1
≥ 4000	6.2	46.2	56.0	63.6	68.3	70.4	72.3	73.2	73.3	73.6	73.7	73.7	73.7	73.7	73.7	73.8
≥ 3500	6.5	48.6	59.3	67.1	71.9	74.2	76.2	77.2	77.4	77.7	77.7	77.8	77.8	77.8	77.8	77.3
≥ 3000	6.8	51.1	62.4	70.5	75.9	78.4	80.6	81.7	81.8	82.1	82.2	82.3	82.3	82.3	82.3	82.3
≥ 2500	6.9	52.5	64.5	72.6	78.3	80.7	83.0	84.1	84.2	84.6	84.7	84.8	84.8	84.8	84.8	84.3
≥ 2000	7.2	53.6	65.8	74.6	80.3	82.9	85.5	86.6	86.8	87.3	87.3	87.4	87.4	87.4	87.4	87.5
≥ 1800	7.2	53.9	66.4	75.1	81.1	83.6	86.3	87.4	87.6	88.1	88.1	88.2	88.2	88.2	88.2	88.2
≥ 1500	7.2	54.8	67.4	76.3	82.5	85.2	88 • Q	89.1	89.2	89.8	89.9	90.0	90.0	90.0	90.0	90.0
≥ 1200	7.2	55.6	68.5	77.5	84.2	87.0	89.9	91.0	91.2	91.9	91.9	92.0	92.0	92.0	92.0	92.1
≥ 1000	7.2	56. Q	69.0	78.4	85.6	88.5	91.5	92.7	92.9	93.7	93.7	93.8	93.8	93.8	93.8	93.9
≥ 900	7.2	56.2	69.1	78.7	85.9	88.8	91.9	93.1	93.2	94.0	94.1	94.1	94.2	94.2	94.2	94.3
≥ 800	7.2	56.3	69.5	79.1	86.4	89.4	92.5	93.7	93.9	94.7	94.8	94.9	95.0	95.0	95.0	95.4
≥ 700	7.3	56.7	69.9	79.6	87.0	90.0	93.2	94.5	94.7	95.5	95.6	95.6	95.8	95.8	95.8	95.9
≥ 600	7.3	56.9	70.1	80.0	87.6	90.9	94.1	95.5	95.7	96.7	96.8	96.8	97.0	97.0	97.0	97.1
≥ 500	7.3	56.9	70.2	80.1	87.9	91.2	94.8	96.4	96.6	97.7	97.8	97.8	98.0	98.0	98.0	98.1
≥ 400	_ 7.3	56.9	70.2	80.3	88.3	91.6	95.2	97.0	97.2	98.4	98.5	98.6	98.7	98.7	98.7	98.9
≥ 300	7.3	56.9	70.2	80.3	88.3	91.6	95.3	97.1	97.4	98.9	99.0	99.0	99.2	99.2	99.2	99.3
≥ 200	7.3	56.9	70.2	80.3	88.3	91.6	95.3	97.1	97.5	99.0	99.2	99.2	99.4	99.4	99.4	99.6
≥ 100	7.3	56.9		80.3	88.3	91.6	95.4	97.2	97.6	99.1	99.2	99.3	99.5	99.5	99.5	99.6
≥ 0	7.3	56.9	70.2	80.3	88.3	91.6	95.4	97.2	97.6	99.1	99.2	99.3	99.5	99.5	99.5	100.0

TOTAL NUMBER OF OBSERVATIONS_

1674

1210W5 FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

leccipin

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITALUKE AB

47-64

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-080L

CEILING							VIS	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING	5.7	18.1	21.4	23.8	26.1	26.7		28.6	28.7	28 • 9	-	29.0	29.1	29.1	29.1	29.2
≥ 20000	7.1			34.4					42.6			43.2			43.5	43.6
. ≥ 18000	7.2	25.7		34.7	38.5		41.6		43.2		43.8	43.8	43.9	44.0	44.1	44.2
≥ 16000	7.2	25.7		35.0	39.0		42.2		43.8	44.1	44.4	44.4	44.5	44.6	44.7	44 • 8
≥14000	7.4	26.9		36.6	40.8		44.4		46.1	46.4	46.7	46.7			47.1	47.3
≥ 12000	7.8			39.3	43.6		47.7	49.4	49.6	50.0	50.4	50.4			50.8	51
≥ 10000	8 - 4	30.8		42.7	47.5		52.3	54.1	54.4	54.9	55.3	55.4	55.5		55.8	56.0
≥ 9000	8.5	31.8		44.3	49.4		54.4		56.5		57.5	57.6	57.7	57.9	58.0	58.2
≥ 8000	9.3	33.8		46.8	52.2	54.5	57.5		59.8	60.5	61.0	61.1	61.2	61.4	61.5	61.7
≥ 7000	10.0				54.3		59.8		62.3		63.5	63.6		63.9	64.0	54.6
≥ 6000	10.5	36.9	44.1	50.4	55.9		61.5	63.8	64.2	65.2	65.6	65.7	65.8	66.0	66.2	66.3
≥ 5000	11.2			52.8	58.6		64.7	67.1	67.4	68 • 6	69.2	69.3	69.4		69.8	69.9
≥ 4500	11.4	39.1	46.8	53.3	59.2	62.0	65.5	,	68.3	1	70.1	70.2	70.3	70.5	70.7	3. or
≥ 4000	12.3	41.2	49.4	56.1	62.5		69.0		72.1	73.4	74.1	74.1	74.2	74.5	74.6	14.8
≥ 3500	12.6		51.6	. 58 . 9	65.6		72.4	75.2	15.6	77.0	77.6	77.7	77.8		78.2	78.4
≥ 3000	13.4			62.3	69.3		76.7	79.6			62.0	82.1	82.2		82.6	82.8
≥ 2500	13.9	47.2		64.1	71.3	75.0	79.3	82.2	82.6	84 - 1	84.8	84.8	85.0	85.2	85.4	85.5
≥ 2000	14.5	48.3	57.9	65.6	73.2	77.0	81.8	84.9	85.4		77.7	87.7	87.9	88.2	88.3	88.5
≥ 1800	14.6	48.5	58.2	65.8	73.5	77.2	82.2	85.4	85.8	87.4	86.2	88.3	88.5	88.7	88.9	89.1
≥ 1500	14.6		59.3		75.1	79.1	84.2				90.5		96.7		91.2	91.3
≥ 1200	14.6		60.1	68.1	76.2	80.3	85.5		89.5		92.2	92.2		1)	1	93.1
≥ 1000	14.6		L	68.6	76.8	81.0	86.3	90.0			_43	93.4	93.5		94.0	94.2
≥ 900	14.6		60.7	68.7	76.9		86.6		- 1	1	930-	73.6		1 1		94.4
≥ 800	14.6			68.9				90.8			94.3					95.2
≥ 700	14.6			69.2	1							95.2		1 1		96.0
≥ 600	14.7			69.6							96.4	96.5				97.3
≥ 500	14.7			69.6			88.5		93.8			97.4				98.3
≥ 400	14.7			69.6								98.0				99.
≥ 300	14.7	51.0		69.6					94.4		98.4	98.4		1		99.5
≥ 200	14.7			69.6				93.9				98.7		99.2		
≥ 100	14.7								94.7		i			99.2		
≥ 0	14.7	51.0	61.2	69.6	78.6	83.0	88.9	93.9	94.7	96.8	98.6	98.7	98.9	99.2	99.5	100.

TOTAL NUMBER OF OBSERVATIONS

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLET

A resident Best Line

lundin E.

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

47-64

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-1100 HOURS (LST.)

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ½	≥11/4	≥ 1	≥ ¾	≥ 3%	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	14.3	26.0		28.5								29.5	29.5		29.5	29.5
≥ 20000	20.3		41.0			45.5					46.2		46.2		46.2	46.2
≥ 18000	20.4	40.1	41.9	44.7	46.0					47.3		47.3	47.3		47.3	اذ • 47
≥ 16000	20.8	41.0			47.4			48.7			48.8		48.8			48.8
≥ 14000	21.3	42.5	44.7	48.0						51.3			51.3		51.3	51.3
≥ 12000	21.9	44.1	46.5		51.7			53.6			53.8					
≥ 10000	22.9	46.8	49.7	53.8						57.9			57.9			
≥ 9000	23.5	48.4	51.5		57.8						60.2		60.2			
≥ 8000	24.4	50.8	54.4		61.0		63.0			63.9		,	63.9	, ,	63.9	63.9
≥ 7000	25.1	52.2	56.0		63.0											
≥ 6000	25.3	53.8	57.8		65.1	1	67.1		1	68.0			68.1	• •	68.1	68.1
≥ 5000	26.0	55.6	59.8		67.6			70.6		70.8			70.9			
≥ 4500	26.3	56.5	60.9		69.1			72.2					72.5	1	72.5	12.5
≥ 4000	27.4	59.4	63.9		72.3				75.6			75.8				
≥ 3500	28.9	61.9	66.5					79.0				-			1 1	
≥ 3000	30.0	64.0	68.8	75.5		80.1			82.1						82.6	82.6
≥ 2500	30.8		71.4	78.6	82.0	83.7			86.1	86.4			86.7	1		86 • 7
≥ 2000	31.6	67.9	73.4	81.1				89.3							90.0	
≥ 800	31.8	68.2	73.9	81.7					90.2				90.8		90.8	,
≥ 1500	32.1	69.5	75.4	83.4	87.3	89.2	90.9		92.1						92.8	
≥ 1200	32.3	70.2	76.1	84.2	88.4	90.3	92.1	93.2	93.4				94.2	-		94.2
≥ 1000	32.3	71.1	77.1	85.4	89.7	91.7	93.7	95.1	95.3	95.6		95.9				96.1
≥ 900	32.3	71.2	77.2	85.6	90.0	92.0	94.1	95.5	95.8	96.1	96.4	96.4	96.5	96.5	96.5	96.5
≥ 800	32.3	71.2	77.2	85.7	90.3	92.4	94.6	96.1	96.4		97.0		97.1	97.1	97.1	97.1
≥ 700	32.4	71.4	77.4	86.0	90.7	92.9	95.3	96.8	97.1	97.5	97.8	97.8	97.9	97.9	97.9	97.5
≥ 600	32.4	71.4	77.4	86.1	90.9	93.2	95.7	97.4	97.7	98.1	98.4	98.4	98.5	98.5	98.5	98.5
≥ 500	32.4	71.4	77.4	86.2	91.0	93.4	96.1	97.9	98.3	98.7	99.0	99.0	99.1	99.1	99.1	99.1
≥ 400	32.4	71.5	77.5	86.3	91.1	93.5	96.2	98.1	98.5	99.0	99.4	99.4	99.5	99.5	99.5	99.5
≥ 300	32.4	71.5	77.5	86.3	91.2	93.5	96.3	98.3	98.7	99.3	99.6	99.6	99.8	99.8	99.8	
≥ 200	32.4	71.5	77.5			93.5	96.4	98.5	98.9	99.5	99.8	99.8	100.0	100.0	100.0	100.
≥ 100	32.4						96.4	98.5	98.9	99.5	99.8	99.8	100.0	100.0	100.C	100.0
≥ 0	32.4	71.5	77.5	86.3	91.2	93.5	96.4	98.5	98.9	99.5	99.8	99.8	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

-monthstately leaded.

CEILING VERSUS VISIBILITY

43310

FUKUOKA KYUSHU JAPAN/I TAZUKE AB

-64

MAY

STATION

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	21.1	28.9 44.7	29.2 46.1	30.0 47.7	30.3 48.3	1	30.3 48.4			30.3 48.4	30.3 48.4				30.3 48.4	30 · 3
≥ 13000 ≥ 16000	31.8	46.0	47.6 49.3	49.3 51.0	50.0 51.7		50.1 51.8	50.1 51.8	50.1 51.8	50.1 51.8	50.1	50.1 51.8		50.1 51.8	50.1 51.8	50.1
≥ 14000 ≥ 12000	33.6	49.6	51.4	53.4	54.2 57.2	54.3	54.4	54.4	54.4	54.4	54.4 57.5	54.4	54.4	54.4	54.4	54.4
≥ 10000 ≥ 9000	36.6	54.9	56.9	56.3	60.2	60.4	57.4	60.5	60.5	60.5	ó0.5	60.5	60.5	60.5	60.5	60.5
≥ 8000	36.9 38.2	55.5 58.3	60.6	63.7	65.0	65.4	65.5	65.7		61.9 65.7	65.7	65.7	65.7	65.7	61.9	65.1
≥ 7000 ≥ 6000	38.4	59.6 61.2		65.0	66.8	67.3 69.4		67.6 69.8			69.8				67.7 69.8	69.8
≥ 5000 ≥ 4500	40.7	63.1		68.9			71.8	72.0 73.1		72.1				72.1 73.2	72.1	72.1
≥ 4000 ≥ 3500	42.7	67.2 69.1	70,4	73.9	76.2 78.6		77.1	77.4 80.0			77.4					
≥ 3000 ≥ 2500	45.4	72.2	76.0	79.9 83.3	82.5	83.5	83.8	84.1	84.1	i	84.2	84.2		84.2	84.2	88.1
≥ 2000	47.8	77.4	81.8	86.0	89.2	90.3	90.7	91.2	91.2	91.2	91.3	91.3	91.3	91.3	91.3	91.3
≥ 1800 ≥ 1500	47.9	77.5 78.3	83.1	87.6		92.2	92.8	93.4	93.4	91.7 93.5	93.6	93.6	93.6	93.6	93.6	93.6
≥ 1200 ≥ 1000	48.6 48.6	79.2 79.3	1			93.3 94.0		95.8	95.8	94.9	96.1	96.1	95.1 96.1	95.1 96.1	95.1 96.1	95.1 96.1
≥ 900 ≥ 800	48.6 48.6	79•6 79•6		89 • 4 89 • 6		94.6 94.9	95.7 96.0			96.8 97.1	97.1 97.4		97.1 97.4	97.1 97.4	97.1 97.4	97.1 97.4
≥ 700 ≥ 600	48.7	79.8 79.9		90.0	93.7 94.1	95.5	96.7 97.1	97.6 98.1		97.9 98.5					98.2 99.0	98.2 99.0
≥ 500 ≥ 400	48.7	79.9 79.9		90.3		96.4	97.6				1				99.5 99.8	1 1
≥ 300 ≥ 200	48.7	79.9 79.9	85.1	90.3	94.5		97.7	98.7	99.0	99.4	99.8	99.8	99.9	99.9		99.9
≥ 100 ≥ 0	48.7	79.9	85.1	90.3	94.5	96.5	97.7	98.7	99.0	99.4	99.9	99.9	100.0	100.0	100.0	100.
	70.1	1707	02.1	70.3	74.0	70.0	71.	70.1	77.0	77.4	77.7	77.7	100-0	1100.0	<u>u.c.o.c</u>	100.0

TOTAL NUMBER OF OBSERVATIONS

1674

1210W5 JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

ولل و حالات ا

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700 HOURS (LST)

CEILING							VIS	BILITY (ST	ATUTE MIL	.ES)						
(FEFT)	≥ 10	> 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	22.2 32.3	28.3	29.0 45.8	29.3	29.6 47.6	29.6 47.8		29.6 47.8	29.6 47.8	29.6 47.8	29.6 47.8	29.6 47.8	29.6	! 1	29.6 47.8	29.6 47.1
≥ 18000 ≥ 16000	33.0 33.6	45.5	47.0	48.7	49.2 50.6	49.3 50.7	49.3	49.3 50.9	49.3 50.9	49.3	49.3	49.3	49.3 50.9	í I	49.3 50.9	49.3 50.9
≥ 14000 ≥ 12000	35.2	49.9	51.6	53.4	54.1 57.4	54.2	54.3	54.3	54.3 57.8	54.3	54.3 57.8	54.3 57.8	54.3	54.3	54.3	54.3
≥ 10000	37.0	52.5 55.3	57.7	56.6	61.0	61.1	61.3	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4
≥ 9000	38.9 40.5	56.1 58.9	58.6 61.6	64.4	65.9	66.0	66.4		66.5	66.5	66.5	66.5	66.5		66.5	66.5
≥ 7000 ≥ 6000	40.6	59.9 60.8	62.7 63.7	67.1	67.4 68.8		68.1 69.7	68.3 69.8	68.3 69.9	68.3 69.9	68.3 69.9	68.3			68.3 69.9	
≥ 5000 ≥ 4500	41.8	62.4	65.5 66.3	68.9 69.8				72.0	72.0		72.0	72.0		72.0	72.0	
≥ 4000 ≥ 3500	43.9 45.1	66.1 68.3	69.5 72.3	73.2		75.6 79.1	76.4 79.9		76.7 80.3		76.7	76.7			76.7 80.3	76.7
≥ 3000 ≥ 2500	46.6		75.3		82.0	82.7	83.8	84.2	84.2	84.3				84.3		
≥ 2000	48.6	75.2	80.2	84.9	87.7	88.9	90.4	90.7	90.9	91.1	91.1	91.1	91.1	91.1	91.1	91.1
≥ 1800 ≥ 1500	48.8	75 • 6 76 • 4	81.6		89.6	90.9	92.5	92.9		93.2	93.2		93.2	93.2	93.2	93.2
≥ 1200 ≥ 1000	49.3	77.4 77.8	83.4	88.7	92.1	93.3	95.1	95.8	95.9		96.2	96.2	96.2	96.2	96.2	96.2
≥ 900 ≥ 800	49.4	77.9 78.1		- ,	92.4 92.6					96 • 8 97 • 4				1		
≥ 700 ≥ 600	49.6	78•1 78•2					1			98 • 1 98 • 7	98 • 2 98 • 8				98.2 98.8	1 !
≥ 500 ≥ 400	49.6	78 · 3	84.0 84.0		1		1	1					99.1 99.5	1	99.1 99.5	
≥ 300 ≥ 200	49.6	78.3	84.0	89.7	93.5	95.0	97.4		98.7	99.4	99.6	99.6	99.6	99.6	99.6	99.€
≥ 100 ≥ 0	49.6	78.3	84.0	89.7	93.5	95.0	97.4	98.4	98.7	99.5	99.6	99.6	99.9	99.9	99.9	99.9
	49.6	78.3	84.0	89.7	42.5	99.0	71.4	90.0	90.8	77.0	77.8	77.0	100.0	100.0	<u> 100-0</u>	<u>u ocec</u>

TOTAL NUMBER OF OBSERVATIONS 1673

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-20C

CEILING							VIS	BILITY (ST	ATUTE MILI	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	13.8		29.7 43.1	30 · 8 45 · 3	31.5			32.2	32.2	32 · 3 48 · 4	32.3 48.4	32.3		32.3	32.3 48.4	32 • 3 48 • 4
≥ 16000 ≥ 16000	19.1	39.8 40.5	44.2 45.2	46.6 47.8	48.2	48.9 50.3		50.1 51.9	50.1 51.9	50 • 2 52 • 1	50.2 52.1	50.2 52.1	50.2 52.1		50.2 52.1	5(· • ∠ 52 • 1
≥ 14000 ≥ 12000	20.1 20.9	42.8	47.6 50.1	50.6 53.7	52.5 55.9	53.3 56.8	54.5		55.3 59.2	55.5 59.7	55.5 59.7	55.5 59.7	55.5 59.7	ı ,	55.5 59.7	55.5 59.7
≥ 10000 ≥ 9000	21.2	46.6 47.5	52.1 53.4	55.9 57.4	58.4 60.0	59.5 61.1	61.0	- 1		62 • 8 64 • 6	62.9 64.6	62.9 64.6	62.9 64.6	64.6	62.9 64.6	62.9 64.0
≥ 8000 ≥ 7000	22.0	48.8 49.9	54.8 56.2	59.2 61.1	62.2 64.3	63.4 65.7	67.4	68.9	t	66 • 9 69 • 6	69.7	66.9 69.7	66.9	. 1	66.9 69.7	69.7
≥ 6000 ≥ 5000	22.6	51.9		62.6	67.3		71.5	73.2	73.2	71 • 5 73 • 9	71.6 73.9	73.9	71.6 73.9	73.9	71.6 73.9	71.6
≥ 4500 ≥ 4000	23.1		59.1 61.0	65.0	68.5 70.8			76.8	76.9	74.8 77.6		75.0 77.8	75.0	77.8	75.0 77.8	75.0 17.6
≥ 3500 ≥ 3000	24.0	55.5 57.7	62.7	69.2 72.2	73.2 76.4		77.5 81.2	83.1	83.3	80 • 2 84 • 0	80.5 84.3		80.5	84.3	84.3	84.3
≥ 2500 ≥ 2000	24.8	60.4	66.9 68.6	73.7	78.3 80.5	82.5		88.2	88.4	86 - 8 89 - 4	87.0 89.7 90.3	87.0 89.8 90.4	87.0 89.8 90.4	89.8		87.5 89.6 90.4
≥ 1800 ≥ 1500	24.9 25.2	61.7	69.0 70.2 71.2	76.3 77.6 78.9	81.1 82.5 83.9	83.0 84.6 86.0	88.3	90.6	90.9	92.0	92.3	92.4	92.6			92.6
≥ 1200 ≥ 1000 ≥ 900	25.2	62.6		79.3		86.7	90.6	93.1	93.4	94.7	95.0	95.2	95.4 96.1		95.4 96.1	95.4
≥ 800 ≥ 700	25.2	62.6			84.9	87.4	91.3	94.0	94.3	95.6	95.9	96.1	96.4			96.4
≥ 600	25.2	62.7	71.6	79.7	85.2	87.9	92.1	95.0	95.5		97.4	97.5		97.8	97.8	97.8
≥ 400	25.2	62.7	71.6	79.8	85.4	88.2	92.8		96.5	98 • 0	98.5	98.6		98.9	98.9	
≥ 200 ≥ 100	25.2	62.7	71.6	79.9	85.5	88.3	92.9	•	96.8	98.5	99.1	99.3	99.6	99.7	99.7	
≥ 0	25.2							F)						1	99.9	100.

TOTAL NUMBER OF OBSERVATIONS_

CEILING VERSUS VISIBILITY

ŧ.

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64 *

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-230s

CEILING							VISI	IBILITY (ST	ATUTE MIL	.ESI						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥1%	≥ 1%	≥ 1	> 1/4	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	5.5	28.6	33.6	37.9	40.1	41.0	41.6	41.8	41.8	41.9	41.9	41.9	41.9	41.9	41.9	41.7
≥ 20000	5.9	33.7	40.4	46.7	49.8	50.8	51.5	51.9	51.9	52.0	52.0				52.0	52.6
≥ 18000	6.0	34.0		47.3	50.7	51.7	52.4	52.7	52.8	52.9	52.9	52.9	52.9	52.9	52.9	52.7
≥ 16000	6.1	34.5	41.5	48.0	51.5	52.5	53.2	53.6	53.6	53.8	53.8	53.8	53.8	53.8	53.8	53.8
≥ 14000	6.5	36.1	43.5	50.4	53.9	55.0	55.7	56.3	56.3	56.5	56.5	56.5	56.5	56.5	56.5	56.5
≥ 12000	6.6	37.9	45.5	53.0	56.9	58.2	59.1	59.7	59.9	60.0	60.0	60.0	60.0	60.0	60.0	64.00
≥ 10000	6.7	39.7	47.9	55.8	60.1	61.4	62.7	63.4	63.6	63.8	63.8	63.8	63.8	63.9	63.9	63.9
≥ 9000	6.7	40.0	48.5	56.6	61.1	62.4	63.6	64.5	64.6	64.8	64.8	64.8	64.8	64.9	64.9	64.5
≥ 8000	6.8	41.5	50.4	58.6	63.1	64.6	65.8	66.7	66.8	67.0	67.0	67.0	67.0	67.1	67.1	67.1
≥ 7000	7.d	42.4	51.7	60.3	65.3	67.0	68.4	69.2	69.4	69.7	69.7	69.7	69.7	69.8	69.8	69.8
≥ 6000	7.3	43.3	52.9	61.9	67.1	68.9	70.3	71.1	71.3	71.6	71.6	71.6	71.6	71.7	71.7	71.7
≥ 5000	7.9	44.9	54.9	64.2	69.5	71.3	72.8	73.7	73.8	74.1	74-1	74.1	74.2	74.3	14.3	74.3
≥ 4500	8.1	45.5	55.7	65.0	70.3	72.2	73.7	74.8	75.0	75.3	75.3	75.3	75.3	75.4	75.4	75.4
≥ 4000	8.3	47.1	57.7	67.4	72.8	74.7	76.3	77.4	77.6	78.0	78.0	78.0	78.1	78.2	78.2	78.2
≥ 3500	8.6	49.2	60.2	70.5	76.2	78.2	79.9	80.9	81.1	81.5	81.5	81.5	81.6	81.7	81.7	81.7
≥ 3000	8.7	51.0	62.2	72.8	78.4	80.6	82.3	83.6	83.8	84 - 2	84 - 2	84.2	84.3	84.4	84.4	84.4
≥ 2500	8.8	52.3	63.8	74.8	80.5	83.0	84.7	86.0	86.1	86.6	86.6	86.6	86.7	86.9	86.9	86.9
≥ 2000	9.0	54.1	65.8	77.1	82.9	85.6			89.1	89.6	89.6	89.6	89.7	89.8	89.8	89.8
≥ 1800	9.0	54.7	66.4	77.7	83.6	86.3	88.4	89.7	89.9	90.5	90.5	90.5	90.6	90.7	90.7	90.7
≥ 1500	9.d	55.3	67.1	78.5	84.5	87.2	89.5	90.9	91.1	91.7	91.8	51.8	91.9	92.0	92.0	92.6
≥ 1200	9.0	55.9	68.0	79.6	85.8	88.6	91.2	92.5	92.8	93.5	93.5	93.5	93.7	93.8	93.8	93.8
≥ 1000	9.d	56.3	68.5	80.3	86.9	89.6	92.6	94.0	94.5	95.2	95.4	95.4	95.5	95.6	95.6	95.6
≥ 900	9.0	56.3	68.6	80.5	87.4	90.3	93.3	94.7	95.2	95.9	96.2	96.2	96.4	96.5	96.5	96.5
≥ 800	9.0	56.6	68.9	80.9	87.9	90.9	93.9	95.3	95.8	96.5	96.8	96.8	97.0	97.1	97.1	97.1
≥ 700	9.0	56.8	69.2	81.2	88.2	91.2	94.2	95.6	96.2	96.9	97.2	97.2	97.4	97.5	97.5	97.5
≥ 600	9.0	56.8	69.2	81.4	88.4	91.5	94.7	96.2	96.9	97.6	98.0	98.0	98.1	98.3	98.3	98.3
≥ 500	9.0	56.8	69.2	81.5	88.6	91.8	95.0	96.7	97.4	98.1	98.5	98.5	98.7	98.8	98.8	98.₺
≥ 400	9.0	56.8	69.2	81.5	88.6	91.8	95.1	96.8	97.6	98.4	98.9	98.9	99.0	99.2	99.2	99.2
≥ 300	9.0	56.8	69.2	81.6	88.7	91.9	95.2	96.9	97.7	98.7	99.2	99.2	99.5	99.6	99.6	99.6
≥ 200	9.0	56.8	69.2	81.7	88.8	92.1	95.5	97.1	98.0					100.0	100.0	100.0
≥ 100	9.0	56.8	69.2	81.7	88.8	92.1	95.5	97.1	98.0	99.0	99.6			100.0	100.0	100.
} ≥ 0	9.0	56.8	69.2			92.1	95.5	97.1	98.0	99.0			99.9	100.0	hoo.c	hoo.c
≥ 200 ≥ 100	9.0	56.8	69.2 69.2	81.7	88.8	92.1	95.5 95.5	97.1 97.1	98.0 98.0	99.0	99.6	99.6	99.9	100.0	100	0.0

TOTAL NUMBER OF OBSERVATIONS

CEILING VERSUS VISIBILITY

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

OGOC-C20

CEILING							VIS	IBILITY (ST.	ATUTE MIL	LES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 1 1/3	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	3.8	18.9	23.0	26.9	28.8	30.2	31.4	31.9	31.9	32.0	32.0	32.0	32.0	32.0	32.C	32 . [
≥ 20000	4.2	24.3	30.4	35 - 2	38.0	39.7	41.8	42.8	42.9	43.2	43.3	43.3	43.3	43.3	43.3	43.3
≥ 18000	4.3	25.1	31.4	36.3	39.2	40.9	43.0	44.1	44.2	44.5	44.6	44.6	44.6	44.6	44.6	44.6
≥ 16000	4.4	25.7	32.2	37.2	40-1	41.7	43.9	44.9	45.1	45.4	45.4	45.4	45.4	45.4	45.4	45.4
≥ 14000	4.5	26.8	33.7	39.1	42.2	43.9	46.4	47.7	47.8	48.3	48.3	48.3	48.3		48.3	48 - 3
≥ 12000	4.8	28.5	35.7	41.3	44.8	46.4	49.3	50.6	50.8			51.5			51.5	
≥ 10000	5.1	30.5	38.1	44.4	48.5	50.1	53.1	54.6	54.8	55 • 4	55.6	55.6	55.6		55.6	55.6
≥ 9000	5.1	30.7	38.5	44.8		50.7	54.0		55.8	56.7		56.8			56.8	
≥ 8000	5.3	32.0		47.2	51.5	53.5	56.7	58.4	58.8	59.7	59.9	59.9	59.9)	59.9	59.5
≥ 7000	5.5	33.1	41.5	49.3	53.8	55.8	59.2		61.2			62.3			62.3	
≥ 6000	5.7	34.1	42.7	50.8		57.3	60 • 7	62.4	62.8			63.9	63.9	1	63.9	
≥ 5000	5.9	35.5	44.2	52.6	57.2	59.3	62.8	64.6	64.9	65.9		66.0			66.0	66.
≥ 4500	6.q	36.9	45.7	54.3	59-1	61.3	64.9	66.9	67.2		68.3	68.3			68.3	
≥ 4000	7.Q	39.9	49.2	58.1	63.0	65.2	69.1	71.0	71.4			72.5			72.5	
≥ 3500	7.4	42.8	52.5	61.7	66.9	69.5	73.5		75.9	76.9	77.0	77.0	77.0	1	77.0	
≥ 3000	8.Q	46.2	56.3	65.8	71.2	73.8	77.8		80.2	81.2		81.4			81.4	
≥ 2500	8.5	48.5	59.0	68.7	74.3	76.9	81.0		83.4	-		84.6	84.6	7		
≥ 2000	8.9		61.3	71.5	<u>77.3</u>	86.2	84.5					88.3			88.3	
≥ 1800	9.0	50.9	62.0	72.3	78.1	80.9	85.3	87.5	87.8	89.0	89.2	89.2	89.2		89.2	
≥ 1500	9.1	51.7	63.1	73.4	79.4	82.5	87.1	89.3	89.6			91.2	91.3	1		
≥ 1200	9.2	53.6	65.2	75.9	82.0	85.1	89.8	92.0	92.4			94∙0		94.1	94.1	94.1
≥ 1000	9.3	54.4	66.1	76.8	83.1	86.3			93.8				95.9			
≥ 900	9.3	54.7	66.5	77.2	83.6	86.7	91.5		94.3				96.7	96.7	96.7	96.1
≥ 800	9.3	55.1	67.2	78.0		87.7	92.6		95.4			97.7	97.8			
≥ 700	9.3	55.2		1	84.8	87.9	92.8		95.7	97 • 7		98.1	98.1	98-1	98.1	1 :
≥ 600	9.3	55.2	67.5			88.5	93.5					98.8	98.8			
≥ 500	9.3		67.6	78.8		88.8							99.3			
≥ 400	n <u>.3</u>	55.3	67.8			89.0		96.7	97.2		99.6	99.6				
≥ 300	9.3		68.0		-		94.4	97.0			1	99.9		100.0		
≥ 200	9.3	55.4	68.0	79.2	85.8		94.4							100.0	·	
≥ 100	9.3)	1				94.4	1		1		99.9		100.0	· -	1
≥ 0	9.3	55.4	68.0	79.2	85.8	89.2	94.4	97.0	97.5	99.4	99.9	99.9	99.9	100.0	100.0	TCO.C

TOTAL NUMBER OF OBSERVATIONS _

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF

No. 4 Mar. in 17

CEILING VERSUS VISIBILITY

43310

FUKUUKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-0500

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FECT)	≥ 10	≥ 6	≥ 5	≥4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/3	≥ 1%	≥ 1	≥ ¾	≥ 1/6	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	2.3	15.4	18.3	21.1	23.0	24.3								27.1		
≥ 20000	3.1			29.8	33.3	35.2			39.5					40.3	4C-3	
≥ 18000	3.2	21.5	26.5	31.0	34.6	36.5	39.1	40.7	40.8	41.5	41.5	41.5	41.6	41.6	41.6	41.7
≥ 16000	3.2	21.5	26.5	31.1	34.8	36.7	39.3	40.9	41.0	41.7	41.7	41.7	41.8	41.8	41.8	41.9
≥ 14000	3.5	23.3	28.5	33.5	37.3	39.7	42.4	44.1	44.3	44.9	45.1	45.1	45.1	1	45.1	45.2
≥ 12000	3.5	23.9	29.3	34.4	38.5	40.9	43.7	45.5	45.6	46.4	46.5	46.5	46.5		46.5	46.0
≥ 10000	4.0	26.1	32.0	37.9	42.3	44.8	47.8	49.6	49.8	50.6	50.7	50.7	50.8	1	50.8	5C • 9
≥ 9000	4.0	26.5	32.5	38.4	42.9	45.4	48.6		50.6	51.7	51.9	51.9			1	
≥ 8000	4.1	27.3	33.8	39.8	44.5	47.0	50.3	52.3	52.4	53.5	53.8	53.8			54.0	1
≥ 7000	4.4	28.1	34.8	41.1	46.0	48.5	51.9			55.4	55.6	55.7	55.8		55.8	
≥ 6000	4.6	28.6	35.6	42.2	47.2	49.8	53.1	55.2	55.4	56.7	57.0	57.0	57.2	1	57.2	
≥ 5000	4.7	30.1	37.3	44.1	49.4	52.2	55.7	58.0	58.1	59.5	59.8	59.8	59.9	 1	59.9	
≥ 4500	5.C	31.0	38.7	45.9	51.4	54.2	57.7	60.0		61.5	61.8	61.9		. ,	62.0	
≥ 4000	5.9	·		49.0								65.6			65.7	65.7
≟ 3500	6.9	36.5	45.2	52.6	58.6	61.5	65.4	67.7	67.9	69.3	69.5	69.6	69.7	1	69.7	69.8
≥ 3000	7.7	39.5	48.8	56.5	63.1	66.1	70.1				74.4	74.5			74.6	
≥ 2500	8.1	43.1	53.5	61.7	69.1	72.1	76.4			80.6	80.9	81.0		,	81.1	81.2
≥ 2000	8.2	45.3	56.6	65.1	73.0	76.2				85.1	85.4	85.5			85.6	
≥ 1800	8.3	1 1	57.5	66.2	74.1	77.5			i .	86.5	86.9	86.9	87.0	1 1	87.0	
≥ 1500	8.5	47.3	59.1	67.9	75.9	79.3	84.5				90.1	90.1	90.3		90.3	
≥ 1200	8.6	48.7	60.9	70.3	78.7	82.2	87.5	90.6		92.9	93.2	93.3	93.5	1 1	93.5	
≥ 1000	8.6	49.5	62.0	71.6		83.5					95.1	95.1	95.3		95.3	
≥ 900	8.6	49.6	62.2	72.0		84.1	1		1	95.4	95.7	95.7		1 1	95.9	96.0
≥ 800	8.6			72.3	80.9	84.4	89.9	93.3			96.3	96.4			96.5	
≥ 700	8 • 6	49.8	62.5	72.5	81.2	84.8	90.3			96.5	96.9	96.9			97.1	97.2
≥ 600	8.6		62.9	73.0									$\overline{}$		98.0	
≥ 500	8.6	50.2	63.1	73.3		85.8	91.5	95.1	95.4		98.5	98.5		1	98.7	98.8
≥ 400	8.6								95.8					+	99.1	99.1
≥ 300	8.6	! ' '					_		96.0		99.1	99.1		: 1	99.5	99.6
≥ 200	8.6							95.7		98.8					99.7	
≥ 100	8.6							95.7								130.0
≥ 0	8.6	50.3	63.3	73.5	82.5	86.2	91.9	95.7	96.1	98.8	99.2	99.3	99.6	99.6	99.8	100.0

TOTAL NUMBER OF OBSERVATIONS____

1620

CEILING VERSUS VISIBILITY

43310

1

11

C

(j

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE

0600-080(

(FROM HOURLY OBSERVATIONS)

CEILING							VIS	IBILITY (ST	ATUTE MIL	LES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/3	≥ 2	≥ 1 %	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	2.7 4.4	9.4 15.3		13.3	15.0 25.1	16.8 27.7	18.0	19.4 32.8		20.5 34.6		20.6 34.9	20.7	20.7 35.2	2C.7 35.2	20.7 35.4
≥ 18000 ≥ 16000	4.7	15.9 15.9	19.1	23.0	26.0		31.4		34.6 35.6	36.0 37.0		36.4 37.4	36.8 37.8	36.8 37.8	36.8 37.8	37.C 38.C
≥ 14000 ≥ 12000	5.0 5.2	17.0 18.1	20.7	25.4	29.3	32.4	35.4 38.2	38.1	38.7	40 • 4	40.8	40.8 44.6	41.2	41.2	41.2 45.1	41.4 45.2
≥ 10000 ≥ 9000	5.7 6.0	19.4	23.8	29.6	34.4	38.0	41.2	44.6	45.2	47 • 2 48 • 7	48.0	48.0	48.6	48.6	48.6 50.7	48.3 50.9
≥ 8000 ≥ 7000	6.1	20.9	26.1	32.3	37.9	41.9	45.4	49.1	49.8 51.8	51.9 54.1		53.3 55.4	54.2 56.4	54.3	54.3	54 • 4
≥ 6000 ≥ 5000	6.4	22.6	28.1 29.5	34.7	40.6	44.7	48.3	52.3	53.1	55 . 4 57 . 9	56.5	56.8	57.8	57.8	57.8	58.0
≥ 4500 ≥ 4000	7.1 8.3	24.8	30.4	37.2 40.1	43.3	47.5	51.4		56.7	59.1 62.5	60.4	60.6	61.5	61.7	61.7	61.9
≥ 3500 ≥ 3000	9.3	30.1	36.4 40.3	43.5	50.1		59.0	63.7		67.0		68.6	69.6	69.6	69.6	69.i
≥ 2500 ≥ 2000	12.9	37.0	44.4	52 • 5 55 • 4	60.2	65.1	70.C	75.2	76.1	79.0 84.0	80.3	80.8	81.9	82.0	82.0	82.2
≥ 1800 ≥ 1500	13.6	39.9	48.0	56.5	64.8	70.2	75.7	81.4	82.3	85 • 6 88 • 0	87.0	87.5	88.8	88.9		89.1
≥ 1200 ≥ 1000	14.1	41.7	50.1 50.7	59.4 60.1	67.9		79.6	85.9	87.0		92.0			93.9	94.0	
≥ 900 ≥ 800	14.2			60.2	68.9		81.3	87.8	88.9	92.4		94.6	95.9	96.0		96.4
≥ 700 ≥ 600	14.2	42.2	51.0 51.0	60.6	69.4	75.4	82.1 82.5	88.7 89.1	89.8	93.5 94.0	95.4	95.9		97.5	97.6 98.1	
≥ 500 ≥ 400	14.2	42.3 42.3	51.2 51.2	60.9 61.0	69.9	76.0	83.0 83.1	89.6 89.7	90.7	94.4			98.6 98.9	1	98.8 99.1	99.1 99.4
≥ 300 ≥ 200	14.2	42.3	51.2 51.2	61.0	70.1	76.2 76.2	83.2 83.2	89.8	91.0	94.8	96.9	97.5	99.1	99.3	99.4 99.5	
≥ 100 ≥ 0	14.2					,	83.2 83.2		91.0 91.0	94.8 94.8	96.9 97.0	97.5 97.5		1		99•8 160•č

OTAL NUMBER OF OBSERVATIONS _______1620_

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

heatik od

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUA. AB

47-54

PERCENTAGE SPECIALISM OF OCCUSRENCE (FROM HOURLY COBSERVATIONS)

CEILING					ViSinte i	Y (STATUTE MII	LES)						
(FEE'	≥ 10] ≥ 5	≥ 4 ≥ 5	} } ≥ 2 ½	2/ 17.	≥ 1%	≥ 1	≥ ¾	≥ %	e 1/2	≥ 5/16	≥ ¼	≥ 0
NO VENTINO			18.9 19.6									20.7	
> 31.30			33.5 34.6										
> 2007	1	- 1	3.00 30.3										
216000	14.930	1 33.											
5: 14030		7 35.				1 44.3							
≥ 12000			41.14										
≥ 10000			44.C 45.C			9.6 50.0							
≥ 9000			44.4 45.8										
≥ 8000			46.0 48.5								54.0		
≥ 7000	17.5 37.	8 42.0	47.3 50.2	4 52-2	54.1 55	5.1 55.6	56.1	56.4	56.5	56.6			
≥ 6000			48.6 51.8									! !	
≥ 5000	17.8 39.	1 43.4	49.0 52.										
≥ 4500	18-0 39												
≥ ,1000	19.5 42	3 46.9	12.9 56.	58.7	60.9 62	2.3 63.0	63.6	64.0	64.0	64.1	64.3	64.3	64.3
≤ 3500	21.4 46.		57.1 61.0										
≥ 3000	24.6 51.	7 56.9	63.5 67.8										
≥ 2500	26.7 56.			76.7	79.2 81	1.2 81.9	82.9	83.2	83.3	83.5	83.7	83.7	83.7
≥ 2000	28.1 59.	0 65.7	73.2 78.5	81.4	84.2 86	5.2 87.0	88.0	88.4	88.5	88.8	89.0	89.0	
≥ 1800	28.5 59	.9 66.7		82.7	85.6 87	7.7 88.4	89 . 4	89.8	89.9	90.2	90.4	90.4	90.4
≥ 1500	28.9 61.	2 68.3	76.1 82.0	35.0	88.0 90	0.4 91.1	92.1	92.6	92.7	93.0	93.1	93.1	93.1
(, ' ≤	29.0 61.	. 8 69.3	77-3 83.4			2.5 93.3							
≥ (.10	29.1 62.	. 2 69.7	78.4 84.	1.07.2	90.7 93	3.6 94.4	95.6	96.1	96.2	96.5	96.7	96.8	40.8
≥ ′ 0	29.1 62.	3 69.8											
≥ 0	29.1 62.	4 69.9	78.3 84.0	87.8	91.5 94	4.4 95.2	96.5	97.1	97.3				
•≥ 700	29.1 62.	.5 70.0				4.9 95.7							98.3
≥ 600	29.1 62.	8 70.5	79.1 85.			5.7 96.5						99.3	99.3
≥ 500	29.1 62.	8 70.5	79.1 85.	89.0	92.7 9	5.7 96.5	91.9						99.4
≥ 400	29.1 62.	8 70.5	79.1 85.			5.9 96.7			99.1				99.8
≥ 300	29.1 62.	8 70.5				5.9 96.7							
÷ 200	29.1 62.	8 70.5				5.9 96.7						100.0	
≥ 100	29.1 52.	. 8 70.5	79.1 85.	7 89.0	92.7 9	5.9 96.7	98.2	99.0	99.1				
> 0	29.1 62	<u>v. 10.5</u>	79.1 85.	89.0	92.7 9	5.9 96.7	98.2	99.0	99.1	99.6	99.8	100.0	100.1

TOTAL NUMBER OF OBSERVATIONS____

CEILING VERSUS VISIBILITY

43310

BUSINESS

FUKUCKA KYUSHU JAPAN/I TAZUKE AE

47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140 HOURS (L S.T.)

CEILING							VIS	BILITY (ST.	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/3	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	12.5		19.4	20.7	21.2	21.4				21.5	21.5		21.5	_		21.5
	21.0				39.1	39.3		39.5		39.5	39.5	39.5		39.5		
≥ 18000	21.9	34.3	36.9	39.6	40.7	40.9			41.1		41.1	41.1	41.1			41.1
	23.1	36.2		41.9		43.6		43.8	43.8	43.8	43.8		43.8		43.8	43.8
≥ 14000 ≥ 12000	24.9	39.1	41.9	44.8	46.0	46.4	46.6		46.9	46.9	46.9	46.9	46.9	('	46.9	46.9
	26.2		44.8	47.9	49.3	49.8		50.2	50.3		50.3			50.3	50.3	50.0
≥ 10000 ≥ 9000	27.2	43.7	47.1	50.7	52.4	53.0			53.8	53.8	53.8		53.8	53.8	53.8	53.8
	27.5			51.9	53.9	54.7	55.1		55.6	55.6	55.6					55.6
≥ 8000	27.7	45.6		53.5	55.6	56.5			57.6	57.7	57.7	57.7	57.7	57.7	57.7	57.7
≥ 7000	28.1		51.1	55.1	57.3	58.3		59.3	59.6	59.7	59.7	59.7				59.7
≥ 6000	28.5	47.6	51.9		58.5	59.6				61.4	61.4	61.4	61.4	61.4		61.4
≥ 5000	29.4		53.5			61.5		63.0			63.5					63.5
≥ 4500	29.8		54.0		60.9	62.1	63.2		64.0	64 - 1	64.1	64.1	64.1	64.1		64.1
≥ 4000	31.6				64.9	66.1		67.8		68 • 3		68.3				68.3
≥ 3500	34.3		61.3	- 1		70.7		72.5			73.0			1		73.
≥ 3000	37.7				75.6			78.8		79.3						19.3
≥ 2500	39.8		71.1			81.9					84.4					
≥ 2000	41.6			81.0			88.4		89.4		89.6					89.7
≥ 1800	42.2		76.2	82.2		88.0				90.9	90.9					91.
≥ 1500	42.5	71.4	77.9			90.6	92.3		93.5	93.9	93.8		93.9			93.9
≥ 1200	42.6	72.2	78.8	85.4	89.9	91.7	93.6		95.3	95.6	95.8	95.8	95.9		1	95.9
≥ 1000	42.6		79.2	85.9	90.4	92.3			96.3	96.7		96.9				97.C
≥ 900	42.6	72.5	79.3	86.0	90.6	92.5	94.4	95.7	96.5	97.0	97.2	97.2				97.3
≥ 800	42.6	72.7	79.5	86.4	91.0	93.0	94.9	96.3	97.1	97.8	98.1	98.1	98.1	98.1	98.1	98.1
≥ 700	42.6	72.7	79.7	86.5	91.4	93.3	95.2	96.7	97.5	98 • 2	98.5	98.5	98.6		98.6	98.€
≥ 600	42.6	72.7	79.9	86.8	91.7	93.6	95.6	97.0	97.8	98.7	99.0	99.0	99.1	99.1	99.1	99.1
≥ 500	42.6	72.8	80.0	86.9	91.9	93.8	95.8	97.2	98.0	98.9	99.2	99.2	99.3	99.3	99.4	99.4
≥ 400	42.6	72.8	80.0	87.0	91.9	93.9	95.9	97.3	98.3	99.2	99.5	99.5	99.6			99.8
≥ 300	42.6	72.8	80.0	87.0	92.0	94.0	95.9	97.3	98.3	99.3	99.6	99.6	99.8		1	1 1
≥ 200	42.6	72.8	80.0	87.0	92.0	94.0	96.0	97.5	98.5	99.4	99.7	99.7			100.0	
≥ 100	42.6	72.8	80-0	87.0	92.0	94.0	96.0	97.5	98.5			99.7		99.9		
≥ 0	42.6	72.8	80.3	87.C	92.0	94.0	96.0	97.5	98.5	99.4	99.7	99.7	99.9	99.9	100.0	166.6

TOTAL NUMBER OF OBSERVATIONS _______162

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

e some en waranged e. with a transfer of the it indicate

/

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700 HOURE (LST.)

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEFT)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/3	≥ 11/4	≥ 1	≥ 3/4	≥ 1/4	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	14.2		- 1	21.9	22.2		r	22.4	22.4	1			22.4 39.5	22.4 39.5		,
≥ 18000 ≥ 16000	23.2		37.9	39.4	40.3	40.6	40.6	40.7	40.7		40.7	40.7		40.7	40.7	40.7
≥ 14000 ≥ 12000	25.7	40.5	42.6	44.5	45.5	46.0	46.2	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5
≥ 10000 ≥ 9000	27.7	45.5	48.3	51.1	49.5 52.7	53.2	53.7	53.9	53.9	54 - 0	54.0	54.0	54.0	54.0	54.C	54.0
≥ 8000	27.9	47.7	51.0	52.1 54.3	53.7 56.1	56.9	57.6	57.9		-1		55.3 58.3	58.3	58.3	58.3	58.3
≥ 7000 ≥ 6000	28.9	49.2	52.8	56.4	58.3	59.2	59.2 60.1	60.4	60.4	60.7	59.9	59.9 60.8	60.8	60.8	60.8	6C . 8
≥ ±000 ≥ 4500	30.1 30.8	52.0	54.5 55.9	59.7	61.8	62.7	64.0	62.6	64.4	64.9	63.1	65.0	65.0	65.0	65.0	
≥ 4000 ≥ 3500	36.0		63.6	68.0		67.5 71.7	73.0	73.3	73.3	73.8	73.9	73.9	73.9	73.9		
≥ 3000 ≥ 2500	39.0 41.3			73.8		77.8 82.7	79.3		79.7 85.0		80.5 85.8	80.5 85.8				
≥ 2000 ≥ 1800	42.4		75.6 76.8		84.5 85.7	86.1	88.1		88.7		89.7 91.1	89.7 91.1	89.8 91.2		89.8 91.2	39.8
≥ 1500	43.2		78.0 79.2	83.8 85.2	87.4	89.0	91.3		92.1	92 . 8		93.1	93.1	93.1	93.1 95.1	93.1
≥ 1000 ≥ 900	43.2	73.6	79.5 79.6	85.5 85.7	89.2	91.2	93.9	95.0	95.0 95.3		96.2 96.6	96.6			96.4	
≥ 800 ≥ 700	43.2	73.9	80.0 80.1	86.4	90.0	92.2	95.1 95.5	96.3	96.3	97.2		97.6 98.3		98.0		98.6
≥ 600	43.2	74.1	80.2 80.2		90.6	92.8		97.2	97.2	98 - 3	98.8	98.8	99.1	99.1	99.1	99.1
≥ 400 ≥ 300	43.2	74.1	80.2 80.2		90.7	92.9	96.0		97.6	98.7	99.3	99.3	99.6		99.6	99.6
≥ 200 ≥ 100	43.2	74.1	80.2		90.7	93.0	96.2	97.9	98.0	99.1 99.1	99.7	99.7	100.0		100.0	10C.J
≥ 0	43.2		80.2		90.7					99.1				100.0		

TOTAL NUMBER OF OBSERVATIONS_

_1616

and the state of t

CEILING VERSUS VISIBILITY

()

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-200

CEILING							VIS	BILITY (ST	ATUTE MIL	.ES)		· 	<u> </u>			
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1%	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	9.0 13.2	16.7 26.5	17.9 29.5	19.6 32.7	20.2	20.5 35.6	20.8 36.5			21.2 37.3			21.2 37.3	21.2 37.3	21.2 37.3	21.2 37.3
≥ 18000 ≥ 16000	13.8	27.7 29.0	31.0	34.4	36.9 38.5	ı	38.5 40.5	39.3 41.4	j	39.4 41.7		-	39.5		39.5 41.9	39.5
≥ 14000 ≥ 12000	14.6	30.6	34.8 37.1	38.8	41.7	42.7 46.0	44.0			45.4			45.7 49.9	45.7 49.9	45.7 49.9	45.7 45.9
≥ 10000 ≥ 9000	15.8 16.0	33 · 8 34 · 6	38.8 39.6	43.5 44.4	46.9 47.8		50.2 51.3	51.8 52.9		52 · 4 53 • 5			53.0 54.4	54.4		53.c 54.4
≥ 8000 ≥ 7000	16.3 16.5		42.7	46.7 48.1	50.4 52.2	53.9	56.1	56.1 58.1		56.9 59.0	59.4	59.6	57.8 60.1	57.8 60.1	57.8 60.1	57.8 60.1
≥ 6000 ≥ 5000	16.8 17.6	37.5 39.1	45.0	48.9 50.7	53.0 54.9	56.9		61.4	61.7	60 • 2 62 • 5			61.4	61.4	61.4	61.4
≥ 4500 ≥ 4000	18.0 19.3	39.8 42.6	45.7 49.0	51.4 55.1	55.7 59.6	61.7	60.1				68.6	68.7		69.4		64.6
≥ 3500 ≥ 3000	20.5	45.1		58 • 2 63 • 2	62.9	70.9			77.0		78.8	79.0		79.6		73.3
≥ 2500 ≥ 2000	22.8	51.5 54.3	58.9 62.0	69.9	72.0	78.8	82.7	85.4		82.5 87.0	87.7	87.8		88.6		88.6
≥ 1800 ≥ 1500	23.3 23.6 23.8	54.8 56.2		70.6 72.4 74.3	76.7 78.8 81.1	81.8	85.8	88.5	88.8	90.1	90.9	91.0	89.4 91.8	91.6	91.8	91.8
≥ 1200 ≥ 1000 ≥ 900	23.9	57.2 57.3	65.7	74.6	81.5	84.9	89.1	92.2	91.7 92.5 92.9		94.9	95.1		95.9	95.9	96.0
≥ 800	23.9	57.5 57.5	66.4	75.4	82.5		90.4	93.5	93.8	95.5	96.4	96.5	97.4	97.4	97.4 98.0	97.5
≥ 600	23.9	57.5 57.5	66.5	75.6 75.6	82.9	86.5	91.1	94.4	94.8	96.5	97.7	97.8		98.6	98.6	98.7
≥ 400	23.9	57.5	66.5	75.8	83.3	87.0	91.7	95.0	95.4	97.3	98.6	98.8	99.6	99.6	99.7	99.8
≥ 200 ≥ 100	23.9	57.5	66.5	75.8	83.4	87.0	91.7	95.1	95.5	97.5	98.8	99.0		99.9		100.€
≥ 0	23.9			1	1		91.7				1 1	99.0		1	i	100.(

TOTAL NUMBER OF OBSERVATIONS

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-2300 HOURS (LST)

CEILING							VISI	BILITY (STA	ATUTE MIL	ES)						
(FEET)	≥ 10	≥6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓2	≥ 2	≥ 1 1/2	≥1%	ا ≤	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING	4.8			23.4	25.2	26.0	- 1	27.7	1	28.0				28.1	28.1	28.1
≥ 20000	5.9			32.4	36.5	37.8	39.1			41.4	1.	41.5		1	41.5	
≥ 18000	6.1	23.0	27.3	33.4	37.7	39.1	40 • 5	- 1	42.2	42 . 8	43.0	43.0	43.0		43.0	- 1
≥ 16000	6.1	23.5		34.4	38.7	40.1	41.6	43.2	43.4	44 - 1	44.3	44.3			44.4	
≥ 14000	6.4	24.6	29.6	36.4	41.0	42.6	44.6	46.5	46.7	47.5	47.7	47.7	47.8	1	47.8	
≥ 12000	6.9	26.4		39.1	44.1	45.7	48.0	50.0	50.2	51.2	51.4	51.4	51.5		51.5	51.5
≥10000	7.0	28.1	34.0	41.7	46.9	48.5	50.9		53.3	54.4	1	54.8		1 1	55.0	55 · U
≥ 9000	7.1	28.5		42.3		49.3	51.7	54.0	54.3	55 • 4		55.9		1	56.1	56.1
≥ 8000	7.2	29.9		44.6	49.9	51.9	54.4		57.2	58 - 5		59.0	59.2	1	59.2	59.4
≥ 7000	7.4	31.5	37.9	46.8	52.2	54.3	56.9		59.6			61.4			61.6	
≥ 6000	7.4	31.9		47.3		55.2	58.0		60.7	62 • 0	1	62.6		1 1	62.8	62.0
≥ 5000	8.0		40.9	50.1	56.0	58.6	61.5		64.3	65.7	66.0	66.2	66.5		66.5	
≥ 4500	8.1	35.3	42.3	51.5	57.7	60.4	63.3	65.9	66.2	67.7	68.1	68.3	68.5		68.5	68.5
≥ 4000	8.7			54.9	61.4	64.1	67.1	69.9	70.2		72.0	72.2	72.5		72.5	72.5
≥ 3500	9.3	40.9		58.3	65.0	68.0	71.0	- 1	74.1	75 • 7	76.0	76.2	76.5	1	76.5	76.5
≥ 3000	10.1	44.4	52.2	62.3		72.3	75.4		78.6			80.8		81.1	81.1	81.1
≥ 2500	10.6		54.8	65 • Q		75.6	78.8	_ (82.1	83.8	- e	84.3			84.6	
≥ 2000	10.8			67.7	75.2	78.8	82.2		86.1	87.8		88.3			88.6	88.6
≥ 1800	10.9	49.9	58.1	68.8	,	80.1	83.4		87.3	89.0	1 1	89.6	•	1	89.9	89.9
≥ 1500	11.1	51.0		70.9		82.2	85.8		89.8		91.9	92.0				92.3
≥ 1200	11.1	52.1	61.3	72.7	80.6	84.4	88.4	_	92.4			94.8		95.1	95.1	95.1
≥ 1000	11.1	52.9		74.0		86.2	90.3		94.5			97.0				97.3
≥ 900	11.1	53.0		74 • 2	82.3	86.5	90.6	1	94.8			97.3	1	97.7	97.7	97.7
≥ 800	11.1	53.1	62.:	74.4					95.2			98.0				
≥ 700	11.1	53.3	63.1	74.9		87.3		95.4	95.8			98.6			98.9	
≥ 600	11.1	53.3		74.9				95.6			98.8	99.0				
≥ 500	11.1	53.3		74.9	, _	87.7		95.7	96.1	98 • 1		99.0				
≥ 400	11.1	53.5		75.1				96.0				99.3			99.6	
≥ 300	11-1			75.4											ľ	
≥ 200	11.1	53.5														99.9
≥ 100	11.1	53.5												100.0		1
≥ 0	11.1	53.5	63.5	75.4	83.8	88.3	92.5	96.4	96.8	98.8	99.5	99.7	100-0	100.0	TOC-0	µ 30 • ∪

TOTAL NUMBER OF OBSERVATIONS_

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0000-320 .

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ 3/8	≥ y ₂	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	12.4	32.6 38.2	36.5 43.0	38.5 45.5	39.1 46.3	39.3 46.5	39.4 46.7		39.5 46.8	39.5 46.8	39.5 46.9	39.5 46.9	(39.6 47.0	39.6 47.0	39.6 47.6
≥ 18000 ≥ 16000	14.9	38 • 8 39 • 2	43.7 44.1	46.2 46.5	47.0	47.2	47.4	47.5	47.6 47.9	47.6 47.9	47.6 48.0	47.6 48.0	47.7 48.0		47.7 48.0	47.7 48.0
≥ 14000 ≥ 12000	15.8	40.9	45.9	48.4	49.3	49.5	49.6	49.8	49.8 52.0	49.8 52.0	49.9 52.1	49.9 52.1	49.9 52.2	49.9 52.2	49.9 52.2	49.9 52.2
≥ 10000 ≥ 9000	16.7 17.0	44.6	50.3	53.7 55.2	54.8 56.3	55.1	55.3	55.4	55.5	55.5 57.0	55.6	55.6 57.1	55.6 57.2	55.6 57.2	55.6 57.2	55.6 57.2
≥ 8000 ≥ 7000	17.6	47.0	53.2	57.1	58.4	58.7	59.0	59.1	59.1	59.1 60.1	59.2 60.2	59.2 60.2	59.3 60.2	59.3 60.2	59.3 6C.2	59.3
≥ 6000 ≥ 5000	18.0	48.6 50.3	54.8	59.1	60.5	60.8	61.2	61.3	61.4	61.4	61.4	61.4	61.5	61.5	61.5	61.5
≥ 4500 ≥ 4000	19.1	51.7 54.7	58.1 61.5	62.4	64.0	64.3	64.8	64.9	65.0 69.2	65.0 69.2	65.1	65.1	65.1	65.1	65.1 69.3	65.1
≥ 3500 ≥ 3000	21.9	59.7 64.5	66.8 72.4	71.9	73.9	74.2	74.9 81.9	75.0	75.0 82.1	75.0 82.3	75.1	75.1 82.4	75.1 82.4	75.1	75.1	75.1 82.4
≥ 2500 ≥ 2000	24.3	67.7	76.2	82.3		85.6	86.6		86.9 90.3	87.0	87.1	87.1 90.6	87.2 90.6		87.2 90.6	87. ₂ 90.6
≥ 1800 ≥ 1500	24.9 25.0	70.4		86.1	89.3	89.7	91.0	91.2	91.3 94.2	91 • 5 94 • 4	91.5	91.5	91.6	91.6	91.6 94.5	91.6
≥ 1200 ≥ 1000	25.1 25.3	72.8		89.3	92.7	93.1	94.7	95.0	95.0 96.3	95.2 96.5	95.3	95.3	95.3 96.7	95.3 96.7	95.3 96.7	95.3 96.7
≥ 900 ≥ 800	25.3	74.0 74.1	84 • 2 84 • 4	91.2	94.6	75.0	96.7	97.0 97.3				91.3	97.4 97.7	97.4 97.7	97.4 97.7	97•4 97•7
≥ 700 ≥ 600	25.3 25.4	_	84.5 84.7	91.4 91.7	94.9	95.4	97.1 97.8	97.5 98.4	97.6 98.4	97.7 98.7			97.9 98.9		97.9 98.9	97.9 98.9
≥ 500 ≥ 400	25.5 25.5			_		96.4	98.1 98.4		98.8 99.2	99 • 1 99 • 5		99.2 99.6	99.3 99.7	99.3 99.7	99.3 99.7	99.3 99.7
≥ 300 ≥ 200	25.5 25.5			1	1	ľ	98.6 98.6	1	1		99.9		1		99.9 99.9	
≥ 100 ≥ 0	25.5 25.5		85.2 85.2	_				1							99.9	99.9 100.(

TOTAL NUMBER OF OBSERVATIONS_

CEILING VERSUS VISIBILITY

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-0500 HOURS (LST)

CEILING							VIS	IBILITY (ST	ATUTE MIL	.FS)						
(FEET)	≥ 10	≥ 6	≥ 5	<u> </u>	≥ 3	≥ 21/2	≥ 2	≥ 1 1/2	21%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	9.5	27.4	31.1	33.2	34.1	34.4	34.7	34.8	34.8	(34.9	34.9	34.9		35.0	
≥ 20000	10.8	31.4		38.3	39.5	39.9	40 - 3		40.6		40.7	40.7		40.8		
≥ 18000	11.1	32.2	36.6	39.0	40.2	40.6	41.1	41.3	41.4	41.4	41.4	41.4	!		41.5	
≥ 16000	11.1	32.7	37.2	39.6	40.8	41.2	41.7	41.9	42.0					42.1	42.1	42.3
≥ 14000	11.7	34.1	38.6	41.1	42.2	42.6	43.1	43.3	43.4	43.5		43.5	,	43.5	43.5	
≥ 12000	<u> 12.3</u>	35.7		43.2	44.5	44.9			45.7		_		45.8			
≥ 10000	13.6	38.4	43.6	46.7	48.3	48.7	49.5	49.8	49.9	50.0		,	1		50.0	
≥ 9000	13.7	39.2	44.4	47.6	49.2	49.6	50.4		50.8							
≥ 8000	14.5	41.2	46.5	49.9	51.6	52.0	52.8	53.1	53.2	53.3		53.3	53.3		53.4	3
≥ 7000	14.8	42.2	47.6	51.3	53.1	53.5	54.3	54.7	54.8	54.9	54.9	54.9	54.9	54.9	<u>54.9</u>	55.1
≥ 6000	15.2	43.5	49.1	52.8	54.5	54.9	55.9	56.3	56.4	56.5	56.5	56.5	56.5	56.5	56.5	56.7
≥ 5000	15.7	45.5	51.3	55.2	57.1	57.6	58.6	59.1	59.1	59.2	59.2	59.2	59.2	59.3	59.3	59.5
≥ 4500	16.Q	47.0	53.0	56.9	58.9	59.4	60.4	60.8	60.9	61.0	61.0	61.0	61.0	61.1	61.1	61.3
≥ 4000	17.2	51.9	58.3	62.6	64.9	65.3	66.5	66.9	67.0	67.1	67.2	67.2	67.2	67.2	67.2	67.4
≥ 3500	19.3	56.7	63.6	68.3	70.9	71.4	72.6	73.0	73.1	73.2	73.3	73.3	73.3	73.3	13.3	73.5
≥ 3000	21.8	61.9	69.5	74.7	78.0	78.5	79.9	80.3	80.3	80.5	80.5	80.5	80.5	80.6	80.6	8C.E
≥ 2500	22.8	65.8	73.7	79.3	83.3	84.0	85.3	85.7	85.8	85.9	86.0	86.0	86.0	86.0	86.0	86.2
≥ 2000	23.1	68.0	76.6	82.6	87.1	87.8	89.1	89.5	89.6	89.7	89.8	89.8	89.8	89.8	89.8	90.0
≥ 1800	23.1	68.4	77.2	83.4	88.0	88.8	90.1	90.6	90.6	90.7	90.8	90.8	90.8	90.9	90.9	91.6
≥ 1500	23.1	69.8	78.6	85.0	89.7	90.6	92.1	92.6	92.6	92.8	92.8	92.8	92.8	92.9	92.9	93.1
≥ 1200	23.2	70.0	79.1	85.8	90.5	91.4	93.0	93.5	93.5	93.7	93.7	93.7	93.7	93.8	93.8	94.0
≥ 1000	23.2	71.1	80.6	87.2	91.9	92.8	94.7	95.2	95.3	95.6	95.7	95.7	95.8	95.8	95.8	96.0
≥ 900	23.3	71.4	80.9	87.5	92.3	93.2	95.2	95.6	95.7	96.1	96.1	96.1	96.2	96.2	96.2	96.4
≥ 800	23.4	71.9	81.5	88.2	93.1	94.0	95.9	96.5	96.5	96.9	97.0	97.0	97.1	97.1	97.1	97.3
≥ 700	23.4	72.2	81.8	88.5	93.5	94.5	96.5	97.0	97.1	97.5	97.5	97.5	97.7	97.7	97.7	97.9
≥ 600	23.4	72.2	81.8	88.8	93.8	94.8	96.8	97.4	97.4	97.8	97.9	97.9	98.0	98.1	98.1	98.3
≥ 500	23.4	72.5	82.2	89.2	94.4	95.4	97.5	98.1	98.1	98.6	98.7	98.7	98.8	98.9	98.9	99.0
≥ 400	23.4	72.6	82.3	89.3	94.6	95.6	97.7	98.3	1		99.0	99.0	99.2	99.3	99.3	99.5
≥ 300	23.4	72.7	82.4	89.4	94.7	95.7	97.8	98.4	98.5	98.9	99.2	99.2	99.3	99.4	99.4	99.6
≥ 200	23.4	-	82.4	89.4	94.9	95.8	98.0	98.6	98.6	99.0			99.5	99.6	99.6	99.8
≥ 100	23.4	72.7	82.4	89.4	94.9	95.8	98.0				99.3	99.3	99.5	99.6	99.6	99.8
≥ 0	23.4		1 :	1	,		1	1		ı	99.3	99.3	99.5	99.6	99.6	loc.c
			<u></u>	<u> </u>	<u></u> .											

TOTAL NUMBER OF OBSERVATIONS_____

__1673

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

· levelskie

The state of the s

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

-0600-080

CEILING		•					VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ⅓	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ y ₂	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	9.6 14.7	18.2 26.3	20.1 28.9	22.3 31.7	23.3 33.3		25.1 35.5	25.6 36.2	25.7 36.3	25.9 36.5	26.0 36.6	26.0 36.6	26.0 36.6		26.0 36.7	26 • 2 36 • 9
≥ 18000 ≥ 16000	15.2 15.3	27.1 27.7	29.7 30.3	32.7 33.3	34.2		36.6 37.3		37.3 38.0	37.5 38.2	37.6 38.4	37.6 38.4	37.6 38.4	37.6 38.4	37.7 38.4	37.9 38.6
≥ 14000 ≥ 12000	16.2	29.5 31.5	32.1 34.2	35.2 37.5	37.1 39.5	38.1 40.5	39.7 42.1	40.4 42.8	40.5	40.7	40.9 43.2	40.9	40.9 43.2	40.9	40.9	41.1
≥ 10000 ≥ 9000	19.4	34.5 35.8	37.7 38.9	41.3	43.5	1 , , , ,	46.3		47.3 48.7	47.5 49.0	47.6 49.1	47.6 49.1	47.6 49.1	47.6 49.1	47.7	47.9
≥ 8000 ≥ 7000	21.0	37.7	41.0 42.5	45.0	47.4	48.7	50.4	51.4	51.5	51.8 53.6		51.9 53.7	51.9 53.7	51.9 53.7	52.0 53.8	52.2 54.0
≥ 6000 ≥ 5000	22.8	40.4	43 · 8 45 · 5	48.0	50.5	51.9	53.6	54.7	54.8	55.1			55.3 57.3	55.3 57.3	55.3 57.3	55.6
≥ 4500 ≥ 4000	23.7	43.2	46.8 50.7		53.6 57.8	55.0	56.8	58.0	58.1	58 • 5 63 • 2	58.7	58.7	58.7 63.3	58.7 63.3	58.7 63.4	59 63.7
≥ 3500 ≥ 3000	28.C 32.3	51.0 58.2		59.8 68.0	62.7	64.4			68.1 77.8	68.5 78.5		68.6	68.6 78.6	68.6 78.6		69.C
≥ 2500 ≥ 2000	34.2 35.1	62.5 64.6	67.7 70.3	73.8 76.5	77.6		82.5		84.5 88.2	85.4 89.2	85.5 89.4		85.5 89.4	85.5 89.4	85.7 89.5	85.9 89.8
≥ 1800 ≥ 1500	35.1 35.2	64.6 65.1	70.4 71.2	76.8 77.8			86.7	88.6	88.8				90.0 92.1	90.0	90.1 92.2	90 • 4 92 • 5
≥ 1200 ≥ 1000	35.3 35.3	65.4 65.8	71.5 72.2		83.6			92.4	92.5 94.5	93.6 95.8		93.8	93.8 96.1	93.8 96.1	94.0 96.4	94.3
≥ 700 ≥ 800	35.3 35.4	65.9 66.2	72.3 72.6		85.1 85.8			94.7 95.4	94.9 95.6	96 • 1 96 • 8	96.4 97.1	96.4 97.1	96.4 97.1	96.4 97.1	96.7 97.4	97.0 97.7
≥ 700 ≥ 600	35.4 35.4	66.2 66.2	72.8 73.0	1				95.8 96.4		97 • 2 98 • 0			97.6 98.3	_	97.8 98.6	
≥ 500 ≥ 400	35.4 35.4	66.2 66.2	73.1 73.1	80.9 80.9	86.7 86.7			96.8 96.8		98.5 98.5			99.0 99.0			
≥ 300 ≥ 200	35.4 35.4	66.3 66.3		80.9 80.9		89.6		96.9		98 • 7 98 • 7			99.2 99.2	99.2	99.5 99.5	
≥ 100 ≥ 0	35.4 35.4	66.3 66.3	1	80.9 80.9		1				98.8 98.8		99.2	99.3	99.3 99.3		99.9 100.0

TOTAL NUMBER OF OBSERVATIONS_____

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-1100

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ ½	≥ 5/16	≥ ¼	≥ 0
NO CEILING	14.6	22.8		24.8	25.4		26.0	26.0	26.0	26.0	26.0	26.0	26.0	26.0	26.0	26.0
≥ 20000	20.8	31.7	33.0	34.3	35.1	35.7	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
≥ 18000	21.0	32.4	33.6	34.9	35.7	36.4	36.5	36.6	36.6	36 . 6	36.6	36.6	36.6	36.6	36.6	36.6
≥ 16000	22.0	33.7	35.1	36.4	37.2	37.9	38.1	38.1	38.1	38 - 1	38.1	38.1	38.1	38.1	38.1	38.1
≥ 14000	24.5	37.1	38.6	40.1	41.2		42.0	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
≥ 12000	26.8	40.3	42.1	43.7	44.8	45.5	45.6	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7
≥ 10000	28.3	43.8	46.1	47.7	48 • 8	49.5	49.7	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8
≥ 9000	29.5	44.7	47.0	48.6	49.7	50.4	50.6	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	_50.7
≥ 8000	30.Q	46.0	48.3	49.9	51.2	51.9	52.1	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2
≥ 7000	31.1	47.4	49.8	51.7	<u> 53.0</u>	53.8	54.0	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
≥ 6000	31.5	48.0	50.3	52.2	53.6	54.3	54.5	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6
≥ 5000	32.3	49.1	51.5	53.5	54.9	55.7	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.1
≥ 4500	33.1	50.3	52.9	54.9	56.3	57.0	57.3	57.4		57.4	57.4	57.4	57.4	57.4	57.4	57.4
≥ 4000	35.7	<u>54.</u> 5	57.1	59.3	60.8	61.5	61.9	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.1
≥ 3500	39.4	60.6	63.3	65.7	67.2	68.0	68.7	68.8	68.8	68 . 8	68.8	68.8	68.8	68.8	68.8	3.80
≥ 3000	46.1	69.4	72.6	75.5	77.2	78.1	78.9	79.2	79.2	79.4	79.4	79.4	79.4	79.4	79.4	79.4
≥ 2500	49.1	74.4	78.1	81.4	83.3	84.4	85.5	86.1	86.1	86.3	86.4	86.4	86.4	86.4	86.4	86.4
≥ 2000	50.€	78.1	82.4	86.1	88.5	89.7	91.0		91.9	92.2	92.4	92.4	92.4	92.4	92.4	92.4
≥ 1800	50.7	78.6	83.0	86.9	89.4	90.6	92.2	93.2	93.2	93.5	93.7	93.7	93.7	93.7	93.7	93.7
≥ 1500	50.7	79.2	83.8	87.8	90.8	92.4	94.1	95.3	95.3	95.6	95.8	95.8	95.9	95.9	96.0	96.0
≥ 1200	50.9	79.6	84.3	88.3	91.6	93.3	95.2	96.6	96.6	96.9	97.1	97.1	97.2	97.2	97.3	97.3
≥ 1000	51.d	79.9	84.8	88.8	92.2	94.0	96.0	97.6	97.6	98.0	98.2	98.2	98.3	98.3	98.4	98.4
≥ 900	51.0	79.9	84.8	88.9	92.4	94.1	96.2	97.8	97.8	98.3	98.5	98.5	98.6	98.6	98.7	98.7
≥ 800	51.0	79.9	84.8	88.9	92.4	94.3	96.4	98.1	98.1	98.7	98.9	98.9	99.0	99.0	99.2	99.2
≥ 700	51.0	79.9	84.8	89.0	92.5	94.4	96.5	98.3	98.3	98.9	99.2	99.2	99.3	99.3	99.4	99.4
≥ 600	51.0	79.9	84.8	89.0	92.5	94.5	96.6	98.5	98.5	99.1	99.4	99.4	99.5	99.5	99.6	99.6
≥ 500	51.0	80.0	84.9	89.1	92.6	94.6	96.7	98.6	98.6	99.2	99.6	99.6	99.7	99.7	99.8	99.8
≥ 400	51.d	80.0	84.9	89.1	92.6	94.6	96.7	98.6	98.6	99.2	99.6	99.6	99.8	99.8	99.9	99.9
≥ 300	51.0	80.0	84.9	89.1	92.6	94.6	96.7	98.6	98.6	99.3	799.7	99.7	99.8	99.8	99.9	99.9
≥ 200	51.0	80.0	84.9	89.1	92.6	94.6	96.7	98.6			99.7	99.7	99.8	99.8	100.0	10c.c
≥ 100	51.0	80.0	84.9	89.1	92.6			98.6		99.3		99.7			100.0	100.0
≥ 0	51.0	80.0	84.9	89.1	92.6				98.6						100.0	100

TOTAL NUMBER OF OBSERVATIONS....

CEILING VERSUS VISIBILITY

43310 FUKUOKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140L

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ ⅓,	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	15.3 24.2	21.1	22.0 34.0	23.0	23.1 35.1	23.3	23.3 35.5	1	23.3	23.3	23.3	23.3	23.3 35.5		23.3	23.3
≥ 18000 ≥ 16000	24.5	33.3	34.5	35.5	35.6	35.9	36.0	36.0	36.0	36.0	36.0	36.0	36.0 37.2	36.0 37.2	36.0 37.2	36.¢
≥ 14000	25.5 27.5	34.4 36.8	35.6	36.6	36.8	37.1 39.7	37.2	37.2 39.8	37.2	37.2	37.2	39.8	39.8	39.8	39.8	39.8
≥ 12000 ≥ 10000	30.3	40.6	41.9	42.9	43.2	43.5	43.6	43.7	43.7	43.7	43.7	43.7	47.2	43.7	43.7	47.7
≥ 9000 ≥ 8000	33.7	45.6	47.0	48.0	48.4 50.3	48.7	48.9 50.8		49.0 51.0	49.0	49.0 51.0	49.0	49.0 51.0		49.0 51.0	49.0 51.0
≥ 7000	35.7	48.7	50.2	51.3	51.8	52.1	52.4	52.5	52.5	52.5	52.5	52.5 53.4	52.5	52.5	52.5	
≥ 6000 ≥ 5000	36.0 36.7	50.7	51.0 52.4	53.5	54.1	54.4	54.7	54.8	54.8	54 - 8	54.8	54.8	54.8	54.8	54.8	54.8
≥ 4500 ≥ 4000	37.4 42.1	51.9 57.5	53.6 59.3	54.8 60.5	55.3 61.0	55.6 61.3	55.9 61.6	56.0 61.7	56.0 61.7	56.0 61.7	56.0 61.7	61.7	56.0 61.7	56.0 61.7	56.0 61.7	56.0 61.7
≥ 3500 ≥ 3000	47.2 55.9		66.1 78.1	67.5 80.0	68.1 80.6	68.4 81.1	68.7 81.6	68.8 81.8	68.8 81.8	68.8 81.8	68.8 81.8	68.8 81.8	68.8 81.8		68.8 81.8	68.8 81.8
≥ 2500 ≥ 2000	59.5		83.7 86.7	86.2	87.1 91.1	87.6 91.7	88.1 92.3	88.3 92.5	88.3 92.5	88 • 5 92 • 8	88.5 92.8	88.5 92.8	88.5			88.5 92.8
≥ 1800 ≥ 1500	60.8	84.0	87.4	90.7	92.3	92.9	93.4	93.7	93.7	94.0	9/0	94.0	94.0	94.0	94.0	94.0
≥ 1200	60.9	84.9	88•1 88•8	92.3	93.2	95.0	95.7	96.2	95.0	96.8	96.8	96.8	96.8	96.8	96.8	96.8
≥ 1000	61.1	85.2 85.2	89.1 89.1	92.6	94.8	95.8	96.4		96.9	97.6 97.8	97.7 97.8	97.8	97.7	97.7 97.9	97.8	
≥ 800	61.1	85•2 85•3	89.1 89.2	92.8	95.0 95.2	95.9	96.7	97.3 97.5		98 • 1 98 • 4	98.3	98.3	98.4	98.4	98.4	98 • 4
≥ 600	61.1	85.5 85.6	89.4	93.2	95.4 95.6	96.5	97.3	98.0	98.0	99.4		99.2	99.3	99.3	99.3	
≥ 400	61.1	85.6	89.6	93.4	95.6	96.7	97.5	98.4	98.4	99.4	99.6	99.6	99.8	99.8	99.8	99.8
≥ 300 ≥ 200	61.1	85.6 85.6			95.6 95.6			98.4	98.5		99.8		99.9	99.9	100.0 100.0	100.0
≥ 100 ≥ 0	61.1	85.6 85.6	89.6 89.6			-		98.4 98.4				99.8 99.8			100.0 100.0	

TOTAL NUMBER OF OBSERVATIONS___

_1672

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

AND THE PROPERTY OF

ومواضعته ا

.....

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700 HOURS (LST.)

CEILING							VIS	IBILITY (ST	ATUTE MIL	LES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 %	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	13.9	18.4	19.4	20.0	20.1	20.1	20.1	20.1	20.1	20 • 1	20.1	20.1	20.1	20.1	20.2	20.4
≥ 20000	25.9	33.8	35.1	35.9	36.1	36.2				36.2	36.2		36.2			
≥ 18000	26.4	34.9	36.2	37.1	37.3	37.4	37.4	37.4	37.4	37.4	37.4	37.4	37.4		1 - 1	37.5
≥ 16000	27.2	35.8	37.2	38 • 1	38.3		38.4			38.4	38.4	38.4	38.4			38.4
≥ 14000	29.2	38.2	39.7	40.6	40.8	40.9	40.9	40.9	40.9	40 • 9	40.9	40.9	40.9			
≥ 12000	31.7	41.8	43.5	44.6	44.8		44.9	44.9			44.9		44.9			
≥ 10000	33.5	44.6	46.6	47.8	48.C	48.1	48 • 2	48.2	48.2	48 • 2	48.2	48.2	48.2	1	48.2	48 - 2
≥ 9000	34.6	46. g	47.9	49.3	49.5		49.7		49.7	49.7	49.7	49.7	49.7		49.8	
≥ 8000	36.2	48.0	50.0	51.7	51.9	52.1	52.2	52.2	52.2	52.2	52.2	52.2	52.2	1 '	52.2	52.2
≥ 7000	37.7	50 • Q	52.1	54 • C	54.2	54.5	54.8			54.8	54.8	54.8			54.9	54.9
≥ 6000	38.1	50.4	52.5	54.5	54.7	54.9	55.2	55.3		55.3	55.3	55.3	55.3			55 - 3
≥ 5000	39.1	52.2	54.3	56.2	56.4	56.7	51.0	57.0	57.0		57.0					57.1
≥ 4500	40.1	54.0	56.1	58.1	58.3	58.6	58.9	58.9	58.9		58.9	58.9	58.9	_		59.C
≥ 4000	44.7	59.8	62.2	64.3	64.6	64.8	65.1		65.2				65.2		65.2	65.2
≥ 3500	49.3	65.9	68.3	70.8	71.0	71.3	71.7	71.7	71.7	71.7	71.7	71.7	71.8	•	71.8	71.8
≥ 3000	56. q	75.3	78.2	81.0	81.4	81.9						82.5			1	
≥ 2500	58.9	80.1	83.2	86.2	86.9	87.4	l .				88.1	88.1	88.2	1	88.2	88.2
≥ 2000	60.8	83.4	86.8	90.0	91.0	91.6				L			92.8		1	1
≥ 1800	60.9	83.7	87.3	90.5	91.5	92.1	92.6	92.9			53.2	93.2	93.4	1		93.4
≥ 1500	61.2	84.6	88.3	91.9	93.1	93.7	94.4	1		L				1	<u> </u>	
≥ 1200	61.2	84.8	88.7	92.6		94.8		ł		1				97.1		97.1
≥ 1000	61.2	84.8	88.7	92.8	94.4	95.0	95.9	1						1	1	
≥ 900	61.2	84.9	88.8	92.9	94.5	95.2	96.1		96.7	97.5		97.7	97.8	1		
≥ 800	61.2	84.9	88.8	92.9	94.6			<u> </u>	L	1			98.1		98.1	98.1
≥ 700	61.2	84.9	88.8	93.0	94.7	95.5	1				i .			1	98.7	98.7
≥ 600	61.3	85.0	89.0	93.3	95.0	95.9	1	1	98.1	99.0			99.3	1	1	1
≥ 500	61.3	85.2	89.2	93.5	95.2			F .	t	1				1	99.8	
≥ 400	61.3	85.2	89.2			1	97.1							1	1	
≥ 300	61.3	85.2	89.2	93.5	1 -	1			1	1	i		99.9	1	1	
≥ 200	61.3	85.2	89.2				97.1	98.4		1	L				100.0	ii
≥ 100	61.3	85.2	89.2			1	97.1	98.4	1	1	i		1		100.0	- 1
≥ 0	61.3	85.2	89.2	93.5	95.2	96.1	97.1	98.4	98.5	99.6	99.8	99.8	99.9	99.9	100.0	100°C
		4.4														

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE

CEILING VERSUS VISIBILITY

43310

'FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-2000 HOURS (LST)

CEILING							VISI	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥c	≥ 5	≥ 4	≥ 3	≥ 2 ⅓2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ 3/6	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	13.6 23.2	21.0 35.8		22.4 38.1	22.6 38.5	22.7 38.7	22.7 38.9	22.8 39.0			22.8 39.0	22.8 39.0				
≥ 18000 ≥ 16000	23.6 23.9	36.6 37.3	37.7 38.5	38.9 39.7	39.3 40.1	39.5 40.3	39.7 40.5	,	40.6	39.7 40.6	39.7 40.6	39.7 40.6	39.7 40.6		39 .7 40.6	39.7 40.6
≥ 14000 ≥ 12000	25.5 27.5	39.6 43.0	40.9 44.5	42.1 45.9	42.5 46.4	42.8 46.7	43.0 46.9	47.0		43 • 1 47 • 0	43.1 47.0				43.1 47.0	
≥ 10000 ≥ 9000	29.6 30.2			49.3 50.6	49.9 51.2	50.2	50.4	52.0	52.0	52 • 0	50.6 52.0	50.6 52.0	50.6 52.0	52.0		52.0
≥ 8000 ≥ 7000 ≥ 6000	31.2 32.1 33.2	49.3 51.0 52.5	51.4 53.1 54.8	53.4 55.2	54.2 56.0	54.5 56.3	54.8 56.7 58.5		55.0 57.0 58.7	55.0 57.0 58.8	55.0 57.0 58.8	55.0 57.0 58.8	55.0 57.0 58.8	57.0		57.0
≥ 5000 ≥ 5000 ≥ 4500	33.8	53.7	56.1 58.0	58.2	58.9	59.2	59.7	60.0			60.1		60.1	60.1	58.8 6C.1	60.1
≥ 4000 ≥ 3500	37.2	59.5		64.9	65.9	66.4	67.1	67.3	67.3		67.4			67.4		67.4
≥ 3000 ≥ 2500	43.4	69.7 74.6	74.0 79.4	77.4 83.1	78.8 84.6	79.4	80.3 86.1		80.6	81.0						81.0
≥ ,2000	46.7	77.7 78.0	82.8 83.4	86.8	88.6	89.4 90.7	90.7	91.4	91.4		91.9	92.0	92.0	92.0 93.4		92.0
≥ 1500 ≥ 1200	47.0 47.0	78.7 79.1	85.0	89.5 90.1	91.4	92.5	93.8	94.6	95.6	95 • 2 96 • 2	95.2 96.2	95.3	96.3	95.3 96.3	95.3	
≥ 1000	47.1	79.2	85.5	90.4	92.6	94.0	95.5	-				97.5 97.5	97.5	97.5	97.5	97.5
≥ 800 ≥ 700 ≥ 600	47.1 47.1 47.1	79.5 79.5 79.5	85.8	91.0	93.2 93.4	94.4 94.4 94.6	95.8 95.9 96.1		97.2	98.1	98.3	98.1 98.4 98.9	98.3		98.3 98.6 99.2	98.6
≥ 500 ≥ 400	47.1 47.1	79.7 79.7	85.9 86.3 86.3	91.5 91.5	93.8	95.0	96.5	98.0		99.2	99.3	99.5	99.1 99.7 99.8	99.7	99.8	
≥ 300 ≥ 200	47.1 47.1	79.7 79.7	86.4 86.4	91.6	93.9	95.2	96.6	98.1	98.2 98.2	99.5	99.6	99.7	99.9	99.9	100.0	100.3
≥ 100 ≥ 0	47.1 47.1	79.7 79.7	86.4 86.4	91.6 91.6		95.2 95.2	96.6		98.2 98.2			99.7 99.7	99.9 99.9		100.0 100.0	

TOTAL NUMBER OF OBSERVATIONS_

1671

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-2300

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ ¾	≥ %	≥ ½	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	16.1	36.3 43.7		40.5					41.1		41.1			41.1 50.7		
≥ 18000 ≥ 16000	19.7	44.2	47.5	50.1 50.4		50.9	51.1	51.2	51.2	51.2		51.2 51.5		51.2	51.2 51.5	51.2
≥ 14000 ≥ 12000	2C.6	46.6		52.9 55.5		53.8	54.0	54.0		54.0 56.7		54.0 56.7	54.0 56.7	54.0	54.C 56.7	54.
≥ 10000 ≥ 9000	23.2	51.7 52.4	55.8	58.9	59.8	59.8	60.1	60.2		60.2	60.2	60.2	60.2	60.2	60.2	65.4
≥ 8000 ≥ 7000	23.6	53.7	58.3	61.8	62.9	63.0	63.3	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4
≥ 6000 ≥ 5000	24.3	55.4	60.3		65.1		65.4	65.5	65.5	65.6	65.6	65.6	65.6	65.6	65.6	
≥ 4500 ≥ 4000	25.1 25.9	58.1 60.4	63.3	67.2	68.3	68.4		68.8	68.8	68.9 72.2	68.9	68.9 72.2	68.9	68.9	63.9 72.2	68.9 72.2
≥ 3500 ≥ 3000	27.3 29.7	64.2		74.7 80.9	76.1	76.3	76.7 83.7	76.8	76.8	76.9 83.9		76.9 83.9	76.9 83.9	76.9		
≥ 2500 ≥ 2000	30.5 30.8	72.9 75.9	79.5 82.7	85.C 88.4		87.4	88.3			88.6 92.6		88.6 92.6	88.6 92.6		88.6 92.6	
≥ 1800 ≥ 1500	30.8 31.0		83.5 84.8	89 • 2 90 • 7		1	92.8	93.1 95.0		93.5 95.5		93.5 95.5	93.5		93.5	
≥ 1200 ≥ 1000	31.2		86 • 1 86 • 4	92 • 2 92 • 5	94.5	95.2	96.5	96.9 97.3		97.4 97.8		97.5 97.9	97.5		97.5 97.9	
≥ 900 ≥ 800	31.2			93.C 93.4	95.4 95.8	_	97.5 97.8		97.9 98.3	98 • 4 98 • 8	98.5 98.9	98.5 98.9	98.5 98.9		98.5 98.9	
≥ 700 ≥ 600	31.2		87.1 87.3	93.6 93.7			98.3 98.5		98.7 98.9	99.2 99.5				- 1	99.3 99.6	
≥ 500 ≥ 400	31.3	+ -							99.0 99.0			99.6 99.6				
≥ 300 ≥ 200	31.4 31.4		87.4 87.5	_		97.1	98.7	99.2	99.2 99.3	99.8	99.9	99.9	99.9		99.9	99.9
≥ 100 ≥ 0	31.4		87.6 87.6						99.3							

TOTAL NUMBER OF OBSERVATIONS_

DATA PROCESSING CIVISION ETAC. USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0000-020.

CEILING							VISI	B ' a f (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥4		≥ 2 ⅓,	≥ 2	≥ 1 ⅓	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	14.9	46.3 52.2		52.7 62.4	53.5 64.0	53.6 64.1	53.8 64.3			53.8 64.5		-,	53.8 64.5	-	53.8 64.5	53.8
≥ 18000	17.4	52.4	59.1	62.7	64.2	64.3	64.6		64.6		64.8	64.8				64.8
≥ 16000	17.6	53.0	59.7	63.3	64.8	64.9	65.2		65.2	65.4	65.4	_			65.4	65.4
≥ 14000	18.C	54.5	61.5		67.1	67.2	67.4	67.5	67.5	67.6	67.6					67.6
≥ 12000	19.1	56.4	63.3	67.3	69.4	69.5	69.7	69.8	69.8	69.9	69.9	69.9	69.9	: 1	69.9	69.9
≥ 10000	20.2	59.1	66.4	70.8	73.1	73.3	73.6	73.7	73.7	73.8	73.8	73.8	73.8	73.8	73.8	13.8
≥ 9000	20.5	59.8	67.6	72.0	74.3	74.6	74.9	75.0	75.0	75.1	75.1	75.1	75.1	75.1	75.1	75.1
≥ 8000	20.7	60.8	68.9	73.5	75.8	76.2	76.5	76.5	76.5	76.6	76.6	76.6	76.6	76.6	76.6	76.6
≥ 7000	21.2	62.5	70.7	75.3	77.7	78.1	78.4		78.6	78.7	78.7	78.7	78.7	78.7	78.7	78.7
≥ 6000	21.3	63.1	71.4	76.1	78.5	78.9	79.2		79.3	79.5	79.5	79.5		: 1	79.5	79.5
≥ 5000	21.5	64.5	72.8	77.5	79.9	80.3	80.6		80.8		80.9			·	80.9	67.9
≥ 4500 ≥ 4000	21.7	65.5	73.9	78.7	81.1	81.5	81.9	_	82.0	82.1	82.1	82.1	82.1	82.1	82.1	82.1
	22.2	68.0	76.6	81.5	83.9	84.3	84.7		84.8	8 * • 9	84.9	84.9			84.9	84.9
≥ 3500 ≥ 3000	22.5	70.4	79.6	84.5	87.0	87.5	87.9		88.1	88.2	88 • 2		88.2		88.2	88 - 2
≥ 2500	23.6	74.6	82.3	89.2	90.1	90.6	91.2			91.5	91.5	91.5 93.7	91.5	91.5	91.5	93.7
≥ 2000	24.3	76.5	86.2	91.5	94.7	- 1	95.9		96.1	76.2	96.2		96.2	1	96.2	96.2
≥ 1800	24.3	76.6	86.3	91.6	94.9			96.4			96.5		96.5		·	96.5
≥ 1500	24.3	76.6	86.4			95.7	_			96.7	96.7		96.7		96.7	96.7
≥ 1200	24.3	77.1	87.0		96.2	97.0				-	98.0					98.0
≥ 1000	24.3	77.5	87.7	93.3	97.1	97.8	98.7	98.9	98.9	99.2	99.2	99.2	99.2	99.2		99.2
≥ 900	24.3	77.5	87.8	93.5	97.3	98.0	98.9	99.0	99.	99.3	99.3	99.3	99.3	99.3	99.3	99.3
_≥ _600_	24.3	77.5	87.9	93.6				99.2		99.5		99.5	99.5	99.5	99.5	99.5
≥ 700	24.3	77.7	88.1	93.7	97.6			99.4		99.7			99.7			99.7
≥ 600	24.3									+	99.8					99.8
≥ 500 ≥ 400	24.3	77.7	88.1	93.8						-					99.9	
	24.3		88.2						97.6						10C-0	
≥ 300 ≥ 200	24.3	77.7	88.2					99.6							100.0	
	24.3	77.7	88.2									_			10C.0	
≥ 100 ≥ 0	24.3							99.6	ı						100.0	
L	E 7 6 31	1101)	30.2	77.07	7100	70.0	7767	77.0	7760	77.7	10000	1000	100.0	1100.0	<u> </u>	* 00 • F

DATA PROCESSING DIVISION ELAC. USAF ASFEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

AUG

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-050

CEILING	 -						VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥: 0
NO CEILING	10.9	42.0	47.0	50.1	51.3	51.5	51.9	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
≥ 20000	12.4	46.2		57.6			60.7				61.1		61.1	61.1	61.1	61.1
≥ 18000	12.5	46.6		58.0	60.4	60.7	61.1	ì '	61.3	61.6	61.6	61.6	61.6	61.6	61.6	61.6
≥ 16000	12.7	46.9	54.0	58.4			61.5		61.7	61.9	61.9		61.9	61.9	61.9	61.9
≥ 14000	13.5	48.8	56.2	60.5		63.3	63.7	63.9	63.9	64.1	64.1	64.1	64.1	64.1	64.1	64-1
≥ 12000	14.0	50.3		62.5			65.8		65.9		66.2		66.2	66.2	66.2	66.2
≥ 10000	14.9	53.q	60.7	66.0	68.9		69.6		69.8	70.1	70-1	70.1	70.1	70-1	70.1	70.1
≥ 9000	15.2			67.1	70.0		70.8				71.2		71.2	71.2	71.2	11.č
≥ 8000	15.4	55.2	63.2	68.7	71.7	72.0	72.4		72.6		72.9	72.9	72.9	72.9	72.9	72.9
≥ 7000	16.1	56.2	·				73.6				74.0					74.0
≥ 6000	16.4	57.3	65.4	-		74.4	74.8			75.3	75.3		75.3	75.3	75.3	
≥ 5000	16.8	59.0	67.2	72.9	75.9		76.7		76.9	77.2	77.2			77.2	77.2	77.2
≥ 4500	16.9	60.2	68.4				78.2	78.4	78.4	78.6	78.6					1
≥ 4000	17.3	63.2	71.8	77.8			81.9		82.1	82.4	82.4					
≥ 3500	17.6		74.5	80.8		84.6			85.4	85.7	85.7	85.7	85.7	85.7	85.7	85 - 7
≥ 3000	18.6		78.5							90.2	90.2	90.2	90.2		90.2	30.2
≥ 2500	18.9			87.1		91.1	91.8		92.1	92.3	92.3			1	92.3	1 1
≥ 2000	19.1	72.4	82.4		93.3	93.7	94.7				95.2	95.2		95.2	95.2	95.2
≥ 1800	19.1		82.5	89.6		-	95.1	95.3	95.3						ľ	95.€
≥ 1500	19.1	72.8	83.0	ر 90	94.5	95.0	96.0	96.2	96.2	96.5					96.5	
≥ 1200	19.1	73.3	83.6	91.2	95.6	96.2	97.5	97.8	97.8	98.1	98.1	98.1	98.1	98.1	98.1	98 • 1
≥ 1000	19.1	73.8		91.9	96.3		98.3	1								
≥ 900	19.1	73.8	84.2	92.0	96.5	97.1	98.4	98.8	98.8	99.1	99.1	,	99.1	99.1	99.1	99.1
≥ 800	19.1	73.9	84.3		96.6							99.3				
≥ 700	19.1	73.9	84.3	92.2	96.7	97.4	,	1	99.0	1)		1	99.5	1 1
≥ 600	19.1	73.9	84.3		96.8		98.8						1			
≥ 500	19.1	73.9	84.3	92.2	96.8	97.5	98.9	99.4	99.4	99.8	99.8	99.8	99.8	99.8	99.9	99•4
≥ 400	19.1	73.9	84.3	92.2			98.9	99.4					<u> </u>			
≥ 300	19.1	73.9	84.3	92.2	96.8	97.5	98.9		1		1	1	1	\$	1	• •
≥ 200	19.1	73.9	84.3	92.2	96.8	97.5	98.9	99.5	99.5			99.8	99.9			
≥ 100	19.1	73.9	84.3	92.2	95.8	97.5	98.9	99.5		1 -					1	1 1
≥ 0	19.1	73.9	84.3	92.2	96.8	97.5	98.9	99.5	99.5	99.9	99.9	99.9	99.9	99.9	100.0	noc.c

TOTAL NUMBER OF OBSERVATIONS_

_1673

CAIA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

> minumenta in posta

CEILING VERSUS VISIBILITY

4331C FUKUCKA KYUSHU JAPAN/I TAZUKE AB
STATION NAME

47-64

AUG

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-080.

CEILING !							VISI	BILITY (ST	ATUTE MIL	FS)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓,	≥ 2	≥ 1 %	≥1%	≥1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	11.7	28٠ د	33.3			- 1	- 1	43.7	-	1			44.0	1	44.0	
≥ 20000	15.7	36.7	43.2	47.6	52.2	53.6	55.9	57.6					58.2		58.2	
≥ 18000	15.7	36.9	43.4	47.1	52.3	53.7	56.0	57.7	57.8	58 . 2	58.3	58.3	58.4	58.4	58.4	
≥ 16000	16.1	37.5	44.1	48.7	53.3	54.8	57.1	58.8	58.8	59.3	59.4	59.4	59.4	59.4	59.4	59.4
≥ 14000	17.3	39.8	46.8	51.6	56.3	57.8	60.2	61.9	62.0	62.5	62.6	62.6	62.7	62.7	52.7	62.1
≥ 12000	18.5	42.1	49.6	54.9	59.8	61.4	64.0	65.9	65.9	66.5	66.5	66.5	66.6	66.6	66.6	66 • t
≥ 10000	19.4	44.3	52.1	57.5	62.6	64.2	67.1	69.0	69.1	69.7	69.8	69.8	69.8	69.8	69.8	69.8
≥ 9000	19.6	44.9	52.7	58.2	63.6	65.2	68.1	70.1	70.1	70.8	70.9	70.9	71.0	71.0	71.0	71.0
≥ 8000	20.5	46.8	55.0	60.8	66.2	67.9	70.9	72.9	72.9	73.6	73.8	73.8	73.8	73.8	73.8	73.8
≥ 7000	20.9	47.4	55.9	61.8	67.2	68.9	71.9	73.9	74.0	74.6	74.9	74.9	74.9	74.9	74.9	74.5
≥ 6000	21.3	48.1	56.7	62.5	68.0	69.7	72.8	74.7	74.8	75.4	75.7	75.7	75.7	75.7	75.7	75.7
≥ 5000	21.7	49.0	57.6	63.7	69.3	71.1	74.3	76.5	76.6	77.2	77.5	77.5	77.5	77.5	77.5	77.5
≥ 4500	22.2	49.9	58.7	64.9	70.5	72.4	75.6	77.8	77.8	78.5	78.7	78.7	78.8	78.8	78.8	78.8
≥ 4000	22.8	52.6	61.5	67.9	73.7	75.5	78.9	81.3	81.4	82.0	82.3	82.3	82.4	82.4	82.4	82.4
≥ 3500	23.5	54.2	63.2	69.7	75.9	77.7	81.2	83.7	83.8	84.5	84.8	84.8	84.8	84.8	84.8	84.8
≥ 3000	25.0	57.3	66.5	73.2	79.7	81.7	85.5	88.2	88.4	89.0	89.3	89.3	89.4	89.4	89.4	89.4
≥ 2500	25.8	59.8	69.1	76.4	83.0	85.1	89.1	91.8	92.1	92.7	93.1	93.1	93.1	93.1	93.1	93.1
≥ 2000	25.9	60.9	70.6	78.2	85.1	87.3	91.3	94.2	94.4	95 . 1	95.5	95.5	95.6	95.6	95.6	95.6
≥ 1800	25.9	61.2	70.8	78.4	85.4	87.6	91.6	94.5	94.7	95.4	95.8	95.8	95.9	95.9	95.9	95.9
≥ 1500	26.1	61.6	71.4	79.3	86.5	88.7	93.0	96.0	96.3	97.0	97.4	97.4	97.5	97.5	97.5	97.5
≥ 1200	26.2	61.8	71.7	79.7	87.0	89.2	93.5	96.7	97.0	97.6	98.1	98.1	98.1	98.1	98.1	98.1
≥ 1000	26.2	61.9	71.9	79.9	87.3	89.5	93.9	97.1	97.4	98.1	98.6	98.6	98.7	98.7	98.7	98.7
≥ 900	26.2	61.9	71.9	79.9	87.3	89.6	94.0	97.3	97.6	98.4	98.9	98.9	99.0	99.0	99.0	99.0
≥ 800	26.2	62.1	72.0	80.0	87.5	89.7	94.1	97.5	97.8	98.6	99.2	99.2	99.2	99.2	99.2	99.4
≥ 700	26.2	62.1	72.0	80.0	87.5	89.8	94.2	97.6	97.8	98.7	99.2	99.2	99.3	99.3	99.3	99.3
≥ 600	26.2	62.1	72.0	80.0	87.5	89.8	94.2	97.7	98.0	98.9	99.4	99.4	99.5	99.5	99.5	99.5
≥ 500	26.2	62.1	72.0	80.0	87.5	89.8	94.2	97.7	98.0	99.0	99.5	99.5	99.6	99.6	99.6	99.6
≥ 400	26.2	62.1	72.0	80.0	87.5	89.8	94.2	97.7	98.0	99.0	99.6	99.6	99.7	99.7	99.7	99.8
≥ 300	26.2	62.1	72.0	80.0	87.5	89.8	94.2	97.7	98.0	99.0	99.6	49.6	99.7	99.7	99.7	99.8
≥ 200	26.2	62.1	72.0	80.0	87.6	89.8	94.3	97.8	98.1	99.1	99.7	99.7	99.8	99.8	99.8	99.4
≥ 100	26.2	62.1	72.0	80.0	87.6	89.8	94.3	97.8	98.1	99.1	99.7	99.7	99.8	99.8	99.8	100.0
≥ 0	26.2	62.1	72.0	80.0	87.6	89.8	94.3	97.8	98.1	99.1	99.7	99.7	99.8	99.8	99.8	100.0

TOTAL NUMBER OF OBSERVATIONS 167

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE DESOLETE

DATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 288C1

- Con Marie Commen

CEILING VERSUS VISIBILITY

11

FUKUCKA KYUSHU JAPAN/LTAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-110.

LEILING						*************	VIS	BILITY (ST.	P.TUTE MIL	.ES)						
€EET)	≥ 10	> 6	≥ 5	≥4	≥ 3	≥ 21/2	≥ 2	≥1%	≥11/4	≥ 1	≥ ¾	≥ %	> 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	17.3 26.5	32.1 46.3	33.9 48.6	36 • 7 52 • 5	37.6 54.2	38.1 54.8	38.3 55.1	-	38.4 55.3	38.5 55.4	38.5 55.4	38.5 55.4			38.5 55.4	38 · 6
≥ 1800. ≥ 1600u	27.0 27.7	47.0	49.3 50.5	53.2 54.5	54.9 56.2	55.6 56.8		56.0 57.3	56.0 57.3		56.2 57.4	56.2 57.4	56.2 57.4	56.2 57.4	56.2 57.4	56.2 57.5
≥ 14000 ≥ 12000	31.3	50.8 53.6	53.5 56.4	57.4	59.1 62.2	59.9 63.0		· 1	60.5	1	ž.	60.5		1 . 1	1	6C.6
≥ 10000 ≥ 9000	33.4	56.8 57.8	59.9 60.9	64.2	66.C	60.8			67.3 68.3	i	67.4			67.4 68.5	67.4 68.5	67.5 68.5
> 8000 ≥ 7000	35.1 36.3	59.7 61.1	63.0	67.3	69.3 71.0	70.1	70.4 72.2		70.6 72.3		70.7 72.5	70.7 72.5	70.7		70.7 72.5	7(• o 72 • ɔ
≥ 6000 ≥ 5000	36.6 37.0	61.9	65.3 66.7	69.7 71.2	71.9 73.4	72.8 74.3			73.4 75.0	73.5 75.1	73.5 75.1	73.5 75.1	73.5 75.1	73.5 75.1	73.5 75.1	73.C 15.2
≥ 4500 ≥ 4000	37.5 3°.0	63.9 66.4	67.4 70.0	72.0 74.7	74.1 76.9	75.1 77.9	75.5 78.3		75.9 78.7	78.8	76.0 78.8		76.0 78.8	78.8	76.0 78.8	76.u 78.9
≥ 3500 ≥ 3000	44.6	75.1	72.8 79.1	77.7 84.3	79.9 86.9	80.9 87.9	88.4	88.7	81.7 88.7	88.9		81.8		88.9	81.8 88.9	88.9
≥ 2500 ≥ 2000	46.8	80.7	82.9 85.2	91.2	91.2		95.7	96.2	93.3 96.4	93.5	96.5	96.5	96.6	96.6	93.5 96.6	93.6
≥ 1800	47.8	81.6		91.8	94.6 95.2	96.4	97.3	97.8			97.1 98.1	97.1 98.1	97.2 98.1	98.1	97.2 98.1	97.3 98.2
≥ 120° ≥ 1000	48.1		86.6 86.8	93.0	95.7 95.9		98.1	98.7	98.8	99.0				99.0	98.8	
≥ 900 ≥ 800	48.1	82.1		93.0		97.3	98.2			99.2	99.3	99.3	99.3		99.1	99.4
≥ 700 ≥ 600	48.1	82. l	86.9	93.0			98.4	99.1	99.3	99.5		99.6	99.7	99.7	99.7	99.8
≥ 500 ≥ 400	48.1	82.1	86.9	93.1	96.1		98.4	99.2	99.4	99.6	99.8	99.8	99.8	99.8		1 1
≥ 300 ≥ 200	48.1	82.1	86.9	93.1	96.1	97.4	98.5		99.5	99.8	99.9	99.9	99.9	99.9	99.9	100 · c
≥ 100 ≥ 0	48.1	82.1	1	93.1	96.1 96.1	1			1	99.8	1 1	1	99.9	1	1	100.0

TOTAL NUMBER OF OBSERVATIONS__

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/1 TAZUKE AB

47-64

AUS

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140c

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	2C.7	29.9 49.1	31.9	32.7	33.1 53.4	33.1 53.6	33.1	33.1 53.7	33.1 53.7	33.1 53.7	33.1 53.7	33.1 53.7	33.1 53.7	33.1 53.7	33.1 53.7	33.1 53.1
≥ 18000 ≥ 16000	35.4 35.9	50.1 50.7	52.5 53.4	53.7	54.5 55.3	54.6 55.5	54.7 55.5	54.7 55.5	54.7 55.5	54 • 7 55 • 5	54.7 55.5	54.7 55.5	54.7 55.5	54.7 55.5	54.7 55.5	54.7
≥ 14000 ≥ 12000	37.7	53.3	56.0	57.1	57.9	58.1	58.2	58.2	58.2	58 • 2	58.2	58.2	58.2	58.2	58.2	58.2 6(.3
≥ 10000	39.3 40.8	56.0 58.5	61.3	59.8	63.2	63.4	60.8	63.5	63.5	60.8	63.5	63.5	63.5	63.5	63.5	63.5
≥ 9000	41.3	59.3 60.8		64.8	65.6	65.8	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.3
≥ 7000 ≥ 6000	43.4	62.8		65.9	66.8	67.0	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1 68.1	67.1	67.1
≥ 5000 ≥ 4500	44.8	64.3	67.4	68.6	69.5 70.5	69.6	69.8	69.8 70.9	69.8		69.8	69.8				69.8 70.5
≥ 4000 ≥ 3500	49.1 52.2	70.0	73.3 78.1	74.5	75.4	75.7 80.5	75.9 80.8	75.9 80.8	75.9 80.8	75 • 9 80 • 8	75.9 80.8	75.9 80.8				
≥ 3000 ≥ 2500	58.4	82.5 86.0		87.6 91.5	88.6	88.9 93.0	89.2		89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
≥ 2000	61.5	88.1	92.3	94.1	95.5	95.8	96.2	96.3	96.3	96.4	96.4	96.4	96.4	96.4	96.4	96.4
≥ 1800 ≥ 1500	61.6	88.2 88.6	92.9	94.4	95.7	96.1 96.8	96.4	96.6	96.6 97.3	97.4	96.7 97.4	96.7				97.4
≥ 1200 ≥ 1000	61.8 61.9	88.8 88.9	93.3	95.1 95.3	96.7 97.1	97.2 97.5	97.5 98.0	98.3	97.8 98.4	98.6	98.0 98.8	98.0 98.8	98.8	98.8	98.8	
≥ 900 ≥ 800	61.9	88.9 88.9		95.5 95.5	97.3 97.4		98.2 98.3	98.7 98.9	98.9 99.0	99.2	99.2 99.4	99.2 99.4	99.2 99.4	99.4		
≥ 700 ≥ 600	61.9	88.9 88.9		95.5 95.5	97.5 97.5		98 • 4 98 • 4		99.2 99.2			99.6	1	f		_
≥ 500 ≥ 400	61.9	88.9 88.9		95.5 95.6	97.5	98.0 98.1	98.5 98.6		99.2		99.7 99.8	99.7	99.8			99.8
≥ 300 ≥ 200	61.9			95.6 95.6	97.7	98.2	98.7	99.3			99.9			100.0	1	
≥ 100 ≥ 0	61.9	89.0		95.6		98.2 98.2	98.7		99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0 100.0

TOTAL NUMBER OF OBSERVATIONS_______167

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-170t

CEILING				·			VIS	BILITY (ST	ATUTE MIL	LES)					·	
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/3	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	22.4 35.2	29.0 47.4	30.2 49.3	30 · 9 50 · 1	31.2 50.4	31.2 50.4	31 · 2 50 · 4	31.2 50.4	31.2 50.4	31 · 2 50 · 4	31.2 50.4	31.2 50.4	31.2 50.4	31.2 50.4	31.2 50.4	31.2 50.4
≥ 18000	36.0	48.3	50.3	51.1	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4
≥ 16000	36.4	49.0	51.0	51.8		52.1	52.1		52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
≥ 14000	38.5	52.0	54.2	55.0		55.3	55.3	1	55.3	55.3	55.3		55.3	55.3	55.3	55.3
≥ 12000	40.5	54.7	57.2	58.0		58.3			58.3	58.3	58.3		58.3		58.3	56.3
≥ 10000 ≥ 9000	42.6	57.6	60.2	61.0	61.3	61.4	61.5	1	61.5	61.5	61.5	1	61.5	61.5	61.5	61.5
ļ	43.0	58.6	61.3	62.1	62.5	62.5			62.6	62.6	62.6				62-6	62.6
≥ 8000 ≥ 7000	43.6	60.Q	62.8 63.8	63.6	64.0	64.0	64.1		64.2	64.2	64.2		64.2	64.2	64.2	64.2
≥ 6000	45.2	62.2	65.1	65.8		65.1	66.4		66.4	65 • 2	65.2	65.2	65.2	65.2	66.4	66.4
≥ 5000	46.7	64.3	67.3	68.1		68.5			68.7	68.7	68.7		68.7	68.7	68.7	68.7
≥ 4500	46.9	64.9	67.9	68.7	69.1	69.3		69.4	69.4	69.4	69.4		69.4	69.4	69.4	69.4
≥ 4000	50.2	69.6	72.7	73.5		74.2	74.3			74.4	74.4			,		74.4
≥ 3500	54.6	75.9	79.2	80.1		80.9	81.0		81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1
≥ 3000	59.3	82.7	86.7	87.9	88.8	89.0				89.4	89.4	89.4	89.4		89.4	89.4
≥ 2500	61.4	86.0	90.2	91.8	92.8	93.0	93.5	93.6	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
≥ 2000	62.1	87.6	92.1	93.9		95.4	96.0	96.2	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥ 1800	62.1	87.8	92.3	94.1	95.3	95.6		96.3	1	96.5	96.5		96.5		96.5	96.5
≥ 1500	62.2	88.1	92.7	94.9		96.5				97.5	97.5				97.5	97.5
≥ 1200	62.2	88.4	93.3	95.6		97.3			98.2	98 • 4	98.4		98.4		7 1	98 • 4
≥ 1000	62.2			95.9		97.8					99.5					99.6
≥ 900 ≥ 800	62.2	88.4		95.9		97.9	The state of the s			99.5	99.6				99.7	99.7
≥ 700	62.2	88.4 88.4	93.5		97.6 97.6	97.9			99.1	99.5	99.6		99.6			99.7
≥ 600	62.2				97.6			99.0			99.6		99.7		j _ I	
≥ 500	62.2				97.6				99.2							
≥ 400	62.2				97.6			99.0			99.8				99.9	
≥ 300	62.2								99.2				99.9		100.0	
≥ 200	62.2	88.4	93.5		97.6		1		,					1	100.0	icc.cl
≥ 100	62.2	88.4	93.5	95.9	97.6	97.9	98.6	99.0	99.2	99.6	99.8	99.8	99.9	99.9	100.0	100.0
≥ 0	62.2	88.4	93.5	95.9	97.6	97.9	98.6	99.0	99.2	99.6	99.8	99.8	99.9	99.9	100.0	toc.cl

TOTAL NUMBER OF OBSERVATIONS_

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUGKA KYUSHU JAPAN/I TAZUKE AB 47-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-2000 HOURS (LST)

CEILING				•			VISI	BILITY (ST	ATUTE MILI	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	19.4 30.3	29.4 47.1	30.7 49.6	32 • 2 52 • 0	32.8 53.0	33.1 53.4	33.3	33.3 53.7	33.3 53.7	33.3 53.7	33.3 53.7	33.3	33.3 53.7	1	33.3 53.7	' '
≥ 18000 ≥ 16000	30.6	47.7	50.3 51.0	52.6	53.7 54.3	54.1	54.3	54.4 55.0	54.4	54.4	54.4	54.4	54.4 55.0	54.4	54.4 55.0	54.4 55.L
≥ 14000 ≥ 12000	32.5 34.2	51.4 53.6	54.4 57.1	56.9 59.7	58.2 61.0	58.6 61.4	58.8 61.8	58.9 61.9		58.9 61.9	58.9	58.9 61.9	58.9 61.9	58.9	58.9 61.9	58.9 61.9
≥ 10000 ≥ 9000	34.7 35.3	55.2 56.3	58.9 60.1	61.8	63.1 64.3	63.5	64.0 65.3	64•2 65•5	64.2 65.5	64 · 2 65 · 5	64.2 65.5	64.2 6: .5	64.2 65.5	64•2 65•5	64.2 65.5	64.2 65.5
≥ 8000 ≥ 7000	35.9 36.2	57.9 58.6	61.7 62.6	64.7 65.8	66.1 67.3	66.6 67.8	67.2 68.4	67.6 68.8	67.6 68.8	67.6 68.8		61.6	67.6 68.8			
≥ 6000 ≥ 5000	36.8 37.2			66.5 68.3	68.2 70.1	68.7 70.7	71.4	69.7 71.8	69.7 71.8	69.7 71.8		71.8	69.7 71.8	71.8	69.7 71.8	
≥ 4500 ≥ 4000	37.2 39.6	65.9	70.1	68.8 73.4	70.7 75.4		76.7		72.3 77.2	72.4 77.3	77.3	77.3	72.4	77.3	77.3	17.3
≥ 3500 ≥ 3000	41.8 44.5	75.1	74.3 79.9	77.7 83.6	79.9 86.1	<u>80. 8</u>	87.6	88.2	81.8 88.2	81.9 88.3	88.3			88.3	88.3	88.3
≥ 2500 ≥ 2000	46.0 46.3	80.C	83.9 85.6	87.8 89.7	90.3	93.2		92.6	92.6	92.7	95.0	92.7 95.0				
≥ 1800 ≥ 1500	46.5		86.2 86.5	90.6	93.9	95.0	96.1	96.7	95.9 96.8	96.0 97.1	97.2	97.2	97.2	97.2		97.2
≥ 1200 ≥ 1000	46.5		86.7 86.9	91.5	94.4			97.2 97.9		97.6 98.4	98.6		97.7 98.6 98.9		97.7 98.6 98.9	98.6
≥ 900 ≥ 800 ≥ 700	46.5 46.5	81.2	86.9 87.0	91.9 92.1 92.1	95.0 95.3 95.4				98.2 98.7 98.7	98 • 8 99 • 3	99.4	98.9 99.4 99.5	99.4	99.4		99.4
≥ 600 ≥ 500	46.5	81.2	87.0		95.4	96.6	97.8		98.9	99.5	99.7	99.7	99.7	99.7	99.7	99.7
≥ 400	46.5	81.3	87.1	92.1	95.5	96.6	97.8	98.9		99.6	99.9	99.9	99.9	99.9	99.9	99.9
≥ 200	46.5	81.3	87.1	92.1	95.5	96.6	97.8	98.9	99.0	99.6	99.9	99.9	99.9	99.9	99.9	99.9 100.6
≥ 0	46.5			92.1			97.8		99.0							100.0

TOTAL NUMBER OF OBSERVATIONS__

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

AUG

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-230c

CEILING							VISI	BILITY (ST.	ATUTE MIL	.ES)			***************************************			
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ½	≥ 2	≥ 1 ½	≥1%	≥ 1	≥ ¾	≥ 5%	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	18.0 21.8	45.0 55.6	47.0 59.4	49.5	50.9 65.7	51.0 65.9	51.3 66.4	51.3 66.4	51.3 66.4			51.3 66.4	51.3 66.4	51.3 66.4	51.3 66.4	
≥ 18000 ≥ 16000	22.0	56.1 56.7	59.9 60.5	64.1	66.2 66.8		66.9 67.5	67.6	67.0 67.6		67.0 67.6	67.0 67.6	67.0 67.6		67.0 67.6	67.0 67.6
≥ 14000 ≥ 12000	22.6	57.9 59.2	62.0 63.7	66.5 68.3	68.8 70.8		71.5	69.5 71.5	69.5 71.5	71.5	71.5	t t	69.5 71.5	69.5 71.5	69.5 71.5	69.5 71.5
≥ 10000 ≥ 9000	23.9 24.1	60.6	65•4 66•5	70 · 1 71 · 2	72.8 74.0	74.2	73.5 74.7	73.5 74.7		73.5 74.7	74.7	73.5	73.5 74.7	73.5	74.7	74.1
≥ 8000 ≥ 7000	24.5	63.9	68.5 69.5	73.3	76.2	77.9		77.0	78.4	77.0 78.4	78.4	78.4	78.4	78.4	78.4	78.4
≥ 6000 ≥ 5000	25.1 25.7	66.7	70.7 72.4	75.7		81.0				81.6	81.6	81.6			81.6	81.6
≥ 4500 ≥ 4000 ≥ 3500	25.9 26.7 27.0	70.6	73.8 76.7 78.5	79.1 82.0 84.1	82.2 85.1 87.4	85.5	86.0		83.1 86.1 88.5	86.1	86.1		83.1 86.1 88.5			86.1
≥ 3000	27.6	74.7		87.3 89.7	1	91.0	91.8	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
≥ 2000 ≥ 1800	28.9	78.3	85.2 85.8	91.4		95.3	96.2		96.4	96.4	96.4			96.4	96.4	96.4
≥ 1500 ≥ 1200	29.3	79.1	86.2	92.7	96.2 97.0	96.8	97.7	97.8		97.9	97.9		97.9	97.9	97.9	
≥ 1000	29.3		87.2 87.3	93.8			98.9 99.0		99.2			99.4				
≥ 800	29.3 29.3		87.3 87.3	93.9	97.5		99.2	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6
≥ 600 ≥ 500	29.3	80.1	87.3 87.3	94.0	97.6	1	99.3		99.6	99.9		99.9	99.9	99.8	99.9	99.9
≥ 400	29.3	80.1	87.3 87.3	94.0	97.6		99.5	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	۱ I
≥ 200 ≥ 100 ≥ 0	29.3	80.1	87.3	94.0	97.6	98.4	99.5	99.8	99.8	100.0	100.0	100.0	100.0		100.0	100.0
L	1 29.3	80.1	87.3	94.0	97.6	98.4	99.5	99.8	99.8	100.0	1100.0	100.0	100.0	1.00.0	100 · C	100.

TOTAL NUMBER OF OBSERVATIONS 1

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

wante Climb & S. c. Z

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0000-0206

CEILING							VIS	BILITY (ST.	ATUTE MIL	LES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	9.8	37.0	40.7	43.2	43.9		44.2	١ .	44.3		44.4	44.4	44.4	44.4	44.4	44.4
≥ 20000	11.2	42.4	47.1	51.0	52.2	52.6		52.8		52.9	52.9	52.9	52.9		52.9	52.9
≥ 18000	11.3	42.8	47.6	51.5	52.7	53.0		53.3	53.3		53.4	53.4	53.4		53.4	53.4
≥ 16000	11.4	43.3	48.1	52.2	53.4			54.0			54.1		54-1	54.1	54.1	54.1
≥ 14000 ≥ 12000	12.g	45.2	50.4	54.5	55.7	56.1			56.3		56.4	56.4		56.4		56.4
	12.7	47.9	53.4	57.8	59.2	59.6			59.8		59.9				.59.9	59.3
≥ 10000 ≥ 9000	13.0	52.0	58.1	62.9	64.5	64.8		65.1	65.1	65.1	65.2	65.2	65.2		1	65.2
	13.2	53.3	59.7	64.5	66.1	66.6			66.8		67.0	67.0			67.0	67.
≥ 8000	13.9	56.1	63.2	68.3	70.0	70.5	70.7	70.8	70.8	70 - 8		70.9				70.9
≥ 7000	14.7	58.1	65.5	70.6	72.4	72.9	73.1	73.2	73.2	73.2	73.3	73.3	73.3		73.3	73.3
≥ 6000	14.9	59.6	67.3	72.6	74.5	75.1	75.3		75.3	75.4	75.4	75.4	75.4	1	75.4	75.4
≥ 5000	15.3	61.6	69.6	75.3	77.2	77.8			78.0	78 - 1	78.2	78.2	78.2		78.2	78.2
≥ 4500	15.6	62.5	70.5	76.6	78.5	79.2			79.4		79.5	79.5		1 :	79.5	79.5
≥ 4000	16.0	63.9	72.1	78.4	80.6	81.3			81.6		81.7	81.7	81.7	81.7	81.7	81.7
≥ 3500 ≥ 3000	16.8	67.1	75.5	82.1	84.4	85.0			85.4	85.5	85.6	85.6			85.6	
	17.6	69.6	78.8	85.7	88.3	89.0			89.5	89.5						
≥ 2500	18.2	72.5	82.2	89.4	92.2	93.0			93.4	93.5	93.5					93.5
≥ 2000	18.5		84.0	91.6	94.5	95.2			95.7	95.8	95.9				95.9	96.4
≥ 1800 ≥ 1500	18.5	74.4	84.4	92.0	95.0	95.7	96.0		96.3	96 • 3	96.4	96.4			97.3	97.3
	18.7	75.0	85.0	92.8	95.9					97.2		97.3			98.3	98.3
≥ 1200 ≥ 1000	18.7	75.3	85.4	93.5	96.6		97.9		98.2		98.3	-		99.1	99.1	99.1
	18.7	75.5	85.7	94.0	97.3		98.8				99.1	99.1	99.1	99.2	99.2	99.2
≥ 900	18.7	75.6	85.8	94.1	97.3		98.9		99.1	99.2		99.2		1		99.4
	18.7	75.7	85.8		97.5										99.4	99.5
≥ 700 ≥ 600	13.7	75.7														
<u></u>	18.7				97.5											
≥ 500 ≥ 400	18.7			94.2							99.6 99.9		1		99.6	
	18.7				97.6								99.9		99.9	
≥ 300 ≥ 200	18.7		85.9	94.2										L '		
	18.7													100.0		
≥ 100	18.7								i					100.0		1 1
	18.7	75.7	85.9	94.3	97.7	98.5	99.5	99.9	99.9	77.9	100.0	100-0	100.0	100.0	HOO. 0	H 00.

TOTAL NUMBER OF OBSERVATIONS 1689

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUOKA KYUSHU JAPAN/I TAZUKE AB 46-64

SEP NONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-0500

CEILING							VIS	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 1 ½	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ %	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	8.8 9.7	34.0 38.5	39.6 45.1	42.2	42.9 51.1	43.0 51.3	43.1 51.4	43.1 51.4	43.1 51.4	43.2 51.5	43.2 51.5	43.2 51.5	43.2 51.5		43.3 51.6	43.3
≥ 18000 ≥ 16000	9.9	39.0 39.4	45.6 46.1	50.1	51.7 52.2	51.9 52.4	52.0 52.5	52.0 52.5	52.0 52.5	52 • 0 52 • 5	52.0 52.5	52.0 52.5	52.0	1 1	52.2 52.6	52.2 52.6
≥ 14000 ≥ 12000	10.2	40.9	48.0 50.6	52.8 55.5	54.4 57.5	54.6	54.7	54.7	54.7	54 • 8 58 • 0	54.8 58.0	54.8 58.0	54.8 58.0	1 8	54.9 58.1	54.9 58.1
≥ 10000 ≥ 9000	11.7	47.0 48.0	54.8 56.1	60.C	62.2	62.6	62.6	62.6		62.7	62.7	62.7	62.7	62.8	62.8	62.8
≥ 8000 ≥ 7000	12.3	50.8 52.6	59.2 61.4	65.2	67.9	68.2	68.3	68.3	68.3	68.4	68.4	68.4	68.4		68.5	68.6
≥ 6000 ≥ 5000	13.3	54.2 56.8	63.2	69.7	72.5 75.4	72.9	73.C 76.0	73.0	73.0	73.1 76.0	73.1	73.1	73.1	73.1	73.2 76.1	73.2
≥ 4500 ≥ 4000	14.2	58.0 60.6	67.3	74.2	77.0	77.4	77.5 81.0	77.5	77.5	77.6 81.1		77.6 81.1	77.6	77.6	77.7	77.7
≥ 3500 ≥ 3000	15.3	63.4	73.0	80.5	83.5 87.0	84.2	84.4	84.4	84.4	84.5	84.5	84.5 88.5	84.5	84.5	84.6	84.7
≥ 2500 ≥ 2000	16.0	68.3	79.0	87.3	90.9	91.7	92.1	92.3	92.3	92.4	92.4	92.4	92.4	92.5	92.5	92.6
≥ 1800	16.0	70.0	81.2	90.C	94.1	95.0		95.6	95.6	95.7	95.7	95.7	95.7	95.8	95.9	95.9
≥ 1500 ≥ 1200	16.1	70.2	81.9	90.5	94.9	96.7	96.2	97.6	97.6	97.8	97.8	97.8	97.8	97.8	97.9	96.9
≥ 1000	16.1	70.4	82.3	91.4	96.0	97.2	97.9	98.5	98.5	98 • 8	98.8	98.8	98.8		98.9	99.0
≥ 800	16.1	70.5	82.3	91.6	96.2	97.3	98.0	98.8	98.8	99.2	99.2	99.2	99.2	99.2	99.3	- 1
≥ 500	16.1	70.5	82.3	91.6	96.3	97.4	98.1	98.9		99.5		99.5		99.6	99.7	99.8
≥ 400	16.1	70.5	82.3	91.6		97.5	98.2	99.1	99.1	99.5	99.7		99.7	99.8	99.9	99.9
≥ 200 ≥ 100	16.1	70.5	82.3	91.6	96.3	97.5	98.2	99.1	99.1	99.6	_	99.7	99.7	99.8	99.9	99.9
≥ 0	16.1	70.5	82.3	91.6	96.3	97.5	98.2	99.1	99.1	99.6	99.7	99.7	99.7	99.8	99.9	100 • C

TOTAL NUMBER OF OBSERVATIONS__

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

SEP

H STATI

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-080.

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	8.1 10.4	20.5	23.7 32.4	26.4 35.8	28.5 38.3		30 · 4 40 · 9	30.8 41.6	31.1 41.9	31 · 2 42 · 1	31.2 42.2	31.2	31.2 42.2	31.2 42.2	31.2	31 • 4 42 • 4
≥ 18000 ≥ 16000	11.0	29.9	33.4 34.3	36.8 37.7	39.3	40.6	41.9	42.7	43.0	43.1	43.2	43.2	43.3	43.3	43.3	43.5
≥ 14000 ≥ 12000	11.7	32.6 35.2	37.6 40.8	41.4 45.1	44.C 47.7	45.4	46.7	47.6 51.8	47.9 52.1	48.2 52.5	48.3 52.7	48.3 52.7	48.4 52.7	48.4 52.7	48.4 52.7	48.6 52.9
≥ 10000 ≥ 9000	13.5	38.0 38.7	44.2 45.0	48 • 8 49 • 7	51.5 52.5		55.0 56.0	56.2 57.3	56.5 57.8	56.9 58.3		57.1 58.5	57.2 58.5	57.2 58.5	57.2 58.5	57.3 58.7
≥ 8000 ≥ 7000	14.9 15.3	42.0	48.8 50.1	54.0 55.6	56.9 58.8		60.9	62.3	62.9 65.0	63.4 65.5		63.6	63.6 65.7	63.6	63.6 65.7	63.9
≥ 6000 ≥ 5000	15.4 16.4	44.1 46.8	51.1 53.9	56.6 59.8	59.8 63.1	61.8	64.0	65.5 68.9	66.1	66.6 70.0		66.8	66.9 70.3	66.9 70.3	66.9 70.3	67.1 70.5
≥ 4500 ≥ 4000	16.4 17.6	47.3 49.9	54.6 57.3	60.8 64.0	64.1 67.6	66.2 69.9	68.5 72.6	70.0 74.2	70.6 74.8	71 · 1 75 · 4	71.3 75.6	71.3 75.6	71.4 75.7	71.4 75.7	71.4 75.7	71.6 75.9
≥ 3500 ≥ 3000	18.8 19.7	52.7 56.0	60.3 64.3	67.4 72.0	71.1 76.1	73.5 78.7	76.2 81.6	1	78.6 84.3	79.3 85.2	1	79.6 85.5	79.6 85.5	79.6 85.5	79.6 85.5	79∙9 85∙8
≥ 2500 ≥ 2000	20.6	57.9 59.5	66.8 68.8	75.2 77.4	79.6 82.5	85.4		88.0 91.4	88.8 92.2	89.8 93.3	93.7	93.7	90.2 93.7	90.2 93.7	90.2 93.7	90 • 4 94 • ·
≥ 1800 ≥ 1500	21.0	59.6 59.9	69.0 69.3	77.8 78.5	82.8 83.8	87.1	90.8	93.7	94.4	93.9 95.7	96.1	96.1	94.4 96.2	94.4	94.4	94 • 6 96 • 4
≥ 1200 ≥ 1000	21.2	60.4	70.0 70.4	79.2 79.6	84.7 85.1	88.0 88.5				96.8 97.7	98.2	98.2	97.3 98.3	97.3 98.3	97.3 98.3	
≥ 900 ≥ 800	21.2	60.7	70.4 70.5	79.7 79.8	85.3 85.4	88.9		96.0	96.7	97.9 98.1	98.6		98.5 98.7	98.5	98.5 98.7	98.8
≥ 700 ≥ 600	21.2		70.6 70.6	79.9 79.9		88.9	92.8			98 • 3 98 • 7	99.2	99.2	98.9 99.3	99.3	98.9	99.5
≥ 500 ≥ 400	21.2	60.8	70.6	79.9		88.9	92.8	96.5			99.5	99.5	99.5	99.6	99.5	99. s
≥ 300 ≥ 200	21.2	60.8	70.6			88.9	92.8	96.5 96.5			99.5	99.5	99.6	99.6	99.6	99.9
≥ 100 ≥ 0	21.2	60.8		79.9 79.9	85.5 85.5			96.5 96.5	1 1			· 1		, .	99.6 99.7	99.9 100.0

TOTAL NUMBER OF OBSERVATIONS_

__1688_

\$210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLE

Language Pa

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-11C:

CEILING							VIS	BILITY (ST	ATUTE MILI	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	_ ≥ 2	≥ 1 1/2	21%	≥ 1	≥ ¾	≥ ¾	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	17.0 23.5	26.1 38.7	27.6	28.8	29.5		29.7	29.8 43.8	29.8 43.8	29 · 8 43 · 8	29.8 43.8	29.8	29.8 43.8		29.8 43.8	
≥ 18000 ≥ 16000	24.1	39.8	41.7	43.4	44.4	44.6	44.7	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44.9	
≥ 14000	25.7	41.0	43.1	44.9	49.5		46.3 50.0	46.6 50.2	50.3	50.4	5C-4	5C.4	50.4	50.4	50.4	50.4
≥ 12000 ≥ 10000	27.1	47.6 51.2	50.4 54.2	52.3 56.7	53.8 58.4		54.9 59.8	55.1	55.3	55.3 60.4	55.3 60.4	55.3 60.4	55.3	55.3 60.4	55.3	55.3
≥ 9000	29.2 31.4	52.7 56.4	55.9 59.9	58.5 62.8	60.2		61.6		66.9	62.3	62.3	62.3	62.3 67.0		62.3	
≥ 8000 ≥ 7000	32.1	57.7	61.6	64.5	66.5	67.3	68.1	68.4	68.6	68.7	68.7	68.7	68.7	68.7	68.7	68.7
≥ 6000 ≥ 5000	32.5 33.3	58.7 60.8	62.7 64.8	65.7 67.8	67.8 70.3	: 1	69.6	1	70.2	70.3	70.3 72.9	70.3 72.9	70.3 72.9	70.3 72.9	70.3 72.9	
≥ 4500 ≥ 4000	33.7 34.9	61.7	65.8 68.4	68 • 9 71 • 5	71.3	72.1 74.9	73.1 76.2	73.6 76.8	73.8 77.0	74.0 77.2	74.0 77.2	74.0 77.2	74.0	74.0 77.2	74.0 77.2	74.5
≥ 3500	36.2	66.8	71.4	74.8	77.5	78.5	79.8	80.5	80.7	80.9	80.9	80.9	80.9	80.9	80.9	80.9 87.7
≥ 3000	39.1 39.9	72.0	77.1 80.0	83.8	83.7	84.8	89.9	90.8	91.1	87.6 91.5	87.7 91.5	87.7 91.5	87.7 91.5	91.5	87.7 91.5	91.5
≥ 2000	40.5	76.4	82.4	85 • 8 86 • 3	89.4 90.0			93.4	93.7	94.7	94.8	94.1	94.1	94.1	94.1	94.1
≥ 1500	40.7	77.3	83.3	87.5	91.4	92.8	94.9	96.0	96.3	96.8	96.9		96.9	96.9 98.4	96.9 98.4	
≥ 1200 ≥ 1000	40.9	77.9 78.0			92.5	94.2	96.7	97.9	98.3	98.9	99.0	99.0	99.1	99.1	99.1	99.1
≥ 900 ≥ 800	41.0	78.1 78.1	84.1 84.1	88 • 6 88 • 6				98.0 98.1	98.5 98.5	99.1	99.1 99.2	99.1		99.2	99.2	i - 1
≥ 700 ≥ 600	41.0	78.1 78.1	1	88.7	92.7	94.6	97.1	98.3	1	1	99.4	99.4	99.5		99.5 99.8	
≥ 500	41.0	78.1	84.2	88.88	92.8	94.7	97.2	98.5	98.9	99.6	99.8	99.8	100.0	100.0	100.0	100.0
≥ 400	41.C	78.1 78.1	84.2	88.88	92.8		97.2				99.8	99.8	100.0	100.0	100.0	100.0
≥ 200 ≥ 100	41.0	78.1 78.1				94.7				99.6				100.0		100.0 100.0
≥ 0	41.0	–				94.7	1	f		1				100.0		

TOTAL NUMBER OF OBSERVATIONS 169

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

The serve with the day

ىكەنگىيەنىۋ ئۇمۇگىيەنىۋ DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140c

CEILING							VIS	BILITY (ST.	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	21.5	26.7 39.2	27.4 40.5	28.C 41.3	28.1 41.4	28.1 41.4	28.1 41.4	28.1 41.4	28.1 41.4	28 • 1 41 • 4	28.1	28.1	28.1 41.4	28.1 41.4	28.1 41.4	28.1 41.4
≥ 18000 ≥ 16000	32.1 32.8	4C.4	41.7	42.6	42.7 44.1	42.7	42.7	42.7	42.7	42.7 44.1	42.7	42.7 44.1	42.7	42.7 44.1	42.7	42.7 44.1
≥ 14000 ≥ 12000	35.0 37.4	45.4	47.4 51.7	48.3	48.5	48.5 52.8	48.5	48.5	48.5	48.5 53.1	48.5 53.1	48.5	48.5 53.1		48.5	48.5 53.1
≥ 10000 ≥ 9000	4C-4 42-1	54.2 57.0	56.5 59.6	57.6	57.7	57.7	57.9	57.9	57.9	58.1 61.7	58.1	58.1	58.1		58.1	58.1
≥ 8000 ≥ 7000	44.1	60.5	63.3	64.8	65.2	65.2	65.3	65.4	65.4	65.5	65.5	65.5	65.5	65.5	65.5	
≥ 6000 ≥ 5000	44.7	62.6	65.5	67.2	67.1	67.8	68.C	68.0	68.0	68.2	68.2	68.2	68.2	68.2		68.2
≥ 4500 ≥ 4000	46.6	65.0	67.8	68.8	70.6	70.7	70.9	71.0	71.0	71.2	70.2	71.2	71.2	71.2	71.2	71.2
≥ 3500	49.1 51.3	72.1	71.7	77.5	74.6	78.9	$\frac{75.1}{79.1}$	75.3	79.3	75.5		79.5	79.6	79.6	79.6	75.5
≥ 3000	56.9	78.8	82.5 86.5	85.C	91.1	91.4	91.8	92.0		92.4	92.4	92.4	92.5	92.5		92.5
≥ 2000	57.7	83.9	87.8 88.5	92.0	92.9	94.2	94.8	95.0				95.4	95.4	95.4	95.4	95.4
≥ 1500 ≥ 1200	58.0 58.1	85.7	90-2	93.3	96.2	96.8	97.8		98.1	98.6	98.6	98.6	98.7	98.7		98.7
≥ 1000 ≥ 900	58.1 58.1	86.0	90.6		96.8	97.4	98.5	98.9	98.9	99.4	99.5	99.5	99.6	99.6	99.6	99.6
≥ 800	58.1 58.1	86.0	90.7	94.4	96.9	97.5	98.6	99.1	99.1	99.6		99.7	99.8	99.8	99.8	99.8
≥ 600 ≥ 500	58.1 58.1	86.0 86.1	90.7	94.5	96.9	97.5	98.8	99.2	99.2		99.9	99.9	99.9	99.9	99.9	99.9
≥ 400	58.1 58.1	86.1 86.1	90.7 90.7	94.5	96.9	97.5 97.5	98.8		99.2	99.8	99.9		100.0	100.0	100.0	100.0
≥ 200 ≥ 100	58.1 58.1	86.1	90.7 90.7	94.5		97.5 97.5		99.2						100.0		
≥ 0	58.1		90.7	94.5		97.5)			99.8	99.9	99.9	100.0	100.0	100.0	1.00.t

TOTAL NUMBER OF OBSERVATIONS 1692

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

Service Belling

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ ¾	≥ ⅓,	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	21.9	26.8 41.4	27.5 42.4	28.0 43.2	28.3 43.5	28.3 43.5	28.3 43.6	28.3 43.6	28.3 43.6	28 · 3 43 · 6	28.3 43.6	28.3 43.6	28.3	28.3 43.6	28.3 43.6	
≥ 18000 ≥ 16000	34.1 34.7	42.5 43.8		44.4 45.8	44.7	44.7	44.8	44.9	44.9	44 . 9		44.9	44.9	44.9	44.9	
≥ 14000 ≥ 12000	36.7 38.9	47.5	49.0	49.9	50.4 55.2	50.4	50.5 55.5	50.6	50.6 55.6	50.6 55.7	50.6 55.7	50.6 55.7	50.6	50.6	50.6	56.6
≥ 10000 ≥ 9000	40.9 41.9	54.7	56.9 59.0	57.9	59.0 61.2	59.0 61.3	59.3	59.5	59.5	59.6		59.6 61.9	59.6		59.6	59.5
≥ 8000 ≥ 7000	43.6	59.4	61.7	63.0	64.3	64.5	64.8	65.0	65.0	65.2	65.2	65.2	65.2	65.2	65.2	65.Z
≥ 6000 ≥ 5000	45.8	63.0	65.6	67.2	68.5	68.7	69.2 71.0	69.4	69.4	69.7	69.7	69.7		69.7	69.7	69.7
≥ 4500 ≥ 4000	47.5	65.9	υ8•6 72•0	68.8 70.3 73.8	70.4 71.8 75.4	72.0	72.4	72.7	72.7	72.9	73.0	73.0	73.0	73.0 76.8	73.0	13.6
≥ 3500 ≥ 3000	50.9	72.0	75.0	77.0 83.1	78.6 84.9	78.9	79.4	76.3 79.8 86.6	79.8	76.6 80.1 87.0	80.2	80.2	80.2	80.2	80.2	86.2
≥ 2500 ≥ 2000	55.4 56.1	80.6	84.4	87.0 89.3	88.9	89.4	90.3	90.9		91.3	91.4	91.4		91.4	91.4	91.4
≥ 1800 ≥ 1500	56.4 56.4	82.9	87.0	89.9 90.8	92.4	93.0	94.3	95.0	95.0	1	95.7	95.7	95.7	95.7	95.7	95.7
≥ 1200 ≥ 1000	56.5 56.5	83.8	88.3	91.5	94.1	94.9	96.4	97.5	97.5	98.0	98.2	98.2	98.2	98.2	98.2	98.2
≥ 900 ≥ 800	56.5	83.9	88.5	91.8 91.9 92.0	94.4 94.5 94.7		96.8 96.9 97.1		98.0	98.6 98.7 98.9	98.9	98.8 98.9 99.1		98.8 98.9 99.1		
≥ 700 ≥ 600	56.5 56.5	83.9	88.5	92.0	94.7	95.6 95.6		98.2	98.3	98.9	99.2	99.2	99.2	99.2	99.2	99.2
≥ 500 ≥ 400	56.5	83.9	88.6	92.1 92.1	95.0	95.8	97.5	98.5	98.6	99.2		99.5		99.6	99.6	39.6
≥ 300 ≥ 200	56.5 56.5	83.9	88.6		95.0	95.8	97.5	98.6	98.8	99.5	99.8	99.8	99.9		99.9	99.9
≥ 100 ≥ 0	56.5	83.9	88.6	92.1	95.0	95.8	97.5	98.6	98.8	99.5	99.8	99.8	99.9	99.9	99.9	100.
0	56.5	83.9	88.6	92.1	95.0	95.8	97.5	98.6	98.8	99.5	99.8	99.8	99.9	99.9	99.9	10C •

TOTAL NUMBER OF OBSERVATIONS

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-200

CEILING							VISI	BILITY (ST.	ATUTE MIL	ES)						į
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ %,	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	16.3	27.2	29.1 40.5	30.2	30.8 43.8	30.9	31.1	31.2	31.2	31.2	31.2	31.2	31.2 44.9	31.2 44.9	31.2 44.9	31.2
≥ 18000 ≥ 16000	22.3	38.4	41.2	43.6	44.8	45.1 46.6	45.6 47.1	45.9	45.9	45.9 47.5	45.9	45.9	45.9	45.9	45.9 47.5	45.9
≥ 14000 ≥ 12000	24.0 25.1	41.6	45.2 48.4	48.1	49.6	50.2	50.9 55.1	51.2	51.2 55.5	51.3 55.7		51.3 55.7	51.3	51.3	51.3 55.7	51.3 55.7
≥ 10000 ≥ 9000	26.0	47.1	52.0	55.4	58.0	59.1	60.3	61.0	61.1	61.3	61.3	61.3	61.3	61.3	61.3 62.9	61.3
≥ 8000 ≥ 7000	27.9	51.2	56.9	56.7	63.7	64.9	66.2	67.0	67.2	67.4	67.4	67.4	67.4	67.4	67.4	67.4
≥ 6000	28.4	52.5	60.1	64.3		68.5	69.8		70.8	71.1	71.1	71.1	71.1	71.1	71.1	1
≥ 5000 ≥ 4500	29.0	54.9 55.4	61.8	66.i	69.4	70.7	72.3		73.3	73.7	73.7	73.7	73.7	73.7	73.7	73.7
≥ 4000 ≥ 3500	30.8	61.2	65.2 68.2	73.0	76.3	77.9	79.6		80.8	81.3	81.3	77.5 81.3	81.3	81.3	81.3	د . 31
≥ 3000	32.9 33.7	67.5	75.8	81.7	85.8	87.6	84.9	90.9		86.8 91.7	91.7		91.7	91.7	91.7	91.7
≥ 2000 ≥ 1800	34.1 34.2	69.3		83.9	88.5 89.1	91.1	93.1		94.7	94.8	95.5	1	95.6	95.6	95.6	95.6
≥ 1500 ≥ 1200	34.4			85.0 85.7			94.3	95.9 97.3		98.4	-	98.5	98.5	98.5		98.5
≥ 1000	34.4		78.9 78.9	86.0 C.88			95.9 95.9			98.9	98.9 99.1		99.0 99.2		99.0	99.0 99.2
≥ 800 ≥ 700	34.4			86.3			96.6 96.6					99.8	99.8	<u> </u>	99.8	
≥ 600	34.4		79.1	86.3			96.6			99.6				99.9	99.9	
≥ 400	34.4	70.2	79.1	86.3	91.5	93.8	96.6	98.5	98.9	99.8	99.9	99.9			100.0	
≥ 200	34.4	70.2	79.1	86.3	91.5	93.8	96.6	98.5	98.9	99.8	99.9				100.0	
≥ 0	34.4				-							-		1	100.0	

TOTAL NUMBER OF OBSERVATIONS.....

_1691

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE DESOLETE

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-230

Γ				-												 7
							VISI	BILITY (ST.	ATUTE MIL	ES)						
CEILING (FEET)		1	1		ì		1	1								
(reer)	= 10	≥ 6	≥ 5	≥ 4	≥ 3 ′	≥ 2 1/2	≥ ?	≥11/2	≥ 1%	۱ ا ≤	≥ %	≥ %	≥ %	≥ 5/16 ¹	≥ %	≥ 0
NO CEILING	īi.d	36.9	39.7	42.0	42.4	42.7	43.0	43.0	43.0	43.0	43.C	43.C	43.0	43.C	43.0	43.1
≥ 20000	12.3	43.8	47.5		52.2			53.3		53.3	53.3	53.3	53.3	53.3	53.3	53.3
≥ 18000	12.6	44.4	48.2	52.2	52.8	53.5	54.C	54.0	54.0	54.0	54.0	54.C	54.0	54.C	54.C	54.4
≥ 16000	13.1	45.3	44.3	53.5	54.1	54.7	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.4
≥ 14000	13.7	47.5	51.8	56.6	57.3	57.9	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5
≥ 12000	14.4	49.6	54.3	59.4	60.2	60.9	61.5	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6
≥ 10000	14.8	53.2	58.2	54.2	65.7	66.4	67.1	67.3				67.3	67.3	67.3	67.3	67.3
≥ 9000	15.d	54. d	59.0	65.2	66.8	67.5	68.2	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3
≥ 8000	16.3	57.0	62.8	69.4	71.2	72.0	72.8	72.9	72.9	72.9	12.9	72.9	72.9	72.9	72.9	72.5
≥ 7000	16.7	58.C	63.9	70.7	72.5	73.4	74.1	74.2	74.2	74.2	74.2	74.2	74.2	74.2	74.2	74.2
≥ 6000	17.0	59.3	65.6	72.5	74.2	75.2	75.9	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0
≥ 5000	17.4	61.7	68.1	75.2	77.2	78.3	79.C	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	19.1
≥ 4500	17.7	62.4	68.9	76.1	78.1	79.1	79.9	80.0	80.0	80.0	80.0	80.0	80.0	80.C	8C.0	8(
≥ 4000	18.0	64.6	71.5	79.1	81.1	82.2	83.0	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2
≥ 3500	18.4	67.0	74.1	82.0	84.2	85.3	86.2	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
≥ 3000	19.C	69.3	77.1	85.7	88.0	89.1	90.1	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.4
≥ 2500	19.3	71.3	79.5	88.3	90.6	91.8	92.8	93.0				93.0	93.0			93.C
≥ 2000	19.6	73.6	82.2	91.1	93.4	94.7	16.C	96.2	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥ 1800	19.6	74.0	82.6	91.6	93.9	95.2	96.5	96.7	96.7	96.9		- (96.9			96.9
≥ 1500	19.7	74.6					97.8		98-1	98.3						98.3
≥ 1200	19.7	75.0		93.2	95.6		98 • 4	98.8		99.1			99.1	99.1	99.1	99-1
≥ 1000	19.7	75.0		93.3	95.9		98.7	99.2	99.2				99.5			99.5
≥ 900	19.7	75.0	83.9	93.4	95.4	, ,	98.8	99.3	99.3	99.6		99.6	99.6	1	99.6	49.E
≥ _80C	19.7	75.1	84.0		96.1			99.5			99.8		99.8			99.8
≥ 700	19.7	75.1	84.0	93.5	96.1	1 †	99.0	99.5	99.5	99.8			99.8			
≥ 600	19.7	75.1	84.0		96.1		99.1	99.6			99.8		99.8			99.8
≥ 500	19.7	75.1	84.0	93.5	96.1	1 1	99.1	99.6		99.9			99.9			
≥ 400	19.7	75.1	84.0				99.1				99.9					
≥ 300	19.7	75.1	84.1	93.6	96.2	1)	99.1	99.7							10C.0	
≥ 200	19.7	75.1	84.1	93.6		97.7	99.1	99.7							100.0	
≥ 100	19.7	75.1	84.1	93.6			99.1							1	100.0	
≥ 0	19.7	75.1	84.1	93.6	96.2	97.7	99.1	99.7	99.7	100.0	100.0	100.0	100.0	100.0	TOC-0	100.0

TOTAL NUMBER OF OBSERVATIONS 16

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. .. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64 1 20 HONTH 0000-0201 PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING					-		VISI	BILITY (ST	ATUTE MIL	ES)						
(FEFT)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥ 1	≥ 3/4	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	10.5 11.1	1	48.8			52.9			53.3		53.4	53.4		53.4	53.4	
≥ 18000	11.5		56.0		61.7				62.5							
≥ 16000	11.5		56.9		1	62.8	63.2	63.4	63.4	63.5	63.6	63.6	63.6	63.6	63.6	63.E
≥ 14000	19		59.0	- 1					65.6							
≥ 12000	12.4				68.1				68.9					69.0		
≥ 10000 ≥ 9000	12.6		64.2 65.7		71.1	71.4 73.0					72.2 73.9	72.2	:	77.2	72.2	1
≥ 8000	13.2		68.5	73.8				77.2		77.3		77.4	77.4			
≥ 7000	13.4		69.3	74.7		77.5		1	1	78.5			78.6	1 1	1	1
≥ 6000	13.8		70.7	76.1	78.8		79.8						80.2		80.2	, ,
≥ 5000	14.5		73.0				82.6				83.0			83.C	83.C	
≥ 4500 ≥ 4000	14.6		74.0		82.9 86.1			84.3	84.3	84.4		84.4	84.4		84.4	
≥ 3500	15.9	<u></u>	79.6						90.5			90.7	90.7		90.7	
≥ 3000	16.5								93.8				93.9	. 4	93.9	
≥ 2500	16.8	73.5	83.0	89.9	93.9						95.8		95.8			95.9
≥ 2000	16.9								97.6							
≥ 1800 ≥ 1500	16.9								97.8		,		98.1 98.4		98.1 98.4	
≥ 1200	16.9			91.4	96.2		97.7 98.0		98.4			98.4	98.7	98.7	98.8	
≥ 1000	16.9	1							98.8				99.2		99.2	
≥ 900	16.9	74.6	84.3		96.5				98.9			99.2	99.2	99.2	99.3	99.3
≥ 800	16.9	1			96.5				98.9			99.3			99.3	
≥ 700 ≥ 600	16.9	1			96.6	1			99.0	99.3					99.5	
-	16.9				96.7		98.6		99.1	99.4						
≥ 500 ≥ 400	16.9						98.6				99.5			1 1		
≥ 300	16.9			91.7		97.6					99.5					
≥ 200	16.9	74.6	84.3	91.7					99.2							
≥ 100	1	74.6	1	:	i	97.6										99.7
≥ 0	16.9	74.6	84.3	91.7	96.7	97.6	98.6	99.1	99.2	99.5	99.6	99.6	99.8	99.8	99.8	<u>μυς.</u>

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/1 TAZUKE AB

UC T

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-350c

CEILING	*****						VIS	BILITY (ST.	- ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥11/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	9.4 9.9	42.5	46.3 52.4	49.3 56.1	50.4 57.7	50.6 58.1	51.3 58.9	- 1	51.7 59.3	51.9 59.5	51.9 59.5	51.9 59.5	52.0 59.6		52.0 59.6	
≥ 18000 ≥ 16000	10.1 10.1	47.8	53.0 54.2	56.6 58.0	58.2 59.6	58.6 60.0	59.4 60.8	59.8	59.8 61.2	60 • 1 61 • 5	60.1	60.1 61.5	60.2	, ,	60.2	
≥ 14000 ≥ 12000	10.8	50.9 53.0	56.4 59.1	60.2	61.9	62.3	63.0	63.4	63.4	63.7	63.7	63.7	63.8	63.8	63.8	1 1
≥ 10000 ≥ 9000	12.0	54.8 56.0	61.3		67.5	67.9	68.7	69.1	69.1	69.4	69.4 71.1	69.4	69.5	69.5	69.5 71.2	69.1
≥ 8000 ≥ 7000	13.0	58.5 59.1	65.3	69.9	72.5	73.0	73.9 74.7	74.3 75.1	74.3 75.1		74.7	74.7	74.8 75.6	74.8	74.8 75.6) ' 1
≥ 6000 ≥ 5000	13.4	63.5	68.0 71.1	72.7	75.5	76.1 79.9	77.1 80.9	17.5	77.5	77.9 81.7		77.9 81.7	78.0 81.8	78.0		1
≥ / 3	14.3	64.3	72.3 75.6	77.6 81.0	80.8		82.5		82.9 86.7	93.3 87.1	83.3 87.1	83.3 87.1	83.4 87.2			
≥ 3500 ≥ 3000	15.4 16.0	69.3 71.3	78.3 80.7	84.2	88.2	88.9	89.9 93.0		90.3	٠,	90.7	90.7	90.8	1 1		: 1
≥ 2500 ≥ 2000	16.1	72.4 73.1	81.9 82.7	88.4 89.5	92.9	93.5	94.6	[1	95.1 96.7	95.6	95.6	95.6 97.2			95.6 97.2	95.8 97.4
≥ 1800 ≥ 1500	16.1	73.1 73.2	82.9 83.0	89.7 89.9	94.5	95.3 95.9	96.6	97.1	97.1 97.7	97.5 98.2	97.6 98.2	97.6 98.2		1	1 1	1 . 1
≥ 1200 ≥ 1000	16.1	73.5 73.6		90.4		96.5 96.7	97.9 98.1	98.5 98.8					99.5		99.2	
≥ 900 ≥ 800	16.1			90.4	95.8		98.1 98.1	98.8	, ,				99.5	1	1	1 3
≥ 700 ≥ 600	16.1	73.6 73.6	1 - : - : 1					1	, ,			99.5 99.7				99.3 100.
≥ 500 ≥ 400	16.1	73.6 73.6						99.0			99.6 99.6			99.8 99.8		100.0
≥ 300 ≥ 200	16.1	73.6 73.6	1 :					99.J 99.0			99.6 99.6	99.7	99.8	99.8	99.8	100.6 100.6
≥ 100 ≥ 0	16.1	•		l .				99.0		99.6 99.6	99.6	1	99.8	99.8	ι	100.

TOTAL NUMBER OF OBSERVATIONS____

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0600-080.

CEILING				-			VISI	BILITY IST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/2	≥1%	≥1	≥ ¾	≥ ¾	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	10.4	25.4	29.5	32.7	35.0	36.2	37.4	38.1	38.4	39.0	39.2	39.2	39.3	39.3	39.3	39.4
≥ 20000	11.9	30.9	35.8	39.7	43.5				49.1		50.1			50.3	50.3	56.4
≥ 18000	12.2	31.7	36.7	40 "	44.5	46.3	48.5	49.9	50.2	51.0	51.2	51.2	51.3	51.4	51.4	51.5
≥ 16000	12.2	31.9	37.1	41.3	45.3				51.6		52.6	52.6	52.7	52.8	52.8	52.9
≥ 14000	12.7	34.2	39.8		48.9		53.8	55.2	55.6	56 .4	56.6	56.6	56.8	56.8	56.8	56.9
≥ 12000	13.9	37.6	43.7		53.7	55.9	58.6	60.2			61.8	61.8			62.C	62.1
≥ 10000	14.8	40-6	47.5	53.0	58.U	60.3		65.0				66.7	66.8	66.8	66.8	06.5
≥ 9000	15.1	41.5	48.3	54.2	59.3		64.8		66.8							68.4
≥ 8000	15.5	43.7	50.7	57.0	62.4	65.1	68.4	70.2	70.7	71.9	72.2	72.2	72.3	72.3	72.3	72.4
≥ 7000	15.8	44.9	52.0	58.6	64.2	66.9	70.2				74.1	74.1	74.3			
≥ 6000	16.2	46.1	53.4	60.2	66.0		72.2					76.3	76.5			
≥ 5000	17.3	48.6	56.1	63.2	69.2	72.2	75.6		78.2	79.6	80.0	80.0	80.2	80.2	80.2	80.4
2: 4500	17.8	49.9	57.7	64.9	70.9	74.0	77.5	79.6				81.9	82.1	82.2	82.2	82.3
≥: 4000	18.8	52.8	60.8	68.3	74.6			83.7	84.2		86.1	86.1	86.3	·		
≥ 3500	19.6	55.0	63.2	71.0	77.5	80.8		86.9		1		89.4		1 1		1 1
≥: 3000	20.1	57.4	66.3	74.1	81.d	84.4	88.2	90.6	91.1	92.7	93.4	93.4	93.7	93.8	93.8	93.9
≥ 2500	20.5	58.6	67.7	75.8	83.0	86.4	90.2	93.0	93.5			95.8	96.1	96.2	96.2	6 î
≥ 2000	20.5	58•9	68.1	76.5			91.3					97.0	97.3	97.4		
≥ 1800	20.7	59.2	68.4	76.8	84.3	87.9	91.8	94.6	95.1			97.5	97.8	t 1	97.9	
≥ 1500	20.7	59.2	68.4	76.8			91.9	94.7					98.2			98.4
:= 1200	[20•7	59.4	68.6	77.0	84.6	88.3						98.2	98.6	98.7		1
≥ 1000	20.7	59.4	68.6							97.8					99.2	
≥ 900	20.7	59.4	68.6	77.0	84.8	88.5	92.5					98.8	99.2	1 !		3 1
≥ 8∪0	20.1	59.4		77.2			92.8									
≥ 700	20.7	59.4		77.2			92.8					99.2	99.6		99.8	1 - 1
≥ 600	20.7	59.4		17.2			92.9		96.6				99.7			100.1
≥ 500	20.7	59.4		77.2		-1	92.9									100.0
≥ 400	20.7	59.4		77.2				96.1	+							100.0
≥ 300	20.7	59.4		77.2				96.1	96.5							100.0
≥ 200	20.7				84.9			96.1		98.5				99.8	,	
≥ 100	20.7			77.2				96.1			99.3				ı	100.0
≥ 0	20.1	59.4	4.89	77.2	84.5	88.8	92.9	96.1	96.6	93.5	99.3	99.3	99.7	99.8	99.9	TCC.r

TOTAL NUMBER OF OBSERVATIONS____

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-110

CEILING							VISI	BILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	18.8	32.8	34.5	36.8		38.7					39.3		39.3		39.3	39.3
≥ 20000	25.0								53.8		54.0			-	54.1	54.1
≥ 18000	25.3			50 - 3	52.7	54.0								,	55.2	55.2
≥ 16000	25.5	45.0		51.3	53.8		55.5		56.0					56.3		56.3
≥ 14000	24.7	47.7	50.8	54.6		58.6		59.6		59.9		59.9	60.0	,	6C.C	60.0
≥ 12000	27.8	50.9		58.9	61.9		+		64.7		64.9			65.0		65.
≥ 10000	29.1	53.7	57.9	62.8	66.1	67.7		69.5	1	69.8		69.8		69.9		69.9
≥ 9000	29.4	54.6			67.2			70.7		71.1		71.1	71.2		71.2	11.4
≥ 8000	30.7	57.0	61.4	66.6		,		74.0			74.5				1 1	74.0
≥ 7000	31.5		63.6		72.8				76.7						77.1	77.1
≥ 6000	31.9	59.8	1	69.8		75.3	1		77.8		78.2		78.3	1	1 :	. 1
≥ 5000	32.8		65.8		75.5					80.3		80.4				
≥ 4500	33.4		66.8	72.4			79.6				81.6				1 1	
≥ 4000	35.9		70.9	76.7			84.1			86.1						
≥ 3500	38.5			81.0								-		1		90.8
≥ 3000	40.2								94.0							
≥ 2500	40.7		79.3		90.5		93.7		1			1			•	96.9
≥ 2000	41.0				91.3			96.5						+		97.8
≥ 1800 ≥ 1500	41.0		79.9	86.6				96.7			97.8					98 - 1
	41.1				92.1				97.6							98.9
≥ 1200 ≥ 1000	41.1			87.2					97.8		, ,	99.0				
<u> </u>	41.1				92.2				98.0							
≥ 900	41.1			,					98.1		1		1	1	•) 1
	41.1				92.4	_			98.2					99.6		
≥ 700 ≥ 600	41.1				92.4				98.3			99.5			99.8	
	41.1								98.4					99.8	99.9	
≥ 500 ≥ 400	41.1				92.4				98.4							1
			80.4											99.9		
≥ 300 ≥ 200	41.1				92.4				98.4							1 1
		74.7												99.9		
≥ 100	41.1	74. 7	80.4	07 4	92.4	94.5	90.0	90.2	90.4	97.2	00.7	97.1	99.5	99.9	100.0	100.
	1 41.1	14.1	80.4	81.4	72.4	74.5	40.0	70.6	70.4	77.2	7701	7701	77.7	99.9	10000	# 00 • C

TOTAL NUMBER OF OBSERVATIONS_____

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OSSOLETE

SM "

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140c

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	30.2 40.0	38.2 51.6	38.7 52.2	39.1 52.9	39.1 53.3	39.1 53.3	39.1 53.3	1 - 1	39.1 53.3	39.1 53.3	39.1 53.3	39.1 53.3	39.1 53.3	39.1 53.3	39.1 53.3	39.1 53.3
≥ 18000 ≥ 16000	41.0 41.9	52.8 54.1	53.5 54.8	54.1 55.5	54.6	54.6 56.0	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	
≥ 14000 ≥ 12000	44.1	57.4	58.3 64.0	59.1	59.6	59.6	59.6		59.6	59.6	59.6	59.6 65.4	59.6	59.6	59.6	59.7
≥ ,000	48.7	65.9	67.3 68.6	68.4	69.0	69.2	67.3	69.7	69.7	69.7	69.7 71.1	69.7	69.7	69.7	69.7	69.7 71.1
≥ 8000 ≥ 7000	50.3 50.9	69.C	70.7 71.8	71.9	72.7	72.8	/3-1 74.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.5 74.8
≥ 6000 ≥ 5000	51.6 53.3	71.4	73.2 75.2	74.5	75.3	75.5 78.0	75.8 78.4	76.2	76.2	76.2	76.2	76.2 78.8	76.2	76.2 78.8	76.2 78.8	76.3
≥ 4500 ≥ 4000	54.0 58.1	74.5 79.2	76.5 81.2	78.0 83.0	79.0 84.0		79.6	80.1	80.1 85.1	80.1	80.1	80.1 85.2	80.1 85.2	80.1 85.2	80.1 85.2	8C • 2 85 • 2
≥ 3500 ≥ 3000	61.2		85.9 89.9	87.7 91.9	88.7	89.1 93.5	89.4	89.9	89.9	90.0	90.0	90.0	90.0	90.0	90.0	
≥ 2500 ≥ 2000	64.7	88.7 89.4	91.0 91.7	93.2	94.5 95.6	94.9 96.1	95.3	95.9	95.9	96.0	96.1	96.1 97.6	96.1 97.6	96 • 1 97 • 6	96.1	96.2 97.6
≥ 1800 ≥ 1500	65.3 65.4		91.8 92.1	94.2	95.7	96.2 96.8	96.8	97.5		97.6 98.4		97.7 98.5	97.7	97.7 98.5	97.7 98.5	97.7 98.5
≥ 1200 ≥ 1000	65.4 65.5		92.4 92.6	95.0 95.2	96.5 96.8	97.2 97.5	98.1 98.4	98.8	98.8	99.0	99.1	99.1	99.1	99.1 99.7	99.1	99.2 99.7
≥ 000 ≥	65.5 65.5		92.6 92.6	95.3 95.3	96.9 96.9	97.6 97.6	98.5 98.5			99.7 99.7	99.8 99.8	99.8	99.8		99.8	99.8 99.9
≥ 700 ≥ 600	65.5 65.5		92.6 92.6	95.3 95.3	96.9 96.9	97.6 97.6	98.5 98.5				99.8 99.9				99.8	· •
≥ 500 ≥ 400	65.5 65.5	90.2	92.6 92.6	95.3 95.3	96.9 96.9		98.5 98.5			99 • 8 99 • 8						100.0 100.0
≥ 300 ≥ 200	65.5 65.5	90.2		95.3 95.3		97.6		99.5	99.5	99 • 8 99 • 8	99.9	99.9		1 ' 1	99.9	100.c
≥ 100 ≥ 0	65.5 65.5	1		95.3 95.3	-					99 • 8 99 • 8		99.9 99.9				100.0

TOTAL NUMBER OF OBSERVATIONS_

DATA PROCESSING CIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

1 20

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-1700 HOURS (LST.)

CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	21%	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	34.8 43.9	41.9 53.8	42.9 55.2	43.3 55.7	43.4 55.9	1	43.4 55.9		55.9	43.4 55.9	43.4 55.9	43.4 55.9	43.4 55.9		55.9	43.4 55.9
≥ 18000 ≥ 16000	44.9	55.1 56.9	56.5 58.6	57.0 59.2	57.2 59.5		57.3 59.5		59.5	57.3 59.5	57.3 59.5	59.5	59.5	59.5	59.5	57.3 59.5
≥ 14000 ≥ 12000	48.6 51.4	6(• 0 65 • 2		+	63.3	69.0	63.3 6°.0		69.0	63.3	63.3	69.0		69.0	69.0	63.3
≥ 10000	53.3 54.1	69.0 70.4		72.8	73.3 75.0	73.6 75.2	73.8 75.5	73.9 75.5	75.5	73.9 75.5	73.9 75.5	75.5	73.9 75.5	75.5	73.9 75.5	73.9 75.5 78.5
≥ 8000 ≥ 7000 ≥ 6000	54.6 55.2 55.8	72.5 73.4 74.4		76.7 77.8 79.0	77.5 78.6 80.0	78.9	78.2 79.4 80.9	78.3 79.5 81.0	78.4 79.6 81.2	78.5 79.7 81.3	78.5 79.7 81.3	78.5 79.7 81.3	78.5 79.7 81.3	79.7	78.5 79.7 81.3	79.7
≥ 5000 ≥ 5000 ≥ 4500	56.7	75.9 77.1	78.9 80.2	80.7	81.7	82.3	82.7	82.8		83.1	83.1	83.1	83.1 84.4	83.1	83.1	83.1
≥ 4000 ≥ 3500	59.9	80.3		85.4	86.5	1	87.8		88.1	88 · 2 92 · 4	88.2 92.4	88.2	88 • 2 92 • 4	88.2	88.2	88 • z
≥ 3000 ≥ 2500	63.6	86.0 87.2	89.4	1 1	93.4		1			95.3	95.3	95.3	95.3 96.9		95.3	95.3
≥ 200^	64.4	87.8 87.9	91.5		95.8 95.9	96.8		98.0	98.2	98 • 4 98 • 5	98.5	98.5	98.5	98.5	98.5	98.5
≥ 1200	64.5	88.0	92.0		96.7	97.7	98.4	99.0	99.3	99.5	99.5		99.5	99.5	99.5	99.5
≥ 1000 ≥ 900 ≥ 800	64.5	88 • 2	92.0	94.7	96.8	97.7	98.6	99.3	99.5	99.8	99.8		99.9		99.9	99.9
≥ 700 ≥ 600	64.5	88 • 2 88 • 2 88 • 2	92.0	94.7	96.8 96.8		98.6	99.4	99.6	99.8	99.8	99.9	100.C	100.0	100.0	100.0
≥ 500 ≥ 400	64.5	88.2	92.0	94.7	96.8		98.6		99.6	99.8	99.8	99.9	100.0	100.0	100.0	100.c
≥ 300 ≥ 200	64.5 64.5	88.2	92.0	94.7	96.8	97.8	98.6	99.4	99.6	99.8	99.8	99.9	100.0	100.0	100.0	100.
≥ 100 ≥ 0	64.5													100.0		

TOTAL NUMBER OF OBSERVATIONS____

__1766

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

Ç* •'

FUKUOKA KYUSHU JAPAN/I TAZUKE AB

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-200.

CEILING					Consumer (ViS	IBILITY (ST.	ATUTE MIL	ES)		-				
(FEFT)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 11/2	≥ 1%	≥ 1	≥ %	≥ 3/6	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	18.3	36.8 44.5	40.4	43.0 52.8	45.3 55.7	45.9 56.8	46.5 57.6		46.9 58.2	46.9 58.2	46.9 58.2	46.9 58.2		, .	46.9 58.2	46.9 58.2
≥ 18000	21.6	44.8		53.3	56.2	57.3	58.1	58.6	58.7	58.7	58.7	58.7			58.7	58.7
≥ 16000	21.8	45.9	50.7	54.7	57.8	58.9	60.0	1	60.6	60.6	60.6	60.6		· - 1	60.6	1
≥ 14000	23.1	48.3	53.3	57.6	60.8	62.0	63.2		63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
≥ 12000	23.5	51.3	56.9	61.9	65.4	66.8	68.4	69.3	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4
≥ 10000	23.8	54.1	60.2	65.5	69.3	70.9	72.9	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74-1	74.1
≥ 9000	24.0	55.0	61.2	66.8	70.7	72.4	74.6	75.7	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.€
≥ 8000	24.2	56.9	63.2	69.0	72.9	74.7	77.2	78.4	78.6	78.7	78.8	78.8	78.8	78.8	78.8	78.8
≥ 7000	24.3	57.4	63.9	69.8	73.8	75.6	78.3	79.6	79.7	79.9	79.9	79.9	79.9		79.9	
≥ 6000	24.5	58.0		71.1	75.3	77.1	79.9		81.4	81.6	81.6	81.6		ì I	81.6	
≥ 5000	25.4	60.3		73.5	77.7	79.6	82.6		84.1	84.3	84.3	84.3	84.3		84.3	د - 84
≥ 4500	25.9	61.7	68.8	75.3		81.6	84.6	-	1	86 • 3	86.4	86.4	86.4	1 1	86.4	
≥ 4000	26.5	63.6	70.9	77.3		84.1	87.2		88.9	89.1	89.2	89.2	89.3		89.3	د 89
≥ 3500	27.2	66.1	73.9	80.6		87.6	90.8		92.5	92 • 8	92.9	92.9		1 ' '	93.0	93.1
≥ 3000	27.5	67.5		82.0	87.0	89.2	92.7		94.4	94.7	94.9	94.9	95.0		95.0	
≥ 2500	27.7	68.4	76.4	83.2	88.3		94.1	95.8	95.9	96 • 3	96.4	96.4	96.5	1 1	96.5	96.5
≥ 2000	27.9	69.2	77.2	84.3	89.4	91.6	95.5		97.3	97.8	98.0	98.0				
≥ 1800	27.9	69 - 2		84 - 4	89.5	91.7	95.6			97.9		98.1	98.1	98.1	98.1	98.1
≥ 1500	27.9	69.4	77.6	84.9		92.2	96.5			98.9	99.1	99.1	99.2		99.2	99.2
≥ 1200 ≥ 1000	27.9	69.6	1	85.3		92.6	96.8		98.8	99.3	99.5	99.5	99.5	1 1	99.5	99.5
	27.9	69.6		85.3		92.6	96.9		99.0	99.5	99.7	99.7	99.7		99.7	99.1
≥ ₹00	27.9	69.6		85.3 85.4		92.6	96.9	1 3	99.0	99.5	99.7	99.7	99.7	99.7	99.7	99.7
	27.9	69.6		85.4		92.7	97.0		99.1	99.6	99.8	99.8	99.8		99.8	99.8
≥ 700 ≥ 600	27.9	69.6		85.4		92.7	97.0		99.1	99.6						
≥ 500	27.9	69.6		85.5			97.1		99.2	99.7	99.9	99.9				
≥ 400	27.9	69.6		85.5				99.0						100.0		
≥ 300	27.9	69.6		85.5	90.6		97.1	99.0	99.2	99.7				100.0		
≥ 200	27.9	69.6		85.5				99.0						100.0		
≥ 100	27.9	69.6		85.5	90.6		97.1			99.7				100.0		
≥ 0	27.9		!	85.5			97.1			29.7				100.0		
	//				7000	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<u> </u>							,		

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

UC F

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

2100-2300

CEILING							VIS	IBILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ½	≥ 1 1/4	≥ 1	≥ ¼	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	11.5	41.9	47.3	51.5	52.4	52.8	.53.C	53.0	53.2	53.2	53.2	53.2	53.3	53.3	53.3	53.3
≥ 20000	12.2	47.1	53.1	58.8	61.0	61.5	61.8	61.8	62.0	62.0	62.0	62.C	62.C	62.0	62.0	62.€
≥ 18000	12.4	47.8	53.8	54.5	61.8	62.3	62.5	62.6	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8
≥ 16000	12.5	48.3	54.5	60.5	62.7	63.3	63.5	63.6	63.7	63.7	63.7	63.7	63.8	63.8	63.8	63.8
≥ 14000	13.0	50.0	56.4	62.4	64.8	65.4	65.8	65.8	66.0	66.0	66.C	66.0	66.1	66.1	66.1	66.1
≥ 12000	13.7	52.7	59.7	66.5	69.3	69.9	70.3	70.4	70.5	70.5	70.5	70.5	70.6	70.6	70.6	76.6
≥ 10000	13.7	54.4	61.9	69.5	72.6	73.4	73.8	73.8	74.0	74.0	74.1	74.1	74.1	74.1	74.1	74.1
≥ 9000	13.9	56.0	63.5	71.C	74.3	75.3	75.7	75.8	75.9	75.9	76.0	76.0	76.1	76.1	76.1	76.1
≥ 8000	14.3	58.4	66.3	74.2	77.8	78.9	79.4	79.5	79.7	79.7	79.8	79.8	79.8	79.8	79.8	79.↓
≥ 7000	14.8	59.3	67.5	75.6	79.5	80.6	81.1	81.2	81.4	81.4	81.5	81.5	81.6	81.6	81.6	81.6
≥ 6000	14.9	60:1	68.5	76.8	80.7	82.0	82.6	82.8	82.9	82.9	83.1	83.1	83.1	83.1	83.1	83.1
≥ 5000	15.6	62.1	70.7	79.1	83.2	84.5	85.2	85.5	85.7	85.7	85.8	85.8	85.8	85.8	85.8	85.8
≥ 4500	15.8	63.2	71.8	80.5	84.6	86.0	86.7	87.0	87.2	87.2	87.3	87.3	87.4	87.4	87.4	87.4
≥ 4000	16.3	64.9	73.9	82.7	87.3	88.6	89.5	89.7	89.9	89.9	90.0	90.0	90.1	90.1	90.1	90.1
≥ 3500	16.7	66.6	75.7	84.5	89.2	90.6	91.5	91.9	92.1	92.1	92.2	92.2	92.2	92.2	92.2	92.4
≥ 3000	17.2	68.2	77.5	86.5	91.7	93.1	94.1	94.5	94.7	94.7	94.8	94.8	94.8	94.8	94.8	94.8
≥ 2500	17.4	68.6	78.0	87.1	92.4	93.8	94.9	95.4	95.5	95.5	95.6	95.6	95.7	95.7	95.7	95.7
≥ 2000	17.6	70.1	79.8	89.1	94.7	96.1	97.3	97.7	97.9	98 - 1	98.2	98.2	98.2	98 - 2	98.2	98 • 2
≥ 1800	17.7	70.3	79.9	89.5	95.1	96.5	97.7	98.1	98.3	98.5	98.6	98.6	98.6	98.6	98.6	98.€
≥ 1500	17.7	70.5	80.2	89.7	95.5	97.0	98.1	98.6	98.8	98.9	99.0	99.0	99.1	99.1	99.1	99.1
≥ 1200	17.7	70.7	80.3	89.9	95.6	97.1	98.3	98.8	99.0	99.2	99.3	99.3	99.3	99.3	99.3	99.3
≥ 1000	17.7	70.8	80.5	90.0	95.8	97.3	98.6	99.2	99.3	99.5	99.6	99.6	99.7	99.7	99.7	99.7
≥ 900	17.7	70.8	80.5	90.0	95.9	97.4	98.7	99.2	99.4	99.5	99.7	99.7	99.7	99.7	99.7	99.7
≥ 800	17.7	70.8	80.5	90.1	95.9	97.5	98.8	99.3	99.4	99.6	99.7	99.7	99.8	99.8	99.8	99.8
≥ 700	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.3	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8
≥ 600	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.4	99.5	99.7	99.9	99.9	99.9	99.9	99.9	99.9
≥ 500	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.4	99.5	99.7	99.9	99.9	99.9	99.9	99.9	99.9
≥ 400	17.7	76.8	80.5	90.1	96.0	97.5	98.8		99.5	99.7	99.9			100.0		
≥ 300	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.4	99.5	99.7	99.9	99.9	100.0	10C.0	100.0	106.0
≥ 200	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.4	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0
≥ 100	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.4	99.5	99.7	99.9	99.9	100.0	100.0	10C.0	100.0
≥ 0	17.7	70.8	80.5	90.1	96.0	97.5	98.8	99.4	99.5	99.7	99.9	99.9	100.0	100.0	100.0	Loc.c

TOTAL NUMBER OF OBSERVATIONS 1765

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0000-0200

CEILING							VIS	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥1%	≥1%	≥ 1	≥ ¾	≥ ⅓	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	8.9	38.4	43.5	49.3	51.5		52.9		53.5	53.9	54-0	54.0	54.0			
≥ 20000	9.4	41.5	47.7	55.0	58.1	59.1	59.9		60.4	60 . 8	60.9		61.0		61.2	61.3
≥ 18000	9.4	41.8	48.C	55.2	58.4		60.2	60.5	60.7	61 - 1	61.2	61.2	61.3	61.3		!!!
≥ 16000	9.4	42.1	48.3	55.6	58.8	59.8	60.6		61.1	61.5	61.6		61.7	61.8		
≥ 14000	9.4	42.7	48.9	56.2	59.5		61.3		61.9		62.4	62.4	62.5	62.5	l l	, ,
≥ 12000	9.5	43.7	50.5	58.3	62.0		64.0		64.5	64.9	65.0	65.0	65.1	65.1	65.3	65.4 68.8
≥ 10000	9.8	45.5	52.6	60.9	64.9	66.2	67.2	67.6	67.8	68 • 2	68.4	68.4	68.4	68.5	1	1
≥ 9000	9.9	45.8		61.4	65.6						69.1	69.1	69.2			
≥ 8000	10.0	46.8	54.4	63.6	68.0	69.2	70.6		71.2	71.6	71.8		71.8			l i
	10.1	47.5		64.6	70.6		73.6	72.0	72.3		74.8	72.8	72.7			
≥ 6000 ≥ 5000		1	56.8	66.3		72.2	78.6		79.3	1		79.8		1 '	,	80.2
<u> </u>	11.8	55.8	64.3		78.7			82.5			83.3					
≥ 4500 ≥ 4000	14.3	59.8	68.5		83.6	. 1		87.6	1	1	1	88.4		1	68.7	, ,
≥ 3500	14.9		70.8		86.8			91.0							92.2	
≥ 3000	15.4		73.1	84.4	89.9			94.3				95.3				95.7
≥ 2500	15.8			86.3	92.0		95.7								97.8	 i
≥ 2000	15.8		74.9	86.7	92.5	1 1	96.4				98.3			•		
≥ 1800	15.8				92.6		96.5				98.4					98.8
≥ 1500	15.8		74.9		92.7		97.0		98.1			98.8		l .		, ,
≥ 1200	15.8			87.C	92.9		97.3		98.4		99.2				99.4	99.6
≥ 1000	15.8		75.1	87.0			97.4		98.7	99.4	99.5	99.5	99.5	99.6	99.7	99.9
≥ 900	15.8	65.4		87.0			97.4	98.5	98.7	99.4	99.5	99.5	99.5	99.6	99.7	99.9
≥ 800	15.8	65.4	75.1	87.0	93.0	95.3	97.4	98.5	98.7	99.4	99.5	99.5	99.5	99.6	99.7	39.9
≥ 700	15.8	65.4	75.1	87.0	93.0	95.3	97.4	98.5	98.7	99.4	99.5	99.5	99.5	99.6	99.7	99.9
≥ 600	15.8	65.4		87.0	93.0	95.3	97.4				99.5					
≥ 500	15.8	65.4	75.1	87.0	93.6		97.4				99.5				1	99.9
≥ 400	15.8	65.4		87.0	93.0			98.5			99.5					
≥ 300	15.8	65.4	75.1	87.0	93.0	1					99.5			1 '		
≥ 200	15.8	65.4	75.1	87.0				98.5							·	
≥ 100	15.8	1	1 1		93.0				, ,		99.5			1	1	1
≥ 0	15.8	65.4	75.1	87.0	93.0	95.3	97.4	98.5	98.7	99.4	99.5	99.5	99.5	99.6	99.7	100.

TOTAL NUMBER OF OBSERVATIONS

1210W5 FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

and superaparation of

CATA PROCESSING CIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-0500 HOURS (LST)

CEILING				-			VIS	IBILITY (ST	ATUTE MIL	ESI						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ⅓	21%	≥ 1	≥ ¾	≥ 3/8	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	10.5 10.8	38.9 41.5	42.5 45.6	47.1 51.6	49.4 54.7		50.7 56.1	51.2 56.6	51.2 56.6	51.3 56.8		51.3 56.8	51.4 56.8	51.4	51.4 56.8	51.5 57.1
≥ 18000 ≥ 16000	16.8	41.6	45.7 46.1	52.2	54.8 55.3		56.3 56.7		56.7 57.2	56.9 57.4		56.9 57.4	57.0 57.4	57.0 57.4	57.0 57.4	57.1 57.6
≥ 14000 ≥ 12000	10.8	42.3 43.9	46.5 48.5	52.7 55.1	55.7 58.4			57.7	57.7 60.4	57.8 60.6		57.8 60.6	57.9 60.6	57.9 60.6	57.9 60.6	
≥ 10000 ≥ 9000	11.5	45.5 46.3		58.1 59.0	61.7 62.6		63.3 64.4	-	64.0 65.1	64.2 65.3		64.2 65.3	64•3 65•3	64.3 65.3	64.3 65.3	64.4
≥ 8000 ≥ 7000	11.5 11.6	48.1 49.1	54.0 55.1	61.8 63.1	65.7 67.2	66.7 68.2			68.4 70.2	68 • 5 70 • 4	70.4	68.5 70.4	68.6 70.4	68.6 70.4	68.6 70.4	70.0
≥ 6000 ≥ 5000	12.0 13.3	50 · 7	60.9	69.2	69.4 73.5	74.7	76.1	76.9	72.5 77.0	72.7 77.1	72.7	72.7 77.1	72.7	72.7	72.7	
≥ 4500 ≥ 4000	14.3	57.5 63.2	64.2 70.2	72.7 79.0		84.9		87.6		80 • 9 87 • 9	88.0	80.9 88.0	81.0	81.0	81.C 88.1	88 - 3
≥ 3500 ≥ 3000	16.9	66.1		83.3	88.2 91.6	92.9	94.9	95.8	92.4	96.1	96.2	92.7	92.7	92.7	92.9	96.€
≥ 2500 ≥ 2000	17.4	69.0		88.1	93.0	94.9		97.8		97.5 98.1	98.2	98.2	97.7	97.7 98.3	97.8	98.6
≥ 1800 ≥ 1500	17.4	69.4 69.4	78.2				·——	98.7	98.2 98.8		99.1	98.5	98.6 99.2	98.6 99.2	98.7 99.3	99.5
≥ 1200 ≥ 1000	17.4 17.4	69.4 69.4	78.2 78.2	88.4	94.0	95.7	97.8 97.9 97.9	98.9	98.8 99.0 99.0	99 • 1 99 • 2	99.3	99.1 99.3		99.4	99.5	99.1
≥ 900 ≥ 800 ≥ 700	17.4	69.4	78.2 78.2 78.2	88.4 88.4 88.5	94.0	95.7	97.9 98.0	98.9			99.3			99.4	99.5	99.7
≥ 600	17.4	69.4		88.5	94.2	95.8		99.0	99.1	99.4	99.4			99.5		99.8
≥ 500 ≥ 400 ≥ 300	17.4	69.4	78.2 78.2		94.2	95.8		99.0	99.1	99.4	99.4		99.5	99.5	99.6	99.8
≥ 200	17.4	69.4	78.2	88.5	94.2	95.8	98.0	99.0	99.1	99.4	99.4		99.5	99.5	99.6	99.8
≥ 0	17.4			_		25.8				99.4			1 1	99.5	1	100.0

TOTAL NUMBER OF OBSERVATIONS_

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

3600-0800

CEILING					-		VIS	BILITY (ST	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	8.5 9.5	25.3 28.1	29.8 33.5	32.7 37.4	36.0 41.8	37.7 43.6	40.1 46.4		48.7	42.6 49.6	42.7 49.6	42.7 49.6	42.8 49.8		42.8 49.8	42.9 49.5
≥ 18000 ≥ 16000	9.5 9.5	28.1 28.4		37.4 37.9	41.8		46.5 47.1	48.6 49.2	49.5		49.8 50.4	50.4	49.9 50.5	50.5	49.9 50.5	49.9 50.6
≥ 14000 ≥ 12000	9.8 9.9	29.2		39.2 41.8	43.8				54.3	52.0 55.3	52.1 55.4	55.4	52.2 55.5	55.5	52.2 55.5	52.3
≥ 10000 ≥ 9000	10.3	32.4		44.4	49.5 50.6		56.3		59.1	58.5	58.7		58.8			58.9
≥ 8000 ≥ 7000	10.8	35.6	42.6	47.4	52.9 54.2	56.8		63.1	63.5	64.5			64.9	64.9	64.9	
≥ 6000 ≥ 5000 ≥ 4500	11.2	36.5 39.9	43.7 47.4 51.2	49.6 53.6 57.4	$\overline{}$	$\overline{}$	61.9 66.2 70.4	64.6 69.0 73.4	69.4	66.1 70.5 75.0		66.3 70.8 75.3	66.5 71.0 75.5	71.0	66.5 71.0 75.5	71.1
≥ 4000 ≥ 3500	14.6 17.7	49.7			71.7		78.6	81.6	82.0			1	84.3	84.3	84.3	
≥ 3000 ≥ 2500	19.9		64.7	72.7	80.2	83.4	88.1	91.6	92.2		94.7	94.7		94.9	94.9	
≥ 2000 ≥ 1800	20.5	57.4	67.0	1	83.2	86.5	91.5	95.1	95.7	97.9	98.3	98.3	98.6	98.6	98.6	
≥ 1500 ≥ 1200	20.5	$\overline{}$			83.7	87.1	92.0	$\overline{}$	96.3 96.8		98.9	98.9			99.2 99.7	99.4
≥ 1000	20.5	57.7		76 • 1 76 • 1	84.2	87.5	92.6	96.3	96.8	98.9	99.5	1	99.8	99.8	99.8	99.9
≥ 800	20.5	57.7	67.7	76 • 1 76 • 1	84.2	87.5	92.6	96.3	96.8	98.9	99.5	99.5	99.8	99.8	99.8	99.9
≥ 600 ≥ 500 ≥ 400	20.5 20.5	57.7	67.7	76.1	84.2	87.5	92.6	96.3	96.8	98.9	99.5	99.5	99.8		99.8	99.9
≥ 400 ≥ 300 ≥ 200	2C.5 2C.5	57.7	67.7	76.1 76.1	84.2 84.2 84.2	87.5	92.6	96.3 96.3 96.3	96.8	98.9	99.5	99.5	99.8	99.8 99.8	99.8	99.9
≥ 100 ≥ 0	20.5	57.7		76.1	84.2	87.5	92.6	96.3	96.8	98.9	99.5	99.5	99.8	99.8		99.9

TOTAL NUMBER OF OBSERVATIONS __

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

NUV

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0900-1100

CEILING							VIS	BILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥	≥ ¾	≥ ¾	≥ 1/3	≥ 5/16	≥ ¼	≥ 0
NO CEILING	14.6	30.4	33.2		37.5			40.9		(41.1			41.2	41.2	41.2
≥ 20000	17.4	36.1	39.8	43.0	45.3	47.3	48.5	49.6	49.7		50.0				50.1	50.1
≥ 18000	17.5	36.3	40.1	43.4	45.7	47.7	49.0	50.1	50.2	50.3	50.5	50.5	50.5	50.5	50.5	50.5
≥ 16000	17.7	36.7	40.6	44.0	42.5	48.5	49.8	50.9	51.0	51.2		51.4	51.4	51.5	51.5	51.5
≥ 14000	18.0	37.7	41.8	45.4	47.8	49.9	51.3	52.5	52.5	52.7	52.9	52.9	52.9	53.0	53.	53.0
≥ 12000	18.5	39.4	43.9	47.8	50.4	52.6	54.1	55.2	55.3	55.5	55.8	55.8	55.8	55.9	55. 7	55.4
≥ 10000	19.2	41.6	46.6	51.4	54.3	56.6	58.5	59.8	59.8	60.1	60.4	60.5	60.8	60.8	60.8	3.00
≥ 9000	19.4	42.2	47.4	52.5	<u>55.7</u>	58.1	60.2	61.5	61.5	61.9	62.3	62.4	62.7	62.8	6.23	62.9
≥ 8000	2C.1	43.5	49.1	54.8	58.2	60.8	62.9	64.3	64.4	64.9	65.4	65.6	66.0	66.0	66.0	66.1
≥ 7000	20.2	44.0	49.8	55.7	59.3	62.0	64.4	66.0	66.1	66.7	67.1	67.4	67.7	67.8	67.8	67.5
≥ 6000	20.6	44.7	50.5	56.5	60.2	62.9	65.5	67.1	67.3	67.9	68.4	68.7	69.1	69.1	69.1	09.2
≥ 5000	21.6	46.8	52.8	59.1	62.8	65.5	68.2	70.0	70.2	70.8	71.4	71.6	72.0	72.1	72.1	72.2
≥ 4500	24.6	50.3	56.5	62.9	66.8	69.5	72.2	74.0	74.2	74.8	75.4	75.7	76.1	76.1	76.1	76.2
≥ 4000	29.4	57.0	63.6	70.4	74.4	77.3	80.4	82.2	82.5	83.2	84.0	84.2	84.7	84.8	84.8	84.9
≥ 3500	31.2	60.1	66.9	74.1	78.5	81.5	84.7	86.6	86.8	87.7	88.5	88.7	89.2	89.3	89.3	89.4
≥ 3000	33.3	63.5	70.5	78.C	82.9	86.0	89.4	91.5	91.8	92.7	93.5	93.7	94.2	94.3	94.3	94 • 3
≥ 2500	34.3	65.2	72.5	80.1	85.2	88.5	92.0	94.3	94.6	95.4	96.3	96.5	97.0	97.1	97.1	97.1
≥ 2000	34.6	66.0	73.3	81.C	86.3	89.5	93.1	95.4	95.7	96.6	97.4	97.7	98 • 2	98.2	98.2	98.3
≥ 1800	34.6	66.0	73.4	81.1	86.4	89.6	93.2	95.5	95.8	96.7	97.5	97.8	98.3	98.4	98.4	98.4
≥ 1500	34.6	66.3	73.8	81.5	86.8	90.1	93.8	96.1	96.4	97.4	98.2	98.4	99.1	99.1	99.1	99.2
≥ 1200	34.6	66.4	73.9	81.6	87.0	90.3	94.1	96.4	96.8	97.8	98.6	98.8	99.5	99.5	99.5	99.6
≥ 1000	34.6	66.4	73.9	81.6	87.0	90.3	94.2	96.5	96.9	97.9	98.7	98.9	99.6	99.7	99.7	19.8
≥ 900	34.6	66.4	73.9	81.6	87.C	90.3	94.2	96.5	96.9	97.9	98.7	98.9	99.6	99.7	99.7	99.6
≥ 800	34.6	66.4	73.9	81.6	87.0	90.3	94.2	96.6	97.0	98.0	98.8	99.0	99.7	99.8	99.8	99.8
≥ 700	34.6	66.4	73.9	81.6	87.0	90.3	94.2	96.7	97.0	98.0	98.8	99.1	99.8	99.8	99.8	99.9
≥ 600	34.6		73.9	81.6	87.0	90.3	74.2	96.7	97.0	98.0	98.8	99.1			99.8	99.9
≥ 500	34.6	66.4	73.9	81.6	87.0	90.3	94.2	96.7	97.0	98.0	98.8	99.1	99.8	99.8	99.8	99.9
≥ 400	34.6	66.4	73.9	81.6	87.0	90.3	94.2	96.7	97.0	98.0	98.8	99.1	99.8	99.8	99.8	99.5
≥ 30C	34.6	66.4	73.9						97.0							100-0
≥ 200	34.6	66.4			37.0	90.3	94.2	96.7	97.0	98.1	98.9	99.2	99.9			
≥ 100	34.6	66.4	73.9						97.0				99.9		99.9	
≥ 0	34.6	66.4	73.9	81.6	87.0	90.3	94.2	96.7	97.0	98.1	98.9	99.2	99.9	99.9	99.9	100.0

TOTAL NUMBER OF QBSERVATIONS_

1 71 C

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

NOV

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-140c

CEILING							VIS	IBILITY (ST.	ATUTE MI	.ES)		~~~				
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/3	≥ 2	≥1%	≥1%	≥ 1	≥ ¾	≥ %	≥ 1/3	≥ 5/16	≥ ¼	≥ 0
NO CE'LING	27.5	36.4	37.1	37.5	37.5	37.6	37.6			37.6	37.6	37.6	37.6			37.6
≥ 20000	33.2	46.4		47.8		48.0										
≥ 18000	33.7	47.3	48.2	48.7	48.8	48.9	48.9		48.9	48.9	48.9	48.9		t I		
≥ 16000	34.6	48.1	49.1	49.6		49.9	49.9			49.9	49.9	49.9				
≥ 14000	35.1	49.6	50.5	51.2		51.4	51.4		- 1	51.4	51.4	51.4				
≥ 12000	36.1	52.0	53.0	53.7	54.0	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2		54.2
≥ 10000	37.5	55.3	57.C	58.4		59.2	59.4			59.4	59.4	59.4		59.4		
	37.8	55.9	57.6	59.2	59.9	60.2	60.4									
≥ 8000	38.4	57.7	59.8	61.9		63.0	63.3			63.7	63.7	63.8				
	38.5	58.1	60.5	62.7	13.6	64-1	64.4									
≥ 6000	38.9	59.2	61.6	64.2		65.7	66.0	[66.1	66.4	- 1			•		66.5
 	40.8	51.5		66.8		68.5	68.8									
≥ 4500 ≥ 4000	43.1	64.8	67.4	70.2	-1	71.9	72.3			72.8		73.0				
<u> </u>	53.7	72.7	75.5 81.2	78.5 84.3			80.9			81.6	81.8		•			81.5
≥ 3500 ≥ 3000	57.4	83.0		89.6		86.4 92.2	86.8 92.7				93.8		ı	ı		
≥ 2500	58.8	85.4	88.5	92.2	94.0	95.1	95.6				96.8					
≥ 2000	59.4		89.6	93.6										I.		
≥ 1800	59.4		89.8	93.7	95.6	96.8	97.5				98.8					98.3
≥ 1500	59.4			93.9				98.2			99.1	99.1	1	99.1	1	99.1
≥ 1200	59.4		89.9	94.0		97.3	98.1			99.4	99.5					
≥ 1000	59.4		89.9	94.0		97.3		1 1) · 1		99.8	ŧ)	,	1
≥ 900	59.4	86.7	90.0		96.2	97.4										
≥ 800	59.4		90.0		96.2				98.9				Į.	99.8	i	
≥ 700	59.4	86.7	90.0	94.1	96.2											99.8
≥ 600	59.4		90.0	94.1	96.2	97.4	98.2	98.8	98.9	99.6	99.8	99.8		99.8	99.8	99.8
≥ 500	59.4	86.7	90.0	94.1	96.2	97.4								99.9		
≥ 400	59.4		90.0	1	96.3			1					1	100.0	1	1
≥ 300	59.4		90.0	94.1	96.3	97.5	98.4			99.8	69.9	100.0	100.0	100.0	100.0	100.0
≥ 200	59.4	86.7	90.0	94.1	96.3	97.5	98.4	99.0	99.1	99.8				100.0		
≥ 100	59.4			94.1	96.3	97.5	98.4	99.0	99.1	99.8	99.9	100.0	100.0	100.0	100.0	10C.U
≥ 0	59.4	86.7	90.0	94.1	96.3	97.5	98.4	99.0	99.1	99.8	99.9	100.0	100.0	100.0	<u> 10೮-0</u>	100.

TOTAL NUMBER OF OBSERVATIONS__

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 288C1

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITA/UKE AB 46-64

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-170

i							VISI	BILITY (ST	ATUTE MIL	ES)	· · • ·					
CEILING			- ,	ı											7	
(FCET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 %	≥ 1%	≥1	≥ ¼	≥ %	≥ 1/2	≥ 5/16	≥ 1/4	≥ 0
NO CEILING	3C.1	38.5	39.2	- 1	`4Õ•Ú			40.2					40.2		40.2	4 • 4
≥ 20000	36.5	49.1	50.5	51.3				51.9		52 .0	52.0		52.C		52.0	52.
<i>≥</i> 180∩0	37.2	49.9	51.4	52.2	52.6	52.8	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52 . 7
-2 16000	37.9	50.8	52.4	53.2	53.7	53.9	54.0	54.1	54.1	54.2	4 . 2	54.2	54.2	54.2	54.2	54 . 2
≥ 14000	36.5	52.6	54.4	55.4	56.1	56.4	56.6	56.7	56.7	56 • •	-6.8	56.8	56.8	56.8	56.8	56.0
≥ 12000	39.3	55.0	57.0	50.3	59.2	59.5	60.0	60.2	60.2	60 . 3	oC . 3	60.3	60.3	60.3	6C.3	06.3
≥ 10000	41.1	57.4	59.8	61.6	62.7	63.1	63.8	64.0	64.0	64 . 2	54.2	64.2	64.2	64.2	64.2	64.
≥ 9000	41.5	57.9	60.5	62.5	63.0	64.1	64.9	65.1	65.1	65.3	65.3	65.3	65.3	1	65.3	65.3
≥ 8000	41.9	59.6	62.3	64.6	65.9	66.5	67.6	67.8	67.8	68.0	68.1	68.1	68.1	68.1	68.1	68.1
≥ 7000	42.0	59.8	62.7	65.3	66.1	67.3	68.4	58.7	68.7	68 • 9	69.1	59.1	69.1	69.1	69.1	69.1
> 6000	42.2	6C.2	63.2	65.8	67.5	68.2	69.3	39.6	69.6	69.8	69.9	69.9	69.9	69.9	69.9	69.9
≥: 5000	43.8	62.4	65.4	68.4	70.3	71.0	72.3	72.6	72.6	72.9	73.0	73.C	73.0	73.0	73.0	73.
≥ 4500	45.8	65.1	68.3	71.6	73.5	74.3	75.6	76.0	76.0	76.3	76.4	76.4	76.4	76.4	76.4	16.4
≥ 4000	50.7	71.0	74.2	77.7	79.8	80.6	82.3	82.8	82.8	83.2	83.3	83.3	83.3	83.3	83.3	83.3
≥ 3500	54.4	76.1	79.5	83.3	85.6	86.4	88.1	88.6	88.8	89.1	89.2	89.2	89.3	89.3	89.3	89.3
≥ 3000	56.7	79.5	83.3	87.2	89.6	90.5	92.4	93.2	93.2	93.6	93.7	93.7	93.8	93.8	93.8	93.0
≥ 2500	57.5	81.3	85.3	89.6	92.3	93.2	95.1	96.0	96.0	96.4	96.5	96.5	96.5	96.5	96.5	96.5
≥ 2000	57.9	81.8	86.0	90.5	93.5	94.6	96.6	97.5	97.5	98.0	98.1	98.1	98.2	98.2	98.2	98.4
≥ 1800	58.0	81.9	86.1	90.6	93.6	94.7	96.7	97.7	97.7	98.1	98.3	98.3	98.4	98.4	98.4	98.4
≥ 1500	58.0		86.1	90.8	93.9	95.1	97.1	98.2	98.2	98 • 6	98.8		98.9	98.9	98.9	98.9
≥ 1200	58.0	81.9	86.1	90.9	93.9	95.1	97.2	98.2	98.2	98.7	58-9	98.9	99.0	99.0	99.0	99.1
≥ 1000	58.0		86.2	91.0	94.0	95.3	91.4			99.1			99.4		99.4	99.4
≥ 900	58.0	82.0	86.2	91.0	94.1	95.3	97.4			9.1	39.4	99.4	99.5		99.5	99.5
_ > 800 _	58.0		86.2	91.1	94.2	95.4	97.5		98.6	99.2			99.6	99.6		99.6
≥ 700	58.0	82.0	86.2	91.1	94.2	95.4	97.5		98.7	99 - 2	99.5	99.5	99.0		· · · · · · · · · · · · · · · · · · ·	74.6
≥ 600	58.0	82.0	86.2	91.1	94.2	95.4	97.6	98.8	98.8	99.4	99.6		99.8	99.8		49.8
≥ 500	58.0	82.0	86.2	91.1	94.2	95.4	97.6		98.8	99.4			99.8	99.8	99.8	99.₺
≥ 400	58.0			91.1					98.9			99.8				
≥ 300	58.0		86.2	91.1		1 1	97.6	,				99.8			,	
≥ 200	58.0			91.1	94.2	+				99.6					100.0	
≥ 100	58.0	!		91.1	94.2		1		1						100.0	_
≥ 0	58.0	82.0	86.2	91.1	94.2	95.4	97.6	98.9	98.9	99.6	99.8	99.8	100.0	100.0	100.0	100.

DATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

NUV

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1800-200.

CEILING				_			VIS	BILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ y,	≥ 5/16	≥ ¼	≥ 0
NO CEILING	7.4	24.5	30.9	36.3	40.5	- 1	45.1	46.9	47.0	47.7	1	47.7	47.8		47.8	1 1
≥ 20000	8.2		35.6	42.4	47.4		53.2		55.3	56.3		56.4	56.4		56.4	
≥ 18000	8.4	28.1	35.7	42.5	47.5		53.4	55.4	55.5	56.5		56.6	56.7	56.7	56.7	26.7
≥ 16000	8.2		35.8	42.7	48.0	50.9	54.0	56.0	56.1	57.1	57.3	57.3		57.3	57.3	
≥ 14000	8.4	28.7	36.5	43.9	49.4		55.8		58.2	59.2			59.4	59.4	59.4	
≥ 12000	8.4	29.8	37.8	45.7	51.6		58.6	61.1	61.3	62.8			63.0		63.0	
≥ 10000	9.5	31.6	40.0	48.8	55.2	58.9	63.1	65.8	66.0	67.5			68.0	68.0	68.0	l .
≥ 9000	9.5		40.3	49.2	55.8								68.8			
≥ 8000	9.4	32.3	41.1	50.3	57.0	61.1	65.8		68.9	70.4	ı 1	70.8	70.9	70.9	70.9	
≥ 7000	9.6	32.4	41.4	50.9		62.0		69.7	69.9							
≥ 6000	9 • ધ્	33.5	42.3	52 · 0	58.9	63.5	68.5	71.5	71.8	73.5		73.9	74.0		74.0	
≥ 5000	10.9	35.3	44.5	54.7	62.3	67.0			75.6	77.4				78.0	78.C	78.
≥ 4500	11.4	36.5	45.7	56.1	64.2	69.1	74.6		77.9	79.7	80.1	80.1	80.3	80.3	80.3	8C • 4
≥ 4000	13.9	40.5	49.8	60.5	68.8	73.7	79.5		83.0						85.8	
≥ 3500	14.9	42.9	52.7	63.6	72.4	77.5	83.6	86.8	87.1	89.1	89.6		89.8	89.8	89.8	89.9
≥ 3000	15.1	45.1	55.2	66.7	75.7	80.9	87.1	90.6	90.9	92.9					93.6	
≥ 2500	15.4	46.2	56.7	68.2	77.4	82.7	89.1	92.6	92.9	94.9	95.4	95.4	95.6	1 1	95.6	95.7
≥ 2000	15.5	47. C	57.9	69.6	79.1	84.6	91.0	94.8	95.0	97.1	97.6	97.6	97.8	97.8	97.8	97.8
≥ 1800	15.6	47.1	58.0	69.8	79.2	84.7	91.1	94.9	95.1	97.2	57.7	97.7	97.9	97.9	97.9	98
≥ 1500	15.6	47.2	58.1	70.9	79.6	85.1	91.6	95.4	95.6	97.7	98.2	98.2	98.4	98.4	98.4	
≥ 1200	15.4	47.2	58.1	70.1	80.1	85.7	92.2	96.0	96.2	98.3	98.8	98.8	99.0	99.0	99.0	99.1
≥ 1000	15.6		58.2	70.2	80.2	85.8	92.3			98.8			99.5	99.5	99.5	
≥ 900	15.4	47.2	58.2	70.2	80.2	85.8	92.3	96.3	96.5	98.8	99.4	99.4	99.5	99.5	99.5	99.6
≥ 800	15.6	47.2	58.2	70.2	80.3	85.8			96.5	98.9	99.4	99.4			99.6	99.6
≥ 700	15.6	47.2	58.2	70.2	80.3	85.8	92.4	96.4	96.6	98.9	99.5	99.5	99.6	99.6	99.6	99.7
≥ 600	15.6	47.2	58.2	70.2	80.4	85.9	92.5	96.5	96.7	99.1	99.6	99.6	99.8	99.8	99.8	99.8
≥ 500	15.6	47.2	58.2	70.2	80.4	85.9	92.6	96.5	96.8	99.1	99.6	99.6	99.9	99.9	99.9	99.9
≥ 400	15.6	47.2	58-2	70.2	80.4	85.9	72.6	96.5	96.8	99.1	99.6	99.6	99.9	99.9	99.9	99.9
≥ 300	15.6	47.2	58.2	70.2	80.4	85.9	92.6	96.5	96.8	99.1	99.6	99.6	99.9	99.9	99.9	100.C
≥ 200	15.6	47.2	58.2	70.2	80.4	85.9	92.6	96.5	96.8	99.1	99.6	99.6	99.9	99.9	99.9	156.0
≥ 100	15.6	47.2	58.2	70.2	80.4	85.9	92.6	96.5	96.8	99.1	99.6	99.6	99.9	99.9	99.9	100.
٥ ح	15.6	47.2	58.2	70.2	80.4	85.9	92.6	96.5	96.8	99.1	99.6	99.6	99.9	99.9	99.9	100.5
				·			·							*	·	

TOTAL NUMBER OF OBSERVATIONS...

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 2"8C1

CEILING VERSUS VISIBILITY,

FUKUCKA KYUSHU JAPAN/ITA/UKE AB 46-64 2100-230 PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING					-		VISI	BILITY (ST	ATUTE MILI	ES)	THE PERSON NAMED IN COLUMN 2 ASSESSMENT IN CO					
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥1%	≥ i	≥ ¾	> 1/0	≥ %	≥ 5/16	≥ ¼	≥ 0
NO CEILING	6.7	29.8	35.9	43.5	47.1	49.3	50.8	51.8	51.9	52 . C	52.0	52.0°	52.1	52.1	52.1	52.1
≥ 20000	7.d	32.9	40.2	49.6	54.7	51.7	59.5	60.6	60.7	61.0	61.0	61.0	61.1	61.1	61.1	01.1
≥ 18000	7.1	33.1	40.5	49.9	55.0	58.1	59.8	60.9	61.1	61.3	61.3	61.3	61.4	61.4	61.4	61.5
≥ 16000	7.1	33.3	40.8	50.2	55.4	58.5	60.3	61.4	61.5	61.9	61.9	61.9	61.9	61.9	61.9	62.0
≥ 14000	7.1	33.9	+1.7	51.2	56.6	59.8	61.6	62.7	62.8			63.2		63.2	63.2	63.3
≥ 12000	7.4	34.7	42.9	52.6	58.5	62.0								65.8		
≥ 10000	7.6	36.1	44.8	55.7	62.2	65.8			69.2	1	1	1	69.8) 1	69.8	•
≥ 9000	7.8	36.4		56.1	63.0		68.9		70.2			76.8	70.8			70.9
≥ 8000	7.8	36.9	45.7	57.3	64.3	68.0	70.5	71.7		72.3	72.4	1	72.5	72.5	72.5	72.
≥ 7000	7.8			58.2	65.4		71.6	72.7			73.5		73.6		73.6	73.6
≥ 6000	8.Q	38.1	47.4	59.4	66.5	70.2	73.1		74.4	74.9		75.0	75.1	1 1	75.1	75.1
≥ 5000	9.2	41.3		63.2	70.4		77.7		79.2	79.7	79.9	79.9	80.0		86.0	
≥ 4500	9.8			65.4	73.C			81.9	,	82.5	82.7	1	82.8			
≥ 4000	10.9		57.7	70.9	78.7		86.5		88.1	88.9	89.1	89.1	89.2		89.2	89.3
≥ 3500	11-1	49.0	59.7	73.2	81.4	85.7		90.9	91.1	91.9	,	i	92.2	1 1	92.2	د . 92
≥ 3000	11.4		62.2	76.0	84.3				94.0	94.9			95.2		95.2	95.3
≥ 2500	11.5		63.2	71.4	86.C	90.6		96.0	1	96.9	-1	97.1	97.3) 1	97.3	97.3
≥ 2000	11.8			78.4	87.5				97.6				98.8			
≥ 1800	11.8		64.2	78.5	87.5	92.1		97.5	1	98 - 5	98.7	98.7	98.8	1 1	1	98.9
≥ 1500	11.8								97.9		98.9		99.1			99.1
≥ 1200	11.8		1	78.7	87.8		96.1	98.0		98.9	99.1	99.1	99.2		99.2	99.3
≥ 1000	11.0			78.8					98.5			99.5			99.6	
≥ 900	11.8			78.8			96.5			99.4					99.7	99.0
≥ 800	11.8								98.6						99.8	
≥ 700	11.8				88.2			98.5				,		: :		
≥ 600	11.8									99.4				99.8		
≥ 500	11.8	l	1 1						98.6						99.8	
≥ 400	11.8			78.8					98.7			99.7		99.8		99.9
≥ 300	11.8		1 '	78.8			96.6					99.8				100.0
≥ 200	11.8								98.7					99.9		100 - 1
≥ 100	11.8								98.7					99.9		100.
≥ 0	11.8	52.9	64.5	78.8	88.2	92.9	96.6	98.6	98.7	99.5	99.8	99.8	99.9	99.9	99.9	130.0

TOTAL NUMBER OF OBSERVATIONS_

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUNUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING					-		VISI	BILITY (STA	ATUTE MIL	.ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1 1/4	≥1	≥ ¾	≥ %	≥ 1/1	≥ 5/16	≥ 1/4	≥ 0
NO CEILING ≥ 20000	8.2	29.2 32.1		37.1 41.3			,	L L		1	,				- 1	4 45 . c
≥ 18000	8.6	32.1	36.5	41.4	43.2	44.3	45.2	45.3	45.3	45.4	45.4	45.4	45.6	45.6	45.6	45.6
≥ 16000 ≥ 14000	8.6	32.8	36.7 37.2	41.5						45.6	*****			46.5		46.5
≥ 14000	8 • 8 9 • C	33.5	38.2	1	44.1	45.2		46.2		47.8		47.9		48.0	1	
≥ 10000	9.3	35.2	40.1			48.8				50.0				+		50.3
≥ 9000	9.6	36.1	41.4	47.0	49.2				- 1	51.7	•	51.7		1	51.8	51.,
≥ 8000	9.7	37.1	42.7	48.7	51.2	i	53.3			53.7					23.9	Ł.
≥ 7000	9.7			49.9	52.5	+				55.0		55.1				55.0
≥ 6000 ≥ 5000	10.4	39.4	45 · 3	51.7 57.6	54.6		56.8			57.2 63.8		57.3 63.9			57.5 64.6	57.7
≥ 4500	14.2	49.7	56.4		66.8					70.0					70.2	
≥ 4000	18.0	61.1	68.7	76.7	80.4					83.9					84.1	
≥ 3500	19.0	66.1	74.6	83.1	87.C	88.4	89.9	90.3	90.3	90.5	90.7	90.7	90.9	90.9	90.9	90.9
≥ 3000	19.6	69.6	78.6		92.0					95.6						
≥ 2500 ≥ 2000	19.8	- ,	79.8		93.5					97.2				,		97.7
≥ 1800	19.8	70.9	80.2	89.5	94.2		97.7	98.1			98.6		98.8		98.8 99.0	
≥ 1500	19.8	71.c	80.3	7	94.3					98.7			99.2		99.2	
≥ 1200	19.8				94.3		97.8				98.9					99.4
≥ 1000	19.8	71.0	80.5	89.7	94.4	96.0	98.1	98.6	98.7	98.9					99.5	99.5
≥ 900	19.8		_		94.4		98 - 1				99.2					
≥ 800	19.8	71.0				96.2				99.2					99.7	99.8
≥ 700	19.8	71.0			94.6					99.2						!
≥ 500	19.8		80.6		94.6			98.9			99.4			99.7		
≥ 400	19.8	71.0								99.3						99.9
≥ 300	19.8				94.6			99.0	-				1			' '
≥ 200	19.8			89.8							99.5				99.9	
≥ 100		71.0		· .	94.6		98.4 98.4				99.5			99.8		99.9
	19.8	71.C	80.6	89.8	74.6	70.0	78 • 4	99.0	77.1	1 77 - 3	39.5	77.5	77.8	77.8	1701	<u> </u>

TOTAL NUMBER OF OBSERVATIONS_

CAIA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

0300-350c

CEILING							VIS	- IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 %	≥1%	≥ 1	≥ ¾	≥ %	≥ ⅓	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	7.9	28.8	32.1	35.1	35.8		36.3	36.4	36.4		36.5	36.5	36.6			36.8 41.9
≥ 18000	8.4	$\frac{31.7}{21.7}$	35.4	39.4	40.7	+	41.3		41.5	+	41.6	41.6	41.7	41.8		
≥ 16000	8.5	31.7	35.5	39.4	40.7	41.4	41.4	41.5	41.7	41.6	41.6	41.6		-	42.0	
≥ 14000	8.5	32.7	36.8	40.7	42.2	42.6	42.8		42.9	43.1	43.1	43.1	43.2	43.2	43.3	43.5
≥ 12000	8.7	33.7	37.7	42.0	43.6		44.2	44.4	44.4	44.5	44.5	44.5	44.6			44.8
≥ 10000	9.0	35.3	39.3	43.8	45.5		46.1	46.3	46.3	46.4	46.4	46.4	46.5	46.5	46.6	46.1
≥ 9000	9.1	36.1		45.0	46.7	47.1	47.4		47.6	47.7	47.7	47.7	47.8			
≥ 8000	9.3	37.8	42.5	47.6	49.5	t	50.3		50.4	50.5	50.5	50.5		50.7	~	
≥ 7000	9.4	38.5		48.7	50.8		51.5		51.7	51.8	51.8	51.8		51.9	52.0	52.1
≥ 6000	9.9	40.2		50.7	52.8		53.5		53.7		53.8	53.8		53.9	54.1	54.1
≥ 5000	12.1	45.6	50.8	56.8	59.5	59.9	60.2	60.4	60.4	60.6	60.6	60.6	60.7	60.7	_6∩.8	60.8
≥ 4500	14.4	51.2	56.9	63.2	66.1	66.5	66.9	67.0	67.0	67.2	67.2	67.2	67.3	67.3	67.4	67.5
≥ 4000	18.6	62.5	68.8	76.0	79.2	79.7	80.0	80.2	80.2	80.3	80.3	80.3	80.5	80.5	80.6	3C •€.
≥ 3500	2C.7	68.8	76.2	84.2	88.2	88.7	89.1	89.2	89.2	89.5	89.5	89.5	89.7	89.7		
≥ 3000	21.6	72.6	80.1	88.4	92.9	93.5	94.2	94.3	94.3	94.6		94.6	94.8			95.1
≥ 2500	22.q	74.4	82.3	90.9	95.6	96.3	97.1				97.7	97.7	97.8	i 1		
≥ 2000	22.0	74.7	82.7	91.4	96.3	97.1			98.2			98.6		98.8		
≥ 1800	22.q			91.6	96.5		98.2					98.8				
≥ 1500	22.0			91.6				98.6			99.0					
≥ 1200	22.0	74.8					1	98.7						, ,	99.4	
≥ 1000	22.0					97.7		98.9								$\overline{}$
≥ 900 ≥ 800	22.0	74.8			96.9		98.7				99.3					i I
	22.0	74.8				97.8			99.0							
≥ 700	22.0	74.8	,,					99.0			1	99.3]]
	22.0					97.8		99.0								
≥ 500 ≥ 400	22.0	74.8	82.9 83.0			97.8					99.4			99.6		
≥ 300	22.0					97.8		99.1								
≥ 200	22.0	_	83. C						99.1					99.6		99.9
≥ 100		74.8			97.1			99.1						99.6		99.5
≥ 0	22.0		33.0			97.8								99.6		1
L	<u> </u>					نكلجت كسيد									<u> </u>	

TOTAL NUMBER OF OBSERVATIONS_

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VIS	IBILITY (ST.	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ 3%	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	5.C 5.4	18.7 21.3	22.4 25.9	24.6 28.7	26.3 31.0	1	28.0 33.1	28.6 33.8	1	29 · 1 34 · 4	,	29.2 34.5	29.4 34.7	29.4 34.7	29.4 34.7	29•5 34•8
≥ 18000 ≥ 16000	5.4 5.4	21.3		28.8 29.0	31.0 31.2		33.1 33.3	33.9 34.2	34.0 34.3	34.5 34.7	34.6 34.9	34.6 34.9	34.7 35.0		34.8 35.1	34.9 35.1
≥ 14000 ≥ 12000	5.6 5.7	22.4	27.1 28.1	30.1 31.5	32.4 34.0		34.5 36.3	35.5	35.6 37.4	36.0 37.9		36.2 38.0	36.3 38.2		36.4 38.3	36 • 4 38 • 3
≥ 10000 ≥ 9000	5.8 5.9	24.3 24.8		33.2 34.1	35.9 36.8		38.3 39.2	39.3 40.2	39.4 40.4	39 • 9 40 • 9		40.1 41.1	40.2 41.3	41.3		
≥ 8000 ≥ 7000	6.2 6.4	26.4 27.0		36.3 37.0	39.3 40.2	41.0	42.9	44.0	43.1 44.1	43.7 44.8				45.1	45.2	44.1 45.2
≥ 6000 ≥ 5000	7.1 9.6	28.5 33.5	40.0		48.4	49.3	45.1 51.5	46.2 52.6	52.7	47.0 53.4	53.6			53.8	47.4 53.8	
≥ 4500 ≥ 4000	11.7 17.2	38 • 5 49 • 9		50.9 63.9	54.6 68.0	68.9	57.9 71.4	72.8	72.9	59.9 73.7	73.9	73.9	60.2 74.0	74.0		74.1
≥ 3500 ≥ 3000	20.9	58.8 63.5	73.7	74.8 81.0		87.6		92.3	84.8 92.5	85.6 93.3	93.7	93.7	93.9 96.8	93.9	94.0	
≥ 2500 ≥ 2000 ≥ 1800	22.8					90.3	95.4	97.0	95.3 97.2 97.3	96 • 2 98 • 0 98 • 1		98.5		98.8	98.8	98.9
≥ 1500 ≥ 1500	22.8 22.8 22.8	65.7 65.7		84.6 84.6 84.7	90.7 90.8 90.8	92.1	95.8 95.8	97.3	97.5	98.4 98.5	98.8	98.9			99.2	99.3
≥ 1000	22.8		76.7 76.7	84.7	90.9	92.2	95.9 95.9	97.5	97.7	98 • 7 98 • 7	99.1	99.2	99.4		99.5	99.5
≥ 800	22.8		16.7 76.7	84.7	90.9 90.9	92.2	95.9	97.6	97.8	98 .8 98 .8	99.3	99.4	99.7	99.7	99.7	99.8
≥ 600	22.8		76.7 76.7	84.7		92.2	95.9	97.6		98 • 8 98 • 9	99.3			99.7	99.7	99.8
≥ 400 ≥ 300	22.8	65.7	76.8 76.8	84.8	91.1	92.5	96.2	97.8	98.0	99.0	99.5	99.6		99.9	99.9	100.u
≥ 200 ≥ 100	22.8	65.7 65.7				92.5				99.0 99.0					99.9 99.9	
≥ 0	22.8	65.7	76.8	84.8	91.1	92.5	96.2	97.8	98.0	99.0	99.5	99.6	99.9	99.9	99.9	100.6

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE. N. C. 28801

CEILING VERSUS VISIBILITY

FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 21/2	≥ 2	≥ 1 1/2	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	7.3 8.2	18.0 21.8		22.C 27.4	23.1 28.9	24.0 30.1	24.7 31.3	25.5 32.2	25.6 32.4	25.9 32.8	32.9	26.0 32.9	26.0 32.9	32.9	26.0 32.9	32.7
≥ 18000 ≥ 16000	8.3 8.4	22.0 22.3	25.5	27.7 28.1	29.1 29.5	30.4 30.8		32.5 33.0	32.7 33.2	33.1 33.6	33.2 33.7	33.2 33.7	33.2 33.7	33.2 33.7	33.2 33.7	33.7
≥ 14000 ≥ 12000	8.9 9.3	23.1 24.1	26.5 27.7	29.3 30.7		33.6		35.9	34.6	35.0 36.4	35.2 36.7	35.2 36.7	35.2 36.7	35.2	35.2 36.7	35.2
≥ 10000 ≥ 9000	9.9 1C.2	26.4 27.2		33.3 34.5	3 <u>6 - 5</u>			40.6	39.2 40.9	39.6 41.2	40.0	40.0	40.0 41.6	41.6	40.0 41.6	41.6
≥ 8000 ≥ 7000	JC.6	28 • 2 29 • 3		35.9 37.3		39.8 41.3		44.3	43.0	43.4	43.8	43.8	43.8 45.4	45.4	43.8	45.4
≥ 6000 ≥ 5000	11.7	30.3 33.7	34.7 38.4	38 • 7 42 • 4	41.3	1		50.3		46.7 51.0	47.1 51.5	47.1 51.5	47.1 51.6		47.1 51.6	47.1 51.6
≥ 4500 ≥ 4000	16.C 22.8	38.2 50.2	43.5 56.4	48.C 61.5	51.1 65.1	53.0 67.2	55.0 69.5	1 1	56.9 71.6	57.3 72.0	57.8 72.5	57.8 72.5		72.6		12.6
≥ 3500 ≥ 3000	28.3 31.1	59.4 63.9	66.5 72.0	72.1 78.7	76.2 83.5	1	81.1	82.9 91.3	83.2 91.6	83.9 92.4	84.3 92.9	84.3 92.9	84.4 93.0	1		
≥ 2500 ≥ 2000	31.9 32.0	66.2 66.5	74.8 75.4	81.7 82.4			92.8 94.2		95.5 96.9		97.1 98.5	97.1 98.5	97.2 98.6	,		1
≥ 1800 ≥ 1500	32.0 32.0	66.5 66.5		82.5 82.5			94.2			97.8 98.1	98.6 98.8	98.6 98.9	98.7 99.0	1		98 • 9 99 • 2
≥ 1200 ≥ 1000	32.0 32.0	66.5		82.7 82.7	88.2 88.3		94.6				99.3 99.5	99.3	99.5 99.7	ŧ		99.7
≥ 900 ≥ 800	32.0 32.0	l .		82.7 82.7	88.3 88.3		ŧ.	97.5 97.5	97.8 97.8		99.5	99.5 99.6				99.9
≥ 700 ≥ 600	32.0 32.0	1		82 • 7 82 • 7	88.3		94.7	97.5 97.5	97.8 97.8			99.7	99.8	l '	100.0 100.0	
≥ 500 ≥ 400	32.0 32.0			82.7 82.7	88.3 88.3			97.5 97.5				99.7 99.7	99.8		100.0 100.0	100.0 100.0
≥ 300 ≥ 200	32.C	66.5	75.7	82.7	88.3	91.3	94.7	97.5	97.8	98.9		99.7 99.7	99.8	99.9	1.	100.c
≥ 100 ≥ 0	32.C 32.0	66.5	75.7	82.7		91.3	94.7		97.8		99.6	99.7	99.8		100.0 100.0	100.0 100.0

TOTAL NUMBER OF OBSERVATIONS_

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 288C1

CEILING VERSUS VISIBILITY

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

46-64

DEC

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1200-1400 HOURS (LST.)

CEILING			• ,				VIS	BILITY (ST	ATUTE MIL	LES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓	≥ 2	≥ 1 1/2	≥11/4	≥ 1	≥ ¾	≥ 3/8	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING	16.9	23.6	24.2	24.3	-		24.5		24.6		24.6			, ,	24.6	24.6
≥ 20000	20.5	29.5	30.4		31.0	31.1	31.1		31.2	31.2	31.2		31.2			31.6
≥18000	20.9	29.9	30.8	31.1	31.4	31.5	31.5	31.6	31.6	31.6	31.6	31.6			31.6	31.6
≥16000	20.9	30.3	31.2	31.5	31.7	31.8	31.8	31.9	31.9	31.9	3:.9	31.9				
≥ 14000	22.C	32.1	33.1	33.6	33.8	34.0	34.C	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1
≥ 12000	23.C	34.3	35.4	36.C	36.3	36.4	36.4	36.6	36.6	36.6	36.6	36.6	36.6		$\overline{}$	_36 • ხ
≥10000	23.8	36.0	37.4	38.C	38.4	38.5	38.6	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9
≥ 9000	24.6	37.4	38.8	39.4	39.9	40.1	40.1	40.4	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40 - 5
≥ 8000	25.5	39.3	41.0	41.9	42.6	42.8	42.8	43.2	43.2	43.3	43.3	43.3	43.4	43.4	43.4	43.4
≥ 7000	26.0	40.4	42.3	43.3	44.C	44.3	44.3	44.7	44.7	44.8	44.8	44.8	44.8	44.9	44.9	44.9
≥ 6000	26.6	41.8	43.9	45.2	46.2	46.4	46.6	46.9	47.0	47.0	47.0	47.0	47.1	47.1	47.1	47.1
≥ 5000	28.2	44.5	47.1	48.6	49.7	50.0	50.3	50.8	50.8	50.9	50.9	50.9	50.9	51.0	51.0	51.
≥ 4500	31.9	49.6	52.3	54 . C	55.2	55.5	55.8	56.3	56.3	56.4	56.4	56.4	56.4	56.5	56.5	56.5
≥ 4000	45.C	65.6	68.8	70.8	72.3	72.7	73.2	74.0	74.1	74.3	74.3	74.3	74.3	74.4	74.4	74.4
2 3500	51.3	75.3	78.9	81.2	82.9	83.3	83.8	84.7	84.8	85.0	85.0	85.0	85.1	85.1	85.1	85.1
≥ 3000	55.9	82.1	86.2	88.9	91.C	91.7	92.4	93.2	93.3	93.7	93.7	93.7	93.7	93.8	93.8	93.b
≥ 2500	56.9	84.2	88.6	91.6	93.8	94.6	95.2	96.3	96.5	96.9	96.9	96.9	96.9	97.0	97.1	97.1
≥ 2000	57.0	84.9	89.4	92.5	94.7	95.5	96.3	47.4	97.6	98.0	98.0	98.0	98.1	98.1	98.2	98.2
≥ 1800	57.2	85.1	89.6	92.6	95.0	95.8	96.6	97.7	97.8	98.3	98.3	98.3	98.4	98.4	98.5	98.5
≥ 1500	57.3	85.2	89.7	92.8	95.1	96.0	96.9			98 - 8	98.8	98.8	98.9	98.9	99.0	99.0
≥ 1200	57.3	85.2	89.8	92.9	95.3	96.2	97.1	98.4	98.6					99.4	99.5	99.5
≥ 1000	57.3	85.2	89.9	93.0	95.4	96.3	97.2	98.5	98.7	99.4	99.4	99.4	99.5	99.5	99.6	99.6
≥ 900	57.3	85.2	89.9	93.C	95.5	96.3				95.5	99.5	99.5	99.6	99.7	99.7	99.7
≥ 800	57.3	85.2	89.9	93.0	95.5	96.4	97.5	98.8	98.9	99.7	99.7	99.7	99.7	99.8	99.8	99.8
≥ 700	57.3	85.2	89.9	93.0	95.5	96.4			98.9	99.7	99.7	99.7	99.7	99.8	99.8	99.8
≥ 600	57.3	85.2	89.9	93.0	95.5		97.5	98.8	98.9	99.7	99.7	99.7	99.8	99.8	99.9	99.9
≥ 500	57.3	85.2	89.9								99.7				99.9	99.9
≥ 400	57.3	85.2	89.9		95.5		97.5		98.9		99.7	99.7	99.8	99.9	99.9	99.9
≥ 300	57.3	85.2	89.9								99.7				99.9	99.9
≥ 200	57.3			93.0			97.5	98.8	98.9	99.7	99.7	99.7	99.8	99.9	99.9	100.0
≥ 100	57.3	85.2			95.5			98.8			99.7					
≥ 0	57.3	85.2						ı		99.7	99.7	99.7	99.8	99.9	99.9	100.0

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

43310 FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1500-170C

CEILING							۸ı۶	IBILITY (ST.	ATUTE MIL	LES)		,	_			
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 ½	≥1%	≥ 1	≥ ¾	≥ ¾	≥ ½	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	19.5 23.7	26.4 34.6	27.2 35.8			27.9 36.9	28 • 1 37 • 1	28.1 37.1	28.1 37.1	28 · 1 37 · 1	28.1 37.1	28.1 37.1	28.1 37.1		28.1 37.1	28.1 37.1
≥ 18000 ≥ 16000	24.1 24.8	35.3 36.4	36.4 37.6			37.6 38.8	37.8 38.9	1 1		1	37.9	37.9 39.0			37.9 39.0	37.9 39.0
≥ 14000 ≥ 12000	25.5 26.7	37•7 40•2	39.0 41.7	39.7 42.7	40.2 43.2	40.4 43.4	40.6 43.6		40.6 43.7		40.7	40.7 43.9	40.7		40.7 43.9	46 • 7 43 • 9
≥ 10000 ≥ 9000	27.4 27.6		43.8 44.9				46.3 47.7		46.5 47.8	46.8 48.1	46.8 48.1	46.8 48.1		46.8 48.1		46.8 48.1
≥ 8000 ≥ 7000	27.9 28.2	44.5	46.2 47.0	48.6		50.0	49.4 50.5	50.9						51.4	51.4	
≥ 5000 ≥ 5000	28.6 30.2	48.2	48.0 51.4	53.4	55.0	51.6 55.3	52.1 55.9	56.4		57.0		53.1 57.0		53.1 57.1		53.1 57.1
≥ 4500 ≥ 4000	33.5	52.4 66.1	55.9 69.8	72.3	74.1	74.7	60.8 75.3	75.9	76.0	76.6			62.0 76.8	76.8	76.8	76.8
≥ 3500 ≥ 3000	51.2 53.5		79.6 84.7	88.0		84.8 91.0	85.6 92.0	92.7		93.3				93.7	93.7	93.1
≥ 2500 ≥ 2000 ≥ 1800	54.1 54.3 54.4	-	86.1 87.1	89.6 91.0	93.7	93.2 95.0	94.2	96.9	97.0	97.6		95.8 97.8	98.0	98.0	98.0	
≥ 1500 ≥ 1500	54.4	82.3	87.4 87.4	91.3	94.3	95.3 95.6 95.8	96.4 96.8 96.9	97.6			98.1 98.5 98.8	98.2 98.6 98.9	98.4 98.8 99.1	98.4 98.8 99.1	98.4 98.8 99.1	98.4 98.8 99.1
≥ 1000 ≥ 900	54.4	82.4		91.6	94.6		97.2	98.1	98.4	99.0		99.3	99.5			_
≥ 800 ≥ 700	54.4	82.4	87.5 87.5	91.6	94.7	96.1 96.1	97.3	98.4	98.6	99.3	- 1	99.6	99.8	99.8	99.8	99.8
≥ 600 ≥ 500	54.4	82.4	,	91.6		96.2 96.2	97.4	98.5	98.7	99.4	99.6	99.7	99.9	99.9	99.9	
≥ 400 ≥ 300	54.4	82.4		91.7		96.2		98.5	98.8	99.5	99.7	99.8	99.9	99.9	99.9	
≥ 200	54.4	82.4	87.5	91.7	94.7	96.2	97.5	98.5	98.8	99.5		99.8	99.9	99.9	99.9	99.9
≥ 0	54.4							98.5			99.7				100.0	1

TOTAL NUMBER OF OBSERVATIONS__

1210WS FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

4331C FUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING			_				VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 ⅓2	≥ 2	≥ 1 ½	≥ 11/4	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	4.6 5.2	18.2	23.0	27.2	30.6 35.1	33.0 38.3		36.0 41.8	36.0 41.9	36 · 3 42 · 2	36.3 42.2	36.3	36.3 42.2	36.3 42.3	36.3 42.3	36.3
≥ 18000 ≥ 16000	5.3 5.4	21.2	26.4	31.5	35.6	38.9	41.4	42.4	42.5 42.8	42.8	42.8 43.2	42.8	42.8 43.2	42.9	42.9 43.2	42.9
≥ 14000 ≥ 12000	5.4 5.4	21.8	27.3	32 • 5 34 • 2	36.8	40.1	42.7	43.9	43.9	44.3	44.3	44.3	44.3	44.3	44.3	44.3
≥ 10000 ≥ 9000	5.4 5.4	22.8	29.4 29.6	35 • 7 36 • 0	40.6	44.5 45.0		49.2 50.0	49.3 50.1	49.8 50.6	49.8 50.8		49.8 50.8	49.9 50.8	49.9 50.8	49.9 50.8
≥ 8000 ≥ 7000	5.5 5.5	23.4	30.5 31.1	37 • 2 38 • 4	42.5			52.0 53.8		52.6 54.5	52.8 54.8		52.8 54.8	1	52.9 55.0	52.9 55.0
≥ 6000 ≥ 5000	5.5 6.5	24.1 27.6	31.7 35.4	39.4 43.5	45.5 50.0	50.0 54.7		55.7 60.7	55.7 60.8	56.5 61.6	56.8 61.9		56.8 62.0		56.9 62.1	56.7 62.1
≥ 4500 ≥ 4000	7.6 11.5	30.9 40.3	39.1 49.2	47.7 58.6	54.4 65.5	59.1 70.9		65.3 77.6		66.4 78.7	66 • 8 79 • 1	66.8 79.1	66.8 79.2		1	66.9 79.3
≥ 3500 ≥ 3000	13.1 13.8	46.0 49.7	55.6 60.0		73.3 78.9			86.1 92.1	86.2 92.2	87.2 93.2	87.5 93.5	93.6	87.9 93.9	93.9	94.0	88. 94.
≥ 2500 ≥ 2000	14.0 14.0	50.7 51.4		72.2 73.1	80.8 82.1	88.0	93.4		96.2	95.5	96 • 1 97 • 7	96.2 97.7	96.4 98.0	98.1	96.5 98.1	96.5 98.1
≥ 1800 ≥ 1500	14.0 14.0	51.5 51.6	62.3	73.4 73.5	82.5 82.7	88.6	94.2	96.8	96.9	97.5 98.0	98.5	98.6		98.9		98.5 99.c
≥ 1200 ≥ 1000	14.C	51.6 51.6	62.4	73.6 73.6		88.9	94.5		97.3	98 • 2 98 • 4	99.1	99.2	99.4	99.5		99.5
≥ 900	14.C 14.C	51.6 51.6	62.4	73.7	83.0 83.0		94.7	97.3	97.5	98.5 98.5	99.2	99.3	99.5	99.6	99.7	99.6
≥ 700 ≥ 600	14.C 14.C		62.4	73.7 73.7	83.0 83.1	89.1	94.7	97.4 97.5	97.6			99.4	99.6	99.7	99.8	
≥ 500 ≥ 400	14.C 14.C		62.4	73.7 73.7	83.1 83.1	89.1 89.1	94.7	97.5 97.5	97.6	98.6	99.4	99.5	99.8	99.8	99.9	99.7
≥ 300 ≥ 200	14.0	51.6 -51.6	62.4		83.1 83.1	89.1		97.5	97.6		99.4	99.5	99.8 99.8	99.8		99.5
≥ 100	14.0 14.0	51.6 51.6	1	73.7 73.7	83.1 83.1	89.1 89.1	94.7	97.5 97.5	1	98.6 98.6			99.8	1		

TOTAL NUMBER OF OBSERVATIONS_

1210WS JUL 64 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

CEILING VERSUS VISIBILITY

EUKUCKA KYUSHU JAPAN/I TAZUKE AB 46-64

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

CEILING							VIS	IBILITY (ST	ATUTE MIL	ES)						
(FEET)	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 1/2	≥ 2	≥ 1 1/2	≥ 1%	≥ 1	≥ ¾	≥ %	≥ 1/2	≥ 5/16	≥ ¼	≥ 0
NO CEILING ≥ 20000	5.4 5.8	23.7 25.8	29.0 31.5	35.C 38.C	38.2 42.7		46.6 44.8	40.0 44.9	40.0	40.0 44.9	46.2 45.2	40.2 45.2	40.2 45.2		40.3 45.3	40 • 3 45 • 5
≥ 18000 ≥ 16000	5.8 5.8	26.0 26.1	31.6 31.8	38.3 38.4	42.9 43.1	44.4	45.1 45.3	45.2 45.4	45.2 45.4	45.2 45.4	45.4 45.7	45.4 45.7	45.5 45.7	45.7	45.6 45.8	45.c
≥ 14000 ≥ 12000	5.9 6.0	26.4 27.0		39.0 40.0	43.7 44.9	45.3	46 • 1 47 • 4		46.3	46.3	47.8	46.5 47.8	46.6	47.9	46.6	47.5
≥ 10000 ≥ 9000	6.1	28.1 28.6		41.7	47.9	46.7 49.7	49.5 50.6		49.8 50.9	49.8 50.9	51.2	51.2	50.1 51.3	50.1 51.3	50.1 51.3	
≥ 8000 ≥ 7000	6.5 6.5	29.3 29.8	37.0	43.8	49.7 50.7	51.5 52.6	52.4 53.7	53.0 54.2	53.0 54.2	53.0 54.2	54.6			53.4 54.7	53.5	54.7
≥ 6000 ≥ 5000	6.7 7.8	30.7 35.0		46.1 51.3	52.6 58.3	54.4 60.2	55.6 61.5		56.3 62.3	56.3 62.3	62.6			62.7	56.8 62.8	62.
≥ 4500 ≥ 4000	9.8 15.0	39.2 50.3	59.5	56.2 68.5	63.5 76.3	78.7	80.3	81,2	67.7 81.3	67.8 81.4	81.8			81.9	68.3 81.9	81.7
≥ 3500	15.4	54.8 57.9	68.8		87.7		91.9	92.9		87.5 93.2	93.7		93.8	93.8	88.2 93.9 96.6	93.0
≥ 2500 ≥ 2000 ≥ 1800	15.8 15.8	59.1 59.6	,		90.9	93.7	94.5 95.7	96.8	95.6 96.8	95.9 97.1 97.5	96.4 97.7 98.1	_	96.5 97.8 98.2	97.8	97.9 98.3	
≥ 1800 ≥ 1500 ≥ 1200	15.8		71.3	81.9 82.1	91.4	94.3	96.1 96.4		97.7 97.7	98 • 1 98 • 6	98.7	98.7	98.8	98.8	98.9	
≥ 1000	15.8 16.0		71.4 71.5 71.6	82.5 82.6 82.6	92.C		96.9 97.1 97.1	98.3	98.4 98.5	98.8 98.9	99.4	99.4		99.5	99.6 99.7	
≥ 800	16.C	60.2	71.6	82.6	92.1	95.0 95.0	97.1 97.2	98.4	98.5	98.9	99.4	99.4	99.5	99.5	99.7	99.7
≥ 600 ≥ 500	16.0 16.0	60.2	71.6	82.6	92.1	95.0 95.0		98.5	98.6	99.0	99.6	99.6	99.7	99.7		99.8
≥ 400	16.0 16.0	60.2	71.6	82.6	92.1	95.0		98.6	98.7	99.1	99.7	99.7	99.8	99.8	99.9	99.7
≥ 200	16.0	60.2	71.6	82.6	92.1	95.0	97.2	98.6	98.8	99.2	99.7	99.7	99.9	99.9	100.0 100.0	100.5
≥ 0	16.0					95.0	1	98.6	98.8		59.7	99.7	99.9	1	1.	i oc 🏮

TOTAL NUMBER OF OBSERVATIONS_

1210W\$ FORM 0-14-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PART D

SKY COVER

This summary is prepared from hourly observations and is a percentage frequency distribution of total sky cover by tenths, plus mean sky cover, and total number of observations. It is presented in two tables as follows:

- 1. By month and annual all hours and all years combined.
- 2. By month by standard 3-hour groups.

The The MANAGE .

- NOTE: #1: Sky cover (total cloud amount) was not reported by U. S. Services until mid 1945. Data, when available, were punched for Air Force stations beginning in 1946, but were not available for Mavy stations until 1948 or 1949. Weather Bureau stations recorded total cloud amount in remarks beginning some time in 1945, but few stations have punched data prior to 1948. This summary will, of course, be limited to period of available data.
- NOTE: #2: Some sources of punched data used for this summary report cloud amounts in oktas. These have been converted to tenths prior to summarizing, and notation is made on the form to indicate that data were originally reported in oktas. The manner of conversion is given below:

OKTAS	TEATIES
0	0
1 2	1
3	3
5	5
6 7	8
8 (or obscured)	10

CATA PROCESSING DIVISION ETAC, USAF ASFEVILLE, N.C. 28801

SKY COVER

43310

FUKUUKA KYUSHU JAPAN/ITAZUKE AB

46-64

ALL

25165

PERIOD

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PER	CENTAGE F	REQUENCY	OF TENTHS	OF TOTAL S	KY COVER				MEAN TENTHS OF	TOTAL NO. OF
MONTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	SKY COVER	OBS.
JAN	ALL	6.5	3.3	3.3	3.5	3.6	3.2	4.7	5.5	8.1	9.5	48.8	7.6	13390
FEB		8.9	4.1	4.1	3.6	3.5	3.3	4.2	5.4	7.2	8.0	47.7	7.2	11543
MAR		12.9	4.4	4.5	4.1	4.1	3.5	3.7	4.8	6.5	6.4	45.2	5.8	12648
APR		14.5	4.4	4.C	4.2	3.1	2.6	3.0	3.6	5.2	5.0	50.4	6.8	12237
MAY		12.3	3.4	3.7	3.6	3.1	2.0	2.7	3.9	5.7	5.3	54.1	7.2	13387
NUL		5.3	2.8	3.1	3.(2.8	2.8	2.6	4.1	6.8	6.8	59.9	8.0	12756
JUL		5.3	3.C	4.5	4.3	4.2	3.3	3.3	5.3	8.5	9.2	48.9	7.6	13380
AUG		9.7	5.4	6.1	6.7	5.7	4.9	4.1	7.0	16.1	8.5	31.8	6.3	13372
SEP		11.2	4.9	4.9	5.1	4.2	3.6	3.5	5.3	7.1	7.7	42.4	6.7	13522
100		18.9	6.0	6.5	5.9	4.9	4.3	3.7	5.1	7.0	6.3	31.4	5.6	14131
พบง		20.0	5.9	5.9	5.4	5.0	4.3	4.5	5.1	7.0	6.1	36.9	5.6	13079
DEC		11.1	3.9	4.7	4.5	4.5	4.0	5.0	6.4	8.1	8.6	39.2	6.7	14132
10	TALS	11.5	4.3	4.6	4.5	4.1	3.5	3.8	5.2	7.3	7.3	44.0	6.8	158377

1210WS FORM 0-9-5 [Det 50] PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

SKY COVER

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB
STATION NAME

47-64

JAN

STATION

PERIOD

MONT

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERC	ENTAGE F	REQUENCY	OF TENTHS	OF TOTAL S	KY COVER				MEAN TENTHS OF	TOTAL NO OF
MONTH	(L.S.T.)	0	1	2	3 /	4	5	6	7	8	9	10	SKY COVER	
JAN	00-62	11.4	3.6	3.8	4.2	3.8	3.4	4.9	5.5	7.0	6.6	46.1	7.0	1674
	03-05	/10.C	3.8	2.6	3.0	2.9	2.6	5.0	5.1	7.7	7.5	49.3	7.3	1074
	06-08	5.6	2.3	2.8	3.4	3.0	2.9	4.4	5.3	9.0	9.7	51.7	7.8	1074
	09-11	2.5	2.5	2.1	3.1	3.4	3.1	5.1	5.3	9.4	13.9	49.6	8.1	1674
	12-14	1.9	2.3	2.9	3.3	4.2	4.9	3.7	6.8	8.3	11.1	50.7	8.0	1674
	15-17	3.1	3.9	3.6	2.8	3.2	3.5	4.7	5.1	7.9	11.8	5₹.3	7.9	1673
	18-20	- 6.6	4.4	4.2	3.3	3.9	2.7	4.3	5.4	8.5	9.1	47.6	7.4	1674
	21-23	-11.0	3.5	4.1	4.4	4.1	3.0	5.8	5.7	7.2	6.2	45.1	7.0	1673
	<u> </u>													
					ĺ									
10	TALS	6.5	3.3	3.3	3.5	3.6	3.2	4.7	5.5	8.1	9.5	48.8	7.6	13390

1210WS FORM 0.9-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

SKY COVER

4331C

FUKUCKA KYUSHU JAPAN/I IAZUKI: AB

48-64

FEB MONTH

STATION

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERC	ENTAGE F	EQUENCY (OF TENTHS	OF TOTAL S	KY COVER				MEAN	JATCI
MONTH	(L.S.T.)	c	1	2	3	4	5	6	7		9	10	TENTHS OF SKY COVER	NO. OF
FEB	00-02	14.2	5.0	4.1	3.9	3.4	2.9	3.1	5.3	6.4	6.8	44.4	6.7	144
	03-05	11.3	4.0	3.5	3.5	3.5	3.2	4.9	5.1	6.4	6 • 2	48.6	7.1	144
	(6-c8	6.9	2.8	4.1	2.7	3.3	3.7	4.4	4.9	7.8	8.1	51.2	7.6	144
T-10-0-10-0	09-11	5.0	3.5	2.6	2.8	2.8	2.9	5.1	4.6	8.7	11.2	50.9	7.8	144
	12-14	5.5	3.3	3.0	3.3	3.4	4.2	3.7	6.4	7.9	10.1	49.3	7.1	144
	15-17	6.6	4.C	4.8	3. ,	3.9	2.5	4.2	7.3	7.8	7.6	47.4	7.3	144
	18-20	8.5	5.1	4.7	4.3	4.9	3.3	4.2	5.2	7.1	7.7	45.0	7. ^	144
	21-23	13.4	4.5	5.8	4.2	3.2	3.7	4.4	4.7	5.2	6.0	44.9	6.6	144
····														
	 				 -									
	<u> </u>												<u> </u>	
TO	TALS	8.9	4.1	4.1	3.6	3.5	3.3	4.2	5.4	7.2	8.0	47.7	7 7	1154

1210W5 FORM 0-9-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC, USAF ASHFVILLE, N.C. 288C1

SKY COVER

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

48-64

MAR

STATION

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PER	ENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	SKY COVER	1			MEAN	TOTAL
MONTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	TENTHS OF SKY COVER	NO. OF OBS.
MAR	00-02	19.7	4.4	4.4	4.0	3.6	2.9	2.8	3.2	5.6	4.1	45.3	6.3	. 1561
	03-05	17.3	3.3	4.6	3.3	4.0	2.5	3.4	4.7	4.8	3.8	48.3	6.6	1581
	06-08	10.1	3.4	3.7	3.7	4.5	3.5	4.6	4.4	7.5	6.6	48.1	7.2	1581
	09-11	10.0	3.6	3.3	4.6	4.0	4.0	4 • 7	5.9	5.8	8.9	45.8	7.1	1581
,	12-14	8.2	5.6	3.5	4.6	4.2	4.8	3.5	5 • 2	1.6	8.2	44.5	7.0	1581
	15-17	8.9	5.1	4.6	3.7	4.2	2.9	3.5	6.1	8.2	8.8	44.0	7.1	1581
	18-20	11.4	5.1	5.2	4.8	4.4	3.3	3.3	5.6	6.4	6.3	44.2	6.7	1581
	21-23	17.4	4.9	6.6	4.3	3.8	4.1	3.9	3.0	6.3	4.4	41.3	6.1	158

10	TALS	12.9	4.4	4.5	4.1	4.1	3.5	3.7	4 . 8	6.5	6.4	45.2	6.8	12648

1210W5 FORM 0.9.5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N.C. 28801

SKY COVER

43310

FUKULIKA KYUSHU JAPAN/I IAZUKE AB

48-64

APR MONTH

STATION

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PER	CENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	SKY COVER	1			MEAN	TOTAL
HTMOM	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	TENTHS OF SKY COVER	NO. OF OBS.
APR	00-02	20.2	3.6	3.9	4.2	3.7	2.6	2.2	4.3	4.7	3.3	47.4	6.4	152
	03-05	20.7	3.7	4.1	3.0	3.8	2.2	3.6	3.3	3.7	2.1	48.9	6.4	153
	บ6 - บ8	12.4	4.8	3.9	4	3.1	3.0	2.7	3.6	4.5	5 • c	J2.5	7.0	153
	09-11	11.3	3.7	4.4	4 . 3	3.7	3.0	3.1	4.3	4.9	6.0	51.2	7.1	152
	12-14	9.4	6.0	4 • 3	4.6	2.7	2.1	2.2	3 • i	5.8	5 • 8	54.0	7.2	152
	15-17	9.9	5.3	3.9	4.6	2.7	2.2	3.0	3.0	5.5	6.7	53.2	7.2	153
	18-20	12.9	3.9	3.3	3.9	2.5	2.9	3.1	4.2	5.7	6.5	51.0	7.1	153
	21-23	19.1	4.0	4.2	4.2	2.8	2.7	3.9	3.4	6.7	3.7	45.2	6.4	153
											_			
													 	
TO	TALS	14.5	4.4	4.C	4.2	3.1	2.6	3.0	3.6	5.2	5.0	50.4	6.	1223

1210WS FORM 0-9-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

ren - Mart o d

CATA PROCESSING DIVISION ETAC: USAF ASHEVILLE, N.C. 28801

SKY COVER

43310

I UKUOKA KYUSHU JAPAN/I TAZUKE AB

MAY MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PER	CENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	KY COVER				MEAN	TOTAL
MONTH	(L.S.T.)	0	1	2	3	4	5	ه	7	8	9	10	TENTHS OF	NO OF OBS.
MAY	60-02	20.8	3.2	4.4	4.3	2.5	2.0	2.8	3.2	4.2	2.6	49.9	6.4	1074
	03-05	18.1	4.2	4.C	3.5	3.3	1.9	2.3	2.1	4.9	3.2	51.7	6.6	1674
	06-08	8.5	3.0	2.5	2.5	2.9	1.9	2.6	3.8	5.2	7.9	59.1	7.8	167
	09-11	9.4	2.7	3.C	3.2	2.5	1.6	2.0	4.5	6.8	5.4	58.8	7.7	1674
	12-14	8.5	3.3	2.7	3.0	3.2	2.5	2.9	4.4	6.3	6.6	56.6	7.7	1674
· · · · · · · · · · · · · · · · · · ·	15-17	7.2	2.8	4.2	4.1	3.3	2.0	2.7	4.9	6.3	6.9	55.5	7.7	1673
	18-20	9.2	4.1	3.1	4.0	3.5	2.5	3.2	4.6	6.5	5.9	53.3	7.4	1671
	21-23	16.9	4.0	5.5	4.3	3.2	1.9	3.3	3.5	5.6	3.8	48.0	6.5	1674
 .													 	
								,						
TO	TALS	12.3	3.4	3.7	3.6	3.1	2.0	2.7	3.9	5.7	5.3	54.1	1.2	1338

1210WS FORM 0 9.5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

DATA PROCESSING DIVISION ETAC, USAF ASHIVILLE, N.C. 28801

SKY COVER

43310

FUKUUKA KYUSHU JAPAN/ITAZUKE AB

47-64

PERIOD

JUN

STATION

STATION NAME

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

MEAN TENTHS OF SKY COVER TOTAL NO. OF OBS. PERCENTAGE FREQUENCY OF TENTHS OF TOTAL SKY COVER HOURS (L.S.T.) MONTH 0 8 10 JUN 00-62 10.7 3.2 3.8 4. 3.8 2.4 3.3 4. Ĉ 5.4 3.8 55.6 1620 7.7 03-05 3.0 3.0 2.5 2.0 3.3 3.5 60.0 162 2.0 2.2 3.6 63.4 8.4 1620 06-08 3.6 2.5 2.3 2.7 2.5 3.8 6.4 09-11 3.3 2.7 2.0 2.6 2.4 3.0 2.6 3.4 7.0 7.4 63.7 102 12-14 2.8 3.2 3.0 1.5 4.C 7.3 9.5 60.4 1621 59.5 15-17 2.0 3.1 3.3 3.7 2.5 3.9 1.8 4.1 8.0 8.2 8.2 1016 18-20 3.7 2.1 2.9 2.3 2.2 2.8 3.0 4.9 6(.6 1620 1626 7.7 3.3 21-23 7.0 2.7 3.5 3.6 3.2 56.3 TOTALS 8.0 12956 59.9 5.3 3.1 3.6 2.8 2.6 4.1

1210WS FORM 0-9-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

क च्यान्स्

LATA PROCESSING DIVISION ELAC, USAF ASHEVILLE, N.C. 28801

SKY COVER

FUKUUKA KYUSHU JAPAN/I TAZUKE AU
STATION NAME

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PER	CENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	SKY COVER				MEAN TENTHS OF	TOTAL NO. OF
MONTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	SKY COVER	
JUL	00-02	13.5	4.0	5.9	4.2	4.4	3.6	4.4	5.6	6.8	6.4	41.3	6.5	1574
	03-05	11.7	3.2	4.6	4.6	3.8	4.1	2.9	4.7	8.2	6.2	46.0	6.9	1673
	06-08	4.;	3.0	4.1	3.6	2.9	2.9	2.2	4.5	8.3	11.7	52.0	7.9	1674
	09-11	2.1	8 و د	4.2	3.9	3.5	2.8	2.9	4.7	9.9	11.1	51.3	7.9	1674
	12-14	. 7	1.4	4.5	4.5	4.8	3.2	2.8	5.C	9.0	12.6	51.6	8.1	16/2
	15-17	• 5	2.2	3.6	3.9	3.9	2.6	3.3	6.6	9.3	10.6	53.5	8.2	1674
	18-20	1.0	2.2	2.9	4.0	4.1	3.7	3.9	5 • 6	9.0	9.7	53.8	8.2	1670
	21-23	8.9	4.5	6.2	6.1	6.1	3.7	4.2	5.9	7 • 2	5.2	42.1	6.7	1669
10	TALS	5.3	3.0	4.5	4.3	4.2	3.3	3.3	5.3	8.5	9.2	48.9	7 6	13360

1210WS FORM 0.9.5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 288/1

SKY COVER

43310

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

47-64

AUG

PERIOD

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERC	ENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	SKY COVER	1			MEAN TENTHS OF	TOTAL NO. OF
MONTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	SKY COVER	
AUG	00-02	24.4	5.9	6.6	6.2	5.5	3.6	4.1	6.7	7.2	5.2	24.6	5.0	1674
	03-65	21.0	7.4	6.8	1.4	4.8	4.8	3.3	6.C	6.0	4.7	27.9	5.2	167
	06-08	5.9	6.3	6.7	6.6	6.1	5.3	3.3	6.4	10.3	9.0	34.1	6.6	1074
	09-11	4.4	4.8	5.2	6.9	5.9	6.0	4.3	7.3	11.5	10.7	32.9	6.8	157
	12-14	. 7	3.5	5.1	6.7	7.3	6.2	4.8	6.9	12.0	11.7	35.2	7.2	167
	15-17	1.4	4.0	6.C	5.9	5.9	4.4	3.3	6. 8	12.8	11.9	37.5	7.3	1666
	18-20	3.4	5.0	4.1	6.1	5.0	5.2	4.7	7.7	12.0	10.7	35.6	7.1	166
	21-23	16.7	5.9	8.7	7.5	5.4	3.5	4 • 8	7.8	8 • 6	4.3	26.8	5.4	167
TO	TALS	9.7	5.4	6.1	6.7	5.7	4.9	4.1	7.0	10.1	8.5	31.8	6.3	1337

1210WS FORM 0.9-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

6

()

DATA PROCESSING DIVISION ETAC. USAF ASFEVILLE, N.C. 20801

SKY COVER

43310

(!

()

(

FUKUCKA KYUSHU JAPAN/I TAZUKE AB

46-64

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERC	ENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	SKY COVER				MEAN	TOTAL
MUNTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	TENTHS OF	NO. OF OBS.
SEP	00-62	22.3	5.2	5.9	5.1	3.7	2.9	3.1	4.4	5.3	4.4	37.7	5.7	1688
	03-05	20.2	5.9	5.0	5.3	4.3	3.4	2.7	4.2	5.5	4.7	38.8	5.9	108
	06-08	7.8	5.9	5.0	4.0	3.9	2.8	3.0	6.8	7.2	9.1	44.5	7.1	158
	09-11	6.7	4.3	3 . 8	4.1	4.8	4.4	3.5	5.5	8.9	9.0	45.0	7.3	169
	12-14	3.5	2.4	4.5	6.7	4.4	4.3	3.7	5.5	8.8	10.9	45.4	7.5	169
	15-17	3.9	5.7	3.5	5.0	4.2	4.6	3.1	5.3	7.7	9.7	47.3	7.5	169
	18-26	6.6	5.0	5.6	4.6	4.6	3.2	3.9	6.6	8.0	9.3	42.6	7.1	169
	21-23	18.3	5.0	6.1	5.8	4.1	3.5	4.9	4.5	5.5	4 • 8	37.6	5.9	169.
· · · · · · · · · · · · · · · · · · ·														
10	TALS	11.2	4.9	4.9	5.1	4.2	3.6	3.5	5.3	7.1	7.7	42.4	6.7	1352

1210WS FORM 0.9.5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CAIA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N.C. 28801

SKY COVER

4331C STATION

FUKUGKA KYUSHU JAPAN/I TAZUKE AB
STATION NAME

CC I

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PER	ENTAGE F	REQUENCY	OF TENTHS	OF TOTAL S	KY COVER				MEAN	TOTAL
MONTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	TENTHS OF SKY COVER	NO. OF OBS.
001	00-32	33.4	4.5	5.3	4.6	3.6	3.6	2.4	3.8	3.6	4.0	31.2	4.8	176
	03-65	30.7	5.0	5.2	5.(4.2	3.3	3.5	4.6	5.4	4.C	29.7	4.9	176
	06-08	13.8	6.1	5.2	4.8	5.0	4.0	4.6	7.0	8.8	8.4	32.3	6.2	176
	09-11	10.2	7.0	6.3	5.4	4.6	6.1	3.9	6.5	9.8	8.5	31.7	6.3	176
	12-14	7.3	5.2	6.9	6.7	6.9	6.0	4.2	5.7	9.2	9.9	32.2	6.5	176
	15-17	9.5	6.7	8.0	8.2	6.7	4.8	3.9	5.4	7.3	6.9	32.5	6.0	176
	18-20	16.2	7.8	8.9	6.7	5.3	2.9	3.7	5.C	7.5	5.0	31.0	5.5	176
	21-23	29.9	5.9	5.9	5.8	3.0	4.0	3.1	3.5	4.4	3.5	30.8	4.9	176
										<u> </u>	······································			
10	TALS	18.9	6.0	6.5	5.9	4.9	4.3	3.7	5.1	7.0	6.3	31.4	5.6	1413

CATA PROCESSING DIVISION ETAC. USAF ASHEVILLE: N.C. 28801

SKY COVER

43310 STATION

FUKULK 1 KYUSHU JAPAN/ITAZUKE AB

46-64

PERIOD

NOV MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS	-		PER	CENTAGE F	REQUENCY	OF TENTHS	OF TOTAL S	KY COVER				MEAN TENTHS OF	TOTAL NO. OF
HTMOM	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	SKY COVER	
NOV	00-02	29.9	5.6	5.8	5.1	5.0	4.0	4.3	4.C	4.4	4.3	27.5	4.8	1/10
	03-05	30.4	5.0	4.9	4.4	3.6	4.0	4.9	4.7	6.3	4.3	27.5	4.9	1710
	06-ú8	17.4	6.7	5.4	5.0	4.9	3.6	4.4	6.4	8.2	7.2	30.6	5.8	1710
	09-11	13.6	5.5	6.4	5.7	5.6	4.3	4.8	5.3	8.5	7.7	32.6	6.1	1769
	12-14	9.8	3.3	5.5	5.4	6.1	6.3	6.4	6.5	8.4	9.1	33.2	6.5	1710
	15-17	11.5	6.5	6.1	5.8	5.8	4.5	4.3	5.4	8.4	7.8	32.8	6.2	:710
	18-20	19.6	7.4	7.5	6.1	3.8	4.0	3.8	4.4	6.4	5.3	32.0	5.5	1710
	21-23	27.9	6.8	5.3	5.4	4.9	3.4	3.2	4.0	2.3	3.5	3C.3	4.4	1710
<u> </u>	-													
TO)TALS	20.0	5.9	5.9	5.4	5.0	4.3	4.5	5.1	7.0	6.1	30.9	5.6	13679

1210WS FORM 0.9.5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSC*ETE.

DATA PROCESSING DIVISION ETAC, USAF ASHLVILLE, N.C. 28801

SKY COVER

FUKUCKA KYUSHU JAPAN/ITAZUKE AB

CEC

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS	· · · · · · · · · · · · · · · · · · ·		PER	CENTAGE F	REQUENCY	OF TENTHS	OF TOTAL	SKY COVER				MEAN	TOTAL NO. OF
MONTH	(L.S.T.)	0	1	2	3	4	5	6	7	8	9	10	TENTHS OF SKY COVER	
DEC	00-02	18.3	4.0	4.8	5.7	4.2	3.6	5.2	5.3	7.3	5.5	36.0	6.C	1765
	03-05	16.6	3.3	6.1	3.7	3.7	3.7	5.4	6.0	7.5	7.0	37.0	6.3	1765
	C6-08	9.5	3.6	4 - 8	3.7	4.1	4.2	4.2	7.3	8.3	9.5	41.0	7.0	1767
	09-11	6.2	3.8	3.6	4.2	4.8	3.6	4.6	6.4	7.6	12.9	42.3	7.3	1767
	12-14	4.5	3.4	3.6	4.4	4.2	4.0	5.0	7.7	8.9	10.8	43.5	7.5	1767
	15-17	6.2	4.4	4.C	4.8	5.1	4.1	4.7	7.4	9.3	10.6	39.4	7.1	1767
	18-20	11.3	5,1	5.8	4.6	5.2	4.0	5.4	5.7	9.2	6.8	37.0	6.5	1767
	21-23	15.5	3.7	5.0	5.0	4.5	4.8	5.4	5 • 2	6.6	5.7	37.5	6.2	1767
-														
to	TALS	11.1	3.9	4.7	4.5	4.5	4.0	5.0	6.4	8.1	8.6	39.2	6.7	14132

1210WS FORM 0-9-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

And the second

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA

PART E

PSYCHROMETRIC SUMMARIES

In this section are presented various summaries of dry-and wet-bulb temperatures, dew points, and relative humidity. The order and manner of presentation follows:

- Cumulative percentage frequency of occurrence derived from daily observations and presented by month and annual for all years combined. These tabulations provide the cumulative percentage frequency to tenths of temperature by 5-degree Fahrenheit increments, plus mean temperature, standard deviation, and total number of observations in three separate tables as follows:
 - a. Daily maximum temperature
 - b. Daily minimum temperature
 - c. Daily mean temperature
- 2. Extreme values derived from daily observations with extreme value given for each year and month of record available. Extremes are provided for a month if all days for a month contain valid observations. All months for a year must have valid extremes before the ANNUAL value is selected for that year. Means and standard deviations are computed for months and annual when four or more values are present for any column. Two tables of daily extreme temperatures are prepared:
 - a. Extreme maximum temperature
 - b. Extreme minimum temperature

2058 30

- 3. Rivariate percentage frequency distribution and computations of dry-bulb versus wet-bulb temperature.

 This tabulation is derived from hourly observations and is presented by month and annual, all hours and all years combined. The following information is provided:
 - a. The main body of the summary consists of a bivariate percentage frequency distribution of wet-bulb depression in 1; classes spread horizontally; by 2-degree intervals of dry-bulb temperature vertically. Also provided for each dry-bulb temperature interval is the percentage of observations with dry-bulb and wet-bulb temperature combined; and again for dry-bulb, wet-bulb, and dew-point temperatures separately. Total observations for these four items is also provided in two lines at end of each tabulation table, which may require two pages in some cases.

MOTE: A percentage frequency in this table of ".O" represents one or more occurrences amounting to less than .O5 percent.

b. Statistical data for the individual elements of relative humidity, dry-bulb, wet-bulb, and dew-point temperatures are shown in the section at the bottom left of the forms. These consist of the sum of squares (ΣX^2) , sums of values (ΣX) , means (X), and standard deviations (σX) . The number of

Page I 1

observations used in the computations for each element is also shown.

c. At the lower right of the form are given the mean number of hours of occurrence for six ranges of dry-bulb, wet-bulb, and dew-point temperatures, and total number of hours possible in the period represented. Mean number of hours is shown to tenths and indicates mean number of hours per year in the annual summary, or mean number of hours per month in the tabulations by month.

NOTE: Wet bulb temperature usually was not reported prior to 1946. Relative humidity usually was not reported prior to 1949, nor subsequent to June 1958; and was computed by machine methods for observations recorded during these periods. All values of dew-point temperature and relative humidity are with respect to water, unless otherwise indicated.

- 4. Means and standard deviations These tabulations are derived from hourly observations and present the mean, standard deviation, and total number of observations for the eight standard 3-hour groups, by month and annual and again at the bottom for all hours combined. Record for all years available are combined. Tables are prepared for the following:
 - a. Dry-bulb temperature
 - b. Wet-bulb temperature
 - c. Dev-point temperature

W = 1.

- 5. Cumulative percentage frequency of occurrence of relative humidity This summary is derived from hourly observations and presents the cumulative percentage frequency of occurrence of relative humidity by increments of 10% classes, plus the mean relative humidity and total number of observations in two tables.
 - a. Table 1 is prepared by month and annual, all years combined, with month being the vertical argument.
 - b. Table 2 is prepared by month by standard 3-hour groups, with the hour groups being the vertical argument and a separate page for each month. All years are also combined for this summary.

DATA PROCESSING DIVISION ETAG. USAF ASHEVILLE, N. C. 28801

DAILY TEMPERATURES

43310

FUKUDKA KYUSHU JAPAN/ITAZUKE AB

64_____

MAXIMUM

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM DAILY OBSERVATIONS)

						· 	- TAILT OB							
<u> </u>	TEMP (°F)	JAN	FEB	MAR	APR	MAY	JUN	ากเ	AUG	SEP	OCT	МОЛ	DEC	ANNUAL
≥	100	ļ	 	 -					•5		 	 		<u> يو </u>
≥.	95		·	1				2.7	7.8	-6	! •		<u> </u>	-9
Ξ	90		<u>'</u>				2.4	34.3	45.5	8.4	2		,	7.5
2	65	<u> </u>	↓	ļ	.2	2.3	14.5	67.6	82.9	32.3	1.3		└──	16.6
≥	86		1		2.4	16.1	44.7	88.88	97.5	65.7	8.2			26.7
≥_	75	<u> </u>	i	8.	10.8	45.2	78.0		100•€	92.5	33.0	2.6		36.2
<u>2</u>	70	<u> L</u> .	.6	4.2	31.6	74.4		100.0		99.4	69.9	16.1	-4	49.3
	65	. 9	3.1	13.1	55.9	94.8	99.8			100.C	93.5	47.2	4.1	59.5
≥	60	4.5	11.4	32.3	84.3	99.1	100.0				99.3	74.4	19.0	68.7
≥	55	16.7	27.2	58.8		100.0					100.0	90.7	43.2	77.8
≥	50	42.3	51.4	83.5	99.4							97.8	71.5	87.2
≥	45	69.5	77.3		100.0							99.8	91.6	94.5
≥	41,	89.1	94.8	99.6							1	100.0	98.9	98.5
2	35	98.9	94.8	100.0								i — —	99.8	97.8
≥	3 C	100.0	100.0										LCO.	100.0
≥		1												
≥		 -	T	 							 			
Σ		1	 	!	t					l		i		
≥		1	†	†										
2		·	 	 										
≥			 	†	l — —	 					<u> </u>	 -	<u> </u>	
Σ		 	+	-						ļ	 	†·	 	
≥		 	 			 				 				
2		 -	 	 	 	 			 	 -	 	 		
Σ			 -	· 	 	 					 			
≥		╅──	·	 -	 	 			 		 	 	 	
Σ		╅		 	 		<u> </u>				 	 		
		 			 	 	 		·	 -	 	 		
AI A		+	 		 -	 	!		·	 	-	 		
Σ		╅──	+	+	 	 			 	-	 	 -	 	
Σ		 	+	+	 	 			 	 		 	 	
		+	+	+	-	-				 	 			
<u>^</u>		 	- -	 	i – 	 	 				 	 		
		┪──			 	 		 	 -	 	 		i	
<u>≥</u>		 		 	 	 	 	 	 	 		 	 	
É		48.1	50.2	124 3	1 22 - A	73.6	78.8	44 7	88.7	61.6	72.3	49 4	83 6	63.3
<u> </u>	MEAN	6.753		56.3	6.601			86.6		81.9				68.2
-	\$ D						5.563	20 393			5.282		6.518	14.840
_	TOTAL OBS	558	481	527	510	558	510	527	527	533	558	540	558	638

1210 WS JUL 64 0.21-5 [Det 50] PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

4212

Like Br.

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28861

DAILY TEMPERATURES

4331C

FUKUREA KYUSHU JAPAN/I TAZUKE AB

64

MINIMUY

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM DAILY OBSERVATIONS)

	TEMP (°F)	JAN	FEB	MAR	APR	MAY	NUL	101	AUG	SEP	oct	NOV	DEC	ANNUAL
<u>} </u>	8 C							2.3	1.5	-2				. 3
	75						3.5	48.6	46.5	6.4				8.7
≥	70					• 7	14.3	86.5	90.5	35.8	1.1			18.9
	65				•6	4.1	45.1	98.1	98.5	6C.4	5.6			25.7
<u>-</u>	60		• 2	. 6	5.5	26.7	78.6	100.0	190.0	81.2	18.3	2.0		34.1
≥	45	. 2	. 4	2.1	19.6	55.6	45.5			96.6	41.0	8.1	1.1	43.2
≥	55	1.1	2.5	8.3	39.4	80	97.8			100.0	69.7	23.3	3.6	52.5
≥	45	5.9	3.5	21.6	62.4	96.4	100.0				91.0	46.9	13.3	62.2
≥	40	17.9	23.3	43.8	85.9	100.0				1	99.6	78.5	33.7	73.6
≥	- 35	44.8	46.2	73.4	98.6			1000	-		100.0	95.7	70.1	8°.8
2	3 C	87.6	96.9	97.3	190.0							100.0	96.1	97.3
≥	25	99.5	99.8	100.0									99.8	\$9.9
2	26	100.0	100.1										100.0	100.0
≥ _														
<u>Z:</u>		T							i	T				
≥									1	!				
≥		T							†					
≥ _		1					·		T					
≥		1			·						i			
≥ .		·							1	 				
≥		1												
≥		† -) !		t									
2									1			· · · · · · · · · · · · · · · · · · ·		
2		-							<u>†</u>			1		
≥		1										†		
≥		1	 !		 					 				
≥		1	-					+·	1		1			
≥		1					 	•		 	1			
≥.		1		i	İ			<u> </u>			 	·		i
≥		 	 		†			İ	 	1	 	<u> </u>		
≥ .		T							1	 	1	T		
≥		†- -	 -				-				1		1	ļ
≥		1	<u> </u>		1	İ	İ	1					1	
≥		1		 	<u> </u>	 	<u> </u>	1				 	İ	<u> </u>
≥		† -	1	†	†		i	Ţ	÷	1			<u> </u>	
	MEAN	34.8	35.4	39.3	47.6	55.3	63.7	73.7	73.8	66.1	53.3	44.7	37.8	52.1
	S D				7.312	5.744							5.627	14.9
	TOTAL OBS	558					510							638

1210 WS JUL 61 0-2. 3 (Det 50) PREVIOUS COITIONS OF THIS FORM ARE OBSOLETE

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

DAILY TEMPERATURES

43310

FURUCKA KYUSHU JAPAN/ITAZUKE AB

MEAN

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM DAILY OBSERVATIONS)

	TE/LP (OF)	JAN	FEB	MAR	APR	MAY	JUN	JL	AUG	SEP	OCT	NOV	DFC	ANNUAL
<u>≥</u> ≥ ≥	90	L							• 2					.0
≥	55	ŀ		•			٠.۷	13.1	15.C	1.3	1	!		2.4
	60			· 			6.3	61.3	74.8	16.7	.4		`	13.1
≥	75					1.4		89.2	98.1	48.0	2.2			21.8
≥	70		<u> </u>		2.2	13.3		98.9	100.C	78.4	10.9			30.1
≥	65			• 9	11.6	50.9		100.0		98.1	36.7	2.5		41.0
<u>≥</u> ≥	60	T	- 8	4.0	32.5	86.9	100.0			100.0	73.8	16.3	1.3	51.3
≥ _	55	2.3	4.0	13.9	56.5	98.6			i	Ī ————	95.0	49.1	5.4	61.3
≥	50	8.6	14.1	35.3	89.4	100.0					94.6	79.3	23.7	70.9
≥	45	26.2	33.3	68.5	99.4						100.0	96.1	55.9	81.7
≥.	4C	63.4	67.6	94.7	100.0				1			99.6	88.4	92.8
2	35	92.8		99.8			ļ			·	 	100.0	99.3	99.0
≥	30	99.8	100.0	100.0				T	f	 	†		100.0	99.9
<u>≥</u>	25	100.0								<u> </u>		<u> </u>		100.0
≥		1	<u> </u>	 -					1	-	1		11	
≥		1	ļ — — — — — — — — — — — — — — — — — — —							1	1			
Σ		† 		† 				 	İ	-		 -	1	<u> </u>
		1		İ			 						 	
<u>≥</u>		1						 	ļ —	 	 	†		
		 	 	 			 	 	 -	 	 	 		
≥		1							 		1			
≥		 	<u> </u>		<u> </u>				-	 	†			
₹		·	†				 	 	 	 	†	 		
<u>≥</u>			 -	 	ļ		 	 	 					
5		1	† -	 -	 			 	 	 	 		 	
Ξ.		 	 	 	i	 	 	 	 			 		
∑−		 -	 	·	 	 	 -	·	 	 	†	 	i	
≥		 	 	†	 	 	 -	 	 	 	 -	 		
		1	 	 	ì	 	 	 	 	+	 	 	i	
Ξ		1	 				 	 	 	+	 	 	 	
		 -	 	 -	 	 	 -	 	 -	 	 	 	 -	
=-		 	 	 	 	 	 	 	 	 	 	 	-	
≟		 	 	 		 	 	 	 	+	 -	 	 	
≥		 -	 	 	 	 	 	 	 	+	 		 	
Ξ		 	 -	 -	 	 	ļ	 	 -		 	 -	 -	
-	MEAN	41.5	63.0	48.0	57.0	52.7	71.2	20.3	41.4	74.1	A2.0	54.1	48 7	66.3
	S D				5.881	6.51	4 774	4 104	3.121	5.007	5 712		5.314	14.56
	TOTAL OBS	558												638

1210 WS JUL 54 0-21-5 (Det 50) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DATA PRUCESSING DIVISION ETAC. USAF ASHEVILLE, N.C. 28861

EXTREME VALUES

MAXIMUM TEMPER MRE
(FROM DAILY OBSERVATIONS)

43310 STATION

FURUDRA KYUSHU JAPAN/ITAZUKE AB 46-64

WHOLE DEGREES FAHRENHEIT

MONTH	JAN,	FEB.	MAR.	APR.	MAY	.NUL	JUL.	AUG.	SEP.	ост.	NOV.	DEC.	ALL MONTHS
46										(90)	76		
47	60				94	84	95	95	93	81	75	67	
48	66	65	71	79	83	90	96	94	92	83	72	70	96
49	54	53	63	75	83	84	95	93	92	79	73	64	95
50	64	65	67	8()	85	88	93	94	92	83	(79)	64	94
51	60	68	70	72	83	90	92	95	84	85	75	69	93
>2	61	57	73	79	86	90	94	36	92	83	76	66	96
53	66	69	71	80	64	83	94	98	91	82	70	(70)	98
54	66	69	78	80	(87)	89	92	96	92	79	74	69	95
55	57	68	73	82	32	62 1	95	92	90	79	71	67	<u> </u>
56	59	56	72	82	82	89	99	100	(93)	83	72	50	167
57	68/	60	66	78	83	34	94	96	85	79	72	65	96
58	63	68	76	75	87	90	94	92	90	84	76	64	94
59	63	69	72	78 78	86	31	95 93	100	95	83 77	76	69	105
60	65	72			86	92 88			88		71	61	99
- 1 62	55 54	56 67	71	75 75	80	89	95	94	91 93	56 86	74	66	95 95
ا ده	54	52	67	79	83	87	95	92	88	75	71	64	9%
	64	54	78	57	84	- 07	7,7	74	- 00	- 12		07	
	04	, T	1 0	31									
								,	1956		,r, ;		
: 1600	1:	٠, ٫		X17.				• • • • • • • • • • • • • • • • • • • •	10,	, \ \ ,	(~ ` ; · · · · ·		
W. C								``					
N 1													
				İ		İ						į	
MEAN	61.6	63.4	71.1	78.5	83.9	88.2	94.4	95.5	90.8	82.1	73.6	65.5	96.2
S. D	4.368		3.998	3.502			1.622						1.974
TOTAL OBS.	558	481	527	510	558	510	527	527	510		540		6364

1210 WS FORM 0 88-5 (Det 50)

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N.C. 26801

EXTREME VALUES

MINIMUM TEMPERATURE
[FROM DAILY OBSERVATIONS]

43316

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

44-44

YEARS

WHOLE DEGREES FAHRENHEIT

MONTH	JAN.	FEB.	MAR.	APR	MAY	אטנ.	JUL	AUG.	SEP.	ост.	NOV.	DEC.	ALL MONTHS
46						<u> </u>		Ī	ĺ	.40	(31)	25	
47	20				42	(49/	61	66	55	/ 38		29	
48	25	25	26	34 .	46	30	24	54	55	44	35	32	25
49	29	32	30	32)	45	54	60)	68	52	42	32	28_	28
6,7	26	28	27	35	43	50	68	(61)	,54	41	36	25	25
51	27	29	29	36	44	51	63	68	(5)	44	33	29	<u> 27</u>
52	29	30	30	35	44	51	63	70	(31)	43	37	31	29
53	26	29	32	33	44	ካ6	62	69	38	46	33	_33	26
54	30	28	28	36	46	53	67	69	56	42	39	23)	23
>5	27	28	35	36	48	56	69	66	57	41	33	29	27
56	29	26	30	34	44	55	67	(61)	55	44	34	27	26
57	28	25	30	35	42	52	68	68	54	42	35	32	25
58	30	31	30	35	42	56	68	69	57	39	34	33	30
59	26	28	32	42	49	53	71	71	56	45	38	32	26
60	30	28	32	35	43	55	70	65	55	41	34	27	27
61	25	26	29	33	46	53	72	72	53	45	35	28	25
62	29	26	28	35	41 `	57	69	65	52	42	34	31	26
63	24	23	28	34	43	57	70	57	53	45	32	30	?3
64	28	27	28	44	46								
MEAN	27.1	27.6	29.6	35.8	44.2	53.4	66.7	67.0	54.4	42.4	34.3	29.1	26.1
S D.	2.587			3.073		2.599	3.636						1.893
TOTAL OBS.	558		527	510	558	510	527	527	510	558	540	558	6364

1210 WS FORM 0-88-5 (Det 50)

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

FUKUOKA KYUSHU JAPAN/ITAZUKE AB 46-64

PAGE 1 ALL

Tem	ıp.						w	ET BULB	TEMPER	ATURE	DEPRESS	ON (F)						TOTAL		TOTAL	
(F)) [0	1 - 2	3 - 4	5 - 6	7 - 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18 1	9 - 20 2	1 - 22 2	3 - 24 2	5 - 26 2	7 - 28 29	30 ≥ 31		Dry Bulb	Wet Bulb	Dew Point
100/	99										•0	.0	.0	•0				10	10		
98/	97						l	- 0	1	- 0	-0	. 0	-0	-0	1		į	30	30	1	
96/	95		1		.0	.0	•0		•0	.0	•0	• 0	•0					110	110		
94/	93		1		.0		• 0	1	.1		. C		1				ļ	339	339	i	
921	91				.0		-1		.1	.0	• 0	• 0						754	754	i	
90/	89		1	•0			. 4	. 4	•1 •1	.0	• 0	• 0	į	- 1	-	•0		1652		ı	
88/	87		•0			.3	.6	. 3	.1	.0	-0	• 0	•0	•0				2195		8	1
86/			.0		. 3	.7	. 5	. 2	.0	.0	- 0	.0	.0	.0	•0	1	ļ	2758	2758	68	3.6
84/			.0		. 7	.7		• 1	•1	•0	•0	.0	•0	•0	•0		i	3230		174	73
82/		.0			1.0			. 1	-1	.0	-0	- 0	-0	• 0			ĺ	4216	1	697	152
80/		• 0		1.6		.3	.2	.1	.1	.0	.0	•0	•0	•0				6079	6079	3225	608
78/		• 0			. 5	.3	3	. 2		. 1	.0	. 0	.0	•0	.0			7003	7005	6957	2735
76/	75	• 2	1.7	1.1	. 5	.4		. 2	.1	.1	•0	.0	•0	•0				7352	7360	9581	7809
74/		. 3	1.5		. 5	.4	• 3 • 3 • 3	. 2	.1	.0		.0	-0		i	•	į	6371	6374		10150
72/		• 2			. 5	.4	.3	. 2	.1	.0	•0	• 0						5762	5764	6155	7916
70/		. 2			. 6	.4	.3	. 2	.1	.0	. 0	• 0	i	- 1	İ	1		6134	6139	5364	5556
68/	67	• 2			. 5	.5	.3	• 2	.1	.0	• C	•0						6042	6055	5539	4751
66/	65	. 2				.4		. 2		.0	• G		1	- 1	- 1			6279	6285	6237	5184
64/	63	.2					•2	.1	•0	.0	.0							6152		6512	5615
52/	61	2			. 6	.3	3	.1	.0	.0	. 0	-	}	!	- 1		j	6219	6221	6938	5954
60/	59	- 3		.9			.3	•1	•0	•0				-				6344	6344	7125	6499
58/		• 2					.2	.1	.0	.0	-0	ŀ	1	i	İ	j	ĺ	5928	5928	6480	6116
56/		. 3		.8	. 6	.4	•2 •2	.0		• 0					1			5884	5891	6584	6429
54/		. 2			. 6		•2	.0		- 1	1	ļ	į		}	1		5935		5867	6019
52/		• 3			. 6	.4		.0		1						1		5922		6352	5851
50/		. 3				.4		.0		i	į	1	İ	1		1		6646		6399	
48/	47	• 3			.7	.4					$\overline{}$					1		6244	6244	6525	
46/	45	• 3								ļ	1	-		İ			-	6402	6402	6680	5947
44/		.2																5850	5850	6507	5959
42/	1	. 2										- 1	l	i]			5361	5361	6337	5934
40/		• 2			.6		.0							Ť			\neg	5336	5336	6220	5771
38/		.1						i	j }		ł	1						4558	4558	5681	5786
36/			1.3			.0					- 			$\neg \uparrow$				3759	3759	5344	
34/		. 2	1.0	.4						ļ	1	ļ	ļ	ļ				2538	2638	4475	
Elemen			Σχ²			Σχ		X	σ _x	T	No Ob	, 1				Ason No	f Hours	vith Temper			
Rcl. H							_						_ 0 F	≤ 3	2 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	T	otal
Dry Bu	ib						_			_								1		_	
																					

Wet Bulb Cew Point

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

43310 FUKUCKA KYUSHU JAPAN/ITAZUKE AB 46-64

PAGE 2 ALL

Temp									DEPRES				,				TOTAL	ļ	TOTAL	
(F)	0 1.				9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 . 20	21 - 22	23 - 24	25 - 26	27 - 28 2	9 - 30	≥ 31		Dry Bulb		
32/ 31	. 1		.2, .0					1 !						1			1	1804		
30/ 29	-1		.1 .0				•	·	<u> </u>	<u> </u>			·				734			4202
28/ 27	• a	•1 _i	.0 .0		1			•				! !	i i		i		225			3240
26/ 25	• 0	• <u>a</u>	, 				1					·	<u> </u>				41			2703
24/ 23	i	• a			ļ		İ			ĺ							3	3	19	1607
22/ 21		i					<u> </u>	i	l				<u> </u>						1	883
20/ 19	1	į.			l									i				1	1	481
18/ 17	!			_ !	1			1 .		[]			1. [1	-		[Í [288
16/ 15		1		!			!		T								Ī			131
14/ 13	i										ļ.	ļ							1	40
12/ 11							,	1												13
10/ 9		ì					•	Ì	ļ			ļ						١,		3
8/ 7				1	i		!		1				1	i						1
6/ 5	İ	1			į		ļ	1							i				-	i
TOTAL	5.234	-623	.315.6	9.7	6.0	3.2	1.4	.6	• 2	.1	•0	.(-0	-0	-0	•0	1	58367	1	58310
	7447	923.	- 512 - 0 -	74.	-	,,,,	1 '] "	1	1 .			1 7	- 7	•		58302		58311	
		1	1 -					 	1	<u> </u>		 	1				2000			
ŀ		1			i			Ì											i	
							 	 	 	-		 								
-		İ			1		!		İ	}				i						
		 -					-	├──				 					 			
		1			1			ļ				1		1					ļ	
							 		-	 -			 							
ì			1	!				į												
			_	 			 	 	 	 		 	+i				 			
!	i	- 1	ł		1	1	-	İ		ŀ	İ								İ	
						<u> </u>	 	 	ļ	├		<u> </u>	ļ				 			
	1	- 1					1			į				1						
				! -		ļ	 	ļ	 	 		ļ	 				<u> </u>	·		
i	1	1	ľ	i i	İ		ľ		ľ		ł	1	1 1					1	1	
				<u> </u>			<u> </u>		ــــــــــــــــــــــــــــــــــــــ	ļ			 				<u> </u>			ļ
	ļ		İ					l											i	
									<u> </u>			<u> </u>	$oxed{oxed}$				<u> </u>			
1			[-															
									<u> </u>					<u>i_</u>			<u>L</u>			
Element (X)	Σχ			Σχ		X	σ _x		No. O					Mean No	of H	ours w	ith Tempe	rature		
Rei Hum	997	0286	97 123	4137	3 7	8.0	14.8	155	158	310	≤ 0	F	≤ 32 F	≥ 67 €		73 F	≥ 80 F	≥ 93 F		otal
Dry Bulb			87 95				15.4			3367			55.2	3320.	523	27.8	1013	6 27	3 D.	760.0
Wet Bulb		3850		7743			14.3			311							123.			764.0
De Point		9255		6091			15.5			310			38 . C	2201.			23.			760.0

CATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

FUKUOKA KYUSHU JAPAN/LTAZUKE A8
STATION NAME J 4/1 MONTH 43310 STATION 47-64 PAGE 1 ALL

Temp.				····-		w	FT BUILE	TEMPE	RATURE	DEPRES	SION (F	1						TOTAL	1	TOTAL	
(F)	0	1 - 2	3 - 4	5 . 6	7 - 8								23 . 24	25 - 26	27 . 28	29 . 3	0 ≥ 31		Dry Bulb	Wet Suib	Daw Point
68/ 67		1.2	3 . 4	3.0	7 - 0	7.10	11 - 12	13 . 14	13 - 10	17 - 10	177 - 20			123 - 20				2	2		
66/ 65			•0	. 1	٠ü	• •	• C	\		i '	1			}			ł	8	1		
64/ 63		<u>ن</u> .		•0		-1	• 0			 				┼	 		 	31	31		
			1 - i			.0	ł .		1		!	•		l	İ		i	42		7	3
62/ 51		• ()	•1	-1	•1	-0					 -			 -	 	├─-		30	3 1	2	
	• 6					.1	.0	ı			l						ĺ	146	1 1	35	31
56/ 57	• 6	• 2		• 3										⊹ −				210		- 107	37
54/ 53	• 1			[1	1				ľ					1	ļ		367		156	-
	- 1	. 3		• 6						 	<u> </u>	<u> </u>			 	├		539	1	313	197
527 51	• 4	1.2			J			Ì	ļ			i		•	! !		1	820			
50/ 49	• 5		1.3	1.7				 		 -	 				 	 	+ -	917		351	345
48/ 47	• 4		1			1 -	1	1						1	!	į	j	1098		820	
46/ 45	. 6					1		<u> </u>	ļ	ļ					<u> </u>	↓	——		1		
44/ 43	• 4	2.5		2.2		ŀ		i	l i					1	!		İ	1174	1344	1109	
42/ 41	• 5		1	2.5		1			ļ	<u> </u>	<u> </u>				<u> </u>	 		1344	(1		
40/ 39	. 4	3.9	1	2.6	1					1		}		i			ļ	1484			1
38/ 37	. 4	4.0							<u> </u>	ļ	L	↓	ļ			<u> </u>	<u> </u>	1443			
36/ 35	. 5	4.3		1.5		ĺ	! !		ĺ	1	ĺ	1		1			1	1357		1621	1183
34/ 33	6					l			<u> </u>	L		L		<u>i </u>		i		1074			
32/ 31	. 9			-							1	ļ	!	i	į			817		1626	
30/ 29	- 5)	<u></u>	ļ		<u> </u>			<u> </u>				<u> </u>		319			
28/ 27	• 1	. 4	1	.0	7					1		I	•			i	1	75		397	
26/ 25	. 1	-1	į.	1		i			1	!	<u> </u>	l	L		<u> </u>			26	26		
24/ 23		-0		1		,			([[Γ	Ī		2	- 2	75	
22/ 21	i	ı		1	1			i		İ	İ										434
20/ 19			1		i –	1					Ĭ	T				T		1			271
18/ 17			,	ĺ	ı	1	1	1		l		į	Į		1	1					146
10/ 15		1	,						1										T		81
14/ 13						!	ļ	1								1	1				25
12/ 11		1	1			1	1	1		1		1			T	1					
10/ 9				}	1.	!	1				Ì						-			ĺ	1
TOTAL	6.6	37.3	28.3	20.6	5.9	1.0	2	.0	×	1	1			1		†		1	13387	r—-	1338
1	1		1		ì		1		Ì	1				1	1		1	13367	r)	13387	
		 	 	1	†	†	†		 	1	 					T	1-	 	1		
			1	1	!		<u> </u>		<u> </u>	!	<u>L</u>					<u> </u>			<u> </u>		<u></u>
Element (X)		Σχ²			Σχ		X	σx		No O							Hours w	ith Tempe			
Rel. Hum.			5164		0451		5.0	14.6			387	≤ 0	F	≤ 32 F	≥ 67		≥ 73 F	≥ 80 F	≥ 93	F	Total
Dry Bulb			5666		55408		1.4	6.9			387			68 • 9		• 3					744.
Wet Bulb		2010	15819		51123	15 3	38.2	6.5	96	13	3367		Ī	166.0)	i_				- 1 -	744.0

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

43310 FUKUOKA KYUSHU JAPAN/ITAZUKE AB 48-64 FEB
, STATION STATION NAME
PAGE 1 ALL
HOURS (5 7)

																					HUUKS	(L S T.)
Temp	· L											SION (F							TOTAL		TOTAL	
(F)		0	1 2	3 - 4	5 - 6	7 - 8	9 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22	23 . 24	25 - 26	27 - 28	29 - 30	< 31	D 8 /W.8	Dry Bulb	Wet Bulb	Dew Poin
72/	71			i	1				•0	_) j	1		
70/	69	1	•0	l	· • 0	i ı		.0	.0	• 0	i						1	1	12	12		
68/	67		. 1	0	.0	.0	•0	.0			1	-							24	24	2	2
66/	65		.0	1 -0	i .d	-1	.1	.0				k				ŀ			24	24	7	6
	63		• 1							.0		1					1	!	75	75	8	1
	61	ŀ	. 2						.0	. (,		ļ		ļ			1	101	101	33	16
	59	. 1	. 1				•2		• 0						1		+		160	160		
	57	• d	.4						• 0							; I	1	i	199	199	74	
	55	1	•6			.4	• 2					\vdash			i	<u> </u>	1		276	276	161	71
	53	. 1											1		Ì	ĺ			440	440	1	
	51	.3	1.6		1.0		.4		i			 -		i	 	<u> </u>	 	 	612	612		
	49	.6					-4	.0	į		1				1		ļ	i	790	790		
48/		- ; ;							i		 	 			 	\vdash	† 	 	873	873		
	45	74	2.8			1.0	.2				i			į			1	İ	1008	1008		
	43	- 3	3.3				.1					 			 		+	!	1050	1050		
	41	- 2	2.5	2.7								1	ĺ					ļ	957	957		
	39	-:									 					_			1108	1108		
	37	.3						1					l					1	1141	1141		1
	35	- 1	4.3					 			 	 			 		1-	 	1002	1002		
	33	. 5				1						1							774	776		1
	31	.3						 			├─	 	 		 	 	<u> </u>	 	531	531		
	29	. 2				1					1						1		254	256		
	27	. 2				 					-	 -					 	-	104	104		
26/		. 1		1	1	'		1					ļ						14	14		
24/			.(-			 	 				<u> </u>	 -	 	 	- i		501
22/			• •	1	Ì				i						1			1	1	•	1	301
20/					 			† – –			 	 			<u> </u>	 	 	 	 			140
	17					'						1									ļ	99
- <u>† 6/</u> -				 	 	 		 -	 		 	 	 		 	 -	 	 	 		 	3
	13							1								1		l				3.
	11					 		 	-	~	 	 			 	 -	 	 	╁──┼			
10/	9					1							1					İ				
TOTAL		E 2	20 /	26.4	10 7		2.6		-1		-(+	 	┼	11535	 	11538
IUIAL	. }	7 • 6	3000	12007		0.7	2.00	- 6	• 4	• (1 • 1	1							11539	41933	11538	
Element	(X)		Σχ²	<u> </u>	-	Σχ	<u> </u>	<u> </u>	σ _X	_	No. O	<u> </u>	<u> </u>	L	<u> </u>	Mean	No o' s	loure w	ith Temper		12230	1
Rel Hu				9295		5688	7 7		15.3	5.8		538	= 0 1		≤ 32 F	± 67	$\overline{}$	73 F	≥ 80 F	≥ 93 1	F T 1	Total
Dry Buli	-			7642		9400		2.8	7.7			535	201	<u> </u>	52 . 8		2.2	73 F	- 200	- 273	<u>'</u>	672.0
Wet Bul				9035		5430		9.4	7.1			1538		٠,	20.9				-	+-	-+-	672.0
Dew Po				9489				4.7	8.5			538			305 • 3		•1		 	+-		672.0
DAM LO	7117		471	, 7707	. •	0016		7401	0.3	7 a		レンフロー		i 4	ノリフゅう	,	취		1	I	1	UILOL

1210 WS JUL 64 0.26-5 [Det 50]

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

43310 FUKUUKA KYUSHU JAPAN/ITA/UKE AB 48-64 PARS MONTH
STATION STATION NAME YEARS PAGE 1 ALL
HOURS R.S. TJ

Temp.						w	ET BULE	TEMPE	RATURE	DEPRES	SION (F	}					TOTAL		TOTAL	
(F) ·	0	1 - 2	3 - 4	5 - 6	7 - 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22 2	23 - 24	25 - 26	27 - 28 29	- 30 ≥ 31	D.8 /W.8	Dry Bulb \	Net Bulb (Dew Point
78/ 77					•0			•0									4	6		
76/ 75					٥٥	.0	• 0				İ	•0					7	7	!	
74/ 73				•0	•0	.0	•0		 -	- O	• 3	•0					10	10		
72/ 71			•0	1				.0		• , ;						l	29	29	İ	
70/ 69			•6	.1	•1	.1	. 1	.0	• 0		.0						61	61	1	
68/ 67		•0		1			.1	.1		.0						i	103	103	11	
66/ 65		• 2					• 2	•1	•0	•0							184	184	23	4
64/ 63		.2	• 3	.5	.3			.1	•0	•0	1						223	223	78	35
627 61	•1	. 3	.5	• 6	.4	.4	- 3	•1	•1	• 0	-						335	335	108	74
60/ 59	. 1	•6	.7	. 8	.7	•6	. 3	-1	•0								474	474	190	93
58/ 57	. 1	.7	.8	1.0	.9	.5			• 1	• 0							544	i	268	138
56/ 55	. 3	1.4	1.2		1.0	.8				1							768		420	252
54/ 53	• 2	1.8	1.7	1.3	1.4	.8											912	912	555	348
52/ 51	• 2	2.2	2.0	1.5	1.3	.6	.0	.0	1								996	996	760	425
50/ 49	• 3	2.7	2.5	2.0	1.5	• 6		,		I -							1218	1218	921	
48/ 47	• 5	2.9	2.5	2.1	1.2			4	İ								1202		1169	755
46/ 45	• 3	3.2	3.1	1.8								1					1170	1170	1292	
44/ 43	• 3	3.1	2.6	1.9	.7		1	ļ				1 1			!		1044	1044	1259	
427 41	• 2	3.3	1.9	1.1	4	.0		1									869	869	1366	987
40/ 39	• 3	3.1	1.8					!									775	775	1203	
38/ 37	• 3			-4	•0				1	1							609	609	968	
36/ 35	. 4		-8			1	!	<u> </u>			<u> </u>	<u> </u>		<u>L</u> .	<u> </u>		510	510	834	
34/ 33	. 2		- 3	,	1	I .		i	! 	ļ				1	l i		312		622	
32/ 31	. 2)	i	<u> </u>								!		198		371	438
30/ 29	- 1							i						1	:	1	74	74	181	
28/ 27	•0	. 1	<u> </u>	<u> </u>		1		<u>i</u>	<u> </u>	; +-	ļ						15	15	47	
26/ 25					1	i	1		1	ĺ	1			į			1	;	3	
24/ 23			1		<u>i </u>	ļ			<u> </u>	ļ	ļ	<u> </u>			<u> </u>					163
22/ 21			!		1	1	i	İ			!						į		į	é i
20/ 19				<u>i</u>	<u>i </u>	<u> </u>	1	<u></u>	ļ	ļ	<u> </u>									25
18/ 17			i			i	1			{	ļ									10
16/ 15		<u> </u>	ļ	ļ		ļ	-	ļ	ļ	ļ	ļ	<u> </u>			<u> </u>		ļ			7
12/ 11				:			Ì													1
Element (X)		Σχ2			Y Z		X	σ _x		No. O	bs.			J	Mean No.		vith Tempe			
Rel Hum.												± 0 f	:	≾ 32 F	e 67 F	≥ 73 F	≥ 80 F	≥ 93 F		otai
Dry Bulb								1									 _			
Wet Bulb						_														
Dew Point				1		l		<u> </u>	L				l_		<u> </u>					

FORM JUL 6: 0-26-5 (Det 50) REVISED PREVIOUS EDITIONS OF THE

1210 WS JUL

}

GATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

43310 FUKUOKA KYUSHU JAPAN/ITAZUKE AB 48-64 MAR
STATION STATION NAME YEARS MONTH
PAGE 2 ALL
HOURS (L. S. T.)

Temo							WET BULL	B TEMPE	RATURE	DEPRES	SION (F)	}						TOTAL	L	TOTAL	
(F)	0	1 - 2	3 -	4 5-	6 7 - 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22 2	23 - 24	25 - 26	27 - 28	29 - 30	≥ 31	DB/WB	Dry Bulb	Wet Bulk	Dew Poin
CTAL	4.	135.	024	417	111.2	5.	1.8	3 - 5	•	3 . 1	• 9	•0		T - T					12648	3	1264
]							j			1		. 1					1	12648		12648	4
							T		:						1						
(1	1		i	1		ĺ	Ì									1		1	Į.
			1			1	7	1	1										<u> </u>		
I		1		+	:	1		1	ı	1		Ì		1 1			İ		1		
		,	1			1	1	1		ļ				Ţ							
į		1		1				İ						<u> </u>			ļ			1	
		1		,	1															1	Ĭ
				1	_	<u> </u>	<u> </u>	1	l	!	!						1	i	i		1
		,		Ţ			1	1 -													
i					_i	<u>L</u>								<u>i </u>			<u>L</u> _	L		<u> </u>	
		!		1				ī - -													1
		1	<u> </u>			<u> </u>			<u> </u>					لـــــــــــــــــــــــــــــــــــــ				1		<u> </u>	
								1						- 7							
l			<u> </u>			<u> </u>	1	<u> </u>	<u> </u>	<u> </u>	<u> </u>					L		<u> </u>			
									1												
					\	1		<u> </u>	İ.,												
										1										1	
			1				1	1		1				<u> </u>			1	<u> </u>			
			Ì	Ì			ì	1	•		i i	l i		i 1		!	1	1	}		Ì
		<u>i </u>				<u> </u>		<u> </u>	<u>i </u>	. İ					لــــــــــــــــــــــــــــــــــــــ	ļ	·			<u> </u>	<u> </u>
Į.		,	ĺ			-		1		-				1 ;			•		İ	1	
		+	_	 	<u> </u>	ļ		<u> </u>	<u> </u>	 	<u> </u>					ļ	 -	 	 	 	
1		!]			}	i	}	i									Ì		}
						 	<u> </u>		 			 				· 		 	 		
į		ı			-	1				1							1	1			-
									 	_		 		 					<u> </u>		
		1						1						1			}	}		Ì	
									 -		 	 		╁╼╼╾┤			┿		 -		
į		ļ	1	İ			-					{						1		1	[
		 -	-	 		+	-i	 	 		 	 		 		í	 	 	 -	+	
					1					1	1	i				İ		1			
Element (X)		Σχ²		_	Σχ	<u> </u>	 X	0,	.	No. O	bs.	ــــــــــــــــــــــــــــــــــــــ		<u> </u>	Mean h	lo. of	Hours w	ith Tempe	rature		
Rel Hu.n			871		9382		74.2	15.	390	12	648	≤ 0 F		≤ 32 F	≥ 67	F	≥ 73 F	≥ 80 F	≥ 93	F	Total
Dry Bulb		300	220	83	6070	13	48.0	8.	361		648			16.9		. 7	1.	4			744.
Wet Bulb		251	920	15	5568		44.0				648			35.4		• 7					744.
Dew Point		206	550	76	4999	22	39.5	8.4	414	12	648			162.1					1		744.

RM 0.26.5 [Det 50] REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

O WS JULY O

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

43310 FUKUOKA KYUSHU JAPAN/ITAZUKE AB
STATION NAME APR PAGE 1 ALL

Temp							w	ET BULB	TEMPE	RATURE	DEPRES	SION (F	1						TOTAL		TOTAL	
(F)		0	1.2	3 - 4	5 . 6	7 - 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22 2	3 - 24	25 - 26	27 - 28	29 - 30	2 31	D B./W B	Dry Bulb	Wat Bulb	Dew Point
88/										• (1									1			
86/	1			·						• 6									1	1		
1	83								• 0									1	3			
	81			!			• C	• 0				- 0						İ	7	7	l	
	79						• 1	• 1	• ()	-0	• 6	-0						-	28	28		
	77					. 1	-1		-1	- 1	• (·							62	62		
1	75		•10		1 1			• 2	• 1	-1	• 1		•0					1	107	107		
	73		.0		. 3				2		• 1					i		_l	160	160	- 2	
1	71		•2				. 4		• 5		1		. ,						275	278	13	5
	69	. C							• 5		. 1	- c							446	446	94	<u> 21</u>
1	67	- 1	• 6		•			1)		1	ì		-		i l		1	547	547	211	89
	65	- 1	.7		1.2							<u> </u>							565	665	330	215
	63	. 2			1	1.0										i			856	856	395	278
	61	. 2	2.3		1.6							<u> </u>				<u> </u>		 	1054	1054	639	408
	59	• 4	3.0		1.7	1.3					¥	İ	İ			! !		1	1258	1258	960	510
	57	-4	3.8			1.1	•5		•1		<u></u> _	ļ	<u> </u>						1175	1175	1156	806
	55	- 5							-0		!	i	1					1	1079	1079	1383	1035
	53				1.3				·		 		·			 			1007	1007	1193	1111
	51	• >	2.8		. 9				I	t		1				1			800	800	1275	1106
	49	- 4										 	· •					·	684	684	1125	1032
1	47	• 3	2.3		. 3		i .	ì	į	!	1	İ				!			534	534	960	998
	45	3						!	ļ	: 	 	ļ. <u></u>	+			<u> </u>		<u> </u>	504	504	758	866
1	43	• 2									1								323	323	599	906
.	41	<u>•¹</u>					<u> </u>	ļ	-	ļ		 						ļ	246	246	422 281	799 630
)9	. 1	, –		• 1	1			1	I	Į		1 1	i		'		ì	200	200		
	37	_ <u>. i</u>			ļ	 			 -	 	 		-						135	135	201	469 333
1	35	.1	1		l		t	1		;	1	1				1			63	63 15	51	249
	33	-0			 				<u> </u>		 	 	 			 -			1 2	12	11	172
	31 29	•0	• • (,			,		1	I		!							4		7.1	98
	27		 	+	 		<u></u>			 -	 -	1	 			 		+	 			5 5
	25				1	İ	1		į	l	ļ										i	37
	23		<u> </u>		 	 	 -	 	 	 	 -	 	├ ──┼			 			 			11
20/			,		1		ĺ	İ	1		1					i i				i		1
Element			Ex2	<u> </u>	+ -	Σχ		X	σ _x		N- 2	<u> </u>						<u> </u>	<u> </u>			
Ref Hu			-X-		 	~ X		<u> </u>	x		No O	DS			22.5				ith Temper	293 F		
Dry Bull									 				= 0 F	┵	32 F	≥ 67	-	≥ 73 F	≥ 80 F	273 8		otal
Wet Bu																 				+		
Dew Po									 -							├			 			
Dam Lo	101				<u>i</u>		!					i				1			L			

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

PSYCHROMETRIC SUMMARY

4331G FUKUCKA KYUSHU JAPAN/ITAZUKE AB 48-64
STATION STATION NAME

PAGE 2 ALL
HOURS R S T)

Temp									DEPRES								TOTAL		TOTAL	
(F)	0 1-	2 3 - 4	5.6	7 . 8 9	- 10	11 - 12	13 - 14	15 - 16	17 - 18	19 . 20	21 . 22 2	3 . 24 25	- 26	27 - 28	29 - 30	> 31	D 8 /W.B	Dry Bulb	Wet Bulb	Daw Point
TOTAL	4.535	622.2	13.9	9.8	6.6	4.1	2.0	•5	• 4	• 1	•4						12240	12249	1224	12240
	l			. 1	ļ	i		ł Į				}				:				!
			+					<u> </u>	 								} _		ļ <u> </u>	
	,	r			į	1	1						İ			1	ļ.		ĺ	
			<u> </u>						 	 			 -			 	 	ļ	 	 -
		1			ļ	1	l 1		ĺ)		}	- }				J			
			1					 		 	 -					 	 		 	
		,		i i	1		}	:				ļ	1	i			1			İ
			!	- -				 				- i-	t			 				
	1	1]	,		!		į		j	1	ļ		1			ļ	1
																	i			
			ļ					<u> </u>								i 	L		<u> </u>	<u> </u>
		į			_ j		1	1				Ī	j	1					ļ	
								<u> </u>	ļ	ļ						<u> </u>	<u> </u>		<u> </u>	<u> </u>
]		1		i 1			1			1				ł		į	Ì
			 					 	ļ			<u></u>				 	 		 	
	ĺ		1	i	[-				[
			 -	 -			├──	 		 -	 -						 	 	 -	
	!	:	1		į		;							}		Í	}			
			 	 	i		 -	 		 	 -	 i				 	 		 	!
		1	1	! !	i		ĺ		İ	1	il	i	ĺ			1	l	ĺ	İ	İ
			 	 -					 							 	 			†
	1	1		! !			ļ.]			- 1	Ì	į		i) !	ļ	
			<u> </u>		1			L	<u> </u>				i.			1			<u> </u>	<u> </u>
				,				!]		j - J)						1	
				<u> </u>				<u> </u>	<u> </u>		<u> </u>					<u> </u>				 _
		1					[1				1	[1			
			 	 -			ļ		}		 _					 	 _		 	 -
			}		ļ		,					1	}	}	i]	j			
Element (X)	Σχ²		+	Σχ	┰┙	X	σ _x	┺┯	No. O	ha.	<u></u>	<u></u>		Mean N	0. 01	Hours w	ith Tempe	rature		
Rel. Hum.		139773		35927	17	6.5	16.3	57	1 2	240	₹ 0 F	≤ 3		≥ 67		273 F	> 80 F	≥ 93	F	Total
Dry Bulb		696327		98023		7.0	8.5	25	1, 2	240		 	-1		•5	21.7			_	720.0
Wet Bulb		13448		44680	5	2.7	7.3	133	1. 3	240		1	.7		•8	•1		 		720.0
Dew Point		220144		99314		9.0			12	240		2	2.d		• 8					720.0

LM 0-26-5 (Det 50) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

FORM 0.26.5 [Day

■ SM O

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

FUKUDKA KYUSHU JAPAN/ITAZUKE AB MAY 43310 PAGE 1 ALL

Temp.							ET BULB											TOTAL		TOTAL	
(F)	0	1 - 2	3 - 4	5 - 6	7 - 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22 2	23 - 24	25 - 26	27 - 28	29 - 30	≥ 31	DB/WB	Dry Bulb	Wet Bulb	Dew Poi
88/ 87												•0	•0					2	- 2		
56/ 85							.0		-0	.0	.0	•0	•0	•0	l i			18	18		ĺ
84/ 83				i		•0	• 0	-1	•0	•1	•1	•0	.0	•0				43	43		i
32/ 81					.1	.1	. 2	.1	_	-1	-1	.1	•0		1			124	124		
80/ 79			.0	• 1	-1	• 3		•3				۵.	• 0		- i			237	237		
78/ 77			.1	. 4	.3			.5				.0	• 0					368			1
76/ 75		•0										.0	.0					581			
74/ 73	.0	1		1 1		1.0	1		1	1 .		•	• .5					707	707	5]	l
777 71	.0					1.0			1			••	——					802	802	2228	
		1				,				t .	(1012		403	1
70/ 69	• 1			1.7	1.4	1.1	• 5						 j						1319	709	
68/ 67	• 2		2.7	1.09	1.5	• 1	. 3		1	• 0	1		j					1313			_
56/ 65	• 5		3.3	2.0	.9					<u> </u>	ļ							1453	<u> </u>	1201	
64/ 63	5		3.1	1.4	.7	.3			•0	1								1420		1722	
62/ 61	• 6	5.2	2.3						<u> </u>		<u> </u>	i_						1352		2090	
60/ 59	.7	4.1	2.2	1.0	.3	•0	• 2		i									1121		1931	_
58/ 57	. 5	3.5	1.6	. 6	-1	1		!				1	į		,		1	840		1472	15
56/ 55	.4	2.9	1.2	. 4	•0		<u> </u>		1		1	-						651	651	117	13
54/ 53	•5					.0	ļ		!	İ			i				1	516	516	88	13
52/ 51	• 3				.0	1	 	 	†	 	 	 						330	330	634	10
50/ 49	. 2						ļ	ŀ	•	1	ì	. i					i	239	239	437	9
48/ 47	• 1				I	 		·	+		 -				 -			139		222	6
46/ 45	.1		-		1		ı	:		,	1						1	68		133	
44/ 43	-:i			}			i -	 -		 		 			·		 	35			1
42/ 41				' t		1	1		ı	ì	ì		l		,			7	7	30	
	•			 _	1	!	ļ		 	 _		 							ļ !	,,,,	
407 39	<u> </u>			1		ì	1				!	İ			;		ı	1	!	•	
38/ 37	<u> </u>	 -	4	<u> </u>	,				-	 	<u> </u>				 +		<u> </u>				
36/ 35				•			1		i	i	1	1]			1	į l	l	Γ
34/ 33				<u> </u>	<u> </u>	<u> </u>		,		ļ 	ļ						ļ •	 			<u> </u>
32/ 31					1	į –									, .		į	1	i		1
30/ 29				i		i	į.				1						L	<u> </u>	1		
28/ 27	<u> </u>	7	T	!			1	T	!		1						[
26/ 15	Ì	1	ı	1		ì	:	1		!		; }]]			j			
20/ 19	1		 	1		 -			1	!	 								1		i
_ ,, -,	1	ı		i	i	1			1	1	1	1		1) i		1	1)	}
Element (X)	 	Σχ²		1	Σx	' 	×	- σ _x	. 	No O	bs .				Mean N	lo of H	ours w	ith Tempe	coture		
Rel. Hum	 			 					· - -			± 0 F	T .	32 F	≥ 67		73 F	≥ 80 F	≥ 93 5	:	Total
Dry Bulb	 			 -				 					+		1 3			 			
Wet Bulb	 														 	+-		 			
Dew Point				i		 - -		 	_						 -			}		 -	
DAM LOIUL	<u> </u>			ــــــــــــــــــــــــــــــــــــــ				<u>i</u>	i_						ــــــــــــــــــــــــــــــــــــــ			ــــــــــــــــــــــــــــــــــــــ		<u>-</u>	

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

STATION			ST	ATION NA	ME TAZE							YE	ARS					PAGE	
																		HOURS	
Temp					WET BUL											TOTAL		TOTAL	
(F ₁	0 1.	2 3 4	5 - 6	7 - 8	9 - 10 11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22 2				29 - 30	2 31	DB/WB.	Dry Bulb	Wet Bull	Ыξ
TOTAL	5.033	.721.7	13.4	8.9	6.5 4.	5i 3. . 0	1.6	•9	-4	•2	• 1	•q				13378	13385	1337	8
							 -												T
				i	<u> </u>	1				_ !	1	į				_		1	1
						•													T
							,		i						1			ļ	1
!!									İ ļ		ł	1			1 1				į
						ļ			L			!			ļ			<u> </u>	_
	1	i	' !	,			į		!			į	1				į	İ	į
		<u> </u>					-								↓			 	4
1	'	i	į		İ	i				į.							!		į
			,					<u> </u>							+		<u></u>	₩	4
		1	:		į	,	!		١ :		ļ								1
 				 -			 -	 							-		 -	┼	- -
		-	į			i									l		Ì	-	
				 		 	 -	 			 -	-			+		 	 	+
{ }		1	1		1		!	1	} ;						ļ		\		1
			i	 		+		 	-						+			 	+
	'	1	İ			1					-								
				 		 	┼──	 	 				-				 	 	+
				i i		!		1							1		Ì		i
	 		 	 		+	├	 	<u> </u>						 		 	 	+
		;	ĺ		1	!			İ	,	,						1	;	i
-			 	+		1	 	 	 								 	 	+
i			1	j		1	ĺ	l	j .			i	i		'		1	i	-
<u> </u>			$\overline{}$	1		1		 	 		<u>i</u>				1		 	†	7
1		;	i	! ;			İ	1	į ,		l	i			1			ļ	1
						-!	1		Ì						1			1	7
			i			ļ					ļ							ł	
			1				T	1	1						i				7
			<u> </u>			_i		1			[_				_			<u> </u>	
			T					T									T	1	T
				<u>11</u>		1	<u></u>	<u> </u>		لــــــــــــــــــــــــــــــــــــــ							<u></u>		_]
Element (X)	Σχ			Σχ	X	σ _χ		No O				_				th Tempe			_
Pel. Hum		460707		40621					378	± 0 F	_ ≤ 3	2 F	≥ 67		≥ 73 F	≥ 80 F	- 93	F	
Dry Bulb		446005		6337					388		_		289		115.6		<u>:</u>		_
Wet Bulb Dew Point		189297		99343	59.8	5.6			378		1		77 35		3.2				_

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

HINOM FUKUUKA KYUSHU JAPAN/ITAZUKE AB

PAGE 1 ALL

92/ 91 90/ 89 88/ 87 86/ 85 84/ 83 82/ 81 80/ 79 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	00 01 10 10 10 10 10 10 10 10 10 10 10 1	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	.0 .8 1.3 1.8 2.1 1.9 2.2 1.0 7	.0 .0 .3 .5 .9 1.0 1.5 1.5 1.5 1.0 .6	.1 .2 .4 .6 1.1 1.1 1.1 .6 .5	.0 .1 .2 .3 .5 .5 .8 .5 .3	.0 .1 .2 .3 .2 .3 .3 .3	.0 .1 .1 .1 .1	.0 .0 .1 .1	.0 .0 .0 .1 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0	•0	• 0 • 0 • 0	•0	• 0	. 30 - 31	0.8./w.s. 644 95 189 273 459 714 1021 1167 1274 1305 1538 1386 1256 852 351	44 95 189 273 459 714 1021 11275 1305 1543 1392 1260 864 623	25 187 623 899 1232 1607 1887 2071 1641 1221	2 26 193 691 1096 1425 1881 1920 1573 1282
90/ 89 88/ 87 86/ 85 84/ 83 82/ 81 80/ 79 .0 78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	1.3 1.6 2.1 1.9 2.2 1.0 .7	1.0 1.5 1.6 1.5 1.0 0.0	.2 .4 .6 1.1 1.1 1.1 .6 .5	.1 .2 .3 .4 .5 .8 .8 .5	.1 .2 .3 .2 .3 .3	.0 .1 .1 .1 .1	.0 .1 .1 .1	.0 .1 .0	•0 •1	•0		• 0		95 189 273 459 714 1021 1167 1274 1309 1538 1386 1256 852 622	95 189 273 459 714 1021 1167 1305 1543 1395 1260 864 623	3 25 187 623 899 1232 1607 1887 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
88/ 87 86/ 85 84/ 83 82/ 81 80/ 79 .0 78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	1.3 1.6 2.1 1.9 2.2 1.0 .7	1.0 1.5 1.6 1.5 1.0 0.0	.2 .4 .6 1.1 1.1 1.1 .6 .5	.2 .3 .4 .5 .8 .5 .8	.3	•1 •1 •1 •2 •1	.0 .1 .1 .1	.0 .1 .0	•0 •1	•0		•0		95 189 273 459 714 1021 1167 1274 1309 1538 1386 1256 852 622	95 189 273 459 714 1021 1167 1305 1543 1395 1260 864 623	3 25 187 623 899 1232 1607 1887 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
86/ 85 64/ 83 82/ 81 80/ 79 .0 78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 66/ 65 1.3 66/ 65 1.3 66/ 65 1.3 56/ 55 .3 56/ 55 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	1.3 1.6 2.1 1.9 2.2 1.0 .7	1.0 1.5 1.5 1.6 1.5 1.0 .6 .5	.4 .6 1.1 1.1 1.1 .6 .5 .3	.3 .4 .5 .8 .5 .3	.2	.1 .1 .1 .2	.1 .1 .1 .1	.1 .0 .1	•0 •1	•0				189 273 459 714 1021 1167 1274 1309 1538 1386 1256 622 351	189 273 459 714 1021 1167 1305 1543 1392 1260 864 623	3 25 187 623 899 1232 1687 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
84/ 83 82/ 81 80/ 79 .0 78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 66/ 65 1.3 64/ 63 .8 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	1.3 1.6 2.1 1.9 2.2 1.0 .7	1.0 1.5 1.5 1.5 1.0 .6 .5 .1	.4 .6 1.1 1.1 1.1 .6 .5 .3	.4 .5 .8 .5 .3	.3 .3 .3	•1 •1 •2 •1	•1 •1 •1	.0	.1	•0				273 459 714 1021 1167 1274 1309 1538 1386 1256 622 351	273 459 714 1021 1167 1275 1305 1543 1392 1260 864 623	25 187 623 899 1232 1607 1887 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
82/ 81 80/ 79 .0 78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 66/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	.8 1.3 1.8 2.1 1.9 2.2 1.0 .7 .2 .1	1.0 1.5 1.6 1.5 1.0 .6 .5	.6 1.1 1.1 1.1 .6 .5 .3	.5 .8 .5 .3	.2 .3 .3	.1 .2 .1	.1 .1 .0	•1	.1					1021 1167 1274 1309 1538 1386 1256 852 622	459 714 1021 1167 1275 1305 1543 1392 1260 864 623	25 187 623 899 1232 1607 1887 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
82/ 81 80/ 79 .0 78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 66/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4	1.0 1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7	1.3 1.3 1.8 2.1 1.9 2.2 1.0 .7	1.0 1.5 1.6 1.5 1.0 .6 .5 .1	1.1 1.1 1.1 .6 .5 .3	.5 .8 .5 .3	.3	•1 •2 •1	•1 •1	.0		•0				714 1021 1167 1274 1309 1538 1386 1256 852 622	714 1021 1167 1275 1305 1543 1392 1260 864 623	25 187 623 899 1232 1607 1887 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
78/ 77 .0 76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4 1.6	1.9 2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7 .3 .2	1.3 1.8 2.1 1.9 2.2 1.0 .7 .2 .1	1.5 1.6 1.5 1.0 .6 .5 .1	1.1 1.1 .6 .5 .3	.8 .5 .3	•3 •3	•2 •1	•1		•0					1021 1167 1274 1305 1538 1386 1256 852 622	1021 1167 1275 1305 1543 1392 1260 864 623	187 623 899 1232 1607 1887 2071 1641 1221	26 193 691 981 1096 1425 1881 1920 1573
76/ 75 .1 74/ 73 .3 72/ 71 .7 70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.4 2.4 2.9 4.2 5.0 5.2 4.0 3.4 1.6	2.0 2.5 2.9 4.0 3.4 2.4 1.6 .7 .3 .2	1.8 2.1 1.9 2.2 1.0 .7 .2 .1	1.6 1.5 1.0 .6 .5 .1	1.1	.5 .3 .1	.1	•1 •0	•0	•0						1167 1274 1305 1538 1386 1256 852 622	1167 1275 1305 1543 1392 1260 864 623 351	623 899 1232 1607 1887 2071 1641 1221	193 691 981 1096 1425 1881 1920 1573 1282
74/ 73 .3 72/ 71 .7 70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .9 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	2.4 2.9 4.2 5.0 5.2 4.0 3.4 1.6	2.5 2.9 4.0 3.4 2.4 1.6 .7 .3 .2	2.1 1.9 2.2 1.0 .7	1.5 1.0 .6 .5 .1 .0	.6	•3 •1 •0	.1	.0								1274 1305 1538 1386 1256 852 622	1275 1305 1543 1392 1260 864 623 351	899 1232 1607 1887 2071 1641 1221	691 1096 1425 1881 1920 1573 1282
72/ 71	2.9 4.2 5.0 5.2 4.0 3.4 1.6 1.0	2.9 4.0 3.4 2.4 1.6 .7 .3 .2	1.9 2.2 1.0 .7 .2 .1	1.0	.3	•1 •0			$\overline{}$							1309 1534 1384 1254 852 622 351	1305 1543 1392 1260 864 623 351	1232 1607 1887 2071 1641 1221 861	981 1096 1425 1881 1920 1573 1282
70/ 69 .6 68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	4.2 5.0 5.2 4.0 3.4 1.0	4.0 3.4 2.4 1.6 .7 .3 .2	2.2 1.0 .7 .2 .1	.6 .5 .1 .0	.1	.0	•0	•0								1538 1384 1256 852 622 351	1543 1392 1260 864 623 351	1607 1887 2071 1641 1221 861	1096 1425 1881 1920 1573 1282
68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	5.0 5.2 4.0 3.4 1.6 1.0	3.4 2.4 1.6 .7 .3 .2	1.0	.1 .0 .0	-1											1384 1254 852 622 351	1392 1260 864 623 351	1887 2071 1641 1221 861	1425 1881 1920 1573 1282
68/ 67 .8 66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	5.2 4.0 3.4 1.6 1.0	2.4 1.6 .7 .3 .2 .1	.7 .2 .1 .1	.1 .0 .0		• 0										1256 852 622 351	1260 864 623 351	2071 1641 1221 861	1881 1920 1573 1282
66/ 65 1.3 64/ 63 .8 62/ 61 .6 60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	5.2 4.0 3.4 1.6 1.0	2.4 1.6 .7 .3 .2 .1	.1	•0												852 622 351	864 623 351	1641 1221 861	1920 1573 1282
64/ 63	4.0 3.4 1.6 1.0	1.6 .7 .3 .2	.1	.a												622 351	623 351	1221 861	1573 1282
60/ 59 .5 58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.6	.3 .2 .1	•1 •0	.0												351	351	861	1282
58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	1.0	.2 .1	•0																
58/ 57 .3 56/ 55 .3 54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	• 6	.2 .1	•0	.0											ļ	199	195	324	
54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35	• 6	.0																	
54/ 53 .1 52/ 51 .1 50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35							ļ		!							117	117	205	
50/ 49 .0 48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35									!!!	ļ	Į.	i	İ		. !	40			263
48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35		<u> </u>					1					- 1				19	19	39	
48/ 47 46/ 45 44/ 43 42/ 41 40/ 39 36/ 35		 -		, ,		ļ	i			- 1	į	1	ļ			2	2	7	69
46/ 45 44/ 43 42/ 41 40/ 39 36/ 35		, !										Ī							28
42/ 41 40/ 39 36/ 35		j l	. !	!!!								ļ	ļ				!!		21
40/ 39 36/ 35															1				6
40/ 39 36/ 35		, ,	. !																4
												Ī			ĺ				6
		i	, !		!	j													1
TOTAL 6.53													Ĭ	— į	1				
	33.0	23.d	13.8	9.7	6.5	3.8	1.8	1.0	.5	. 3	-1	- 1	.d	•d			12954		12925
												i				12925		12926	
}			1 1	l !	l						1]						
Element (X)	Σχ²		 	Σχ		x	σ _X		No Ob	. 1				Magn No	of House	with Tempe	coture		<u> </u>
		3256		4595	2 0	0.9				925	≤ O F		32 F	≥ 67 F	2 73 F	2 80 F	≥ 93 F	F T	otal
		2409		1915		1.0	6.7			954	- 0 1		V4 1	527.					720.0
	マフグ	4777				4 9 V				926				7410		7 174	e and		
	5744	0205				4.4	K A							360.				ì	720-0
Dem Foliti		0285 19664	8	6068 3075	5 6	4.3	5.5			925			.1	360 · 0	96.	7	4		720.0

OATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

FUKUCKA KYUSHU JAPAN/1 TAZUKE AB 47-64 PAGE 1 ALL

Temp			_							DEPRESS							TOTAL		TOTAL	
(F)	0	1 2	3 4	5 - 6	7 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22 23	24 25 - 2	6 27 - 28	29 3	0 ≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Poin
00/ 99			, , ,							• -							1	1		1
96/ 97									• *	1 - 1	• 0		t t			i	ڌ إ	لأرث إ	1	
96/ 95							.0	• 1	• 1	. a	•0						20	20		
94/ 93			,		.0	• 1	• 2	•1	• 3	3	•0	,					133	133	(
92/ 91				• 1	.1	• 2	. 6	.7	• :	1 .1	• 1			1			292	292		
90/ 69			. ci	1	. 3		2.1						İ	!			659	659	1	
88/ 87			.1	• 3	1.5		1.4	• 2	.0					1 1			858	858		
86/ 85		•0	.2	1.1	3.1	2.3							İ			i	995	995	15	9
84/ 83		0	.8	3.2	3.3											-	1142	1143	54	24
82/ 31	• d	. 3		4.7	1.6								İ	1			1371	1371	234	
80/ 79	•0	2.2	7.9		. 9		•0		<u> </u>								2047	2047	1203	204
78/ 77	. 3	5.7	, ,		1	.0											1969	1970	2847	99.
76/ 75	. 9	6.1		1.1		913								1			1598			299.
74/ 73	1.0														 -		984		2538	3829
72/ 71	. 9	2.7								†				1	$\overline{}$		629	625	146	2750
70/ 69	. 8												- 1				400		762	1366
68/ 67	-4	.7	.2		1									1		- 	176	176	392	709
66/ 65	. 1	. 3							Ì								57			294
64/ 63	-1	•1			†					 				-		+	33	33	50	
62/ 61	. 1	.0							i								13			
60/ 59					 		 		 	 				+					1	1 7
58/ 57	i				}	ļ	i												1	1 1
56/ 55					1				 	1 -				 	 	 -	 	 		1
TOTAL	4.6	24.5	26.0	16.5	11.3	8.8	5.4	2.1		.2	•0	l i	ł				1	13382	<u> </u>	1337
					1	133			 -	1				1	<u></u>		13376		13378	
																		Ì		
			 		+	 						 		1	<u> </u>		 	i		-
									l						ŀ		ł	1		
			 	 	 		 	 	 	i 			\dashv	 			 		 	<u> </u>
																		ļ		
					 	 	 			 				+	 	+	 	 	 	
] ,)		1		1	J .			}			1	1			ļ
			-	 -	 					1			-+	1			 		 	t
								!		1 1										
Element (X)		Σχ²		 	Σχ	<u>'</u>	X	σ _x	Ή-	No. Ob	s. T	<u> </u>	1	Mean N	lo. of	Hours w	ith Tempe	rature		
Rel. Hum			3246		8088	6 8		11.8			378	± 0 F	≤ 32 F	≥ 67		≥ 73 F	≥ 80 F	≥ 93 1	F .	Total
			1397		6760		9.8	5.7			362		<u> </u>	738		671.) • E	744.
Dry Bulb Wet Bulb			2343		0176		4.9	3.3	37	13	378		1	731	. 8	586.	43.	, 31		744.

1. 844 W.3.

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

PSYCHROMETRIC SUMMARY

FUKUOKA KYUSHU JAPAN/ITAZUKE AB 43310 STATION 47-64

YEARS

AUG MONTH

PAGE 1 ALL

																				HOURS	(L S 1)
Temp.						w	ET BULB	TEMPE	RATURE	DEPRES	SION (F)			_			TOTAL		TOTAL	
(F)	0	1.2	3 - 4	5 - 6	7 - 8	9 - 10	11 - 12	13 - 14	15 - 16	17 - 18	19 - 20	21 - 22	23 - 24	25 - 26	27 - 28 2	9 - 30	≥ 31	D B /W.B.	Dry Bulb	Wet Bulk	Dew Poi
00/ 99										• 0	•0	• C	•0					9	—-৻		
98/ 97							•0		•0	• 1	.0	•0	•0					25	25		j
96/ 95				• 6	•0	•0	• *	•2	• 3	.1	•0	.0			 -	-		85	85	 	
94/ 93				.0			1 1	.5		. 1								193	193	1	i
92/ 91				•1	• 2	• 5				• ()	1							407	407	1	
90/ 89			• 3	1 1						i								819	818	1	
88/ 87		•0		. 5		3.0		• 3										963	963	1	
86/ 85		•0																	1139		1
84/ 83		•1	1.2			•9		• 1										1161		1	
82/ 81	• α	. 6				. 3		.0										1398			
80/ 79	• 0	3.5		2.3				•0			 				 			1898			360
78/ 77	. 3						.0					İ						1918			
76/ 75	. 9						· · · · ·				 	 i				+		1652			
74/ 73	1.0	4.9	1.0	• 2	•0													950	950		
72/ 71	• 5	2.1	.4								 					$\overline{}$		416	417	115	211
70/ 69	. 2	1.0	.2															190	190		96
68/ 67	.1		.1								1							84	84	18	46
66/ 65	• 0		•1								İ							37	37	86	21
64/ 63	• 0	•1								-						1		14	14	3.	7
62/ 61	- 9	• 1				1		ì		ļ		i				!		12	12	1.	3
60/ 59																				2	1
OTAL	3.1	28.6	22.8	14.5	11.4	9.4	5.8	2.6	1.1	. 4	-1	-1	• 1			i			13372	2	1336
	_																	13369		1336	1
					-		i					- 1	i			-					1
							ļ —					1									
						į	1			!		į					,				1
																					1
					<u></u>	<u> </u>										j					1
							1														
						L	1														
																				i	
					L	<u> </u>	L														
					ļ —																
				<u></u>	<u></u>	L,	<u> </u>				<u></u>										<u> </u>
Element (X)		Σχ ²	2617		z _x 7682	• -	X	σ _χ		No OI								th Temper			
Rel. Hum.			2514 1284		7955		0.5	12.5			369	± 0 F		32 F	≥ 67 F		73 F	≥ 80 F	≥ 93		Total
Dry Bulb			3849		1173		3.7	5.8 3.2			369				736.			396.	1 -	.4	744.
Wet Builb Dew Point			2091		8554		3.7	3.1	k		369				725		27.8		- 1		744.
Daw Point		1 / IK	2 1 W	, 4	A 7 7 9		3.1												MI.	1	144.

AND THE PROPERTY OF THE PARTY O

DATA PROCESSING DIVISION ELAC. USAF ASHEVILLE, N. C. 28801

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

PSYCHROMETRIC SUMMARY

SEP

STATION STATION NAME MONTH PAGE 1 ALL HOURS & S TJ WET BULL TEMPERATURE DEPRESSION (F) TOTAL TOTAL (F) 1 - 2 3 · 4 5 · 6 7 · 8 9 · 10 11 · 12 13 · 14 15 · 16 17 · 18 19 · 20 21 · 22 23 · 24 25 · 26 27 · 28 29 · 30 ≥ 31 D.B /W.B. Dry Bulb Wet Bulb Dew Point 96/ 95 94/ 93 - 1 13 92/ 91 90/ 49 127 127 •0 58/ 87 274 274 1.0 86/ 85 401 401 84/ 83 . 2 58**0** 580 1.4 • 1 • 1 1.8 1.5 . 1 770 82/ 61 . 8 77a 80/ 19 1042 1042 284 36 1.2 • 1 1.9 1405 78/ 77 1404 768 2.2 3.5 1.6 1742 76/ 75 1739 132 951 1.0 4 . 8 1613 1739 2.8 1861 74/ 73 5.1 1.4 1611 4.2 2.2 1299 1859 1879 72/ 71 1.2 3.8 1581 .0 1116 1116 1666 70/ 69 1414 68/ 57 2.9 1.9 • 5 817 818 1326 66/ 65 2.9 638 1274 1270 638 982 2.7 549 549 1125 64/ 63 • C 376 729 375 1:31 62/ 61 840 60/ 1.8 332 332 509 200 208 -4 1.1 366 611 58/ 57 56/ 55 91 91 181 390 • 6 54/ 53 48 63 224 46 52/ 51 110 53 48/ 47 10 46/ 45 44/ 43 42/ 41 13513 TOTAL 13522 4.735.122.213.4 9.9 7.7 4.1 1.7 13512 1351

ΣX Element (X) Mean No. of Hours with Temperature 13513 267 F 273 F 260 F 293 F 599.3 427.1 145.9 92105102 1101556 81.5 13.070 Rel Hum ≤ 0 F Total 995175 73.6 7.287 935587 69.2 5.613 13522 720.6 Dry Bulb 13959627 13513 498.2 239.5 720.0 65232903 8.3 Wet Bulb 418.0 158.5 61405316 907110 67.1 6.15/ 13513 Dew Point

0.26

armer Spina

DATA PROCESSING DIVISION ETAC. USAF **PSYCHROMETRIC SUMMARY** ASHEVILLE, N. C. 28801 FUKUGKA KYUSHU JAPAN/ITAZUKE AB 43310 UCT MONTH PAGE 1 ALL HOURS & S. T.) WET BULB TEMPERATURE DEPRESSION (F) TOTAL D.B./W.B. Dry Bulb Wet Bulb Dew Point (F) 1.2 3.4 5.6 7.8 9.10 11.12 13.14 15.16 17.18 19.20 21.22 23.24 25.26 27.28 29.30 = 31 90/ 89 88/ 87 15 86/ 85 84/ 83 28 28 .0 • 0 827 61 87 87 RG/ 79 112 112 250 45 478 478 16/ 15 741 73 613 615 120 .6 72/ 71 . 9 .0 897 897 203 138 - 8 208 1095 1095 426 70/ 69 1180 1160 689 402 68/ 67 995 1241 1241 589 66/ 65 1.4 1224 1224 1297 911 64/ 63 3.0 2.1 . 6 1188 1188 1086 62/ 61 3.2 1561 60/ 59 1158 1158 1631 1301 1663 1349 58/ 37 1071 1071 4.3 1.5 .0 56/ 55 893 .7 3.6 893 755 735 1109 1469 54/ 53 1.6 943 1360 52/ 51 .6 3.0 .0 601 601 2.6 722 1134 561 352 352 502 926 48/ 47 46/ 45 1.1 224 224 350 677 103 103 174 432 44/ 43 . 2 • 0 98 192 41 41 41 421 97 27 40/ 39 18 18 38/ 37 49 36/ 35 34/ 33 32/ 31 36/ 29 28/ 27 7.037.417.712.110.1 8.4 4.9 1.7 14133 14129 TOTAL No. Obs. Element (X) Mean No. of Hours with Temperature 14133 92171458 1120704 79.3 15.288 ≥ 67 F ≥ 73 F ≥ 80 F ≥ 93 F Total 250.8 882666 62.5 8.303 822909 58.2 6.668 744.0 56115772 14129 83.8 Dry Bulb 744.0 48543087 9.4

43.0

Wet Bulb

2

782149

55.3 7.047

43987605

1000

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

PSYCHROMETRIC SUMMARY

NUV FUKUOKA KYUSHU JAPAN/ITAZUKE AB 43310 46-64

PAGE 1 ALL

Temp	,									DEPRESS				I				TOTAL		TOTAL	
(f)	_ 0	1 . 2	3 - 4	5 - 6	7.1	9.	10 11 - 12		15 - 16	17 - 18 1	9 - 20	21 - 22	23 - 24	25 - 26 2	27 - 28 2	9 - 3	0 231	D B./W B	Dry Bulb	Wet Bulb	Dew Po
80/ 79	ļ			ŀ			.0 .0]					l		Į.	4	I.	1	
76/ 75				• (d		0 00		• 6	<u> </u>				 			- i	23	23		
74/ 73	,														;		1	60	60		
72/ 71			•1)		1		.1							 			 	110			 -
70/ 69	1	. 1	.2			4	.4			!)				1	i			256			1
68/ 67		.1	.4		5 .	6	.7 .	5 . 1	.0	,							 	362	382	41	
66/ 65	• 1		.9			8 1	.0 .0	1	1	1 1				1	ļ			663			
64/ 63	. 1	. 8	1.3	1.	1 1.	0	.9 .4											774			
62/ 61	1	1.9	1.3	1.	11.	2 1	-1 -:											949			
60/ 59	. 3	2.2	1.5	1.	2 1.	1	.9 .:								į			1022			1
58/ 57	3	2.3					.7											1087			1 -
56/ 55	• 5	2.5	2.0	1	1		-5		į				:		}		į.	1142		1	1 .
54/ 53	• 5			1.		. 8	<u>• 2</u> • (1067	1069		10
52/ 51	• 4	3.6		1.		•	-11 -0	3				į						1057	1057		1 7 1
50/ 49	•6		2.2			5	•1	 -										916			1
48/ 47	• 1	3.9				. 3	• 0			1 1				; !			1	899			14
46/ 45	• 7	3.4	• 6			.3		- 	 	++				 				724			
42/ 41	.6	1 1 .				. 1	Ì	İ		1 1					1			599			
40/ 39	- 5					-	 -			 -		 		 				397			
38/ 37	. 3	r	1		٦				İ								1	214	l		1
36/ 35	• 2								 	+		 -		 			-	1112			4
34/ 33	.1	•		1						1					ĺ		Ì	42	42	104	3
32/ 31	• C			1								 						7	7	2	_
30/ 29				ļ		.!		<u>i</u>											i		1
28/ 27																				1	
26/ 25		l			-					11				11					L	!	<u> </u>
24/ 23												1			1				į		
22/ 21			<u> </u>		<u> </u>	_ <u>;</u> _ ;				 		ļ		 				 		<u> </u>	1
TOTAL	6.4	39.3	26.6	314.	qıc.	.0 6	. 7 2.	9 •(5	1 -0		İ .		i					1367		136
		-	-					-	 -					 				13669		1366	1
					1_				1									<u> </u>	<u> </u>	<u> </u>	
Element (X)		Σχ²			Σχ		X	σ,		No. Ob								ith Tempe			
Rel. Hum		8655	1981		067		78.1	15.			6/39	± 0 1	-	≤ 32 F	≥ 67		≥ 73 F	2 80 F	≥ 93	F	Total
Dry Bulb			5710		735		53.8		395		678			4	44		4.	1			720
Wel Bulb			6000		682		49.9		078		669			1.4		• 4		 			720
Dew Point		3037	10558	9	635	755	46.5	17.0	555	13	669		L_	23.6		• 4		<u> </u>		i_	720

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE. N. C. 28801

and the state of t

PSYCHROMETRIC SUMMARY

4331C FUKUORA KYUSHU JAPAN/ITAZUK: AB 46-64

STATION STATION NAME

PAGE 1 ALL
HOURS (L S T.)

Tem								FT ALLS	TEMPE	PATUPE	DEPRESS	ION (F)							TOTAL		TOTAL	
(F)		0	1 - 2	3 . 4	5 . 6	7 - 8	9 . 10				17 - 18		21 . 2'	23 . 24	25 . 24	27 . 28	20 . 20	> 31	D.B./W.B.	Dry Bulb		Daw Point
79/		-	1 . 4	3.4	•0		, 0	-11.12	.3 . 14	.5 . 10	17 . 18	., - 20	2 / 2	-3 . 24	23 . 20	27 - 28	47 - 30	- 31	a	8		
			1	.1	.0			• 0	• 0	•0									28	28	İ	
66/			•0		• 1	• 1	.0		•0		1								53	53		
	63	.0	.1	,1	.2		.1	.0		l									101	101	26	6
627	61	•0	•2				•1	-1	J.		 	-				-			176	176	41	23
60/	58	. C	.6	3			. 2	• 2											378	378	96	52
58/	57	•0	.8			.7	. 4				 				-				461	461	178	94
56/	55	. 1	1.1	•8		. 9	.5	.0				1							657	657	292	162
34/	53	.2	1.2	1.3	1.3	1.2	• 3	•0		-									784	784	419	261
52/	51	. 2	1.6	1.7	1.7	1.2	. 2	.0	,	İ]				944	944	59/	325
507	49	-4	2.1		2.1	1.2	• 2	•0											1237	1237	850	445
48/	47	- 4	2.8	2.7	2.2	1.1	-1				1 1							Ì	1311	1311	1091	577
46/	45	-3	3.6	3.1		• 9	•1			·		1		i					1431	1431	1332	603
44/	43	. 3	3.9	2.9	2.3		•0	1		İ					1				1397	1397	1505	
421	41	-3	4.1												, —				1298	1298		1153
40/	39	.6	4.7							i	<u> </u>	!		L	L				1354	1354	1673	
387	37	.4	4.0			•0								1					1014	1014		
36/	35	- 5	3.3																715	715	1229	
347	33	• 5	2.0						!										419	419	921	
32/	31	. 3							1	1	<u> </u>							!	249	249	537	
307	29	• 1	-4		• 0				1	ř ļ	! !			[85	85	242	
28/	27	• 1	•1			l									1 ,				31	31	71	
26/	25		•0	_		1		:		! !	!								1 1	1	20	
24/					Ì.	 	! 	<u> </u>		ļ	1			<u> </u>				<u> </u>	<u> </u>		2	
22/	21			1	1		1	ł	ţ			į				:				Į		85
501				ļ	1		ļ	<u> </u>	ļ	<u> </u>	4			<u> </u>	<u> </u>					i		43
18/	17	į		1								- 1						1				33
16/				 	<u> </u>				ļ	<u> </u>	 			<u> </u>	<u> </u>	ļ						
14/	13											ļ			1				i l			6
12/				+	ļ	<u> </u>		<u> </u>	ļ	<u></u>				<u> </u>				! 	 			3
8/	7	i		i		1	į	!											i l			
6/	5	<u> </u>	46 -	 4 	100	- A	4 4			ļ	4			ļ				 -	1	14132		1417
TOTAL	١ ١	>.0	38 • l	42.0	19.7	9.3	2.3	- 5	• 1	• (1					j		l	1 1			
 		- :	Σχ²	<u> </u>	 	ΣX	<u> </u>	!	-		ليبا			<u> </u>				!	14132		14132	<u> </u>
Elemen Rel. Ho				9083	10	7199	7 7	- X - 5•9 -	σ _χ		No. Ob	132	± 0		≤ 32 F	Mean N ≥ 67			ith Temper			otal
Dry Bu				9265		4417			7.4			132	2 0		19.3		-9	73 F	2 80 1	≥ 93 F		744.0
Wet Bi				6992		9571		2.2	6.7			132		$-\vdash$	45.9				 		-	744.0
Day P				4119		3684		8.0	7.7			132			80.5		\dashv		 	+ -	+-	744.0
D0# P	Jini		- 1 47	7 5 7 7		7004	-1-3	200		201				<u>.</u>	30 0 3	<u> </u>						

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N. C. 28801

STATION

MEANS AND STANDARD DEVIATIONS

DRY-BULB TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

YEARS

43310 FUKUOKA KYUSHU JAPAN/ITAZUKE AB 46-64

RS (LST)	1	JAN	FEB.	MAR	APR.	MAY	אענ	JUL.	AUG.	SEP	OCT.	NOV.	DEC	ANNUAL
	MEAN	39.0	39.5	43.7	52.1	59.3	66.7	76.4	76.5	69.6	57.4	49.2	42.3	56-2
00-02	S D.	6.128	7-020	7.528	7.791	5.992	5.476	3.749	3.352	6.211	6.791	6.938	6.590	14.62
	TOTAL OBS	1674	1441	1581	1530	1674	1620	1674	1674	1689	1765	1710	1765	1979
	MEAN	38.4	38.9	42.9	51.2	58.1	65.8	75.6	75.5	68.6	56.4	48.3	41.7	55.
03-05	S D			7-536	8.079			3.812			7-123	7.157		14.6
	TOTAL OBS	1671	1441		1530	1673				1				197
	TOTAL OBS													
	MEAN	38.1	38.8	43.3	52.5	60.4	67.7	76.8	76.9	69.5	57.1	48.4	41.7	56.
06-08				7.370								7.157		15.0
		1674				1673		1674				1710		197
	TOTAL OBS	1014	1773	1301	1750	1012		2017	1014	1001	1.01	2110		
		41.9	44 1	50.5	60.5	68.4	74.0	82.1	84.0	76.8	66.8	57-1	47.2	63.
09-11	MEAN			6.727										15.3
09-11	S D.													198
	TOTAL OBS	1674	1441	1581	1530	1674	1620	1673	1017	1091	1101	1103	1101	170
		45.9	48.3	54.4	63.9	71.5	76.6	84.7	97 1	80.1	70.9	61.9	51.7	66.
	MEAN							5.824				6.400		14.9
12-14	u. u.			7.153										. 198
	TOTAL OBS	1674	1441	1581	1530	1674	1620	1672	1673	1692	1767	1710	1.101	- 179
		45.7	48.0	53.8	63.1	70.5	75.8	84.0	85.9	79.C	69.4	60.4	50.9	65.
	MEAN													14.7
15-17			7.043			-		5.722						
	TOTAL OBS	1673	1443	1581	1530	1673	1616	1674	1665	1691	1766	1710	1767	197
			44.0	100	-		70 3	00.0	41 0	74.3	(2.0	E1 3	44 9	61.
	MEAN	42.2		49.5	58.6	66.1	72.3	80.9		74.3	62.8	54-1	46.1	
18-20			6.481					4.893						14.6
	TOTAL OBS	1674	1443	1581	1530	1673	1619	1671	1668	1691	1767	1710	1767	197
							400					-		
	MEAN	39.9			54.4	61.6	ľ	77.8	78.1	70.8	58.9	50.6	43.4	57.
21-23	\$. D	5.953						3.865		1		1		14,
	TOTAL OBS	1673	1442	1581	1530	1674	1620	1671	1671	1692	1763	1709	1767	197
											-	l		
	MEAN		42.8	48.0	57.0			79.8			62.5			60.
ALL HOURS	S D												7.435	15.4
	TOTAL OBS	13387	11535	12648	12240	13388	12954	1 1 3 3 8 2	13372	13522	14129	13678	14132	1583

1210 WS HH AL 0-89-5 [Det 50]

· Selection of the sele

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

MEANS AND STANDARD DEVIATIONS

WET-BULB TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

43310 STATION FUKUOKA KYUSHU JAPAN/ITAZUKE AB STATION NAME

46-64

VEARS

FEB. APR. HRS (LST) IAN MAR MAY MIL JUL. AUG. SEP OCT. NOV. DEC. ANNUAL 36.7 37.3 41.4 57.1 74-0 49.8 64.6 73.6 67.5 55.6 47.3 40.0 53.9 MEAN 7.479 6-208 6-964 7-223 5.736 5.074 2.991 2.725 5.892 6.54d 6.739 6.416 14.463 S. D. 1441 1530 1671 1687 1707 19786 1674 1581 1616 1674 1767 TOTAL OBS 1673 36.1 36.7 56.2 63.9 73.0 73.3 66.8 54.7 46.4 39.5 6.049 5.469 2.998 2.895 6.159 6.826 6.904 6.381 40.7 49-1 53.2 MEAN 03-05 6.914 7.330 7.841 14.495 5. D. 1671 1442 1581 153d 1670 1617 1671 1672 1707 19782 TOTAL OBS 1689 1767 35.9 6.244 1674 36.6 40.9 6.808 7.197 57.6 65.0 73.5 73.9 67.2 55.2 46.5 39.4 5.510 5.080 3.039 2.867 6.068 6.718 6.912 6.253 49.9 53.7 MEAN 06-08 S. D. 7.49d 14.709 1686 1581 1670 1530 1613 1673 19784 1443 1673 1767 1707 TOTAL OB 38.5 40.1 6.304 6.585 1674 1441 61.5 67.7 75.6 76.9 70.6 60.6 52.0 43.2 4.467 4.412 3.065 2.550 4.979 5.344 6.146 6.153 45.5 54.5 57.4 MEAN 09-11 6.396 6.083 14-105 S.D. 1674 1692 19794 1581 153d 1673 1617 1673 1767 1709 TOTAL OBS 63.0 69.1 76.8 78.1 71.9 62.3 54.4 45.8 4.527 4.376 3.100 2.737 4.971 5.266 5.867 6.235 47.8 41.0 42.7 56.3 MEAN 12-14 6.548 6.657 6-396 6.019 13.61 S. D. 1672 TOTAL OB 1674 1443 1581 1530 1674 1617 1689 1767 1710 1767 19797 1673 41.1 6.591 62.7 68.9 76.6 77.8 71.7 61.8 53.8 45.5 4.462 4.263 3.130 2.682 4.901 5.367 5.939 6.309 1673 1613 1674 1665 1687 1766 1710 1767 59.0 42.7 47.6 56.1 MEAN 15-17 6.718 6.436 6.084 13.597 S. D. TOTAL OB 1581 1530 19782 1673 1443 61.0 67.5 75.5 76.4 69.9 59.0 50.7 42.8 4.568 4.247 3.073 2.657 5.150 5.686 6.093 6.050 1673 1616 1670 1668 1691 1767 1710 1767 6.214 6.671 6.430 6.231 1674 1443 1581 6.231 MEAN 13.967 18-20 S. D. 19790 TOTAL OS 37.3 38.4 43.1 51.6 58.8 66.0 74.5 75.1 68.3 56.6 48.4 40.9 6.074 6.826 6.831 6.929 5.122 4.590 2.965 2.616 5.572 6.130 6.490 6.235 55.1 MEAN 21-23 S. D. 14.322 1671 1673 1442 1674 1671 1581 153d 1692 1765 1709 1767 19792 TOTAL OB 1617 52.7 59.8 66.6 74.9 75.7 69.2 58.2 49.9 42.2 7.333 5.657 5.062 3.337 3.217 5.813 6.668 7.078 6.708 12240 13378 12926 13378 13369 13513 14133 13669 14132 38.2 39.4 44.0 6.596 7.154 7.314 13387 11538 12648 56.1 MEAN 14.345 \$. D. HOURS TOTAL OBS 158311

- Commence of the Commence of

the state of the s

. ŧ

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 28801

MEANS AND STANDARD DEVIATIONS

DEW-POINT TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

FUKUDKA KYUSHU JAPAN/ITAZUKE AB 43310

46-64

YEARS STATION NAME FEB. MAR APR. JUI4 JUL. AUG. SEP. OCT NOV HRS (L.S.T.) 33.0 34.0 38.6 47.8 55.6 63.4 72.4 73.1 66.5 54.3 45.4 37.1 7.860 8.224 7.978 8.033 6.085 5.285 3.063 2.819 6.088 6.816 7.386 7.436 1674 1441 1581 1530 1671 1616 1674 1673 1687 1767 1707 1765 52.0 MEAN 15.491 00-02 S. D. 19786 TOTAL OBS 62.8 71.9 72.4 65.8 5.598 3.020 2.970 6.299 1617 1671 1672 1689 53.5 44.6 51.3 54.8 MEAN 7.082 7.526 7.408 15.549 7.877 8.277 8.269 8.414 6.350 03-05 1707 19782 1617 1767 1765 1671 1442 1581 1530 1670 TOTAL OBS
 32.4
 33.2
 37.9
 47.5
 55.7
 63.5
 72.2
 72.7

 7.779
 8.234
 8.207
 8.278
 5.991
 5.364
 3.023
 2.864

 1674
 1443
 1581
 1530
 :670
 1613
 1673
 1673
 53.8 66.0 6.261 7.005 7.502 7.277 15.702 06-08 5 D. 1707 1767 19784 1686 1767 TOTAL OBS 67.7 56.4 47.6 53.3 64.4 73.1 39.8 49.4 57.1 33.7 MEAN 7.496 7.635 15.544 5.897 6.789 6.276 5.914 3.082 2.932 8.050 8.360 8.466 8.455 09-11 19798 1617 1692 1767 1709 1530 1673 1674 1673 1441 1581 TOTAL OF 53.9 48.0 39.3 57.6 65.2 68.1 56.7 34.6 35.7 40.7 MEAN 3.336 6.389 15.610 7-265 8.056 6.988 5.965 3.104 7.786 9-010 8.425 8.768 8.830 12-14 S. D. 1689 1767 19797 1672 1767 1710 1674 1617 1673 1581 1530 1443 TOTAL OB 34.9 35.9 40.9 50.4 57.6 65.3 73.8 74.7 68.2 56.8 8.536 8.962 8.730 8.773 6.824 5.544 3.116 3.210 6.168 7.242 48.2 7.242 7.873 8.287 15.538 15-17 \$. D. 1613 1665 1687 1710 19782 1674 1766 1673 1530 TOTAL OF 1673 1443 1581 34.4 35.6 40.6 50.2 57.6 65.1 73.4 74.3 67.8 56.3 47.6 38.8 8.103 8.770 8.226 8.063 6.003 5.013 3.100 2.966 5.805 6.630 7.341 7.770 15.363 18-20 S. D. 19789 1668 1691 1767 1710 1767 1615 1670 1443 1581 1530 1673 1674 TOTAL OSS 52.6 56.9 64.6 73.1 33.4 34.8 39.8 49.2 MEAN 5.817 6.579 15.463 4.907 3.023 2.791 7:224 7.502 7.832 8.255 7.925 7.886 5.751 21-23 S. D. 19792 1530 1671 1692 1765 1709 1767 1674 1617 1671 1581 33.6 34.7 39.5 49.0 56.6 64.3 72.9 73.7 67.1 55.3 46.5 38.0 8.109 8.538 8.414 8.458 6.379 5.530 3.136 3.103 6.157 7.047 7.655 7.757 13387 11538 12648 12240 13378 12925 13378 13369 13513 14133 13669 14132 52.8 15.566 S. D. HOURS 158310

1210 WS HOLE 0-89-5 (Det 50)

A come administration as

enteres de la constitución de la

-

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AG

46-64

ALL

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE	HUMIDITY GRE	EATER THAN			MEAN RELATIVE	TOTAL NO. OF
MONTH	(L.S T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	OBS.
JAN	ALL	100.0	100.0	100.0	99.6	94.8	30.6	61.1	41.1	17.5	75.3	13387
FEB		100.0	100.C	99.9	98.8	92.0	78.1	61.1	41.3	16.4	74.3	11538
WAX		100.0	99.9	49.5	98•0	90•2	78.↑	62.5	41.6	16.8	74.2	12048
APR		100.0	100.0	99.5	96.9	91.0	81.4	68.6	49.8	21.2	76.5	12240
MAY		100.0	99.9	99.3	97.2	92.0	83.6	71.4	53.8	24.4	77.8	13378
JUN		100.0	100.0	97.8	98.9	96.6	90.4	78.2	60.2	28.2	80.9	12925
JUL		100.0	100.0	100.0	100.0	99.4	93.9	78.3	56.4	23.3	80.8	133/8
AUG		100.0	100.0	100.0	99.8	98.8	92.3	76.C	56.0	26.7	80.5	13369
SEP		100.0	100.0	100.0	99.7	97.8	31.7	78.7	61.4	28.9	81.5	13513
001		16^.0	100.0	100.0	99.3	95.0	84.6	71.6	56.4	29.6	79.3	14133
NOV		100.0	100.0	100.0	99.5	94.0	82.5	69.7	53.1	25.8	78.1	13669
DEC		100.0	100.0	100.0	99.6	95.0	81.4	64.5	44.4	18.2	75.9	14132
10	TALS	100.0	100.0	99.8	99.0	94.8	85.0	70.3	51.4	23.2	78.0	15831C

121CWS FORM 0-87-5 (Det 50)

To assess .

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

4331.

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

47-64

JAN

STATION

STATION NAME

PERIOD

HONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE	HUMIDITY GR	EATER THAN			MEAN	TOTAL
MONTH	(L.S.T)	10%	20%	30%	40%	50%	60%	70%	80%	90%	RELATIVE HUMIDITY	NO. OF OBS.
JAN	₹ .۶	100.0	100.1	100	100.7	97.3	89.1	74.3	55.9	26.4	79.9	1674
	°3- 5	10.0	iro.	10.0	10	98.4	89.5	76.1	55.4	27.4	82.3	1671
	^6 - '9	100.0	100.0	100.0	99.9	98.1	90.0	76.0	57.3	28.2	80.5	1674
	C9-11	100.0	190.0	100.0	99.6	95.6	80.6	57.5	35.3	13.3	73.7	1574
	12-14	100.0	100.1	10 - 0	98.5	87.5	59.6	33.5	17.3	5•á	65.6	1674
	15-17	100.0	100.0	99.9	98.9	29.1	63.8	36.3	20.1	7.1	67•1	1673
	18-70	100.0	100.0	10.0	99.9	95.4	84.1	62.7	36.1	12.2	74.7	1674
	21-23	1 6.0	100.3	10.•0	100.0	96•7	87.8	72.8	51.2	20.0	78•5	1673
ļ											· · · ·	
101	TALS	110.0	100.0	160.0	99.6	94.8	80.6	61.1	41.1	17.5	7540	13387

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 2/801

RELATIVE HUMIDITY

43310

5

FUKUUKA KYUSHU JAPAN/TTAZOKE AN

48-64

FER

STATION

STATION NAME

MONTH

CUMPLATIVE PERCENTAGE FREQ JENCY OF OCCURRENCE (FROM HOURL, OBSERVATIONS)

	HOLKS L			PERCENTAGE	FREQUEN CY C	DE RELATIVE H	IUMIDITY GRE	ATER THAN			MEAN	TOTAL
WORE	11513	10%	-0%	30%	40%	50%	60%	70%	80%	90%	RELATIVE	NO. OF OBS.
FL.	30-02	160.0	10 .5	ا م	100.3	98.3	91.4	81.5	618	25.3	81.3	1441
	.s- 5	100.0	100.3	10 7	19.9	97.9	91.1	80•6	6	27.7	81.4	1442
	06-08	1(0.0	100.3	100	29.9	97.6	90.2	80.0	61.1	24.3	80.9	1443
	09-11	100.0	:00.0	100.0	98.6	91.3	74.0	49.8	27.3	10.1	70.7	1441
	12-14	130.6	110.0		95.5	77.3	51.1	36.7	16.1	6.7	63.2	1443
	15-17	100.0	99.9	99.8	96.7	80.4	55.0	31.3	16.8	7.1	64.2	1443
	18-20	100.0	100.0	99.9	99.6	95.0	80.6	57.2	31.7	11.9	73.1	1443
	21-23	100.0	100.0	100.0	100.0	98.5	21.7	77.8	53.1	18.2	79.4	1442
				 -								
* >	TALS	100.0	100.0	99.9	98.8	92.0	78.1	61.1	41.3	16.4	74.3	11538

1210WS FORM 0-87-5 (Det 50)

A CAN THE PROPERTY OF THE PARTY

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

(j

FUKUOKA KYUSHU JAPAN/ITAZUKE AH

48-64

MAR

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY (OF RELATIVE I	IUMIDITY GRE	ATER THAN			MEAN	TOTAL
MONTH	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	RELATIVE HUMIDITY	NO. OF OBS.
MAR	00-02	100.0	100.0	100.0	100.0	98.6	94.9	85.3	65.7	28.5	82.9	1531
	03-05	100.0	100.0	100.0	99.9	97.8	94.3	86.1	67.9	31.1	83.0	1561
	06-08	100.0	100.0	100.0	99.8	98.0	92.7	84.3	62.6	27.6	82.0	1501
	09-11	100.0	100.0	99.6	97.4	85.8	66.2	44.3	23.8	9.2	68.2	1581
	12-14	100.0	99.7	98.0	92.4	72.0	49.2	29.4	15.5	5.7	61.9	1581
	15-17	100.0	99.7	98.5	95.2	77.4	53.7	32.6	16.4	6.4	63.5	1531
	18-20	100.0	100.0	100.0	99.4	93.4	78.7	57.2	29.5	9.3	72.3	1581
	21-23	100.0	10.0	160.0	99.7	98.4	94.5	80.7	51.7	16.8	79.8	1581
												
<u> </u>												
101	TALS	100.0	99.9	99.5	98.0	90.2	78.0	62.5	41.6	16.8	74.2	12648

1210WS FORM 0-87-5 (Det 50)

garanggu e. Mer is t DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

48-64

APR

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY (OF RELATIVE H	UMIDITY GRE	ATER THAN			MEAN	TOTAL
MONTH	(L.S T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	RELATIVE HUMIDITY	NO. OF OBS.
APR	00-02	100.0	100.5	100.0	100.0	99.8	98.0	93.2	76.1	35.6	85.8	1530
	03-05	100.0	100.0	100	100.0	99.6	98.2	92.2	77.1	40.3	86.4	1530
	C6+08	100.0	100.0	100.0	99.9	99.1	95.8	87.7	68.2	32.1	84.0	1530
	C9-11	100.0	100.0	99.5	95.1	84.1	67.1	47.5	28•4	9.0	68.7	1530
	12-14	100.0	99.9	98.1	88•6	73.0	54.3	36.4	22.4	6.4	63.4	1530
·	15-17	100.0	100.0	98.8	92.6	77.8	59.4	38.6	22.5	7.7	65.5	1530
	18-20	100.0	100.0	99.9	99.0	94.9	82.1	63.7	38.4	13.5	74.7	1530
	21-23	100.0	100.0	99.9	99.9	99.3	96.7	89.6	65.7	24.6	83.2	153(
TO	TALS	100.0	100.0	99.5	96.9	91.0	81.4	68.6	49.8	21.2	76.5	12240

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

5

C.

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

47-64

MAY

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE I	IUMIDITY GRE	ATER THAN			MEAN	TOTAL
MONTH	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	RELATIVE HUMIDITY	NO. OF OBS.
MAY	00-02	100.0	100.0	100.0	106.0	100.0	99.5	95.6	83.2	44.1	88.0	1671
	C3-05	100.0	100.0	100.0	100-0	100.0	99.7	97.4	85.6	49.8	89.1	1670
	06-08	100.0	100.0	100.0	100.0	99.7	98.1	90.6	71.1	33.5	85.0	1670
	09-11	100.0	100.0	99.2	96.3	86.4	69.4	48.5	28.0	8.7	69.2	1673
	12-14	100.0	99.9	97.5	90.3	75.9	57.3	39.4	21.7	6.9	64.4	1674
	15-17	100.0	99.7	98.1	92.9	80.3	62.2	40.2	23.6	8.2	66.1	1673
	18-20	100.0	100.0	99.6	98•6	94.5	84.8	65.6	41.6	13.9	75.4	1673
	21-23	100.0	100.0	100.0	99.9	99.5	98.0	93.7	75.4	30.4	85•3	1674
10	TALS	100.0	99.9	99.3	97.2	92.0	83.6	71.4	53.8	24.4	77.8	13378

DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N.C. 28861

RELATIVE HUMIDITY

43310

FUKUOKA F (1) , JAPAN/ LIAZUKE AB

47-64

JUN

STATION

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE	HUMIDITY GRE	ATER THAN			MEAN RELATIVE	TOTAL NO. OF OBS.
MONTH	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	
NUL	00-02	100.0	100.0	100.C	100.0	100.0	99.6	97.4	90.9	48.8	89•4	1616
	03-5	100.0	100.0	107.0	100.0	100.0	49.8	98.3	92.0	54.7	90.5	1617
	60-63	100.0	100.0	100.0	100.0	99.9	99.1	94.7	79.0	36.5	86.8	1613
	C9-11	99.9	99.9	99.4	98.3	93.8	81.4	60.4	35.4	13.7	73.7	1617
	12-14	100.0	99.9	99.2	95.5	88.6	73.8	48.2	26.5	9.8	69.7	1617
	15-17	100.0	100.0	99.7	97.9	92.2	77.7	52.3	28.0	10.5	71.4	1613
	18-20	160.0	100.0	99.9	99.6	98.5	92.8	78.3	48.5	16.3	79.0	1615
	21-23	100.0	100.0	100.0	100.0	100.0	99.2	95.8	81.4	35.4	86.9	1617
<u>-</u>												
10	TALS	100.0	100.0	99.8	98.9	96.6	90.4	78.2	60.2	28.2	80.9	12925

1210WS JUL 64 0-87-5 (Det 50)

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

47-64

JUL

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE H	IUMIDITY GRE	ATER THAN			MEAN RELATIVE	TOTAL NO. OF OBS.
MONTH	(L S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	
JUL	00-02	100.0	100.0	100.0	100.0	100.0	99.4	98.1	86.2	38.6	88.0	1674
	03-05	100.0	100.0	100.0	100.0	100.0	99.6	98.3	88.3	42.4	88.7	1671
	06-08	100.0	100.0	100.0	100.0	100.0	99.7	96.6	76.2	30.4	86.1	1673
	C9-11	100.0	100.0	100.0	100.0	99.6	92.3	62.2	30.2	10.9	75.1	1673
	12-14	100.0	100.0	100.0	99.9	97.6	79.8	46.2	22.5	8.7	71.1	1672
	15-17	וט • 100	100.0	100.0	99.9	98•2	84.5	52.0	25.7	9.6	72.6	1674
	18-20	100.0	100.0	106.0	100.0	99.8	96.7	77.1	45.0	14.3	78.8	1670
	21-23	100.0	100.0	100.0	100.0	99.9	99.5	95.9	77.0	31.3	85.9	1671
10	TALS	100.0	100.0	100.0	100.0	99.4	93.9	78.3	56.4	23.3	80.8	13378

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

5

FUKUNKA KYUSHU JAPAN/ITAZUKE AB

47-64

AUG

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE	HUMIDITY GRE	ATER THAN			MEAN RÉLATIVE	TOTAL NO. OF OBS.
MONTH.	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	
AUG	00-02	190.0	100.0	100.0	100.0	100.6	99.0	97.8	91.3	52.4	89.5	1673
	03-05	100.C	100.0	100.0	100.0	190.0	99.8	98.3	92.5	54.9	90.3	1672
	06-08	100.0	100.6	100.0	106.0	100.0	99.7	97.5	82.3	37.4	87.3	1673
	09-11	100.0	100.0	100.0	99.9	99.2	90.3	58.6	19.7	5.5	72.9	1674
	12-14	100.0	100.0	100.0	99.4	95.2	73.1	35.2	12.9	5.0	67.7	1673
	15-17	100.0	100.0	100.0	99.5	96.7	80.9	45.2	18.7	6.1	70.3	1665
	18-20	100.0	100.0	100.0	99.9	99.5	95.7	79.0	45.7	13.4	79. C	1668
	21-23	100.0	99.9	99.9	99.9	99.9	99.4	96.8	84.8	38.5	87.4	1671
то	TALS	100.0	100.0	100.0	99.8	98.8	92.3	76.0	56.0	26.7	80.5	13369

1210WS FORM 0-87-5 (Det 50)

, are the second of the second

DATA PROCESSING DIVISION ETAC. USAF ASHLVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

46-64

SEP

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENC	F RELATIVE H	IUMIDITY GRE	ATER THAN			MEAN RELATIVE	TOTAL
HTMOM	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	NO. OF OBS.
SEP	00-62	100.0	100.0	100.0	100.0	100.0	99.7	98.6	92.1	52.1	90.1	1657
	03-05	100.0	100.0	100.0	100.0	100.0	99•8	98.6	93.3	57.0	90.9	1089
	06-08	100.0	100.0	100.0	100.0	99.9	99.5	97.7	88.4	45.1	88.9	1686
	09-11	100.0	100.0	100.0	99.8	97.7	86.9	63.8	30.7	8.7	74.4	1692
	12-14	100.0	100.0	99•8	98.7	90.6	71.3	40.3	18.6	6.0	68.1	1689
	15-17	100.0	100.0	99.9	99.1	94.6	79.5	47.5	23.4	7.6	70.8	1687
	18-20	106.0	100.0	100.0	100.0	99.5	76.9	85.0	56.2	15.6	80.9	1691
	21-23	100.0	106.0	100.0	100.0	100.0	99.9	98.2	88-4	38.8	88.1	1692
101	TALS	100.0	100.0	100.0	99.7	97.8	91.7	78.7	61.4	28.9	81.5	13513

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

FUKUUKA KYUSHU JAPAN/ITAZUKE AB

46-64

100

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE H	UMIDITY GRE	ATER THAN			MEAN RELATIVE	TOTAL NO. OF OBS.
MONTH	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	
OC T	00-02	100.0	100.0	100.0	100.0	99.9	98.9	96.7	89.2	55.0	89•8	1767
	03-05	100.0	100.0	100.0	100.0	99.9	98.8	96.4	88.8	62.0	90.3	1767
-	06-08	100.0	100.3	100.0	100.0	99.7	98.8	95.5	86.2	51.2	89.0	1767
	09-11	100.0	100.0	100.0	99.2	93.9	75.4	5C.8	26.7	5.4	70.6	1767
	12-14	100.0	100.0	99.9	96.9	79.5	49.5	23.5	11.2	4.1	62.0	1767
	15-17	100.0	100.0	99.9	92.1	88.3	61.1	33.4	14.9	4.1	65.5	1766
	18-20	100.0	100.0	100.0	100.0	99.3	96.3	81.2	51.7	13.4	79.9	1767
	21-23	100.0	100.0	100.0	100.0	99.9	98•1	95.0	82.9	41.8	87.4	1765
					-							
10	TALS	100.0	100.0	109.0	99.3	95.0	84.6	71.6	56.4	29.6	79.3	14133

DATA PROCESSING DIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

C

(

ŧ**Ç**l

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

46-64

NOV

STATION

STATION NAME

PERIOD

HINOM

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE	HUMIDITY GRE	ATER THAN			MEAN	TOTAL
MONTH	(L.S T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	RELATIVE HUMIDITY	NO. OF OBS.
иои	CO2	100.0	100.0	100.0	99.8	99.1	96.8	92.6	81.1	46.3	87.2	1707
	03-05	100.0	100.0	100.0	100.0	98.9	96.4	91.7	81.5	49.6	87.5	1757
	06-08	100.0	100.C	100.0	100.0	99.6	96.5	90.9	79.0	45.7	86.8	17.7
	09-11	100.0	100.0	160.0	99.6	94.3	76.1	53.8	29.6	8.4	71.8	17.9
	12-14	100.0	100.0	99.9	97.1	76.3	46.7	25.5	12.0	3.5	61.7	1710
	15-17	100.0	100.0	99.9	99.2	85.4	57.8	32.5	16.7	5.1	65.2	1710
	18-20	100.0	100.0	100.0	99.9	98.8	93.1	79.2	48-2	14.7	79.1	1710
	21-23	100.0	100.0	100.0	100.0	99.4	96.8	91.4	76.8	33.2	85.4	1709
TOT	ALS	100.0	100.0	100.0	99.5	94.0	82.5	69.7	53.1	25.8	78.1	13669

1210WS FORK 0-87-5 [Det 50]

DATA PROCESSING CIVISION ETAC, USAF ASHEVILLE, N.C. 28801

RELATIVE HUMIDITY

43310

FUKUOKA KYUSHU JAPAN/ITAZUKE AB

46-64

DEC

STATION

STATION NAME

PERIOD

MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAGE	FREQUENCY	OF RELATIVE I	HUMIDITY GRI	EATER THAN			MEAN RELATIVE	TOTAL NO. OF
MONTH	(L.S.T.)	10%	20%	30%	40%	50%	60%	70%	80%	90%	HUMIDITY	OBS.
DEC	CO-62	100.0	100.0	100.0	100.0	98.8	92.2	83.2	65.5	29.8	82.5	1765
	03-05	100.0	100.0	100.0	99.9	98.3	91.8	83.3	67.1	32.2	82.8	1765
	66-08	100.0	100.0	100.0	100.0	98.8	92.2	81.4	64.0	29.7	82.1	1767
	09-11	100.0	100.0	100.0	99.5	95.8	80.9	56.3	30.4	8.8	72.1	1767
	12-14	100.0	100.0	100.0	98.6	84.2	55 • 1	28.7	12.1	3.5	63.7	1767
	15-17	100.0	100.0	100.0	99.2	88.5	60.3	31.9	15.0	4.4	65.5	1767
	18-20	100.0	100.0	100.0	99.9	97.5	87.4	69.7	46.0	11.9	76.3	1767
	21-23	100.0	100.0	100.0	100.0	98.4	91.5	81.8	61.3	25.7	81.2	1767
										<u>. </u>		
то	TALS	100.0	100.0	100.0	99.6	95•0	81.4	64.5	44.4	18.2	75.9	14132

DATA PROCESSING DIVISION ETAC/USAF AIR WEATHER SERVICE (MATS) ASHEVILLE, NORTH CAROLINA

PART F


PRESSURE SUMMARY

Presented in this part are two tables giving the means, standard deviations, and total number of observations of station pressure and sea-level pressure by month and annual for the local hourly observations corresponding to the eight 3-hourly symoptic times GCT. The same computations are also provided at the bottom of the page for all hours combined. All years of data available are combined in both of these tables, although the overall period is limited to January 1946 through December 1963 because of changes in reporting practices before and after those dates.

- 1. Station pressure in inches of mercury.
- 2. Sea-level pressure in millibars.

3000 Sec. 1

Provided below is a scale to convert pressure values in inches of mercury or millibars to pressure altitude in 1000's of feet. This scale is an enlarged model of the pressure altitude scale in the Smithsonian Meteorological Tables.



DATA PROCESSING DIVISION ETAC. USAF ASHEVILLE, N. C. 298C1

MEANS AND STANDARD DEVIATIONS

STATION PRESSURE IN INCHES HG FROM HOURLY OBSERVATIONS

YEARS

43310 STATION FUKUUKA KYUSHU JAPAN/I TAZUKE AB STATION NAME

46-63

JAN FEB. MAR APR. SEP OCT. MAY JUN JUL AUG HRS (LST 3C.114BC.094BO.06CE9.476B4.86CB9.752B4.744B9.755B9.85CBC.021BC.122BO.152 29. 158 00 .154 .139 .248 .163 .156 .149 .143 .120 -108 .151 .141 .138 .144 5 0 527 6235 TOTAL OBS 527 452 496 480 527 510 521 533 558 540 558 3(.11cBu.u86Bc.04529.95629.83829.73129.72629.73929.83330.C08Bc.11cBu.144 29. 144 MEAN .158 .144 .143 C.3S. D. .162 .151 .152 .145 .127 -111 .153 .136 .141 . 412 527 540 TOTAL OB 496 480 510 527 527 6232 9.84529.73729.73229.74329.836BC.011B0.1C9BC.141 24. 345 MEAN 30.10480.08480.04429.9582 .131 .150 .152 .135 .211 06 .164 .149 .160 .155 .146 .113 S. D. 531 539 496 480 6231 TOTAL OBS 527 9.75029.74629.75729.86230.04330.14130.171 29.970 34.13480.11580.07329.78424.8642 MEAN .143 .165 .152 .164 .155 .145 .130 .151 .137 .147 .146 .216 69 -113 5 D 527 452 496 480 526 510 527 527 533 558 540 6234 TOTAL OB 30.12380.16580.06189.47184.85389.74089.73689.74889.85280.92180.11880.153 29.957 MEAN .151 .153 .142 .127 .111 .140 .139 .132 .145 .212 12 S D .165 .162 TOTAL OBS 452 527 527 527 533 558 540 6235 527 496 480 510 29. 319 36.082B0.057BC.01829.9312 9.8212 9.71629.69629.71929.81629.98680.08180.113 MEAN 237 (412) .136 15 .154 .155 .149 .136 .124 .135 .131 .141 .145 .163 S. D 6227 TOTAL OBS 527 496 480 527 506 521 36.09680.07686.02489.92889.81389.71689.70589.71589.81989.99180.69780.130 29. 125 MEAN .139 .149 18 S. D. .161 .149 .153 .136 .119 .109 .135 .139 .133 .211 480 524 6229 TOTAL OBS 526 452 496 526 510 527 558 29.84729.74129.73429.75029.85580.02580.12580.151 29.)55 36.120B0.093BC.0552 9.966 MEAN

.117

510

YE. 110

.108

527

.136

527

9.45929.84329.73529.72729.74129.84030.01230.11380.144 .153 .143 .125 .179 .142 .146 .137 .143 .146 3840 4214 4076 / 4216 4213 4259 4461 4317 4463

.146

.142

558

.139

540

749858 2.21

29. 747

.210

6235

C115

.146

<u> 558</u>

.146

1210 WS JUL 64 0-89-5 (Det 50)

S. D.

TOTAL OB

MEAN S. D.

TOTAL OBS

21

.161

.163

4215

** x9* * x02 x 24/56 * * * * * * * AND STATE OF

527

.151

36,11080,08880,047

.152

3616

452

.153

496

.158

3968

.149

480

.142

527

DATA PROCESSING DIVISION EFAC. USAF ASHEVILLE, N. C. 28801

MEANS AND STANDARD DEVIATIONS

SEA LEVEL PRESSURE IN MBS FROM HOURLY OBSERVATIONS

43310 FUKUOKA KYUSHU JAPAN/ITAZUKE AB 46

46-63

YEARS

IRS (LST)		JAN	FEU.	MAR	APR.	MAY	JUN	JUL	AUG.	SEP	OCT	NOV	DEC	ANNUAL
	MEAN	1020.8	1020.2	1019.1										1015.
CC	S. D.	5.509	5.220	5.253	5.046	4.833	4.073	3.654	4.699	5.101	4.766	4.661	4.863	7. 3
	TOTAL OBS	527	452	496	480		510		527	533	558	540	558	623
							<u> </u>							
	MEAN	1020.7	1019.9	1018.6	1015.5	1011.5	1007.9	1007.7	1008.2	1011.3	1017.2	1020.7	C21.9	1015.
С3	S D.	5.466	5.134	5.335	5.143	4.897	4.339	3.765	4.844	5.164	4.583	4.753	4.854	7.17
	TOTAL OBS	527			480							540		623
	MEAN	1.20.5	1019.9	1018.5	015.6	1011.7	1008.1	1007.9	1008.3	1011.4	1017.4	1020.7	1021.8	1015.
60	S D	5.536	5.070	5.410	5.238	4.,17	4.444	3.820	5.067	5.157	4.538	4.853	4.876	7.13
	TOTAL OBS	527	452	496	1.80		510				558			623
	MEAN	1021.5	1020.9	1019.5	1016.5	1012.4	1008.5	1008.4	1008.9	1312.3	1018.4	1021.8	022.7	1016.
09	S. D	5.556	5.130	5.538	5.254	4.908	4.414	3.835	4.877	4.851	4.507	4.964	4.392	7.27
1	TOTAL OBS	527			480				527			540	. ,	623
									i					
	MEAN	1021.2	020.6	1019.1	016.1	1012.0	1008.2	1008.1	1008.5	1012.0	1017.7	1021.0	1022.2	1015.
12	S D.							3.786						7.16
	TOTAL OBS	527											· •	623
	MEAN	1019.8	019.0	1017.6	014.7	1010.9	1007.4	1007.3	007.5	C1C.8	1016.3	1019.7	020.8	1014.
15	S D							3.729						6.93
	TOTAL OBS	527						527						622
						i								
	MEAN	1020.3	1019.4	1017.8	1014.6	1,10.7	1007.2	1007.0	1007.3	010.9	1016.7	1020.3	021.4	1014.
18	\$ D.							3.692						7.13
1	TOTAL OBS	527												622
	MEAN	1021.0	020.2	1018.9	1015.9	1011.8	1008.2	1008.0	C.8.5	C12.1	1017.8	1021.2	022.1	1015.
21	s. D	5.455	5.123	5.186	5.041	4.700	3.979	3.668	4.598	4.925	4.785	4.711	4.917	7.10
	TOTAL OBS									532				623
									-					
	MEAN	1020.7	020.0	1018.6	015.6	1011.7	1008.0	1007.8	008.2	011.6	017.4	1020.8	1021.9	1015.
ALL	S. D												4.911	7.14
HOURS	TOTAL OBS	4216		3968			4076			4254			1 1	4985

1210 WS JUL 64 0-89-5 (Det 50)